

Copyright © 1999-2008 IntelliCAD Technology Consortium. All rights reserved.

www.intellicad.org

Information in these materials is furnished for informational use only, is subject to change without notice and does not represent a commitment on the part of the IntelliCAD Technology Consortium. These materials, as well as the software described herein (“Software”), are furnished under license; there is no transfer of title. The Software is subject to the license agreement that accompanies or is included with the Software, which specifies the permitted and prohibited uses of the Software. Any unauthorized duplication or use of the IntelliCAD Technology Consortium Software, in whole or in part, in print, or in any other storage and retrieval system is prohibited. No part of these materials may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language in any form or by any means (electronic, mechanical, recording or otherwise) for any purpose other than the purchaser’s personal use without the express written permission of the IntelliCAD Technology Consortium. The IntelliCAD Technology Consortium assumes no responsibility or liability for any errors or inaccuracies that may appear in these materials. Use these materials at your own risk.

The Software, as with all computer-aided design software and other technical software, is a tool intended to be used by trained professionals only. It is not a substitute for the professional judgment of trained professionals. The Software is intended to assist with product design and is not a substitute for independent testing of product stress, safety and utility. Due to the large variety of potential applications for the Software, the Software has not been tested in all situations under which it may be used. The IntelliCAD Technology Consortium shall not be liable in any manner whatsoever for results obtained through the use of the Software. You agree that you are solely responsible for determining whether the Software is appropriate in your specific situation in order to achieve your intended results. You are also responsible for establishing the adequacy of independent procedures for testing the reliability and accuracy of any items designed by using the Software.

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, THE INTELICAD TECHNOLOGY CONSORTIUM AND ITS SUPPLIERS DISCLAIM ANY AND ALL WARRANTIES AND CONDITIONS, EITHER EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, AND NON-INFRINGEMENT, AND THOSE ARISING OUT OF USAGE OF TRADE OR COURSE OF DEALING, CONCERNING THESE MATERIALS. THESE MATERIALS ARE PROVIDED “AS IS” WITHOUT WARRANTY OF ANY KIND.

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, IN NO EVENT SHALL THE INTELICAD TECHNOLOGY CONSORTIUM OR ITS SUPPLIERS (OR THEIR RESPECTIVE AGENTS, DIRECTORS, EMPLOYEES OR REPRESENTATIVES) BE LIABLE FOR ANY DAMAGES WHATSOEVER (INCLUDING, WITHOUT LIMITATION, CONSEQUENTIAL, INCIDENTAL, DIRECT, INDIRECT, SPECIAL, ECONOMIC, PUNITIVE OR SIMILAR DAMAGES, OR DAMAGES FOR LOSS OF BUSINESS PROFITS, LOSS OF GOODWILL, BUSINESS INTERRUPTION, COMPUTER FAILURE OR MALFUNCTION, LOSS OF BUSINESS INFORMATION OR ANY AND ALL OTHER COMMERCIAL OR PECUNIARY DAMAGES OR LOSSES) ARISING OUT OF THE PURCHASE OR USE OF THESE MATERIALS, HOWEVER CAUSED AND ON ANY LEGAL THEORY OF LIABILITY (WHETHER IN TORT, CONTRACT OR OTHERWISE), EVEN IF THE INTELICAD TECHNOLOGY CONSORTIUM HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, OR FOR ANY CLAIM BY ANY OTHER PARTY. Because some jurisdictions do not allow the exclusion or limitation of liability for consequential or incidental damages, the above limitation may not apply to you.

Unless otherwise noted, all names of companies, products, street addresses, data, characters and persons contained herein are part of a completely fictitious scenario or scenarios, are designed solely to document the use of an IntelliCAD Technology Consortium product, and are in no way intended to represent any real individual, company, product or event.

Certain LZW graphics capability licensed from Unisys Corporation under U.S. Patent No. 4,558,302 and foreign counterparts.

This software is based in part on the work of the Independent JPEG Group.

IntelliCAD Technology Consortium Trademarks: IntelliCAD, the IntelliCAD logo, and SDS (Solutions Development System) are either registered trademarks or trademarks of the IntelliCAD Technology Consortium in the United States and/or other countries.

Third-Party Trademarks: All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

US Government Restricted Rights: These materials are provided with RESTRICTED RIGHTS. Use, duplication or disclosure by the Government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of The Rights in Technical Data and Computer Software clause at DFARS 252.227-7013 or subparagraphs (c)(1) and (2) of the Commercial Computer Software-Restricted Rights at 48 CFR 52.227-19, as applicable. The contractor/manufacturer is the IntelliCAD Technology Consortium, USA.

Contents

Chapter 1

Introduction	1
About IntelliCAD and other CAD software	3
Using AutoCAD legacy drawings	3
Using AutoCAD commands with IntelliCAD	4
Comparing IntelliCAD and CAD to manual drafting	5
Drawing to scale	5
Using tools	6
Organizing information	6
Drawing accurately	7
Drawing efficiently	8
Reusing CAD drawings and entities	10
Making changes	11
Working with other data and programs	11
Using advanced CAD features	13
Using the IntelliCAD Explorer	13
Editing multiple documents simultaneously	13
Editing multiple entities	13
Using the Customize dialog box	13
Performing unlimited undo and redo	13
Getting more information	13
What's new in IntelliCAD 6.0 – 6.5	14
What's new in IntelliCAD 6.5	14
What's new in IntelliCAD 6.4	15
What's new in IntelliCAD 6.3	15
What's new in IntelliCAD 6.2	16
What's new in IntelliCAD 6.1	18
What's new in IntelliCAD 6.0	19

Chapter 2

Getting started	23
System requirements	24
Installing IntelliCAD	24
Starting IntelliCAD	25
Working in IntelliCAD	25
Displaying commands on a shortcut menu	27
Displaying and hiding toolbars	27
Using the command bar	28
Using the status bar	29
Using prompt boxes	30
Selecting commands	32
Using commands	32
Starting commands using toolbars	32
Starting commands using menus	32

Starting commands using the command bar	33
Repeating a command	33
Nesting a command	33
Modifying a command	34
Using the Prompt History window	34
Using mouse shortcuts	35
Using scripts	35
Correcting mistakes	36
Customizing IntelliCAD	36
Getting online Help	37
Saving your drawing	37
Exiting IntelliCAD	37

Chapter 3

Working with drawings	39
Creating a new drawing	40
Opening a drawing	41
Opening an existing drawing	41
Opening damaged files	42
Setting up a drawing	44
Setting the current layer	44
Setting the current entity color	45
Setting the current linetype	46
Setting the linetype scale	47
Setting the current lineweight	48
Setting the current print style	49
Setting drawing units	50
Understanding scale factors	53
Setting the text height	54
Setting the drawing limits	56
Working with colors	58
Using index colors	58
Using true colors	59
Using color books	61
Using the grid, snap alignment, and cursor restriction	66
Setting a reference grid	66
Setting snap spacing	69
Changing the snap and grid angle and base point	69
Using isometric snap and grid	71
Using orthogonal locking	72
Using polar tracking	73
Using entity snaps	74
Setting entity snaps	75
Nearest Snap tool	76
Endpoint Snap tool	76
Midpoint Snap tool	76
Center Snap tool	77

Perpendicular Snap tool	77
Tangent Snap tool	78
Quadrant Snap tool	79
Insertion Point Snap tool	79
Point Snap tool	80
Intersection Snap tool	80
Apparent Intersection Snap tool	81
Quick Snap command	82
Clear Entity Snaps tool	82
Using fly-over snapping	83
Saving your drawing	85
Saving a drawing	85
Saving a drawing with a new name or file format.	86
Saving a drawing with a password	87

Chapter 4

Creating simple entities	89
Drawing lines	90
Drawing circles	91
Drawing arcs	93
Drawing ellipses	96
Drawing elliptical arcs	97
Creating point entities	98
Changing the size and appearance of point entities.	98
Drawing rays	100
Drawing infinite lines	101
Creating freehand sketches	103
Erasing freehand sketch lines	104
Setting the sketch method and accuracy	104

Chapter 5

Creating complex entities	107
Drawing rectangles	108
Drawing polygons	110
Drawing polygons by side	111
Drawing polylines	111
Drawing splines	114
Specifying fit tolerance	115
Drawing a closed spline.	116
Drawing donuts	117
Creating planes	119
Drawing wipeouts	121
Drawing wipeouts using polygons and polylines	121
Turning wipeout frames on or off	122
Creating boundary polylines	123
Using islands and island detection.	124
Adding hatching	127
Specifying a hatch pattern	127

Selecting entities for hatching	132
Selecting areas for hatching	133

Chapter 6

Viewing your drawing	137
Redrawing and regenerating a drawing	138
Moving around within a drawing	138
Using scroll bars	138
Using the Pan command	139
Rotating the view in real time	141
Changing the magnification of your drawing	142
Zooming in and out	142
Zooming methods	142
Displaying the previous view of a drawing	144
Zooming to a specific scale	144
Combining zooming and panning	144
Displaying the entire drawing	145
Displaying multiple views	146
Working with multiple views of a single drawing	146
Opening a new window of the same drawing	146
Dividing the current window into multiple views	147
Saving window configurations	149
Working with multiple drawings	149
Controlling visual elements	151
Turning Fill on and off	151
Turning Quick Text on and off	152
Turning highlighting on and off	153
Turning Blips on and off	153
Controlling the display of lineweights	154

Chapter 7

Working with coordinates	155
Using Cartesian coordinates	156
Understanding how coordinate systems work	156
Understanding how coordinates are displayed	158
Finding the coordinates of a point	159
Using two-dimensional coordinates	159
Entering absolute Cartesian coordinates	160
Entering relative Cartesian coordinates	161
Entering polar coordinates	162
Using three-dimensional coordinates	163
Using the right-hand rule	163
Entering x,y,z-coordinates	163
Entering spherical coordinates	164
Entering cylindrical coordinates	165
Using xyz point filters	166
Using point filters in two dimensions	166
Using point filters in three dimensions	167

Defining user coordinate systems	168
Defining a user coordinate system.....	168
Using a preset user coordinate system.....	169

Chapter 8

Working with the IntelliCAD Explorer	171
Using the IntelliCAD Explorer	172
Copying settings	174
Deleting settings	175
Purging elements	177
Organizing information on layers	177
Creating and naming layers.....	180
Setting the current layer	182
Controlling layer visibility	182
Locking and unlocking layers	184
Controlling layer printing	185
Setting the layer color	185
Setting a layer's linetype	187
Setting a layer's lineweight	188
Setting a layer's print style	189
Working with linetypes	190
Setting the current linetype	191
Loading additional linetypes	192
Creating and naming linetypes	193
Working with text fonts and styles	198
Creating and naming text styles.....	199
Modifying text styles	200
Setting the current text style	202
Working with coordinate systems	202
Defining and naming user coordinate systems	204
Setting the current user coordinate system	205
Using named views	206
Saving and naming views	207
Restoring named views	208
Changing named view properties	208
Working with blocks and external references	209
Creating and naming blocks	212
Inserting a block	213
Inserting a drawing as a block	213
Attaching a drawing as an external reference	214
Working with dimension styles	216
Creating and naming dimension styles	217

Chapter 9	Getting drawing information	219
	Specifying measurements and divisions	220
	Measuring intervals on entities	221
	Dividing entities into segments	222
	Calculating areas	223
	Calculating areas defined by points	223
	Calculating areas of closed entities	224
	Calculating combined areas	224
	Calculating distances and angles	227
	Displaying information about your drawing	228
	Displaying information about entities	228
	Displaying the drawing status	229
	Tracking time spent working on a drawing	230
Chapter 10	Modifying entities	233
	Selecting entities	234
	Displaying selected entities highlighted	234
	Entity-selection methods	234
	Choosing the command first	237
	Selecting entities first	238
	Deselecting entities	238
	Turning grips on and off	239
	Editing with grips	239
	Modifying the properties of entities	240
	Deleting entities	242
	Copying entities	242
	Copying entities within a drawing	242
	Copying between drawings	244
	Making parallel copies	244
	Mirroring entities	246
	Arraying entities	246
	Rearranging entities	248
	Moving entities	248
	Rotating entities	249
	Reordering entities	250
	Resizing entities	251
	Stretching entities	251
	Scaling entities	252
	Extending entities	253
	Trimming entities	256
	Editing the length of entities	257
	Breaking and joining entities	259
	Breaking entities	259
	Joining entities	260
	Grouping entities	261
	Creating groups	261

Modifying groups	262
Ungrouping entities	263
Editing polylines	264
Opening and closing polylines	264
Curving and decurving polylines	265
Joining polylines	266
Changing the polyline width	267
Editing polyline vertices	268
Exploding entities	270
Chamfering and filleting entities	271
Chamfering entities	272
Filleting entities	274

Chapter 11

Working with text	277
Creating line text	278
Creating paragraph text	279
Working with text styles	281
Formatting text	282
Setting the line text style	282
Setting the paragraph text style	283
Setting the line text alignment	283
Setting the paragraph text alignment	284
Including special text characters	285
Changing text	285
Changing line text	285
Changing paragraph text	287
Checking the spelling	289
Checking the spelling of text	289
Customizing the spelling words	290
Changing the dictionary	292
Using an alternate text editor	293
Selecting an alternate text editor	293
Creating paragraph text in an alternate text editor	293
Working with text written in different languages	295
Using Unicode characters	295
Specifying character sets for drawings	295

Chapter 12

Dimensioning your drawing	299
Understanding dimensioning concepts	300
Creating dimensions	302
Creating linear dimensions	302
Creating angular dimensions	307
Creating diametral and radial dimensions	308
Creating ordinate dimensions	309
Creating leaders and annotations	311
Dimensioning model space entities in paper space	312

Editing dimensions	313
Making dimensions oblique	313
Editing dimension text	313
Understanding dimension styles and variables	316
Controlling dimension arrows	317
Controlling dimension format	319
Controlling line settings	321
Controlling dimension text	323
Controlling dimension units	325
Adding geometric tolerances	327
Controlling dimension tolerance	330
Controlling alternate dimension units	332

Chapter 13

Working with blocks, attributes, and external references 335

Working with blocks	336
Creating blocks	336
Inserting blocks	338
Redefining blocks	340
Exploding blocks	341
Working with attributes	342
Defining attributes	342
Editing attribute definitions	344
Attaching attributes to blocks	345
Editing attributes attached to blocks	345
Extracting attribute information	346
Working with external references	348
Attaching external references	349
Viewing the list of external references	351
Opening external references	352
Removing external references	352
Reloading external references	353
Changing the path for external references	354
Binding external references to drawings	355
Clipping external references	356

Chapter 14

Printing drawings 359

Getting started printing	360
Defining layouts for printing	361
Understanding layouts	361
Understanding paper space and model space	362
Viewing drawings in paper space and model space	364
Displaying the Model and Layout tabs	365
Creating a new layout	365
Reusing layouts from other files	366
Managing layouts in a drawing	367
Working with layout viewports	368

Customizing print options	373
Setting the paper size and orientation	373
Selecting a printer or plotter	374
Setting the scale and view	374
Choosing how lineweights print	377
Using print styles	379
Reusing print settings	389
Printing or plotting your drawing	391
Previewing a drawing before printing	391
Printing a drawing	393

Chapter 15

Drawing in three dimensions	395
Viewing entities in three dimensions	396
Setting the viewing direction	396
Creating three-dimensional entities	399
Applying elevation and thickness	399
Creating three-dimensional faces	403
Creating rectangular meshes	404
Creating polyface meshes	405
Creating ruled surface meshes	405
Creating extruded surface meshes	406
Creating revolved surface meshes	407
Creating edge-defined Coons surface patch meshes	409
Creating boxes	410
Creating wedges	411
Creating cones	412
Creating pyramids	413
Creating cylinders	415
Creating spheres	416
Creating dishes	417
Creating domes	418
Creating tori	419
Creating regions	420
Creating extruded solids	421
Creating revolved solids	422
Creating composite solids	423
Editing in three dimensions	425
Rotating in three dimensions	425
Arraying in three dimensions	426
Mirroring in three dimensions	428
Aligning in three dimensions	429
Editing three-dimensional solids	430
Chamfering and filleting solids	430
Sectioning and slicing solids	431
Modifying faces	432
Modifying edges	438

Imprinting solids	439
Separating solids	439
Shelling solids	440
Cleaning solids	440
Checking solids	441
Hiding, shading, and rendering	441
Creating hidden-line images	442
Creating shaded images	442
Creating rendered images	443
Creating custom rendered images	445
Printing a rendered image	446


Chapter 16

Working with other programs	447
Saving and viewing snapshots	448
Using images in a drawing	449
Attaching images	449
Modifying images	452
Changing the display of images	454
Clipping images	455
Unloading and reloading images	456
Changing the path for images	457
Deleting images	458
Using data from other programs in IntelliCAD drawings	458
Embedding objects into drawings	458
Linking objects to drawings	460
Editing an embedded or linked object from within IntelliCAD	461
Importing files created in other formats	462
Using IntelliCAD data in other programs	464
Embedding drawings	464
Editing an embedded IntelliCAD object in place	465
Linking drawings	465
Dragging IntelliCAD drawings into other programs	466
Exporting drawings	467
Sending drawings through e-mail	471
Using IntelliCAD with the Internet	472
Add hyperlinks to a drawing	472
Publishing drawings to the Internet	474
Inserting drawings from a Web site	474
Accessing the IntelliCAD Web site during a drawing session	474

Chapter 17

Customizing IntelliCAD	475
Setting and changing options	476
Changing the options on the General tab	476
Changing the options on the Paths/Files tab	478
Changing the options on the Display tab	480
Changing the options on the Crosshairs tab	483
Changing the options on the Profiles tab	484
Changing the options on the Printing tab	488
Changing the options on the Snapping tab	490
Customizing menus	491
Understanding menu compatibility	492
Creating new menus and commands	492
Setting the experience levels for menus	495
Saving menu files	495
Loading menu files	496
Creating custom shortcut menus	496
Customizing toolbars	498
Creating a new toolbar	499
Naming toolbars	501
Creating flyouts	501
Setting the experience levels for tools	502
Creating custom toolbar tools	503
Importing toolbars	504
Creating toolbars that you can share as files	505
Customizing the keyboard	508
Creating a keyboard shortcut	509
Saving keyboard shortcut files	510
Loading keyboard shortcut files	511
Creating aliases	511
Creating, redefining, and deleting aliases	512
Saving alias files	513
Loading alias files	514
Customizing entities	514
Working with audio notes	514
Using shape files	517
Creating and replaying scripts	518
Programming IntelliCAD	521
Using LISP routines	521
Using ADS applications	523
Using DCL with IntelliCAD	524
Using VBA	525
Using DIESEL with IntelliCAD	525
Using a digitizer tablet	526
Configuring the tablet	526
Calibrating the tablet	528
Understanding transformation types	528
Customizing the tablet interface	530

Appendix	Understanding AutoCAD compatibility	531
	Using enhanced AutoCAD commands in IntelliCAD	532
	Using additional selection sets	533
	Using additional IntelliCAD commands	534
	Recognizing subtle command differences	537
	Identifying unsupported commands and features	538
	Identifying what does not display	539
	Supporting AutoCAD customization	540
	Understanding menu compatibility	540
	Importing and exporting customization files	541
	Programming IntelliCAD	542
	Understanding AutoLISP compatibility	542
	IntelliCAD and AutoCAD list of terms	544
	Glossary	545
	Index	559



Introduction

Using *IntelliCAD* is part of an integrated documentation set that includes this manual and a comprehensive collection of help resources to give you the information you need to create drawings in *IntelliCAD*®.

This manual is organized into chapters that parallel how you work in *IntelliCAD*, according to the tasks you might perform. The tasks are divided and organized into the following work-focused chapters:

Introduction: Chapter 1 An overview of the key features of *IntelliCAD* plus basic concepts of computer-aided design (CAD) as they apply to *IntelliCAD*.

Getting started: Chapter 2 Installing *IntelliCAD*, starting and exiting *IntelliCAD*, working with toolbars, and selecting commands.

Working with drawings: Chapter 3 Opening and saving an existing drawing and starting a new drawing. Using drawing settings to establish paper size, scale factors, and text height. Working with colors in your drawings. Using drawing aids such as entity snaps and orthogonal mode to draw accurately.

Creating entities: Chapters 4–5 Working with simple entities such as lines, circles, and arcs and with complex entities such as polygons, spline curves, planes, wipeouts, boundary hatches, and more.

Viewing your drawing: Chapter 6 Moving around in the drawing, changing its magnification, creating multiple views, and saving arrangements of windows of the drawing.

Topics in this chapter

<i>About IntelliCAD and other CAD software</i>	3
<i>Comparing IntelliCAD and CAD to manual drafting</i>	5
<i>Using advanced CAD features</i>	13
<i>Getting more information</i>	13
<i>What's new in IntelliCAD 6.0 – 6.5</i>	14

Working with coordinates: Chapter 7 Working with Cartesian coordinate systems, specifying two-dimensional and three-dimensional coordinates, and defining your own user coordinate systems.

Working with the IntelliCAD Explorer: Chapter 8 Using the IntelliCAD Explorer to manage your drawings: controlling layers, linetypes, text styles, coordinate systems, views, and blocks and copying information between drawings.

Getting drawing information: Chapter 9 Working with the additional information in IntelliCAD drawings, calculating areas and distances, and displaying other drawing information.

Modifying entities: Chapter 10 Selecting, copying, rearranging, resizing, and editing entities.

Annotating and dimensioning your drawing: Chapters 11–12 Using text to annotate drawings; using dimensions to annotate the measurement of entities.

Working with blocks, attributes, and external references: Chapter 13 Using blocks and external references to combine entities and data for reuse; creating attribute information to extract for use in other programs.

Formatting and printing drawings: Chapter 14 Combining drawings into finished layouts, customizing print options, and printing copies.

Drawing in three dimensions: Chapter 15 Creating and editing three-dimensional entities. And visualizing them using hidden line removal, shading, and photo-realistic rendering.

Working with other programs: Chapter 16 Sharing drawings and data with other users, documents, and programs.

Customizing IntelliCAD: Chapter 17 Customizing the appearance and operation of the program to suit your needs.

Understanding AutoCAD compatibility: Appendix Describes similarities and differences between IntelliCAD and AutoCAD.

About IntelliCAD and other CAD software

IntelliCAD is designed for anyone who wants a fast and efficient CAD program with all the power and versatility of standard programs such as AutoCAD® by Autodesk®, Inc., or MicroStation® by Bentley Systems, Inc., at an affordable price. Using today's advanced technology, IntelliCAD integrates the Microsoft® Windows® interface with a powerful CAD engine.

IntelliCAD provides unparalleled compatibility with AutoCAD, using most of the same file formats including those for drawings (.dwg files), commands, linetypes, hatch patterns, and text styles. You can also use AutoCAD menu files and run Autodesk® AutoLISP® programs. If you have written your own ADS (Autodesk® AutoCAD Development System®) programs, simply recompile them to link with the IntelliCAD libraries. Many third-party ADS programs already support IntelliCAD. If you have a program that is not already supported, ask your software vendor to provide an IntelliCAD-compatible version of the program.

IntelliCAD is more compatible with the AutoCAD program than any other CAD product, delivers additional tools with advanced CAD features, and has a seamless Microsoft® Windows integration. This powerful program provides a superb combination of features for CAD users like architects, engineers, and designers.

IntelliCAD incorporates standard features found in other CAD programs, along with features and capabilities you won't find anywhere else. Its multiple-document interface (MDI) lets you open and work with several drawings at the same time. You can easily copy drawing entities between drawings. In addition, the powerful IntelliCAD Explorer lets you manage information and settings and quickly copy layers, linetypes, and other information between drawings.

Using AutoCAD legacy drawings

IntelliCAD fully supports AutoCAD legacy drawings. IntelliCAD reads and writes DWG files in their native format without any loss of data, from AutoCAD 2007 back to Version 11, including AutoCAD LT®. Because IntelliCAD uses DWG as its native file format, no translation is required.

IntelliCAD provides you with the appropriate tools for your experience level—whether you are a beginner, intermediate, or advanced CAD user. If you are just starting out with CAD, you may want to use the beginner level, which provides toolbars containing the basic tools such as lines, arcs, and circles. As you become more experienced, you can move to the intermediate level and then to the advanced level, which gives you access to more than 300 commands through toolbars, menus, and keyboard entries. You can change the experience level in the Options dialog box on the Tools menu.

IntelliCAD supports three-dimensional wireframes and surfaces. Three-dimensional drawings can be displayed in wireframe, hidden-line view, and surface shading. Some versions of IntelliCAD also support creating and editing 3D solids; all versions display 3D solids, along with limited editing features.

Some versions of IntelliCAD support displaying and working with raster images in your drawings. However, IntelliCAD does not display images located inside of blocks and externally referenced drawings (xrefs). When a drawing containing proxy entities is loaded into IntelliCAD, a message displays indicating that some entities will not display, however, the entities reappear when you open the drawing later in AutoCAD.

It's easy to customize IntelliCAD. You can modify menus and toolbars, create custom menus, dialog boxes, command aliases, and scripts, and add custom programs written in any of several programming languages, including LISP (the program's Autodesk® AutoLISP-compatible language) and SDS™ (Solutions Development System™, the program's Autodesk® ADS-compatible language). There is also Microsoft® Visual Basic for Applications (VBA).

You can run existing Autodesk® AutoLISP applications in IntelliCAD with little or no modification. IntelliCAD uses the `APLOAD` command so you can easily load LISP programs. IntelliCAD reads files that contain dialog control language (DCL) statements as well, which makes IntelliCAD compatible with dialog boxes created for AutoCAD.

Using AutoCAD commands with IntelliCAD

Because IntelliCAD supports hundreds of AutoCAD commands, you use the commands you already know. For example, to draw a circle, use the `CIRCLE` command. To copy a circle, use the `COPY` command.

When you press `Enter` or the spacebar, you activate the command—just like in AutoCAD. IntelliCAD accepts the special characters used by AutoCAD, such as point filters (for example, `.xy`), relative coordinates (the `@` symbol), and the apostrophe (the `'` prefix) for transparent commands. IntelliCAD function keys are also similar to those used in AutoCAD.

Because you do not need to learn a new set of commands, you are immediately productive with IntelliCAD.

Comparing IntelliCAD and CAD to manual drafting


IntelliCAD greatly reduces the time and effort it takes to create and revise drawings. Not only can you produce accurate drawings faster, you can also reuse the information in your drawings. These are the primary reasons for making the transition to CAD from traditional, manual drafting on paper.

As with any tool, however, to use it effectively, you need to be familiar with some of the special features, functions, and concepts of CAD. If you are familiar with manual drafting, you'll find some conceptual similarities in CAD as well as some differences.

Drawing to scale

In traditional, manual drafting, you usually determine the scale of the drawing before you even start to draw, because you are working with a sheet of paper of a fixed size. You may have to reduce or enlarge the entity you are drawing to fit within the confines of the paper.

When you create a drawing in IntelliCAD, you draw everything full-size. You determine the type of units in which your drawing is measured. If you are drawing a building, 1 drawing unit might equal 1 inch. If you are drawing a map, 1 drawing unit might equal 1 mile. Your drawing environment and the CAD drawing file itself are not limited to the size of a particular sheet of paper.



1 drawing unit equals 1 inch.

1 drawing unit equals 1 foot.

As you draw, you can use commands such as Pan and Zoom to work on different portions of the drawing and to magnify the display of the drawing to view small details. These commands have no effect on the actual size of the entities in your drawing; they affect only the way the drawing is displayed on your screen. Only when you print or plot your drawing do you need to set the scale so that the printed drawing fits within a specific paper size.

Using tools


In manual drafting, you use tools such as pencils, rulers, T-squares, templates, erasers, and so on. When you create a drawing in IntelliCAD, you use a mouse instead of a pencil, and you use the mouse to select other tools—commands you select from a menu or a toolbar.

You use some tools to create basic entities, such as lines, circles, and arcs, and other tools to modify existing entities (for example, to copy or move them or to change properties such as color and linetype).

Organizing information

In traditional drafting, you often separate elements such as walls, dimensions, structural steel members, and electrical plans onto separate, translucent overlays. When you want to print the working drawings, you can create several different drawings by combining different overlays.


When you create a drawing in IntelliCAD, you use layers to organize elements in a similar manner. However, the layers feature in CAD offers numerous advantages over physical transparencies. The number of overlays you can combine to print a manually drafted drawing is limited by the printing process. There is no such limitation in CAD. With IntelliCAD, you can define an unlimited number of layers, any of which can be visible or invisible at any time. You can name each layer and assign each its own color, linetype, lineweight, and print style. You can also lock individual layers to ensure that information on those layers isn't altered accidentally.



Use layers to organize drawing information.


Drawing accurately

When you create a manual drawing, ensuring accuracy typically requires a lot of manual calculations and rechecking. By contrast, IntelliCAD offers a number of drawing aids that ensure accuracy from the start. For example, you create and modify entities based on an underlying Cartesian coordinate system. Every location in the drawing has its own x,y,z -coordinates. You can also display a grid as a visual reference to your coordinate system.




Every location in the drawing has its own x,y,z -coordinates within the underlying Cartesian coordinate system. Point $5,2,0$ is 5 units to the right (along the x -axis), 2 units up (along the y -axis), and 0 units (along the z -axis) from the origin (the $0,0,0$ point).

Settings such as snap and entity snap allow you to draw accurately without specifying coordinates. The snap setting forces the selected points to adhere to the grid increment or to any other increment you set. Entity snaps let you snap to precise geometric points on existing entities—for example, the endpoint of a line or the center of a circle. Another setting, orthogonal, constrains lines so that they are drawn parallel to the vertical and horizontal axes.



Paper-based drawings lack the high degree of accuracy possible when using CAD. Lines often overlap or fail to meet adjacent lines.




Snap and entity snap force the cursor to adhere to a specified increment or attach to key geometric points on existing entities. You can also constrain lines to vertical and horizontal axes.

Drawing efficiently


In paper-based, manual drafting, you often have to redraw the same entity several times at different scales or from different vantage points. You may also need to redraw the border and title block on each new sheet.

One of the most powerful features of IntelliCAD is that when you create a drawing, you can reuse individual entities, borders, and title blocks as often as you want. You need draw an entity only once; the final printed drawing can show the entity at several different scales and viewpoints.

You usually begin drawing in model space on the Model tab, creating the drawing (a floor plan, a map, or a three-dimensional part) without regard to the final layout on paper. When you are ready to print your drawing, you have the option to switch to paper space on a Layout tab, where you lay out the drawing as you want it to appear on a sheet of paper. For example, you can insert a drawing file that contains the standard border and title block that you created. You can define and arrange multiple views of the drawing at appropriate scales and with specific portions visible or invisible—again, without having to redraw the border and title block for each view.




You create the basic drawing in model space on the Model tab.



When you're ready to print or plot your drawing, you can switch to paper space on a Layout tab, where you provide a layout of the drawing as you want it to appear on a sheet of paper.

Reusing CAD drawings and entities

When you create a paper drawing manually, you can draw repetitive symbols by tracing a plastic template. After you draw a symbol in IntelliCAD, you can reuse that symbol without having to redraw it. You simply save the symbol as a block. You can then insert copies of that block anywhere in your drawing. You can also save the symbol as a separate drawing for use in other drawings.




You can draw a symbol one time, save it as a block, and then insert multiple copies of that symbol anywhere in your drawing.

In addition, you can reuse entire drawings and insert individual drawings into other drawings. You can also use an external reference, which acts as a pointer to another drawing rather than a copy of the entire drawing. Using an external reference has an added advantage: when you update the externally referenced drawing, each drawing that references it can be automatically updated.

Making changes

To make changes to a paper drawing, you erase and then redraw. With IntelliCAD, you use commands to modify entities in the drawing. You can move, rotate, stretch, or change the scale of entities. When you want to remove an entity, you can delete it with a single click of the mouse. If you make a mistake while creating or modifying your drawing, you can easily reverse your actions.




You can easily change an entity using commands such as move, rotate, stretch, and scale instead of redrawing the entity.

Working with other data and programs

Traditional paper drawings serve only as a means of communicating information between the person who created the drawing and the person viewing the drawing. The drawings contain no more information than what is visually imparted by the creator and seen by the viewer.

IntelliCAD offers rich possibilities for analyzing drawings and attaching additional data to them. For instance, although it may be impractical to count entities in a complex paper drawing, this task is simple in CAD. IntelliCAD can calculate the number of entities in a drawing and compute area and distance.

CAD drawings can also contain information in addition to visible entities. You can attach invisible database information to visible drawing entities and extract the information for analysis in a database or spreadsheet. (Working with information in a database requires a program from a third-party vendor, or you can create your own means of exporting the data in LISP or SDS. Or, you can also use VBA.)



You can extract information stored in the drawing as visible or invisible attributes... and use that data for analysis in a database or spreadsheet.

IntelliCAD provides in-place editing of Microsoft® objects, such as those created in Microsoft® Word and Microsoft® Excel software programs. In-place editing makes it easy to share data with other users and programs. For example, you can include IntelliCAD drawings in files created using Microsoft® Word, and you can insert files created using Microsoft® Word into your IntelliCAD drawings.

Using advanced CAD features

In addition to being compatible with AutoCAD, IntelliCAD goes several steps further by providing you with innovative features to increase your productivity.

Using the IntelliCAD Explorer

The IntelliCAD Explorer has an interface similar to the Windows Explorer, allowing you to view and manage the elements of multiple, open drawings, such as layers, blocks, linetypes, views, user coordinate systems, and text styles.

Editing multiple documents simultaneously

With IntelliCAD, you can open and edit multiple drawings simultaneously. You can also copy and paste elements between open drawings.

Editing multiple entities

IntelliCAD allows you to change most of the properties of all selected entities using a single, tabbed dialog box.

Using the Customize dialog box

IntelliCAD has a single, tabbed dialog box for changing toolbars, menus, keyboard shortcuts, and command aliases. You can also use the drag-and-drop method to customize toolbars, including flyouts. The simple, point-and-click action lets you easily create new menu items and keyboard shortcuts—no programming or manual text editing required.

Performing unlimited undo and redo

IntelliCAD increases your power with unlimited undo and redo of editing actions.

Getting more information

In addition to the IntelliCAD documentation, much of the assistance you need as you use IntelliCAD is specific to the commands you work with on the screen. To obtain immediate information as you work, use these additional sources of information:

ToolTips To find out what a specific tool on a toolbar does, pause the cursor over it for a moment. A ToolTip appears on the screen.

Status bar To find out more detailed information about a tool when you pause the cursor over it, look on the status bar at the bottom of the screen.

Online help IntelliCAD online help is available on the screen when you press F1, choose a command from the Help menu, or click the question mark in a dialog box. The online help also presents information that does not appear in this manual, including a programming reference that describes how to program in LISP, SDS, and DIESEL. The programming reference also describes programming in VBA.

What's new in IntelliCAD 6.0 – 6.5

What's new in IntelliCAD 6.5

Performance enhancements

Performance has been enhanced considerably when using real-time zoom, real-time pan, and saving drawings.

Toolbar and menu icons

The IntelliCAD user interface has been enhanced with new 24-bit icons for all color toolbar icons and menus.

Use polar tracking

Polar tracking is a new tool used to help you draw with precision. When polar tracking is turned on, guides display on the screen automatically at specified polar angle increments. For more details, see “Using polar tracking” on page 73.

Check the spelling of text

You can check the spelling of single-line text, multiline text, paragraph text, attributes, attribute definitions, and dimension text. Additional features include loading dictionaries from different sources, including various languages, and adding your own words to a custom dictionary.

For more details, see “Checking the spelling of text” on page 289.

Copy multiple entities

Now it's easier to copy multiple entities. IntelliCAD defaults to prompting for additional copies of selected entities during the Copy command. For details, see “Copying entities within a drawing” on page 242.

Work with additional image formats

The number of image formats available for drawings has been expanded. You can include images in the following formats: ECW, JPG 2000, ERS, ALG, HDR, DAT, DOQ, FST, NTF, ASC, IMG, DEM, DDF, DT0 and DT1, and HDF (including MET, L1R, and L1G).

For details about working with images, see “Using images in a drawing” on page 449.

Layer toolbar

You can now use the Layer toolbar to specify layout-specific layer settings. The Layer toolbar also displays more text, making it easier to use large layer lists. For details about working with layers, see “Organizing information on layers” on page 177.

Customize the status bar and menus using DIESEL

You can use DIESEL from the command line, in MNU menu files, and in LISP to customize the status bar and menus. For more details, see the Developer’s Reference online help.

Use new and enhanced system variables

New system variables include: AUTOSNAP, COPYMODE, DCTCUST, DCTMAIN, DCTMAINPATH, DIMTFAC, POLARADDANG, POLARANG, POLARDIST, POLARMODE, SNAPTYPE, and TRACKPATH.

What’s new in IntelliCAD 6.4**Work with the newest DWG 2007 format**

IntelliCAD supports the updated DWG 2007 format by opening, printing, and saving new entity types, such as annotations.

There are also many new system variables that are supported for DWG file compatibility only.

What’s new in IntelliCAD 6.3**Work with DWG 2007 files**

IntelliCAD supports opening, modifying, printing, and saving drawings in DWG 2007 format. The DWG 2007 format is now the default format in which IntelliCAD drawings are saved.

Create and edit color books

Now you can create and edit color books, which help you organize collections of colors, right from IntelliCAD. For more details, see “Using color books” on page 61.

Work with images

IntelliCAD Professional version includes enhanced imaging features to help you work with images in your drawings. Working with images is similar as in previous IntelliCAD versions, with easy-to-use features located on the Image menu in IntelliCAD. For more details, see “Using images in a drawing” on page 449.

Use new layout viewport features

There are several new features for layout viewports:

- Snap to model space entities from paper space.

- Lock layout viewports to lock the model space view or location while panning or zooming in paper space.
- Assign a unique UCS to a layout viewport.

For details, see “Working with layout viewports” on page 368.

Manage character sets for drawings

IntelliCAD allows you to manage which character set is assigned to a drawing. This unique feature can be very helpful when sharing or distributing drawings in geographic regions where several languages are used that require different character sets to display text properly. For details, see “Specifying character sets for drawings” on page 295.

Reverse the zoom direction of the mouse wheel

Instead of zooming in and out by moving the mouse wheel forward and backward, you can reverse the settings to zoom in when spinning the mouse wheel backward and zoom out when spinning the wheel forward. This can be especially helpful if you use the mouse with your left hand. For details, see “Changing the options on the Display tab” on page 480.

Use new and enhanced system variables

New system variables include: 3DDWFPREC, DIMARCSYM, DWGCODEPAGE, IMAGEHLT, RASTERVERNUM, RTDISPLAY, UCSVP, and ZOOMWHEEL.

Enhanced system variables include: DELOBJ, FACETRATIO, HALOGAP, HIDEPRECISION, OBSCUREDColor, OBSCUREDLTYPe, OLEQUALITY, and TEXTEVAL.

There are also many new system variables that are supported for DWG file compatibility only.

What’s new in IntelliCAD 6.2

Assign true colors and color book colors

You’ve always been able to add color to your drawings using index colors, but now you use two new color features:

- **True colors** — Defined using 24-bit color, there are more than 16 million true colors from which you can choose.
- **Color books** — Defined with a list of colors, color books help you organize collections of colors. For example, you can store a unique color scheme for a client in a color book and then use colors only from that color book for the client’s drawings.

For more details, see “Working with colors” on page 58.

Work with raster images using ADeko Raster

IntelliCAD Professional version includes new raster imaging software to help you work with images in your drawings. Working with raster images is similar to previous IntelliCAD versions, with easy-to-use features located on the Image menu in IntelliCAD. For more details, see “Using images in a drawing” on page 449.

Export to PDF and 3D DWF format

You can export drawings to two new formats:

- **PDF** — Portable Document Format files allow you to distribute your drawing to others for viewing with Adobe® Acrobat® Reader®, which is free software that users can download, and for viewing, reviewing, and editing with Adobe® Acrobat. For more details, see “Exporting to a PDF file” on page 468.
- **3D DWF** — 3D Design Web Format files can be viewed in a Web browser if Autodesk® DWF Viewer is also installed on the computer. DWF Viewer is a free tool from Autodesk® that always supported viewing 2D DWF files, but now supports viewing DWF files in three dimensions. For more details, see “Exporting to a DWF file” on page 470.

Use entity snaps

When using the extension option with Intersection Snap and Apparent Intersection Snap, IntelliCAD draws dashed extension lines to help guide you as you use the extension snap option. For more details, see “Using entity snaps” on page 74.

If you are working in the command bar, you can modify the active command by typing *m2p* or *mtp* to enable a one-time snap to the midpoint of two points that you specify. For details, see “Modifying a command” on page 34.

Edit text in the command line

The command bar and Prompt History window include enhanced text editing, including cutting, copying, and pasting text; copying the last command line or the entire command history; and repeating a previously executed command. For details, see “Starting commands using the command bar” on page 33. Also see “Using the Prompt History window” on page 34.

Create wipeout entities

Wipeouts are unique entities that can help you hide areas of your drawing. They display with the current background color, so the details behind the wipeout do not display or print. However, if your version of IntelliCAD does not include raster image capability (that is, does not include an Image menu), wipeout entities display, but the details behind the wipeouts also display. For details, see “Drawing wipeouts” on page 121.

Create audio notes from existing *.wav files

In addition to recording audio notes in IntelliCAD and attaching them to entities, you can now create audio notes from existing *.wav files. Audio notes created from an existing *.wav file are saved in the drawing file and the separate *.wav file remains unchanged. For details, see “Working with audio notes” on page 514.

View thumbnails of drawings

When you open or save a drawing, drawing files can be displayed in a number of ways, including by filename with or without the additional details. Now you can also view thumbnail images of drawing files. For details, see “Opening a drawing” on page 41.

You can also view thumbnail images when you browse drawing files on your computer using programs that came with your operating system, such as Windows File Explorer or My Computer.

Use new and enhanced system variables

New system variables include: AUDIOICONCOLOR, NOMUTT, OSNAPCOORD, OSNAPHATCH, OSNAPZ, and RTSKIPCOUNT.

Enhanced system variables include: CECOLOR and SNAPCOLOR.

What’s new in IntelliCAD 6.1**Create rendered images**

IntelliCAD uses new and enhanced rendering features to create higher-quality and more photo-realistic images of models.

Both IntelliCAD Standard and IntelliCAD Professional include the new rendering solution, while some versions provide additional rendering capabilities with a complete set of materials, backgrounds, lighting options, and render settings.

For details, see “Hiding, shading, and rendering” on page 441.

Format text

New formatting features are available when you enter text using Insert > Multiline Text. You can specify text color, first line indents, paragraph indents, right indents, and tabs.

For details, see “Creating paragraph text” on page 279.

Attach and record audio

IntelliCAD provides the unique ability to record audio notes, which are sound clips attached to entities and available for playback at any time. For example, audio notes in a factory floor plan can describe maintenance activities for specific areas of the factory — employees can play the audio notes to hear instructions.

For details, see “Working with audio notes” on page 514.

Work with 3D solids

In addition to slicing and sectioning solids, you can now slice regions and bodies (typically sheets).

For details, see “Sectioning and slicing solids” on page 431.

Use entity snaps

You can now snap to hatch patterns when using entity snaps:

- Snap to the middle points and end points of hatch pattern lines.
- Snap to the nearest point and perpendicular point on a hatch pattern line.
- Snap to any intersection point or apparent intersection point where the pattern line intersects with other entities that are supported by entity snaps.

For details, see “Using entity snaps” on page 74.

Use new system variables

New system variables include: AUDIOICON, AUDIOICONCOLOR, and AUDIOICONSCALE.

What’s new in IntelliCAD 6.0

Utilize performance enhancements

Many IntelliCAD features include increased performance. The following table describes the main enhancements and estimated performance increases.

Feature	Performance increase
True Type Fonts	
Pan	4X (400%)
Zoom	7X (700%)
Polylines	
Pedit	50X (5000%)
Linetypes	
Zoom extents	7X (700%)
Pan	10X (1000%)
Regen	7X (700%)
Hatch Patterns	
Regen	50X (5000%)
LISP Performance	10X (1000%)
General	
Blocks	
Symbol table search	7X (700%)
Regen	7X (700%)
Viewports	
Regen	4X (400%)
Model space	4X (400%)
Block display	4X (400%)
Paper space	3X (300%)

Assign print style tables

The following printing features have greatly enhanced flexibility and control over the printing process:

- Previously you could use the PenMap/Width mapping to associate colors with specific pen widths on your printer. New print style tables allow you to still specify color-based settings, but also allow you to specify pen widths, linetypes, and lineweight regardless of color.
- Print style tables (.ctb and .stb files) are stored in files; you can share the files across multiple drawing files or with other users.

Print style tables affect numerous existing features, including: New Drawing and New Drawing Wizard; Properties and Entity Properties toolbar; Change; IntelliCAD Explorer (Layers); Drawing Settings > Entity Creation tab; Status bar; Options > Paths/Files tab; Options > Printing tab; and Print > Advanced tab.

There are also several new commands for print style tables: Print Style (*printstyle*), Print Styles Manager (*stylesmanager*), Convert Drawing Print Style Tables (*convertpstyles*), and Convert CTB Print Style Table (*convertctb*).

For details, see “Using print styles” on page 379.

Manage external references

Attaching and working with external references is now easier with the new Xref Manager. You can view a detailed list of the referenced drawing, or you can view a hierarchical display that shows how drawings are nested and related to one another. Quickly attach, detach, reload, bind, open, and change the path for all external references in the current drawing.

The Xref Manager allows you to use the same external reference features as in previous versions of IntelliCAD, but in a more efficient manner.

For details, see “Working with external references” on page 348.

Work with 3D solids

IntelliCAD Standard version now supports viewing and limited editing of 3D solids, including moving, rotating, and scaling. IntelliCAD Professional version still allows you to create and more completely edit 3D solids.

For details, see Chapter 15, “Drawing in three dimensions.”

Use entity snaps

The existing Intersection Snap has a new Extended option, which snaps to the logical location where two entities would intersect if they were of infinite length.

The new Apparent Intersection Snap tool snaps to the intersection of two entities that are not in the same plane but seem to intersect in the current view. You can also use its Extended option, which snaps to the logical location where two entities would intersect if they were of infinite length.

For details, see “Using entity snaps” on page 74.

Customize more options

The following features are new to the Tools > Options dialog box:

- **General tab** Set the default Save As format. Specify how drawings are opened.
- **Paths/Files tab** Specify search paths for print style tables.
- **Display tab** Use Up/Down arrows in the command history. Show or hide the Model and Layout tabs. Show or hide scroll bars.
- **Profiles tab** Create and manage drawing environment profiles.
- **Printing tab** Specify headers and footers for all drawings. Assign default print style table settings for new drawings.

For details, see “Setting and changing options” on page 476.

Save and restore drawing environment profiles

Customize the settings that control your drawing environment, and then save and restore those settings in a profile. For example, if you prefer working with custom menus and toolbars, you can save these settings as your own profile.

Profiles can be helpful if you have multiple users with different preferences, or if you are a single user who works on various projects that require unique settings. You can even export your profile and bring it with you when you work on a different computer.

For details, see “Changing the options on the Profiles tab” on page 484.

Navigate model space and paper space

Use the enhanced Model/Paper Space control in the status bar to switch more efficiently between model space and paper space on either the Model tab or a Layout tab. For details, see “Viewing drawings in paper space and model space” on page 364.

You can also change the display of the Model and Layout tabs in the following ways:

- Show or hide the Model and Layout tabs. For details, see “Displaying the Model and Layout tabs” on page 365.
- Reorder the position of the Layout tabs. For details, see “Managing layouts in a drawing” on page 367.

Work in the command bar

In the command bar, you can do the following:

- Select text, and then right-click to copy, cut, and paste.
- Press Ctrl + K and Ctrl + L to move forward and backward in the command history.
- Use the Up and Down arrows to scroll the command history, if enabled by choosing Tools > Options.

For details, see “Repeating a command” on page 33. Also see “Using the Prompt History window” on page 34.

Choose single IntelliCAD sessions

Use the new Single Session command (type *singleton*) to choose whether IntelliCAD can be started one time or multiple times simultaneously.

Use new system variables

New system variables include: APBOX, CPLOTSTYLE, CTRLMOUSE, DEFLPSTYLE, DEFPLSTYLE, DEFPLSTYLETBL, FONTALT, PSTYLEMODE, PSTYLEPOLICY, MBUTTONPAN, SAVEROUNDTRIP, and SHOWTABS.

Getting started

This section helps you get started using IntelliCAD software by explaining how to install it and providing basic information about how to use it.

NOTE *This guide assumes that you have used other Windows-based programs and are familiar with Windows terminology and techniques.*

Topics in this chapter

<i>System requirements</i>	24
<i>Installing IntelliCAD</i>	24
<i>Starting IntelliCAD</i>	25
<i>Working in IntelliCAD</i>	25
<i>Selecting commands</i>	32
<i>Correcting mistakes</i>	36
<i>Customizing IntelliCAD</i>	36
<i>Getting online Help</i>	37
<i>Saving your drawing</i>	37
<i>Exiting IntelliCAD</i>	37

System requirements

You need the following software and hardware to install and run IntelliCAD:

- Microsoft® Windows Vista®, Windows XP Professional, Windows XP Professional x64 Edition, Windows XP Home Edition, Windows 2000, or Windows® 98
- 300 megahertz (MHz) or faster processor recommended; 233 MHz minimum required (single or dual processor)
- 1 gigabyte (GB) of RAM minimum for Windows Vista
512 megabytes (MB) of RAM minimum for Windows XP and Windows 2000
- 1.5 GB of free hard disk space recommended; 160 MB is required for a full installation, including sample files, electronic documentation, and online Help
- Super VGA (800 x 600) or higher resolution, video adapter, and monitor
- Keyboard and mouse, or other pointing device
- CD-ROM or DVD drive for installation, if installing from a CD or DVD

Installing IntelliCAD

A setup program guides you through the IntelliCAD installation process. The program transfers files to a folder that it creates on your hard disk. The program also creates a menu item on the Start menu.

Installation starts automatically after you insert the IntelliCAD compact disc into your CD-ROM drive. If installation does not start, you can install IntelliCAD by using the following procedure.

To install IntelliCAD from a compact disc

- 1 Insert the IntelliCAD compact disc into your CD-ROM drive.
- 2 Do one of the following:
 - Wait for the autorun feature to start.
 - Choose Start > Run and in the Open field, type *d:\setup*, where *d* is the letter assigned to your CD-ROM drive. Click OK.
- 3 Follow the instructions on your screen.

NOTE *If you did not receive an IntelliCAD compact disc, for example, if you downloaded the program from the Internet, follow the instructions that came with the program.*

Starting IntelliCAD

To start IntelliCAD, choose Start > Programs > ITC > IntelliCAD (may vary, depending on your operating system).


When you start IntelliCAD, the program opens a new, blank drawing based on a default template, `icad.dwt`. Using a template as the basis for a new drawing has several advantages:

- You can use predetermined units of measure, grid settings, text heights, and other settings appropriate for the type of drawing you're creating.
- You can predefine special layers.
- You can predefine the type of print style table.
- You can include predefined title blocks and borders.

Each time you start IntelliCAD, a Tip of the Day appears on your screen. To display the Tip of the Day dialog box at any time, choose Help > Tip of the Day. To prevent the Tip of the Day dialog box from being displayed, click the check box for Show Tips On StartUp to clear it.

Working in IntelliCAD

You can work with the IntelliCAD window and its elements in a variety of ways. For example, you can display and rearrange the toolbars, display the command bar, and enable the status bar. The toolbars and command bar can also be floated anywhere on the screen or docked to the edges of the main IntelliCAD window.



- A You can customize the menu bar at the top of the window.
- B You can customize the toolbars, changing the appearance and arrangement of tools and adding your own commands and macros.
- C Your drawings are displayed in the drawing window.
- D Click a tab to switch between the drawing of your model and a printed layout.
- E You can type commands in the command bar. To reposition the command bar, drag it to another location on your screen.
- F The status bar displays information such as the name or purpose of a tool, the current cursor coordinates, layer name, and mode settings.
- G The user coordinate system (UCS) icon indicates the orientation of the drawing in three-dimensional space.
- H You can move and dock the toolbars to any location on your screen.

Displaying commands on a shortcut menu

Shortcut menus provide quick access to specific commands. A shortcut menu displays when you right-click an entity, toolbar, status bar, the Model tab name, or a Layout tab name. The selections presented in the shortcut menu depend on what you clicked.

When you right-click a toolbar, the program displays a shortcut menu that lets you toggle the command bar, status bar, and various toolbars on and off. If you select one or more entities and then right-click, the program displays a shortcut menu from which you can choose a command to modify the selected entities. To display a shortcut menu from which you can choose an entity snap, press and hold down the Shift key, and then right-click anywhere within the drawing window.

Displaying and hiding toolbars

When you start IntelliCAD the first time, multiple toolbars are displayed. IntelliCAD provides more than a dozen toolbars, which you can customize by adding and deleting tools. You can also move and resize toolbars, and you can create new toolbars. You can use a shortcut menu to display or hide toolbars.


You can also choose whether toolbars are displayed large or small and in color. You can choose to display or hide ToolTips, which provide descriptions of tools that display when you pause the cursor over them. Go to View > Toolbars to make these selections.

Toolbars are either docked or floating. A floating toolbar has a title bar and a Close box, can be located anywhere on the screen, and can be resized. A docked toolbar does not display a title or Close box, cannot be resized, and is attached along one of the edges of the drawing window.

- To dock a toolbar, drag it to the perimeter of your drawing; to undock it, drag it away from the perimeter.
- To position a toolbar in a docking area without docking it, press Ctrl while you drag it.
- To move a toolbar, drag it to a new location.
- To resize a toolbar, move your cursor to the edge until it changes to a resize arrow, and then drag.

To choose which toolbars to display

- 1 Do one of the following:
 - Choose View > Toolbars.
 - Right-click anywhere on a docked toolbar to display the toolbar shortcut menu, and then choose Toolbars. You can also select the toolbars you want displayed directly on the shortcut menu.
- 2 In the Select Toolbars dialog box, choose the toolbars you want displayed, and then click OK.



Select the check boxes for the toolbars you want to display.

Using the command bar


The command bar is a dockable window in which you type IntelliCAD commands and view prompts and other program messages. To display the command bar, choose View > Command Bar. The command bar displays the three most recent lines of prompts. You can move the command bar by dragging it.

When the command bar is floating, you can drag the top or bottom of the window to change the number of lines of text it displays. You can dock the command bar at the top or bottom of the drawing.

Using the status bar

If you elect not to use the command bar, the status bar displays information about the selected command or tool. It also displays the current cursor coordinates, the name of the current layer, mode settings, and other information about current settings.

In addition to displaying information, the status bar is a quick way to access many features. You can click status bar items to make changes, and right-click items to display short-cut menus that allow you more choices.



- | | |
|---|--|
| A Information about the current command. | J Snap setting. Double-click to toggle on or off. |
| B Cursor coordinates (x,y,z). | K Grid setting. Double-click to toggle on or off. |
| C Layer name. Double-click to change layers. | L Orthogonal setting. Double-click to toggle on or off. |
| D Drawing color. Double-click to change colors. | M Polar tracking setting. Double-click to toggle on or off. |
| E Linetype. By default, the linetype is BYLAYER. Double-click to change linetypes. | N Entity snap setting. Double-click to select entity snaps. |
| F Lineweight. By default, the lineweight is BYLAYER. Double-click to change lineweights. | O Lineweight display. Double-click to toggle on or off. |
| G Text style. Double-click to change text styles. | P Model space or paper space. Double-click to toggle between model space and paper space. |
| H Dimension style. Double-click to change dimension styles. | Q Digitizer mode. Double-click to toggle on or off. |
| I Print style. Double-click to change print styles. (Available only for drawings that use named print style tables.) | |

To change the items that display on the status bar

- 1 Right-click an empty area of the status bar.
- 2 Select an item to add or remove it.

To change the setting of an item on the status bar


- 1 Do one of the following:
 - Double-click the status bar item.
 - Right-click the status bar item you want to change, and then select the desired setting.

To display or hide the status bar

- 1 Do one of the following:
 - Choose View > Status Bar.
 - Type *statbar* and then press Enter.


Using prompt boxes

IntelliCAD commands often provide several options. These options appear in the status bar or command bar and also in a prompt box (called a *context menu* in AutoCAD) initially displayed in the upper right corner of the screen. You can move the prompt box by dragging it; future prompt boxes will appear where you last placed it. The options appear as menu selections. Choose the appropriate option by selecting it in the prompt box. To close a prompt box, click the Close box.



Command options appear in a prompt box.

The prompt box is displayed by default. To turn off the display of prompt boxes, choose Tools > Options, click the Display tab, and then click the Display Prompt Boxes check box to clear it.



The IntelliCAD user interface.

Selecting commands

Select commands using any of these methods:

- Choose a command from a menu.
- Click a tool in a toolbar.
- Type the command in the command bar.

Some commands remain active until you end them, so you can repeat an action without having to select a command repeatedly. You can end a command by clicking Done in the prompt box or by pressing Esc.

Using commands

You can use most commands while another command is active. For example, while drawing a line, you may want to use the Pan command to move the drawing across the screen to select the endpoint of the line. You can also change the settings of drawing aids such as snap or grid while other commands are active.

Starting commands using toolbars

To start a command from a toolbar, click a tool and respond to the prompts.

NOTE *The available toolbars depend on the experience level that is set. To change the current experience level, choose Tools > Options, and then click the General tab.*

Some tools, such as Line or Arc, contain flyouts, which are options either for using the basic tool with different methods or that contain other, related tools. Flyouts are indicated by a small triangle in the lower right corner of a tool. To display a flyout, click the tool and hold down the mouse button. To select a tool from a flyout, point to the tool you want and then release the mouse button. The tool you select on the flyout becomes the default tool on the toolbar.

Starting commands using menus

To start a command from a menu, choose it from the list of menu options available.

The available menu options depend on the experience level that is set. To change the current experience level, choose Tools > Options, and then click the General tab.

Starting commands using the command bar

Type a command, and then press Enter. If the command bar is displayed, the command you typed appears there. If the command bar is not displayed, the command you typed appears in the status bar.

TIP *Quickly start commands using the command bar by copying, cutting, and pasting text. In the command bar or Prompt History window, right-click to select various cut, copy, and paste commands.*

Repeating a command

You can repeat a command you used previously without having to reselect it.

To repeat the command you just used

- 1 Do one of the following:
 - Press the spacebar.
 - Press Enter.
 - Click the right mouse button in the drawing.

To repeat commands you used previously

- 1 Do one of the following:
 - In the command bar or Prompt History window, press Ctrl and double-click the previous command text.
 - In the command bar or Prompt History window, right-click, choose Recent Commands, and then choose the desired command.
 - Press Ctrl + K, repeat until you get back to the desired command, and then press Enter. Press Ctrl + L to move forward to the desired command, and then press Enter.
 - Use the Up and Down arrows to display previously used commands, if Use Up/Down Arrows for Command History Navigation is selected in Tools > Options.

TIP *If you are using the command bar to type commands, you can type multiple before starting some commands (Circle, Arc, and Rectangle, for example) to repeat a command indefinitely. When you are done with a command, press Esc.*

Nesting a command

If you are working in the command bar, you can use another command from within a command, called *nesting*. To use a command inside an active command, type an apostrophe before you type the command, such as 'circle, 'line, or 'pyramid. You can nest commands indefinitely in IntelliCAD. Many menu and toolbar macros work this way by default; for example, select color, reference grid, zoom, and snap. When you have finished with the nested command, the original command resumes.

Modifying a command

If you are working in the command bar, there are special ways that you can modify a command as you work. You can modify the active command using any of the following options:

- **Entity snaps** — Type an entity snap command, such as *nearest* or *midpoint*, to enable a one-time entity snap for a single selection. You can also use a one-time entity snap to override a running entity snap.
- **Extension snaps** — Type *int* after selecting a command, such as Line or Circle, to enable a one-time snap to the logical location where two entities would intersect if they were of infinite length. Type *app* to enable a similar one-time snap if the extensions would not intersect in three-dimensional space but would intersect in the current view.
- **Midpoint snaps** — Type *m2p* or *mtp* to enable a one-time snap to the midpoint of two points that you specify.

Using the Prompt History window

The Prompt History window displays a history of the commands and prompts issued since you started the current session of IntelliCAD. By default, the program tracks up to 256 command lines. There is no limit to the number of command lines you can track, but program performance may be degraded if you choose to track an excessively high number of lines.

To display or close the Prompt History window

- Press F2.

To view entries in the Prompt History window

- 1 Do one of the following:
 - Use the scroll bars.
 - Press Ctrl + K to browse backward; press Ctrl + L to browse forward.
 - Use the Up and Down arrows to display previously used commands, if Use Up/Down Arrows for Command History Navigation is selected in Tools > Options.

To copy or paste text in the Prompt History window

- 1 If copying text, do one of the following:
 - Highlight text using your mouse.
 - Press Ctrl + Shift + arrow keys to highlight text.
- 2 Right-click and choose whether to copy or paste.

TIP You can also copy the entire command history by choosing *Copy History* or copy the last command line by choosing *Copy Last Line*.

To change the number of command lines to track

- 1 Do one of the following:
 - Choose Tools > Options, and then click the Display tab.
 - Type *options* and then press Enter. Click the Display tab.
- 2 In the Command Lines To Track field, type the number of command lines you want to display, and then click OK.

Using mouse shortcuts

You can use your mouse, often combined with the keyboard, to start commands and perform other actions.

Mouse shortcuts

Shortcut	Action
Ctrl + Shift + Hold and drag left mouse button	Real-Time Zoom command
Ctrl + Shift + Hold and drag right mouse button	Real-Time Pan command
Ctrl + Hold and drag left mouse button	Real-Time Sphere command
Ctrl + Hold and drag right mouse button	Real-Time Z command
Shift + Left-click mouse	Deselect entities
Shift + Right-click mouse	Entity snap shortcut menu
Hold and drag left mouse button	Move selected entities
Ctrl + Hold and drag left mouse button	Copy and move selected entities
Right-click mouse	Display shortcut menu for the selected entity
Rotate mouse wheel	Zoom In and Zoom Out commands
Hold mouse wheel, and then move mouse	Pan command

Using scripts

The IntelliCAD Script Recorder captures and saves many of your actions so you can play them back. After you enable the Script Recorder, all commands and options that you type in the command bar are recorded until you type a command to stop recording. When you run the script, the program carries out the recorded commands in succession.

Correcting mistakes

IntelliCAD tracks the commands you use and the changes you make. If you change your mind or make a mistake, you can undo, or reverse, the last action or several previous actions. You can also redo any actions that you reversed.



- A** Click the Undo tool to reverse the last action.
B Click the Redo tool to reverse the previous undos.

You can undo multiple actions by typing *undo* and specifying the number of actions to undo.

Customizing IntelliCAD

You can tailor many aspects of IntelliCAD to better suit your needs. For example, you can easily create and modify toolbars by simply dragging and dropping icons. If you want to restore any area of the user interface back to its default state, click Reset. IntelliCAD stores your customized settings in the Windows registry; you can also store them in a separate file, called a profile.

IntelliCAD supports the most important AutoCAD customization files, including linetypes, hatch patterns, text fonts, the unit conversion file, menus, toolbars, and aliases. In addition, IntelliCAD unifies four AutoCAD customization functions with a single *customize* command: command aliases, keyboard shortcuts, menus, and toolbars.


You can also add custom programs written in any of several programming languages, including the following:

- LISP (the program's Autodesk® AutoLISP-compatible language)
- SDS (the program's Autodesk® ADS-compatible language)
- DIESEL
- Microsoft® Visual Basic for Applications (VBA)

Getting online Help

IntelliCAD includes online Help, which contains task-oriented topics, a command reference, a system variables reference, and a programming language reference.


You can display online Help in any of these ways:

- On the Standard toolbar, click Help (.
- Press F1.
- Choose a command from the Help menu.
- Click the question mark in a dialog box.
- Type *help* in the command bar.

Saving your drawing

You can save your drawing at any time.

To save a drawing, use one of the following methods:

- On the Standard toolbar, click Save (.
- Choose File > Save.
- Type *save* and then press Enter.

TIP When you save a drawing the first time, the program displays the *Save Drawing As* dialog box so that you can choose a directory and type a name for the drawing. To save the drawing later using another name, choose File > Save As and type the new name.

Exiting IntelliCAD

When you have finished working in IntelliCAD, choose File > Exit.

Working with drawings

CAD drawings help you organize information for greater efficiency. With IntelliCAD, you can draw entities representing different types of information on various layers and use those layers to control color, linetype, and visibility. IntelliCAD also includes drawing aids that help you draw accurately.

This section explains setting up drawings and using built-in drawing aids, including how to:

- Create new drawings, open existing drawings, and save changes to drawings.
- Use aids such as the grid, snap, and orthogonal settings to draw accurately.

Topics in this chapter

<i>Creating a new drawing</i>	40
<i>Opening a drawing</i>	41
<i>Setting up a drawing</i>	44
<i>Working with colors</i>	58
<i>Using the grid, snap alignment, and cursor restriction</i>	66
<i>Using orthogonal locking</i>	72
<i>Using entity snaps</i>	74
<i>Saving your drawing</i>	85

Creating a new drawing

When you start IntelliCAD, the program automatically creates a new drawing based on a template drawing, `icad.dwt`. This template includes predefined settings such as drawing units, text size, print style table type, and drawing area. You can either use these settings or change them according to your needs. There is nothing unique about a template drawing. You can use any drawing as a template for future drawings.

You can save many steps by basing a new drawing on an existing template (`.dwt` file). By doing this, a new drawing will contain all the settings and entities you need. When you open a new drawing from your custom template, you can modify existing settings and delete any entities that you don't need. When you save a drawing that was created using a template, you do not change the template.

To create a new drawing based on a template

- 1 Do one of the following:
 - Choose File > New.
 - Type `newwiz` and then press Enter.
- 2 Click Use A Template Drawing, and then click Next.
- 3 To display the Open Template dialog box, click Browse.
- 4 Select the template (`.dwt`) file that you want, and then click Open.
You can also choose any drawing (`.dwg`) file to use as a template.
- 5 Click Finish.

Opening a drawing

You can open drawing (.dwg) files, Drawing Exchange Format (.dxf) files, Design Web Format™ (.dwf) files, and drawing template (.dwt) files.


You can also open and check drawings that you suspect are damaged.

Opening an existing drawing

You can open any of these drawing files:


- Standard drawing files with a .dwg extension.
In addition to your own drawing files, you can open and use one of the sample drawings that are included with IntelliCAD.
- Drawing Exchange Format files with a .dxf file extension.
- Design Web Format files with a .dwf file extension.
- Drawing templates with a .dwt file extension.

To open an existing drawing

- 1 Use one of the following methods:
 - Choose File > Open.
 - On the Standard toolbar, click the Open tool ().
 - Type *open* and then press Enter.
- 2 In Files of Type, choose the type of file you want to open.
- 3 Choose the folder containing the desired file.
- 4 Do one of the following:
 - Choose the drawing you want to open, and then click Open.
 - Double-click the drawing you want to open.

If the drawing requires a password, enter the password, click OK to verify the password, and then click Open again.

TIP You can also open drawings while browsing files on your computer using programs that came with your operating system, such as Windows File Explorer or My Computer. Simply double click the file to open it in IntelliCAD. Easily find the drawing you want by viewing thumbnail images of the drawing files as you browse them.



- A** Displays a description of the file size, creation date, and other information about the drawing.
- B** Opens the drawing as read-only to prevent making changes to the file.
- C** Turns the drawing preview on or off.
- D** Unavailable when opening drawings; available only when saving drawings.
- E** If a thumbnail image exists in the selected drawing, displays an image of the drawing before you open it.
- F** Defines how drawings display in the list, including file details and thumbnail images.

TIP To quickly open a drawing file that you recently used, choose **File > <file name>**. The program tracks the last four drawings.

Opening damaged files

Files can become damaged for many reasons. For example, if you are working on a drawing during a power outage, a system crash, or a hardware failure, your drawing file may become damaged. IntelliCAD allows you to open and check damaged files to attempt file recovery.

Recovering a file attempts to open one of the following file types:

- Standard drawing files with a .dwg extension.
- Drawing Exchange Format files with a .dxf file extension.
- Design Web Format files with a .dwt file extension.
- Drawing templates with a .dwt file extension.

You can also audit any open file to check it for errors. You specify whether you want IntelliCAD to fix any errors that are found automatically. IntelliCAD fixes as many errors as possible and any errors that cannot be fixed are reported as “Ignored” in the Prompt History window.

To open a damaged file

- 1 Use one of the following methods:
 - Choose File > Recover.
 - Type *recover* and then press Enter.
- 2 In Files of Type, choose the type of file you want to recover.
- 3 Choose the directory containing the damaged file.
- 4 Choose the damaged file you want to recover.
- 5 Click Open.

If you want to check all drawings for errors automatically when you open them, choose Tools > Options > General tab and mark the check box for Open Drawings using Recover.

To check a drawing file for errors

- 1 With the drawing open that you want to check, do one of the following:
 - Choose File > Audit.
 - Type *audit* and then press Enter.
- 2 Choose whether you want IntelliCAD to fix any found errors automatically, and then press Enter.

NOTE *If the AUDITCTL system variable is set to On and errors are found during a file recovery or audit, an ASCII file is created that describes the audit. The ASCII file is saved in the same folder as the audited drawing and has the same name as the drawing file, but with an .adt extension.*


Setting up a drawing


You can specify individual settings when you create a new drawing or when you modify settings in a drawing created from a template.

Setting the current layer

Layers are like the overlays that you use in manual drafting. You use layers to organize different types of drawing information. Every drawing has at least one layer, the default layer, named “0.” Your drawing can also contain an unlimited number of additional layers. When you create an entity, it is created on the current layer.

To set the current layer

- Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
 - Type *la* and then press Enter.
- Double-click the layer name that you want to make current.
- Close the IntelliCAD Explorer window.



Double-click the layer name that you want to make current.

TIP On the status bar, right-click on the current layer control, and from the list, select the layer you want to make current.


Setting the current entity color

An entity's color determines how it is displayed and, if you are using a color printer, how it prints. Entities are created in the current color.

When you open a new drawing, entities are created in the color BYLAYER, which adopts the color of the current layer. Initially, layer 0 is both the only layer and the current layer. Its default color is white, so your entities appear as white.

There are index colors, which contain two additional color properties that are often referred to as colors, true colors, and color book colors. The two additional color properties are BYLAYER and BYBLOCK. These color properties cause an entity to adopt the color either of the layer or of the block in which it is a member.

To set the current entity color

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool () .
 - Type *settings* and then press Enter.
- 2 Click the Entity Creation tab.
- 3 Click Select Color.
- 4 In the Color dialog box, click one of the following tabs and select a color:
 - **Index Color** — Click BYBLOCK, BYLAYER, or one of the 255 index colors. You can also type the color number in the Index box.
 - **True Color** — Click a basic color, click a color in the color palette, enter the Hue, Saturation, and Luminance (HSL) values, or enter the Red, Green, Blue (RGB) values. There are more than 16 million true colors from which you can choose.
 - **Color Books** — Select a color book from the list, then click a color. You can select Show Only Color Book Colors Used in Drawing to limit the selection to only those color book colors that are used in the current drawing.
- 5 Click OK.
- 6 Click OK again.

TIP *On the status bar, right-click on the current color, and select from the list the color you want to use for new entities. You can also click Select Color to choose additional colors.*

For more details about using color in the many aspects of your drawing, see “Working with colors” on page 58 in this chapter.

Setting the current linetype


Linetypes help convey information. You use different linetypes to differentiate the purpose of one line from another. A linetype consists of a repeating pattern of dots, dashes, or blank spaces. Linetypes determine the appearance of entities both on the screen and when printed. By default, every drawing has at least three linetypes: CONTINUOUS, BYLAYER, and BYBLOCK. Your drawing may also contain an unlimited number of additional linetypes.

When you create an entity, it is created using the current linetype. By default, the current linetype is BYLAYER. IntelliCAD indicates that the entity linetype is determined by the current layer's linetype by assigning the BYLAYER property as the default linetype setting. When you assign BYLAYER, changing a layer's linetype changes the linetype of all the entities assigned that layer (if they were created using the linetype BYLAYER).

You can also select a specific linetype as the current linetype, which overrides the layer's linetype setting. Entities are then created using that linetype, and changing the layer linetype has no effect on them.

As a third option, you can use the linetype BYBLOCK property, in which case new entities are drawn using the CONTINUOUS linetype until you group them into a block. The entities then inherit the block's linetype setting when you insert the block into a drawing.

To set the current linetype

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool () .
 - Type *settings* and then press Enter.
- 2 Click the Entity Creation tab.
- 3 In the Entity Linetype list, choose the linetype that you want to make current.
- 4 Click OK.

TIP *On the status bar, right-click the word BYLAYER for the current linetype, click Properties, and then choose the linetype that you want to make current.*


Setting the linetype scale

You can specify the linetype scale. The smaller the scale, the more repetitions of the linetype pattern are generated per drawing unit. For example, a linetype pattern is defined as a sequence of dashed lines and open spaces, each 0.25 units long. The linetype scale uses the drawing scale factor to determine the length. A scale factor of 0.5 would reduce the length of each line and space to 0.125 units; a scale factor of 2 would increase the length of each to 0.5 units.


NOTE *Setting the linetype scale too large or too small may result in a line pattern looking like a solid line, depending on what the scale view is or at what scale the drawing is printed.*

You can control a new entity's individual linetype scale factor as well as the overall or global scale factor applied to all the entities in the drawing.

To set the current individual linetype scale

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool (.
 - Type *settings* and then press Enter.
- 2 Click the Entity Creation tab.
- 3 In the Linetype Scale field, type or choose the linetype scale that you want to make current.
- 4 Click OK.

To change the global linetype scale

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool (.
 - Type *settings* and then press Enter.
- 2 Click the Entity Creation tab.
- 3 In the Global Linetype Scale field, type or choose the global linetype scale that you want to change.
- 4 Click OK.

Setting the current lineweight

Lineweights help differentiate the purpose of one line from another. Lineweights determine how thick or thin entities appear both on the screen and when printed. Every drawing has these lineweights: DEFAULT, BYLAYER, BYBLOCK, and many additional lineweights in millimeters (or you can use inches).

When you create an entity, it is created using the current lineweight. By default, the current lineweight for a new entity is BYLAYER. This means that the entity lineweight is determined by the current layer. When you assign BYLAYER, changing a layer's lineweight changes the lineweight of all the entities assigned that layer (if they were created using the lineweight BYLAYER).


You can also select a specific lineweight (or DEFAULT) as the current lineweight, which overrides the layer's lineweight setting. Entities are then created using that lineweight (or the DEFAULT lineweight), and changing the layer lineweight has no effect on them.

As a third option, you can use the lineweight BYBLOCK property, in which case new entities are drawn using the DEFAULT lineweight until you group them into a block. The entities then inherit the block's lineweight setting when you insert the block into a drawing.

If you choose a lineweight that is less than .025 millimeter, it displays as one pixel when you create your drawing. When you print your drawing, it prints at the thinnest lineweight that is available for your printer.

You cannot assign lineweights to planes, points, TrueType fonts, or raster images (if supported in your version of IntelliCAD).

To set the current lineweight

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool () .
 - Type *settings* and then press Enter.
- 2 Click the Entity Creation tab.
- 3 In the Lineweight list, choose the lineweight that you want to make current.
- 4 Click OK.

TIP *On the status bar, right-click the word BYLAYER for the current lineweight, and then choose the current lineweight. You can also double-click the word LWT to toggle the display of lineweights on and off.*

NOTE *To see lineweights in your drawing, you may need to turn on lineweights. For details, see see “Controlling the display of lineweights” on page 154.*

Setting the current print style

Print styles are used to change the appearance of an entity when it prints, without actually changing the entity in the drawing.


If your drawing uses named print style tables, you can specify a print style for any entity. Named print style tables contain print styles that you set up. If your drawing uses color-dependent print style tables, the print style is BYCOLOR, which cannot be changed. These types of print style tables determine printing requirements by the color assigned to an entity or layer. For details about converting a drawing that uses color-dependent print style tables to use named print style tables, see “Changing a drawing’s print style table type” on page 387.

When you create an entity in a drawing that uses named print style tables, the entity is created using the current print style. By default, the current print style is BYLAYER. When you assign BYLAYER, changing a layer’s print style changes the print style of all the entities assigned that layer if they were created using the print style BYLAYER.

You can also select a specific print style as the current print style, which overrides the layer’s print style setting. Entities are then created using that print style, and changing the layer print style has no effect on them.

As a third option, you can use the print style BYBLOCK, in which case new entities use the Normal print style until you group them into a block. The entities then inherit the block’s print style setting when you insert the block into a drawing.

To set the current print style in a drawing that uses named print style tables

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool () .
 - Type *settings* and then press Enter.
- 2 Click the Entity Creation tab.
- 3 In the Print Style list, choose the print style that you want to make current. If necessary, choose Other and then select a print style.
- 4 Click OK.


TIP *On the status bar, right-click the word BYLAYER for the current print style, click Other, and then choose the print style that you want to make current. Or, type printstyle to choose the current print style.*

Setting drawing units

With IntelliCAD, you typically draw at full-size (1:1 scale), and then set a scale factor when you print or plot your drawing. Before you begin drawing, however, you need to determine the relationship between drawing units and real-world units.


For example, you can decide whether one linear drawing unit represents an inch, a foot, a meter, or a mile. In addition, you can specify the way the program measures angles. For both linear and angular units, you can also set the degree of display precision, such as the number of decimal places or smallest denominator used when displaying fractions. The precision settings affect only the *display* of distances, angles, and coordinates. IntelliCAD always stores distances, angles, and coordinates using floating-point accuracy.

To set the linear drawing units

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool ().
 - Type *settings* and then press Enter.
- 2 Click the Drawing Units tab.
- 3 Under Change Settings For, choose Linear Units.
- 4 Under Unit Types, select a unit type.
- 5 Under Display Precision, type the display precision according to the number of decimal places you want, or click the arrows to select it.

The field above this setting shows an example of the linear unit type at the current precision.


- 6 Click OK.



A Select the type of linear units.


B Choose the display precision for linear units.

To set the angular drawing units

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool () .
 - Type *settings* and then press Enter.
- 2 Click the Drawing Units tab.
- 3 Under Change Settings For, choose Angular Units.
- 4 Under Unit Types, select a unit type.
- 5 Under Display Precision, type the display precision according to the number of decimal places you want, or click the arrows to select it.

The field above this setting shows an example of the angular unit type at the current precision.

- 6 Under Angle Direction, select the direction in which angles increase when you specify a positive angle value.
- 7 Under Angle Base, specify the compass location for the zero angle.
For example, by default, angle 0 is at the “three o’clock” or “east” position.
The adjacent icon shows the current location of the angle base.
- 8 Click OK.



- | | |
|---|--|
| <p>A Determines the type of units you are controlling.</p> <p>B Select the type of angular units.</p> <p>C Choose the display precision for angular units.</p> | <p>D Select the direction in which angles increase.</p> <p>E Select the angle base, the direction of the zero angle.</p> |
|---|--|

Understanding scale factors

Instead of drawing to a particular scale, you draw everything in the program full-size. Although it's a good idea to keep your scale factor in mind when setting up a drawing, you don't need to set the scale until you print it. For example, when you draw a mechanical part 40 inches in length with IntelliCAD, you actually draw it as 40 inches, rather than applying a scale factor as you draw. When you print your drawing, you can assign the scale at which the drawing is to print.

Scale, however, does affect the way a few elements such as text, arrows, or linetypes print or plot in your drawing. For these, you can make adjustments when you first set up your drawing so that they print or plot at the correct size. For example, when you draw text, you need to determine the text size so that when you print it later at a particular scale, the text height is correct.

After you determine the eventual scale of your finished drawing, you can calculate the scale factor for the drawing as a ratio of one drawing unit to the actual scale unit represented by each drawing unit. For example, if you plan to print your drawing at $1/8" = 1'-0"$, your scale factor ratio is 1:96 ($1/8" = 12"$ is the same as $1 = 96$). If you want your printed scale to be 1 inch = 100 feet, your scale factor ratio is 1:1200.

The following table shows some standard architectural and engineering scale ratios and equivalent text heights required to create text that measures 1/8-inch high when you print the drawing at the specified scale.

Standard scale ratios and equivalent text heights

Scale	Scale factor	Text height
$1/16" = 1'-0"$	192	24"
$1/8" = 1'-0"$	96	12"
$3/16" = 1'-0"$	64	8"
$1/4" = 1'-0"$	48	6"
$3/8" = 1'-0"$	32	4"
$1/2" = 1'-0"$	24	3"
$3/4" = 1'-0"$	16	2"
$1" = 1'-0"$	12	1.5"
$1\ 1/2" = 1'-0"$	8	1"
$3" = 1'-0"$	4	0.5"
$1" = 10'$	120	15"
$1" = 20'$	240	30"
$1" = 30'$	360	45"
$1" = 40'$	480	60"
$1" = 50'$	600	75"
$1" = 60'$	720	90"
$1" = 100'$	1200	150"

You can use these scale factors to predetermine the size of your drawing to make sure that it fits on a specific size paper when you print it. You control the size of your drawing by the drawing limits. To calculate the drawing limits to match the size of your paper, multiply the dimensions of your paper size by your scale factor.

For example, if the paper you use to print measures 36 inches x 24 inches and you print your drawing at $1/8'' = 1'-0''$ (in other words, using a scale factor of 96), the size of your drawing measured in drawing units is 36 x 96 (or 3,456 units) wide and 24 x 96 (or 2,304 units) high.


Keep in mind that you can print the finished drawing at any scale, regardless of the scale factor you calculate. You can also print on paper of a different size and use the Layout tabs to create different views of your drawing and to position and scale those views differently. The scaling factor is not related to the size of the entities you draw; it simply provides a preliminary guide to help you establish the text height and drawing limits when you begin your drawing. You can change the text height and drawing limits at any time.


Setting the text height

The text height setting controls the height of text, measured in drawing units. Set this value initially so that text used for your most common annotations, when scaled to the size at which you will print a drawing, measures 1/8-inch high on the printed drawing.

For example, if you plan to print your drawing at $1/8'' = 1'-0''$ and you want your text to be 1/8-inch high in the final drawing, create that text 1 foot high (in your real-world drawing units) so that when you print it, it appears 1/8-inch high on the paper. You must create text 4 feet high that you want to print 1/2-inch high.

To set the text height

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool () .
 - Type *settings* and then press Enter.
- 2 Click the Entity Creation tab.
- 3 Under Change Settings For, choose Text.
- 4 In the Default Text Height field, select the text height or type the text height value that you want.
- 5 Click OK.



A Choose Text.

B Specify the text height in drawing units.


NOTE *The default text height applies only if the current text style height is 0.0. Otherwise, the text height for the current style takes precedence.*

Setting the drawing limits


You can specify the drawing limits that form an invisible boundary around your drawing. You can use the drawing limits to make sure that you do not create a drawing larger than can fit on a specific sheet of paper when printed at a specific scale.

For example, if you plan to print your drawing at $1/8" = 1'-0"$ (in other words, using a scale factor of 96) on a sheet of paper measuring 36 inches x 24 inches, you can set drawing limits to 3,264 units wide (that is, 34×96) and 2,112 units high (22×96), which allows a 1-inch margin around the edges of the printed image.

To set the drawing limits

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool ()
 - Type *settings* and then press Enter.
- 2 Click either the Coordinate Input tab or the Display tab.
- 3 Under Change Settings For, choose Limits.
- 4 Specify the x-coordinate and y-coordinate of the upper right drawing limit and the lower left drawing limit.

You can also click Select to specify the drawing limits by selecting points in the drawing.
- 5 To constrain your drawing to these drawing limits, click the Disallow Input Beyond Limits check box.
- 6 Click OK.



- A** Choose limits.
- B** Specify the x-coordinate and y-coordinate of the upper right drawing limit.
- C** Specify the x-coordinate and y-coordinate of the lower left drawing limit.
- D** When you click this check box, the program prevents you from drawing outside the drawing limits.
- E** Specify the drawing limits by selecting points in the drawing.

Working with colors

An entity's color determines how it is displayed and, if you are using a color printer, how it prints. Entities are created in the current color specified for the drawing.

Layers can also control the color of entities. When you open a new drawing, entities are created in the color BYLAYER, which adopts the color of the current layer. Initially, layer 0 is both the only layer and the current layer. Its default color is white, so your entities appear as white.

For entities and layers in IntelliCAD, there are three different types of colors:

- Index colors
- True colors
- Color book colors

NOTE *True colors and color books are unavailable in some cases, such as dimension entities and cursor display.*


You can choose colors by selecting them from the Color dialog box. In the command bar or in some dialog boxes, you specify a color either by name or by number.

Using index colors

There are 255 standard index colors and two additional color properties that are often referred to as colors (BYLAYER and BYBLOCK). You can use seven of the 255 standard index colors by name: red, yellow, green, cyan, blue, magenta, and white. (Numbers eight and nine are not named.) Each index color has a unique number from 1 to 255. The two additional color properties are BYLAYER and BYBLOCK. These color properties cause an entity to adopt the color either of the layer or of the block in which it is a member. BYLAYER is color number 256, and BYBLOCK is color number 0. In all commands for which you would use a color, you can indicate BYLAYER and BYBLOCK as well as by numbers 256 and 0, respectively.

To select an index color

- 1 Click Select Color in the desired dialog box, such as Layers, Drawing Settings, Properties, or Multiline Text.
The Color dialog box opens.
- 2 Click the Index Color tab.
- 3 Do one of the following:
 - Click BYBLOCK.
 - Click BYLAYER.
 - Click the color of your choice, or type the color number in the Current box.
- 4 Click OK.



- | | |
|--|--|
| <p>A Click to select one of the standard colors.</p> <p>B Click to select one of the gray shades.</p> <p>C Click to select any one of the available index colors.</p> | <p>D Indicates the current color.</p> <p>E Displays the color number, or enter the color number.</p> <p>F Click to set the color to BYLAYER.</p> <p>G Click to set the color to BYBLOCK.</p> |
|--|--|

Using true colors


There are more than 16 million true colors from which you can choose. True colors are defined using 24-bit color.

Even with so many colors available, you can quickly choose a color from the display of basic colors or by clicking the color palette. Alternatively, if you know the values used to define the desired color, you can enter the Hue, Saturation, and Luminance (HSL) values, or you can enter the Red, Green, Blue (RGB) values.

To select a true color

- 1 Click Select Color in the desired dialog box, such as Layers, Drawing Settings, Properties, or Multiline Text.
The Color dialog box opens.
- 2 Click the True Color tab.

- 3 Do one of the following:
 - Click a basic true color.
 - Click a true color in the color palette.
 - Enter HSL values for the desired true color.
 - Enter RGB values for the desired true color.
- 4 Click OK.






- | | |
|--|--|
| <p>A Click to select one of the basic true colors.</p> <p>B Click to select one of the custom true colors, if any are defined.</p> <p>C Click to add the selected color to the custom color area.</p> <p>D Enter (or view) the amount of red, green, and blue of the desired true color.</p> | <p>E Enter (or view) the amount of hue, saturation, and luminance of the desired true color.</p> <p>F Slide or click to adjust the color luminance.</p> <p>G Click to select a true color in the color palette.</p> |
|--|--|

Using color books


IntelliCAD uses color books to store collections of colors. For example, you can store a unique color scheme for a client in a color book and then use colors only from that color book for the client's drawings.

To select a color book color

- 1 Click Select Color in the desired dialog box, such as Layers, Drawing Settings, Properties, or Multiline Text.
The Color dialog box opens.
- 2 Click the Color Books tab.
- 3 Select a color book from the list.
- 4 If you want to narrow your color search, do one of the following:
 - In the list of colors, select a color book page, if one is available. Pages are particularly helpful in large color books — they help group colors so you can find them quickly.
 - Select Show Only Color Book Colors Used in Drawing. Only those color book colors that are used in the current drawing will display in the list.
- 5 Select the desired color.
- 6 Click OK.

- 6 Do the following to define organizational pages in the color book:
 - In the contents of the color book, click an existing page or color where you want to add a page.
 - Define a color in the palette.
 - Enter the name of the page, and then click Add Page.
- 7 Do the following to define colors in the color book:
 - In the contents of the color book, click an existing page or color where you want to add a color.
 - Define a color in the palette.
 - Enter the name of the color, and then click Add Color.
- 8 Do any of the following to change existing pages and colors in the color book:
 - Modify pages and colors — Select a page or color in the color book, define its new color settings in the palette, enter any changes to its name, and then click Modify.
 - Delete pages and colors — Select a page or color in the color book, and then click Delete.
 - Rearrange pages and colors — Select a page or color in the color book, and then click the up arrow () or down arrow ().
- 9 In the Color Book Editor dialog box, click the Save tool ().
- 10 Enter a filename for the color book, and then click Save.

By default, the file is saved in the default folder where IntelliCAD searches for color books.







- A** Click New to create a color book; click Open to open a color book; click Save to save the color book; click Save As to save the color book with a new filename.
- B** Select a page or color to modify, delete, or reorder it, or to view its settings.
- C** Click to create a new page in the color book using the current color settings.
- D** Click to create a new color in the color book using the current color settings.
- E** Click to delete the selected page or color from the color book.
- F** Click to redefine the selected page or color to use the current color settings.
- G** Click to move the selected page or color up or down one position in the color book.
- H** Enter the name of the page or color as you want it to appear in the color book.
- I** Enter (or view) the amount of red, green, and blue of the desired color.
- J** Enter (or view) the amount of hue, saturation, and luminance of the desired color.
- K** Slide or click to adjust the color luminance.
- L** Click to select a color.
- M** Enter the name of the color book.

Modifying color books

You can modify your own color books and the color books that came with IntelliCAD. If you modify a color book that came with IntelliCAD, it is recommended that you save it with a new filename first so the original color book is not overwritten.

To modify a color book

- 1 Click Select Color in the desired dialog box, such as Layers, Drawing Settings, Properties, or Multiline Text.
The Color dialog box opens.
- 2 Click the Color Books tab.
- 3 Select the color book you want to modify.
- 4 Click Color Book Editor.
- 5 In Color Book Name, enter any changes to the color book name. This name appears in the list of color books on the Color Books tab in the Color dialog box.
- 6 Do any of the following to modify pages or colors in the color book:
 - Add pages — In the contents of the color book, click an existing page or color where you want to add a page. Define a color in the palette, enter the name of the page, and then click Add.
 - Add colors — In the contents of the color book, click an existing page or color where you want to add a color. Define a color in the palette, enter the name of the color, and then click Add.
 - Modify pages and colors — Select a page or color in the color book, define its new color settings in the palette, enter any changes to its name, and then click Modify.
 - Delete pages and colors — Select a page or color in the color book, and then click Delete.
 - Rearrange pages and colors — Select a page or color in the color book, and then click the up arrow () or down arrow ().
- 7 Do one of the following to save the color book:
 - To save the color book with the same filename, click the Save tool () in the Color Book Editor.
 - To save the color book with a new filename or in a new location, click the Save As tool () in the Color Book Editor.

Loading color books

If you have a color book given to you by a client or developed by a third-party, simply save it on your computer in a folder where IntelliCAD can find it. By default, color books are stored in following folder: \Documents and Settings\YourName\My Documents\Color Books.

To load a color book

- 1 Save the color book in the folder where IntelliCAD searches for color books.

To verify the folder location, choose Tools > Options, click the Paths/Files tab, and find the Color Book folder in the Paths list.

- 2 In a Color dialog box, click the Color Books tab.

The previously loaded color book displays in the list of color books.

Using the grid, snap alignment, and cursor restriction

Grid and snap settings are effective tools to use in your drawing to ensure accuracy. Although many users find it convenient to match grid points to snap settings, they are independent of each other and should not be confused. Grid points are for visual reference only; they do not affect your drawing and they do not print. Snap points are, by themselves, not visible; however, when set, they constrain the creation of new entities.


In addition, the cursor can be restricted to move orthogonally only or guides can display on the screen automatically at specified polar angle increments.


Setting a reference grid


A reference grid displays as a pattern of regularly spaced dots. You can turn the display on and off, and you can specify how far apart the dots are spaced.

The reference grid extends only to the limits of the drawing, helping you to visualize the boundary of your drawing and to align entities and visualize distances between entities. You can turn the grid on and off as needed. You can also change the spacing of the grid at any time.

To turn the grid on and set the grid spacing

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool () .
 - Type *settings* and then press Enter.
- 2 Click the Coordinate Input tab.
- 3 Under Change Settings For, choose Snap And Grid.
- 4 Under Reference Grid, click the Show Grid check box.
- 5 Under Reference Grid Spacing, in the X field, choose the horizontal grid spacing.
- 6 Under Reference Grid Spacing, in the Y field, choose the vertical grid spacing.
- 7 Click OK.

TIP To toggle the grid display on and off at any time, double-click the *GRID* setting on the status bar, click the Reference Grid tool () on the Settings toolbar, or press *F7*.





- A** Click the check box to enable orthogonal mode.
- B** Click the check box to display the reference grid.
- C** Specify the x and y grid spacing.
- D** Click the check box to enable snap mode.
- E** Specify the x and y snap spacing.
- F** Click the check box to use an isometric snap and grid.
- G** Click the current isometric plane.
- H** Specify the grid rotation angle.
- I** Indicates the current grid rotation angle.
- J** Specify the x- and y-coordinates of the snap origin.
- K** Click to match the grid spacing to the snap spacing.

Setting snap spacing

Another way to ensure drawing accuracy is to turn on and set snap spacing. When snap is turned on, the program restricts the selection points to predetermined snap intervals. Although it is often helpful to match the snap spacing to some interval of the grid spacing or another related setting, the settings do not have to match.

To turn snap settings on and set snap spacing

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool () .
 - Type *settings* and then press Enter.
- 2 Click the Coordinate Input tab.
- 3 Under Change Settings For, choose Snap And Grid.
- 4 Under Snap Settings, click the Snap check box to turn Snap on.
- 5 Under Snap Settings Spacing, in the X field, choose the horizontal snap spacing.
- 6 Under Snap Settings Spacing, in the Y field, choose the vertical snap spacing.
- 7 Click OK.


TIP To toggle snap settings on and off at any time, double-click the *SNAP* setting on the status bar, click the Snap tool () on the Settings toolbar, or press F9.


In addition to setting the snap spacing, you can change the snap and grid orientation. You can also rotate the alignment of the grid or set it to create isometric drawings.

Changing the snap and grid angle and base point


The snap and grid are both normally based on the drawing origin, the 0,0 coordinate in the World Coordinate System (WCS). You can relocate the snap and grid origin, however, to help you draw entities in relation to a different location. You can also rotate the grid to a different angle to realign the crosshairs to the new grid angle. If the grid is on, and the grid spacing is 0,0, then the grid defaults to the snap spacing.

To change the snap angle and base point

- 1 Do one of the following:
 - Click Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool ()
 - Type *settings* and then press Enter.
- 2 Click the Coordinate Input tab.
- 3 Under Change Settings For, select Snap And Grid.
- 4 Under Snap Settings, click the Snap check box to turn Snap on.
- 5 Under Reference Grid, click the Show Grid check box to turn Show Grid on.
- 6 Under Snap And Grid Settings, in the X Origin field, type the x-coordinate of the new snap origin.
- 7 Under Snap And Grid Settings, in the Y Origin field, type the y-coordinate of the new snap origin.
- 8 Under Snap And Grid Settings, in the Rotation field, type the grid rotation angle.
- 9 Click OK.



Default grid and snap alignment.



Rotated grid and snap alignment.

Using isometric snap and grid


You can use the Isometric Snap And Grid option to create two-dimensional isometric drawings. With the isometric option, you are simply drawing a simulated three-dimensional view on a two-dimensional plane, much the same as you might draw on a piece of paper. Do not confuse isometric drawings with three-dimensional drawings. You create three-dimensional drawings in three-dimensional space.


The isometric option always uses three preset planes, which are denoted as left, right, and top. You cannot alter the arrangement of these planes. If the snap angle is 0, the three isometric axes are 30 degrees, 90 degrees, and 150 degrees.

When you check the Isometric Snap And Grid option and select an isometric plane, the snap intervals, grid, and crosshairs align with the current plane. The grid is always shown as isometric and uses y-coordinates to calculate the grid spacing. If you click the Draw Orthogonal check box, the program restricts the drawing of entities to the current isometric plane.

TIP To toggle between isometric planes, press F5.

To turn the Isometric Snap And Grid option on

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool ().
 - Type *settings* and then press Enter.
- 2 Click the Coordinate Input tab.
- 3 Under Change Settings For, select Snap And Grid.
- 4 Click the Isometric Snap And Grid check box.
- 5 Under Isometric Crosshairs, click the option for the isometric plane you want (Top, Left, or Right).
- 6 Click OK.




Isometric planes left (A), right (B), top (C).


Using orthogonal locking

You can restrict cursor movement to the current horizontal and vertical axes so that you can draw at right angles, or orthogonally. For example, with the default 0-degree orientation (angle 0 at the “three o’clock” or “east” position), when the Draw Orthogonal option is enabled, lines are restricted to 0 degrees, 90 degrees, 180 degrees, or 270 degrees. As you draw lines, the rubber-banding line follows either the horizontal or vertical axis, depending on which axis is farthest from the cursor. When you enable the isometric snap and grid, cursor movement is restricted to orthogonal equivalents within the current isometric plane.

NOTE *IntelliCAD ignores orthogonal drawing when you type coordinates in the command bar or when you use entity snaps. Additionally, orthogonal locking and polar tracking cannot be used at the same time — turning one option on turns the other option off.*

To enable orthogonal locking

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool ()
 - Type *settings* and then press Enter.
- 2 Click the Coordinate Input tab.
- 3 Click the Draw Orthogonal check box.
- 4 Click OK.


TIP *To toggle orthogonal drawing on and off at any time, double-click the ORTHO setting on the status bar, click the Draw Orthogonal tool () on the Settings toolbar, or press F8.*

Using polar tracking

When polar tracking is turned on, guides display on the screen automatically at the polar angle increment that you specify. For example, if you draw a line with polar tracking turned on at 45 degrees, the rubber-banding line displays at 45 degree angle increments.

Polar tracking and orthogonal locking cannot be used at the same time — turning one option on turns the other option off.

To enable polar tracking and specify the polar angle increment

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool ().
 - Type *settings* and then press Enter.
- 2 Click the Coordinate Input tab.
- 3 Under Change Settings For, select Polar Tracking.
- 4 Click the Polar Tracking check box.
- 5 Do one of the following to specify the polar angle increments:
 - In Increment, select an angle.
 - Mark the Additional Angles check box and click New to define a custom angle increment.
- 6 Click OK.

TIP To toggle polar tracking on and off at any time, double-click the POLAR setting on the status bar.

Using entity snaps

Entity snaps enable you to quickly select exact geometric points on existing entities without having to know the exact coordinates of those points. With entity snaps, you can select the endpoint of a line or arc, the center point of a circle, the intersection of any two entities, or any other geometrically significant position. You can also use entity snaps to draw entities that are tangent or perpendicular to an existing entity.

You can use entity snaps any time the program prompts you to specify a point—for example, if you are drawing a line or other entity. You can work with entity snaps in one of two ways:

- Enable a running entity snap that remains in effect until you turn it off by choosing an entity snap when no other command is active.
- Enable a one-time entity snap for a single selection by choosing an entity snap when another command is active. You can also use a one-time entity snap to override a running entity snap.


TIP *If you type the name of the entity snap, you need to type only the first three letters.*


When using entity snaps, the program recognizes only visible entities or visible portions of entities. You cannot snap to entities on layers that have been turned off or to the blank portions of dashed lines.

When you specify one or more entity snaps, an entity snap target box is added to the crosshairs. In addition, an icon appears adjacent to the crosshairs indicating the active entity snap. When you select an entity, the program snaps to the snap point closest to the center of the target box.

TIP *Type m2p or mtp to enable a one-time snap to the midpoint of two points that you specify, such as two points selected using entity snaps.*

To change the size of the entity snap target box

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool ()
 - Type *settings* and then press Enter.
- 2 Click the Coordinate Input tab.
- 3 Under Change Settings For, choose Entity Selection.
- 4 Under Entity Snap Aperture, change the value in the Aperture field.
- 5 Click OK.



A Choose Entity Selection.

B Type or select the entity snap aperture size.

Setting entity snaps

You can set entity snaps using any of the following methods:

- Choose Settings > Entity Snap, and choose the entity snap you want to set.
- On the Entity Snaps toolbar, click one of the entity snap tools.
- In the command bar, type an entity snap command.
- In the status bar, double-click ESNAP.
- Press and hold down the Shift key while right-clicking anywhere within the drawing window to display the entity snap shortcut menu, and then choose the entity snap you want to set.

You can also set entity snaps using the Drawing Settings dialog box. To do this, choose Settings > Entity Snap > Entity Snap Settings. The Drawing Settings dialog box is displayed with the Coordinate Input tab active. In the Entity Snap Modes list, click the check box for each of the entity snaps that you want to set.


TIP When you select an entity snap, a check mark appears next to the entity snap in the menu, the associated tool if the Entity Snaps toolbar is active, and the corresponding box is checked in the Coordinate tab of the Drawing Settings dialog box.

Nearest Snap tool

Use the Nearest Snap tool to snap to the nearest point of another entity. You can snap to the nearest point on an arc, circle, ellipse, elliptical arc, line, point, polyline segment, ray, spline, infinite line, or hatch pattern that is visually closest to the cursor.

To set the Nearest Snap

Do one of the following:


- Choose Settings > Entity Snap > Nearest Snap.
- On the Entity Snaps toolbar, click the Set Nearest Snap tool ().
- Type *nearest* and then press Enter.


Endpoint Snap tool

Use the Endpoint Snap tool to snap to the endpoint of another entity. You can snap to the closest endpoint of an arc, line, polyline segment, ray, hatch pattern, plane, or three-dimensional face. If an entity has thickness, the Endpoint Snap also snaps to the endpoints of the edges of the entity.

To set the Endpoint Snap

Do one of the following:

- Choose Settings > Entity Snap > Endpoint Snap.
- On the Entity Snaps toolbar, click the Set Endpoint Snap tool ().
- Type *endpoint* and then press Enter.




To snap to the endpoint, select anywhere on the entity near its endpoint (A).


Midpoint Snap tool

Use the Midpoint Snap tool to snap to the midpoint of another entity. You can snap to the midpoint of an arc, ellipse, line, polyline segment, plane, infinite line, spline, or hatch pattern. In the case of infinite lines, the midpoint snaps to the first defined point. If an entity has thickness, the midpoint entity snap also snaps to the midpoint of the edges of the entity.

To set the Midpoint Snap

Do one of the following:

- Choose Settings > Entity Snap > Midpoint Snap.
- On the Entity Snaps toolbar, click the Set Midpoint Snap tool ().
- Type *midpoint* and then press Enter.




To snap to the midpoint, select anywhere on the entity near its midpoint (**A**).


Center Snap tool

Use the Center Snap tool to snap to the center point of another entity. You can snap to the center of an arc, circle, polygon, ellipse, or elliptical arc. To snap to the center, you must select a visible portion of the entity.

To set the Center Snap

Do one of the following:

- Choose Settings > Entity Snap > Center Snap.
- On the Entity Snaps toolbar, click the Set Center Snap tool (.
- Type *center* and then press Enter.




To snap to the center, select anywhere on the visible portion of the entity (**A**).


Perpendicular Snap tool

Use the Perpendicular Snap tool to snap to the perpendicular point of another entity. You can snap to an arc, circle, ellipse, line, polyline, infinite line, ray, spline, hatch pattern, or edge of a plane to form a perpendicular alignment with that entity or with an imaginary extension of that entity.

To set the Perpendicular Snap

Do one of the following:

- Choose Settings > Entity Snap > Perpendicular Snap.
- On the Entity Snaps toolbar, click the Set Perpendicular Snap tool (.
- Type *perpendicular* and then press Enter.




To form a perpendicular angle (**A**) to an entity (**B**), select anywhere on the entity.


Tangent Snap tool

Use the Tangent Snap tool to snap to the tangent point of another entity. You can snap to the point on an arc, ellipse, spline, or circle that, when connected to the previous point, forms a line tangent to that entity.

To set the Tangent Snap

Do one of the following:

- Choose Settings > Entity Snap > Tangent Snap.
- On the Entity Snaps toolbar, click the Set Tangent Snap tool ().
- Type *tangent* and then press Enter.




To snap to a tangent, select the entity near the tangent point (**A**).


Quadrant Snap tool

Use the Quadrant Snap tool to snap to the quadrant point of another entity. You can snap to the closest quadrant of an arc, circle, ellipse, or elliptical arc.

To set the Quadrant Snap

Do one of the following:

- Choose Settings > Entity Snap > Quadrant Snap.
- On the Entity Snaps toolbar, click the Set Quadrant Snap tool ().
- Type *quadrant* and then press Enter.




To snap to a quadrant, select the entity near the quadrant point (A).


Insertion Point Snap tool

Use the Insertion Point Snap tool to snap to the insertion point of an attribute, block, or text entity.

To set the Insertion Point Snap

Do one of the following:

- Choose Settings > Entity Snap > Insertion Point Snap.
- On the Entity Snaps toolbar, click the Set Insertion Point Snap tool ().
- Type *insertion* and then press Enter.




To snap to an insertion point, select anywhere on the entity (A).


Point Snap tool

Use the Point Snap tool to snap to a point entity.

To set the Point Snap

Do one of the following:

- Choose Settings > Entity Snap > Point Snap.
- On the Entity Snaps toolbar, click the Set Point Snap tool ().
- Type *node* and then press Enter.



To snap to a point entity, select the entity (A).

Intersection Snap tool


The Intersection Snap tool snaps to the actual intersection in three-dimensional space of any combination of entities. You can snap to the combination of an arc, circle, line, infinite line, polyline, ray, ellipse, elliptical arc, spline, hatch pattern, polygon mesh, or polyface mesh. You can also snap to an intersection point within a single entity, including a polyline or spline.


The Extended Intersection Snap option snaps to the logical location where two entities (lines, arcs, or elliptical segments) would intersect if they were of infinite length. IntelliCAD automatically uses the extension option only when you type *int* in the command bar (not the full *intersection* command name) after selecting a command, such as Line or Circle. Dashed extension lines are drawn to help show the extended intersection.

NOTE *There are two types of intersection snaps. You can set the Intersection Snap or Apparent Intersection Snap, but you cannot use both at the same time.*

To set the Intersection Snap

Do one of the following:

- Choose Settings > Entity Snap > Intersection Snap.
- On the Entity Snaps toolbar, click the Set Intersection Snap tool ().
- Type *intersection* and then press Enter.



To snap to an intersection, select the intersection (A).

To snap to an extended intersection point

- 1 Choose a command, for example, *line*.
- 2 Type *int* and then press Enter.
- 3 Select an extended intersection point.

The Extended Intersection Snap turns off automatically after you select a point.

Apparent Intersection Snap tool


The Apparent Intersection Snap tool snaps to the intersection of two entities that do not intersect in three-dimensional space but seem to intersect in the current view. You can snap to any two entities in the combination of an arc, circle, line, infinite line, polyline, ray, ellipse, elliptical arc, spline, hatch pattern, polygon mesh, or polyface mesh. You can also snap to an intersection point within a single entity, including a polyline or spline.


The Extended Apparent Intersection Snap option snaps to the logical location where two entities (lines, arcs, or elliptical segments) would intersect if they were of infinite length. IntelliCAD automatically uses the extension option only when you type *app* in the command bar (not the full *apparent* command name) after selecting a command, such as Line or Circle. Dashed extension lines are drawn to help show the extended apparent intersection.

NOTE *There are two types of intersection snaps. You can set the Apparent Intersection Snap or Intersection Snap, but you cannot use both at the same time.*

To set the Apparent Intersection Snap

Do one of the following:

- Choose Settings > Entity Snap > Apparent Intersection Snap.
- On the Entity Snaps toolbar, click the Apparent Intersection Snap tool (.
- Type *apparent* and then press Enter.



To snap to an intersection, select the apparent intersection (A).

To snap to an extended apparent intersection point

- 1 Choose a command, for example, *line*.
- 2 Type *app* and then press Enter.
- 3 Select an extended apparent intersection point.

The Extended Apparent Intersection Snap turns off automatically after you select a point.

Quick Snap command

Normally, an entity snap searches all the entities crossing the target and selects the one closest to the center of the target. Use the Quick Snap command to modify the current entity snap so that the program stops searching for the snap point as soon as it finds one entity with at least one point of the current entity type.

To set the Quick Snap

- Type *quick* and then press Enter.

Clear Entity Snaps tool

Use the Clear Entity Snaps tool to turn off all entity snap settings, regardless of how they were set: by menu, tool, command, or in the Drawing Settings dialog box.

To set Clear Entity Snaps

Do one of the following:












- Choose Settings > Entity Snap > Clear Entity Snaps.
- On the Entity Snaps toolbar, click the Clear Entity Snaps tool (✖).
- Type *none* and then press Enter.

Using fly-over snapping


Fly-over snapping is a visual aid to help you see and use entity snaps more efficiently. When fly-over snapping is turned on, IntelliCAD displays a colored marker at matching entity snap points as you move the crosshairs around the drawing.

Each entity snap has its own marker.


Fly-over snap markers

Marker	Entity snap
	Endpoint Snap
	Nearest Snap
	Midpoint Snap
	Center Snap
	Perpendicular Snap
	Tangent Snap
	Quadrant Snap
	Insertion Snap
	Point Snap
	Intersection Snap
	Apparent Intersection Snap

When fly-over snapping is enabled and multiple entity snaps are on, you can press Tab to cycle through the available entity snap points of the entities covered by the target box. For example, when the Endpoint and Midpoint Snaps are on and the aperture box is located on a line, press Tab to cycle between the line's closest endpoint and midpoint.



To set the fly-over snapping options

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - Choose Settings > Entity Snap > Entity Snap Settings.
 - On the Settings toolbar, click the Drawing Settings tool ()
 - Type *settings* and then press Enter.
- 2 Click the Coordinate Input tab.
- 3 Click Fly-Over. The Options dialog box opens to the Snapping tab.
- 4 Mark Enable Fly-Over Snapping to turn on fly-over snapping.
- 5 Set the fly-over options, including the color, size, and thickness of the snap marker.
- 6 Click OK.
- 7 Click OK again.

NOTE For details about the various fly-over snapping options, see “Changing the options on the Snapping tab” on page 490.

Saving your drawing

When you save a drawing, your work is saved in a drawing (.dwg) file.


After you have saved your drawing for the first time, you can save it with a new name. In addition to drawing (.dwg) files, you can also save a drawing in a Drawing Exchange Format (.dxf) file or a drawing template (.dwt) file.

If you created your drawing using a template, saving the drawing does not alter the original template.


If you need an added level of security for your drawing files, you can save the drawing with a password so only you and those who know the password can open the drawing.

Saving a drawing

To save a drawing, choose any of the following methods:

- Choose File > Save.
- On the Standard toolbar, click Save ()
- Type *save* and then press Enter.
- Type *qsave* and then press Enter.

TIP When you save a drawing the first time, the program displays the Save Drawing As dialog box so that you can choose a directory and type a name for the drawing. You can use any name when you first save the drawing.



- A** Displays a description of the file size, creation date, and other information about the drawing.
- B** Unavailable when saving drawings; available only when opening drawings.
- C** Turns the drawing preview on or off.
- D** Saves the drawing with a password.
- E** Displays an image of the drawing before you save it.

Saving a drawing with a new name or file format

You can save a drawing with a new name and in any of the following file formats:

- Standard drawing files with a .dwg extension. You can choose a .dwg file format that is compatible with various versions of AutoCAD.
- Drawing Exchange Format files with a .dxf file extension. You can choose a .dxf file format that is compatible with various versions of AutoCAD.
- Drawing templates with a .dwt file extension. Drawing templates allow you to easily create new drawings that reuse your drawing settings and entities.

To save a drawing with a new name or file format

- 1 Do one of the following:
 - Choose File > Save As.
 - Type *saveas* and then press Enter.
- 2 In the Save Drawing As dialog box, under Save As Type, choose the file format.
- 3 Specify the name of the file you want to create.
- 4 Click Save.

TIP You can also export drawing files to various file formats. For more details, see “Exporting drawings” on page 467.

Saving a drawing with a password

Sometimes drawings may contain confidential information and you want to control who has access to that information. If you need an added level of security, you can save a drawing with a password so only you and those who know the password can open the drawing.

To save a drawing with a password, you must save it in the DWG 2004, or later, drawing (.dwg) file format.

NOTE If you forget a drawing’s password, the drawing cannot be opened or recovered. You may want to store all passwords in a safe place.

To save a drawing with a password

- 1 Do one of the following:
 - Choose File > Save As.
 - Type *saveas* and then press Enter.
- 2 In the Save Drawing As dialog box, under Save As Type, choose a DWG format that is 2004 or later.
- 3 Click Password Protect.
- 4 Choose a folder where you want to save the drawing.
- 5 In File Name, specify the name of the file you want to create.
- 6 Click Save.
- 7 In the Password dialog box, enter a password.
- 8 If desired, record and store the password in a safe place. If you forget the drawing’s password, the drawing cannot be opened or recovered.
- 9 Click OK.

Creating simple entities

With IntelliCAD, simple entities include lines (both finite and infinite), circles, arcs, ellipses, elliptical arcs, points, and rays. In addition, IntelliCAD includes a freehand sketch tool. Entities drawn freehand are also considered to be simple entities.

This section explains several methods for creating simple entities, including how to:

- Use menu commands on the Insert menu.
- Use the tools on the Draw 2D toolbar.
- Type commands in the command bar.

In some cases, there are a number of different ways to create an entity. For the most part, one or two are given here. Refer to the online Help to learn how to create entities using other methods.

When you use a tool or a drawing command, the program prompts you to enter coordinate points, such as endpoints or insertion points. You can enter the points or distances either using a mouse or by typing coordinate values in the command bar. As you draw, IntelliCAD also displays a context-sensitive prompt box with appropriate additional options for the type of entity you are drawing.

After you create entities, you can modify them using the entity modification tools.


Topics in this chapter


<i>Drawing lines</i>	90
<i>Drawing circles</i>	91
<i>Drawing arcs</i>	93
<i>Drawing ellipses</i>	96
<i>Drawing elliptical arcs</i>	97
<i>Creating point entities</i>	98
<i>Drawing rays</i>	100
<i>Drawing infinite lines</i>	101
<i>Creating freehand sketches</i>	103

Drawing lines

A line consists of two points: a start point and an endpoint. You can connect a series of lines, but each line segment is considered a separate line entity.

To draw a line

- 1 Do one of the following:
 - Choose Insert > Line.
 - On the Draw 2D toolbar, click the Line tool ().
 - Type *line* and then press Enter.
- 2 Specify the start point.
- 3 Specify the endpoint.
- 4 In the prompt box, choose Done to complete the command.





Start point (A) and endpoint (B).

The prompt box provides several options as you draw. For example, when you draw the first line segment, you can specify its length or orientation angle. After you draw at least one line segment, you can click Undo to remove the previous line segment. You can click Done to end the line command. After you draw two or more line segments, you can click Close to complete the line command by drawing a line segment that connects to the start point of the first line segment you drew.

If the last entity you drew was an arc, you can also draw a line tangent to and starting from the endpoint of the arc.

To draw a line as a continuation from the end of an arc







- 1 Do one of the following:
 - Choose Insert > Line.
 - On the Draw 2D toolbar, click the Line tool ().
 - Type *line* and then press Enter.
- 2 In the prompt box, choose Follow.
- 3 Specify the length of the line.




Endpoint of previous arc (A) and length of the line (B).


Drawing circles

The default method for drawing a circle is to specify a center point and radius. You can draw circles using any of the following methods:

- Center-Radius ()
- Center-Diameter ()
- Two points ()
- Three points ()
- Radius-Tangent-Tangent ()
- Convert Arc to Circle ()


To draw a circle by specifying its center and radius


- 1 Do one of the following:
 - Choose Insert > Circle.
 - On the Draw 2D toolbar, click the Circle Center-Radius tool ().
 - Type *circle* and then press Enter.
- 2 Specify the center point.
- 3 Specify the radius of the circle.



Center point (A) and radius (B).


To draw a circle tangent to existing entities


- 1 Do one of the following:
 - Choose Insert > Circle.
 - On the Draw 2D toolbar, click the Circle Radius-Tangent tool (). Go to step 3.
 - Type *circle* and then press Enter.
- 2 In the prompt box, choose Radius-Tangent-Tangent.
- 3 Specify the radius of the circle.
- 4 Select the first entity to which to draw the circle tangent.
- 5 Select the second entity to which to draw the circle tangent.



Radius of circle (A) and tangent lines (B) and (C).

To convert an arc to a circle


















- 1 Do one of the following:
 - Choose Insert > Circle.
 - On the Draw 2D toolbar, click the Convert Arc to Circle tool. (). Go to step 3.
 - Type *circle* and then press Enter.
- 2 In the prompt box, choose Turn Arc Into Circle.
- 3 Select the arc you want to convert to a circle.




Select an arc (A) to convert to a circle.


Drawing arcs

An arc is a portion of a circle. The default method for drawing an arc is to specify three points—the start point, a second point, and the endpoint. You can draw arcs using any of the following methods:

- Three points on an arc ().
- Start point-center-endpoint (), or Start point-endpoint-center (), or Center-start point-endpoint ().
- Start point-center-included angle (), or Start point-included angle-center (), or Center-start point-included angle ().
- Start point-center-chord length (), or Center-start point-chord length ().
- Start point-endpoint-radius (), or Start point-radius-endpoint ().
- Start point-endpoint-included angle (), or Start point-included angle-endpoint ().
- Start point-endpoint-starting direction (), or Start point-starting direction-endpoint ().
- Start point-radius-angle ().
- As a tangent continuation of the previous arc or line ().

To draw an arc by specifying three points


- 1 Do one of the following:
 - Choose Insert > Arc.
 - On the Draw 2D toolbar, click the 3-Point Arc tool ().
 - Type *arc* and then press Enter.
- 2 Specify the start point.
- 3 Specify a second point.
- 4 Specify the endpoint.




Start point (A), second point (B), and endpoint (C).

The prompt box provides additional options for drawing arcs. For example, after you specify the start point of an arc, you can choose Angle, Center, Direction, Endpoint, or Radius. You can select the options in a different order as well. For instance, you can draw an arc by specifying its start point, endpoint, and radius, or you can specify the start point, radius, and then endpoint.


To draw an arc by specifying its start point, center point, and endpoint


- 1 Do one of the following:
 - Choose Insert > Arc.
 - On the Draw 2D toolbar, click the Arc Start-Center-End tool () .
 - Type *arc* and then press Enter.
- 2 Specify the start point.
- 3 In the prompt box, choose Center.
- 4 Specify the center point.
- 5 Specify the endpoint.



Start point (A), center point (B), and endpoint (C).

To draw an arc by specifying two points and an included angle


- 1 Do one of the following:
 - Choose Insert > Arc.
 - On the Draw 2D toolbar, click the Arc Start-End-Angle tool () .
 - Type *arc* and then press Enter.
- 2 Specify the start point.
- 3 In the prompt box, choose Angle or type *angle*.
- 4 To draw an arc in a counterclockwise direction, enter a positive value for the included angle.
 To draw an arc in a clockwise direction, enter a negative value for the included angle.
- 5 Specify the endpoint.




Start point (A), endpoint (B), and included angle (C).


If the last entity you drew was an arc or a line, you can also draw an arc tangent to and starting from the endpoint of the arc or line.

To draw an arc tangent to an arc or line

- 1 Do one of the following:
 - Choose Insert > Arc.
 - On the Draw 2D toolbar, click the Tangent Arc tool (). Go to step 3.
 - Type *arc* and then press Enter.
- 2 In the prompt box, choose Follow.
- 3 Specify the endpoint.







Endpoint (A).


TIP To convert an arc to a circle, on the Draw 2D toolbar, click the Convert Arc To Circle flyout tool ().


Drawing ellipses

The default method for drawing an ellipse is to specify the endpoints of one axis of the ellipse, and then specify a distance representing half the length of the second axis. The endpoints of the first axis determine the orientation of the ellipse. The longer axis of the ellipse is called the major axis, and the shorter one is the minor axis. The order in which you define the axes does not matter. The program determines the major and minor axes based on their relative lengths. You can draw ellipses using any of the following methods:

- Axis-axis ()
- Axis-rotation ()
- Center-axis ()
- Center-rotation ()

To draw an ellipse by specifying the axis endpoints





- 1 Do one of the following:
 - Choose Insert > Ellipse.
 - On the Draw 2D toolbar, click the Ellipse Axis-Axis tool ().
 - Type *ellipse* and then press Enter.
- 2 Specify the first endpoint.
- 3 Specify the second endpoint.
- 4 Specify the half-length of the other axis.




First axis endpoint (A), second axis endpoint (B), and half-length of other axis (C).

Drawing elliptical arcs


An elliptical arc is a portion of an ellipse. The default method for drawing an elliptical arc is to specify the endpoints of one axis of the ellipse, and then specify a distance representing half the length of the second axis. Then you specify the start and end angles for the arc, measured from the center of the ellipse in relation to its major axis. You can draw elliptical arcs using any of the following methods:

- Axis-axis ()
- Axis-rotation ()
- Center-axis ()
- Center-rotation ()

To draw an elliptical arc by specifying the axis endpoints

- 1 Do one of the following:
 - Choose Insert > Elliptical Arc.
 - On the Draw 2D toolbar, click the Elliptical Arc Axis-Axis tool ().
 - Type *ellipse* and then press Enter, and then type *a* (for Arc) and press Enter.
- 2 Specify the first endpoint.
- 3 Specify the second endpoint.
- 4 Specify the half-length of the other axis.
- 5 Specify the start angle of the arc.
- 6 Specify the end angle.

NOTE IntelliCAD draws elliptical arcs in the direction you specify. Go to Settings > Drawing Settings > Drawing Units tab. Under Change Settings For, select Angular Units. The default setting is counterclockwise.




First axis endpoint (A), second axis endpoint (B), half-length of other axis (C), start angle of arc (D), and end angle (E).


Creating point entities

You can draw a point entity formatted as either a single dot or as one of 19 other possible display styles.

To draw a point

- 1 Do one of the following:
 - Choose Insert > Draw Point.
 - On the Draw 2D toolbar, click the Point tool ().
 - Type *point* and then press Enter.
- 2 Specify the location of the point.


To draw several points

- 1 Do one of the following:
 - Choose Insert > Draw Point.
 - On the Draw 2D toolbar, click the Point tool ().
 - Type *point* and then press Enter.
- 2 In the prompt box, choose Multiple Points.
- 3 Specify the location of each point.
- 4 In the prompt box, choose Done to complete the command.


Changing the size and appearance of point entities

Changing the size and appearance of point entities affects all point entities already in the drawing, as well as all points that you subsequently draw. Positive values represent the absolute size of the point entity measured in drawing units. Negative values represent a percentage relative to the drawing screen, so that points retain their visual size as you use the *Zoom* command to change the magnification of the drawing.

To change the size and appearance of point entities

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool ().
 - Type *settings* and then press Enter.
- 2 Click the Entity Creation tab.
- 3 Under Change Settings For, click Points.
- 4 Under Point Display Type, select the style you want.
- 5 Under Point Size, select the point size, or choose one of the options.
- 6 Click OK.

When you regenerate the drawing, all point entities change to reflect the new size and appearance settings.




- A** To increase or decrease the point size, type or select a value. **C** Select the button for the Point Display Type that you want.
- B** To use one of the preset point size options, click the one that you want.


Drawing rays

A ray is a line in three-dimensional space that starts at a point and extends to infinity. Because rays extend to infinity, they are not calculated as part of the drawing extents. The default method for drawing a ray is to select the start point of the ray and then specify its direction. You can draw a ray in any of the following ways:

- Horizontal draws the ray parallel to the x-axis of the current user coordinate system (UCS).
- Vertical draws the ray parallel to the y-axis of the current UCS.
- Angle draws the ray parallel to a specified angle.
- Bisect draws the ray perpendicular to an existing entity.
- Parallel draws the ray parallel to an existing entity.

To draw a ray

- 1 Do one of the following:
 - Choose Insert > Ray.
 - On the Draw 2D toolbar, click the Ray tool ().
 - Type *ray* and then press Enter.
- 2 Specify the start point.
- 3 Specify the direction.
- 4 To complete the command, press Enter.



Start point (A) and direction (B).


Drawing infinite lines


Infinite lines are sometimes referred to as construction lines. An infinite line is a line through a given point, oriented at a specified angle in three-dimensional space and extending to infinity in both directions. Because infinite lines extend to infinity, they are not calculated as part of the drawing extents.

The default method for drawing an infinite line is to select a point along the line and then specify the direction of the line. You can draw an infinite line in any of the following ways:

- Horizontal draws the infinite line parallel to the x-axis of the current UCS.
- Vertical draws the infinite line parallel to the y-axis of the current UCS.
- Angle draws the infinite line parallel to a specified angle.
- Bisect draws the infinite line perpendicular to an existing entity.
- Parallel draws the infinite line parallel to an existing entity.

To draw an infinite line


- 1 Do one of the following:
 - Choose Insert > Infinite Line.
 - On the Draw 2D toolbar, click the Infinite Line tool ().
 - Type *infinite* and then press Enter.
- 2 Specify a point along the line.
- 3 Specify the direction.
- 4 To complete the command, press Enter.




Point along the infinite line (**A**) and the direction (**B**).

You can also draw infinite lines at a specific angle or at an angle relative to an existing entity.

To draw an infinite line at a specified angle relative to another entity

- 1 Do one of the following:
 - Choose Insert > Infinite Line.
 - On the Draw 2D toolbar, click the Infinite Line tool ().
 - Type *infinite* and then press Enter.
- 2 In the prompt box, choose Angle.
- 3 In the prompt box, choose Reference.
- 4 Select the reference entity.
- 5 Specify the angle of the infinite line in relation to the selected entity.
- 6 Specify the location of the infinite line.
- 7 To complete the command, press Enter.





Reference entity (A) and angle in relation to entity (B).


Creating freehand sketches

A freehand sketch consists of many straight line segments, created either as individual line entities or as a polyline. Before you begin creating a freehand sketch, you must set the length, or increment, of each segment. The smaller the segments, the more accurate your sketch, but segments that are too small can greatly increase the file size.

After you specify the length of the sketch segments, the crosshairs change to a Pencil tool. Your freehand sketch is not added to the drawing until you “write” the sketch into your drawing. This means that you temporarily save the segment that you’ve drawn and the segment length, and you can continue sketching.

To create a freehand sketch

- 1 Do one of the following:
 - Choose Insert > Freehand.
 - On the Draw 2D toolbar, click the Draw Freehand tool ().
 - Type *freehand* and then press Enter.
- 2 Specify the length of the sketch segments.
- 3 Click the mouse button to place the Pencil tool () on the drawing to begin sketching.
- 4 Move the pencil image to draw a temporary freehand sketch.
- 5 Click the mouse button to lift the pencil up to stop sketching.
- 6 In the prompt box, choose Write, Then Resume to write the temporary freehand sketch into the drawing.
- 7 Click the mouse button to put the pencil down again and resume sketching.
- 8 Click the mouse button again to lift the pencil up to stop sketching.
- 9 In the prompt box, choose Done to write the temporary freehand sketch into the drawing and end the command.





A freehand sketch consists of individual line entities or a polyline.

Erasing freehand sketch lines

You can erase temporary freehand sketch lines that have not yet been written into the drawing by choosing the Delete On option in the prompt box. The pencil changes to an Eraser tool. You can erase portions of the line when you move the eraser over a temporary freehand line without clicking the mouse button.


To erase freehand sketch lines


- 1 Do one of the following:
 - Choose Insert > Freehand.
 - On the Draw 2D toolbar, click the Draw Freehand tool ()
 - Type *freehand* and then press Enter.
- 2 Specify the length of the sketch segments.
- 3 Select a point on the drawing to display the Pencil tool and begin sketching.
- 4 Click the mouse button to lift the pencil up to stop sketching.
- 5 In the prompt box, choose Delete On.
- 6 Move the Eraser tool () to the beginning or end of the freehand sketch line that you drew, and then move it as far along the line as you want to erase.
- 7 Click the mouse button to put the Pencil tool down to resume sketching.

Setting the sketch method and accuracy

Using polylines for freehand sketches makes it easier to go back and edit sketches. You control whether to create freehand sketches using line segments or polylines in the Drawing Settings dialog box. You can also control the length of sketch segments in this dialog box.

To specify lines or polylines when sketching

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool ().
 - Type *settings* and then press Enter.
- 2 Choose the Entity Creation tab.
- 3 Under Change Settings For, click Freehand Sketches.
- 4 Under Freehand Sketching Methods, click either Freehand Command Creates Lines or Freehand Command Creates A Polyline.
- 5 Click OK.



A Select the sketch method.

B Specify the default length of sketch segments.

Creating complex entities

With IntelliCAD, complex entities include polylines (including rectangles and polygons), spline curves, donuts, and planes. In addition, IntelliCAD includes tools for adding hatching to your drawings.

This section explains several methods for creating complex entities, including how to:

- Use menu commands on the Insert menu.
- Use the tools on the Draw 2D toolbar.
- Type commands in the command bar.

When you type a drawing command or select a tool, the program prompts you to enter coordinate points, such as endpoints or insertion points. As you draw, the program displays a context-sensitive prompt box with appropriate additional options for the type of entity you are drawing.

After you create complex entities, you can modify them using the entity-modification tools. Several of these entity types require special editing commands.


Topics in this chapter


<i>Drawing rectangles</i>	108
<i>Drawing polygons</i>	110
<i>Drawing polylines</i>	111
<i>Drawing splines</i>	114
<i>Drawing donuts</i>	117
<i>Creating planes</i>	119
<i>Drawing wipeouts</i>	121
<i>Creating boundary polylines</i>	123
<i>Adding hatching</i>	127

Drawing rectangles

With IntelliCAD, rectangles are closed polylines with four sides. You draw a rectangle by specifying its opposite corners. The rectangle is normally aligned parallel to the current snap and grid alignment, but you can use the Rotated option to align the rectangle to any angle.




To draw a rectangle

- 1 Do one of the following:
 - Choose Insert > Rectangle.
 - On the Draw 2D toolbar, click the Rectangle tool ()
 - Type *rectangle* and then press Enter.
- 2 Specify one corner of the rectangle.
- 3 Specify the opposite corner of the rectangle.




Opposite corners (**A** and **B**).


Resulting rectangle.

You can edit each side of a rectangle individually using the Edit Polyline tool () on the Modify toolbar. You can convert the sides into individual line entities using the Explode tool () on the Modify toolbar. You can control whether wide rectangle lines are shown filled or as outlines using the Fill tool () on the Settings toolbar.

You can also use the Rectangle tool to draw a square. Instead of specifying the opposite corners, you specify the length of one side and the alignment of the square.

To draw a square

- 1 Do one of the following:
 - Choose Insert > Rectangle.
 - On the Draw 2D toolbar, click the Rectangle tool ().
 - Type *rectangle* and then press Enter.
- 2 In the prompt box, choose Square.
- 3 Specify one corner of the square.
- 4 Specify the length of one side of the square by selecting its other end.
The point you specify determines both the size and alignment of the square.




Endpoints of one side of the square (**A** and **B**).

Resulting square.

TIP To control the line width of the rectangle, choose the *Width Of Line* option in the prompt box. After you change the width of the line, the new width setting remains in effect for subsequent rectangles until you change it again.


Drawing polygons


Polygons are closed polylines composed of a minimum of three and a maximum of 1,024 equal-length sides. The default method for drawing a polygon is to specify the center of the polygon and the distance from the center to each vertex. You can draw a polygon using any of the following methods:

- Center - by vertex () on the Draw 2D toolbar
- Center - by side () on the Draw 2D toolbar
- Edge () on the Draw 2D toolbar

The vertex polygon drawing method creates an equal-sided polygon defined by its center point and the distance to its vertices. You specify the number of sides, the center point, and the location of one vertex, which determines both the size and orientation of the polygon.

To draw a polygon by vertex

- 1 Do one of the following:
 - Choose Insert > Polygon.
 - On the Draw 2D toolbar, click the Polygon, Center-Vertex tool () .
 - Type *polygon* and then press Enter.
- 2 Type 5 to specify five sides for the polygon.
- 3 Specify the center of the polygon.
- 4 Specify the vertex of the polygon.




The center (A) and vertex (B).

Resulting polygon.

Drawing polygons by side

The side polygon drawing method creates an equal-sided polygon defined by its center point and the distance to the midpoint of a side. You specify the number of sides, the center point, and the location of the midpoint of one side, which determines both the size and orientation of the polygon.




To draw a polygon by side

- 1 Do one of the following:
 - Choose Insert > Polygon.
 - On the Draw 2D toolbar, click the Polygon, Center-Side tool () .
 - Type *polygon* and then press Enter.
- 2 Type 3 to specify three sides for the polygon.
- 3 Specify the center of the polygon.
- 4 In the prompt box, choose Specify By Side, and then press Enter.
- 5 Specify the midpoint of the side.



The center (A) and midpoint of one side (B).


Resulting polygon.


You can edit each side of a polygon individually using the Edit Polyline tool () on the Modify toolbar. You can convert the sides into individual line entities using the Explode tool () on the Modify toolbar. You can control whether wide polygon lines are shown filled or as outlines using the Fill tool () on the Settings toolbar.

Drawing polylines

With IntelliCAD, a polyline is a connected sequence of arcs and lines that is treated as a single entity. You can draw a polyline with any linetype and using a width that either remains constant or tapers over the length of any segment. When editing a polyline, you can modify the entire polyline or change individual segments.

After you specify the start point of a polyline, a prompt box provides several options as you draw, such as Distance, Halfwidth, and Width. You can specify different starting and ending widths to create a tapered polyline segment.

After you draw at least one polyline segment, you can use the Undo tool () to remove the previous segment. After you draw two or more polyline segments, you can use the Close option to complete the command by drawing a segment that ends at the start point of the first polyline segment you drew. Choose Done to complete the command without closing the polyline.





Curved polyline with tapered width.

Polyline with straight segments.

Closed polyline.

To draw a polyline with straight segments

- 1 Do one of the following:
 - Choose Insert > Polyline.
 - On the Draw 2D toolbar, click the Polyline tool ().
 - Type *polyline* and then press Enter.
- 2 Specify the start point.
- 3 Specify the endpoint of each segment.
- 4 To complete the command, choose Close or Done.




Polyline start point (A) and segment endpoints (B).


With the Draw Arcs option, you can continually draw arc segments until you select the Draw Lines option to go back to drawing line segments. When you draw arc segments, the first point of the arc is the endpoint of the previous segment. By default, you draw arc segments by specifying the endpoint of each segment. Each successive arc segment is drawn tangent to the previous arc or line segment. If you choose Close while in the Draw Arcs option, the closing segment is created as an arc.

You can also specify the arc using any of the following methods:




- Start point, included angle, center point
- Start point, included angle, radius
- Start point, center point, endpoint
- Start point, included angle, endpoint
- Start point, center point, included angle
- Start point, center point, chord length
- Start point, direction, endpoint
- Start point, radius, included angle
- Start point, second point, endpoint

To draw a line segment followed by an arc polyline segment

- 1 Do one of the following:
 - Choose Insert > Polyline.
 - On the Draw 2D toolbar, click the Polyline tool ().
 - Type *polyline* and then press Enter.
- 2 Specify the start point.
- 3 Specify the endpoint.
- 4 In the prompt box, choose Draw Arcs.
- 5 Specify the endpoint of the arc segment.
- 6 To complete the command, choose Done.




Polyline start point (A), line endpoint/arc start point (B), and arc endpoint (C).

You can edit entire polylines and individual segments using the Edit Polyline tool () on the Modify toolbar. You can convert polylines into arc and line entities using the Explode tool () on the Modify toolbar. You can control whether wide polylines are shown filled or as outlines using the Fill tool () on the Settings toolbar.

Drawing splines

A spline is a smooth curve defined by a set of points. You can use splines to create sculptured shapes such as the cross section of a turbine blade or an airplane wing.


To draw a spline

- 1 Do one of the following:
 - Choose Insert > Spline.
 - On the Draw 2D toolbar, click the Spline tool ().
 - Type *spline* and then press Enter.
- 2 Specify the first point of the spline.
- 3 Specify the second point of the spline.
- 4 Specify as many more points as you want.
- 5 When you have finished, press Enter.

You can add tangents to the spline, which are lines that give it shape.

To add tangents to a spline

- 1 Specify the starting tangent point.
- 2 Specify the ending tangent point.




Spline.

Spline with starting tangent point (A) and ending tangent point (B).

Specifying fit tolerance

By default, a spline passes through all of the control points. When you draw a spline, you can change this by specifying the fit tolerance. The fit tolerance value determines how closely the spline fits the set of points you specify. For example, a spline fit tolerance value of 0 causes the spline to pass through the control points. A value of 0.01 creates a spline that passes through the start and endpoints and within 0.01 units of the intermediate control points.


To specify the fit tolerance


- 1 Do one of the following:
 - Choose Insert > Spline.
 - On the Draw 2D toolbar, click the Spline tool ().
 - Type *spline* and then press Enter.
- 2 Specify the first point of the spline.
- 3 Specify the second point of the spline.
- 4 In the prompt box, choose Fit Tolerance.
- 5 To accept the default of 0.0000, press Enter.
To specify a different fit tolerance, type the number, and then press Enter.
- 6 Specify the additional points you need to draw a spline or a closed spline.

Drawing a closed spline

You can draw a closed spline, which is a spline for which the start point and endpoint are the same. Because the spline is closed, you specify only one tangent.

To draw a closed spline

- 1 Do one of the following:
 - Choose Insert > Spline.
 - On the Draw 2D toolbar, click the Spline tool ().
 - Type *spline* and then press Enter.
- 2 Specify the first point of the spline.
- 3 Specify the second point of the spline.
- 4 Specify as many more points as you want.
- 5 When you have finished, in the prompt box, choose Close.
- 6 To complete the command, specify the tangent point.





The start point and endpoint (A) of a closed spline.

Drawing donuts

Donuts are solid, filled circles or rings created as closed, wide polylines. You can draw a donut using one of several methods. The default method is to specify the inside and outside diameters of the donut, and then specify its center. You can then create multiple copies of the same donut by specifying different center points until you press Enter to complete the command.

To draw a donut

- 1 Do one of the following:
 - Choose Insert > Donut.
 - On the Draw 2D toolbar, click the Donut tool ().
 - Type *donut* and then press Enter.
- 2 Specify the inside diameter of the donut.
- 3 Specify the outside diameter of the donut.
- 4 Specify the center of the donut.
- 5 Specify the center point to draw another donut, or choose Done to complete the command.





Inside diameter (A) and outside diameter (B).

The prompt box provides additional options for drawing donuts. For example, you can specify the width of the donut and two points on the diameter of the donut, or you can specify the width and three points on the donut. You can also draw a donut tangent to existing entities.




TIP A donut can be a completely filled circle by specifying an inside diameter of zero.

To draw a donut tangent to existing entities

- 1 Do one of the following:
 - Choose Insert > Donut.
 - On the Draw 2D toolbar, click the Donut tool (.
 - Type *donut* and then press Enter.
- 2 In the prompt box, choose Radius Tangent Tangent.
- 3 Specify the width of the donut.
- 4 Specify the diameter of the donut.
- 5 Select the first tangent entity to which to draw the donut.
- 6 Select the second tangent entity to which to draw the donut.



Width (A) and diameter (B) of the donut and tangent entities (C).

You can edit donuts using the Edit Polyline tool () on the Modify toolbar. You can convert donuts into arc entities using the Explode tool () on the Modify toolbar. You can control whether donuts are shown filled or as outlines using the Fill tool () on the Settings toolbar.


TIP You can control the default outside and inside diameter of donuts by choosing Settings > Drawing Settings, and then clicking the Entity Creation tab and choosing the options you want.


Creating planes

With the Plane tool, you can draw rectangular, triangular, or quadrilateral areas filled with a solid color. The default method is to specify the corners of the plane. After you specify the first two corners, the plane is displayed as you specify the remaining corners. Specify corner points in a triangular manner. The program prompts you for the third point and then the fourth point. If you continue specifying points, the third- and fourth-point prompts toggle until you press Enter to complete the command.

Creating planes in IntelliCAD is similar to the Solid command in AutoCAD.

To draw a quadrilateral plane


- 1 Do one of the following:
 - Choose Insert > Plane.
 - On the Draw 2D toolbar, click the Plane tool ().
 - Type *plane* and then press Enter.
- 2 Specify the first point.
- 3 Specify the second point.
- 4 Specify the third point.
- 5 Specify the fourth point.
- 6 To complete the command, press Enter.




After you select the first two points (A) and (B), the sequence in which you select the third (C) and fourth (D) points determines the shape of the resulting quadrilateral plane.



The prompt box provides additional options for drawing planes. For example, you can draw rectangular, square, or triangular planes.

To draw a rectangular plane

- 1 Do one of the following:
 - Choose Insert > Plane.
 - On the Draw 2D toolbar, click the Plane tool ()
 - Type *plane* and then press Enter.
- 2 Choose Rectangle.
- 3 Specify the first point.
- 4 Specify the opposite corner.
- 5 Specify the rotation angle.
- 6 To complete the command, specify the opposite corner to draw another rectangle, or press Enter.

Opposite corners (**A** and **B**) and rotation angle (**C**).

Resulting plane.

You can control whether planes are shown filled or as outlines using the Fill tool () on the Settings toolbar. You can convert planes into individual line entities corresponding to the outline of the plane using the Explode tool () on the Modify toolbar.

Drawing wipeouts

Wipeouts are unique entities that can help you hide areas of your drawing. They display with the current background color, so the details behind the wipeout do not display or print.

Wipeouts are similar to other entities — you can copy, mirror, array, erase, rotate, and scale them, and they can be used in both model space and paper space.


If you want to print the wipeout entities located in a drawing, you must print to a raster-capable printer. Note that in some cases you may have unexpected results when printing drawings that contain wipeout entities, for example, if printing on colored paper.


NOTE *If your version of IntelliCAD does not include raster image capability (that is, does not include an Image menu), wipeout entities display, but the details behind the wipeouts also display.*

Drawing wipeouts using polygons and polylines

Wipeouts are created using existing polygons, closed zero-width polylines made up of only line segments, or new polylines that you draw while using the Wipeout command.

To draw a wipeout


- 1 Do one of the following:
 - Choose Insert > Wipeout.
 - On the Draw 2D toolbar, click the Wipeout tool ()
 - Type *wipeout* and then press Enter.
- 2 Specify the start point.
- 3 Specify the endpoint of each segment.
- 4 After specifying the last endpoint, choose Done or press Enter.



Drawing without wipeout.

Drawing with wipeout.


To create a wipeout using an existing polygon or polyline


- 1 Do one of the following:
 - Choose Insert > Wipeout.
 - On the Draw 2D toolbar, click the Wipeout tool () .
 - Type *wipeout* and then press Enter.
- 2 Choose Polyline.
- 3 Select the closed polyline to use for the wipeout.
- 4 Choose one of the following:
 - **Yes** — Creates the wipeout and deletes the polyline used to create the wipeout.
 - **No** — Creates the wipeout and keeps the polyline used to create the wipeout.

Turning wipeout frames on or off

Each wipeout has a frame along its boundary. Wipeout frames can be turned on or off for any drawing. When wipeout frames are on, you can select and modify wipeouts. You may want to turn off wipeout frames when it's time to print.

To turn wipeout frames on or off

- 1 Do one of the following:
 - Choose Insert > Wipeout.
 - On the Draw 2D toolbar, click the Wipeout tool () .
 - Type *wipeout* and then press Enter.
- 2 Choose Frames.
- 3 Choose On or Off.




Wipeout frames turned on.

Wipeout frames turned off.

Creating boundary polylines

With the Boundary command, you can designate a specific area of a drawing for operations such as hatching and dimensioning. You create a boundary polyline by selecting an area inside a closed loop. The area you select can be bounded by a single closed entity or by multiple entities that intersect.

In cases where entities intersect, IntelliCAD interprets the boundary as the closed loop closest to the point specifying the area. In the following figure, for example, the area point selected in the rectangle results in a boundary consisting of the closed loop nearest the point selection, as opposed to the closed loop formed by the rectangle itself.




Selected point (A).

Resulting boundary (B).

To make boundaries more specific, you can create a boundary set. A boundary set specifies which entities are considered in determining the boundary path. This can make creating the boundary polyline faster if you are working with a complex drawing.

In the following figure, the circle and triangle are the selected entities. If you select an area anywhere inside the circle or the triangle, the result is a polyline that bounds the shaded area.




Selected entities (A and B).

Point specified in the selected area (C), which results in a new boundary around the shaded area.

Using islands and island detection

Islands are closed loops that reside inside other closed loops. IntelliCAD provides island-detection options so that you can specify which islands, if any, should be considered in the area selection for a boundary.


The following figure shows a rectangular polyline with two islands. The circle is referred to as the outer island, and the octagon is referred to as a nested island.



Rectangular polyline (A) with outer island (B), with point (C) specifying the area selection, and nested island (D).

You can choose from three island-detection methods.


- **Nested Islands** The outer entity and all its islands are considered for the polyline.
- **Outer Only** Only the outer entity and its outer island are considered for the polyline.
- **Ignore Islands** Only the outer entity is considered for the polyline.



Nested islands (A), with outer island (B), and with ignore islands (C).


To draw a boundary polyline

Advanced experience level

- 1 Do one of the following:
 - Choose Insert > Boundary Polyline.
 - On the Draw 2D toolbar, click the Boundary tool ()
 - Type *boundary* and then press Enter.
- 2 Specify the entities that you want made available for the boundary polyline by doing one of the following:
 - **All entities** Select All Visible Entities to have all entities in the drawing considered when creating the boundary polyline.
 - **Custom selection** Define only specific areas to be considered when creating the boundary polyline, which can improve system performance if you are working with a complex drawing. Click Select Boundary Set. In the drawing, select the entities individually or by choosing a selection method from the prompt box, and then press Enter. The Current Selection Set option becomes selected automatically, which indicates that the entities you selected with the Select Boundary Set button will be considered when creating the boundary polyline.

NOTE *You can alternate between All Visible Entities and Current Selection Set without having to select entities again using the Select Boundary Set button. The Current Selection Set option uses the last set of entities you selected with the Select Boundary Set button.*

- 3 Choose an island-detection option.
- 4 Click Select Area.
- 5 In the drawing, click inside the area whose closed perimeter forms the boundary, not on the polyline itself. If desired, continue clicking inside additional closed perimeters.
- 6 To complete the selection, press Enter.
- 7 In the Boundary dialog box, click OK.



- A Opens the drawing area for selection of entities to be considered when creating the boundary polyline.
- B Choose to consider all visible entities when creating the boundary polyline.
- C Choose to use the entities you selected for the boundary set. (Becomes available after you click the Select Boundary Set button.)
- D Select an island-detection option.
- E Opens the drawing area for selection of the enclosed areas used to create new boundary polylines.

Adding hatching


When you add hatching to a drawing, IntelliCAD fills entities or enclosed areas with a pattern. You can choose a predefined hatch pattern, or you can create your own hatch pattern.

First you specify the hatch pattern and other options, and then you choose which entities or enclosed areas that you want to hatch.

NOTE *Hatch patterns are memory intensive and can take a considerable amount of time to draw and display. To improve performance, add hatching as one of the last steps when you create a drawing, or insert hatches on a separate layer that you can freeze as you continue to work on your drawing.*

To open the Boundary Hatch dialog box

Do one of the following:

- Choose Insert > Hatch.
- On the Draw 2D toolbar, click the Boundary Hatch tool ().
- Type *bhatch* and then press Enter.


Specifying a hatch pattern

A hatch pattern consists of a repeating pattern of lines, dashes, and dots. You can select a hatch pattern from a set of predefined patterns, or you can define a pattern of your own. The hatch pattern you used most recently is the default pattern the next time you add hatching.

The program supplies predefined standard hatch patterns, which are stored in the *icad.pat* and *icadiso.pat* hatch pattern library files. You can use other external hatch pattern libraries, such as an office standard library, customized patterns, and libraries available from vendors or standards organizations.

NOTE *The icad.pat hatch pattern library files are ANSI (American National Standards Institute)-compliant patterns; the icadiso.pat hatch pattern library files are ISO (International Standards Organization)-compliant.*

To specify a predefined hatch pattern


- 1 Do one of the following:
 - Choose Insert > Hatch.
 - On the Draw 2D toolbar, click the Boundary Hatch tool ().
 - Type *bhatch* and then press Enter.
- 2 From the Boundary Hatch dialog box, click the Pattern Properties tab.
- 3 In the Pattern Type list, click Predefined.

With Predefined, you can apply a scale factor to make the pattern larger or smaller than the default size.
- 4 For Scale, enter the scale factor as a percentage of the default.
- 5 For Angle, enter the angle of the pattern in degrees (1-360).


The default angle is clockwise; you can change the angle of any hatch pattern by entering a numerical value.
- 6 For ISO Pen Width, enter the pen width.

If you choose a predefined, ISO standard pattern, you can scale the pattern based on the ISO pen width.
- 7 To copy the pattern properties from an existing hatch, choose Copy Hatch Properties and select the hatch.
- 8 To associate the hatch pattern to its boundary entities, under Hatch Attributes, select the Associative check box. An associative hatch updates automatically if you move any of its boundaries.
- 9 To continue, add a hatch by doing one of the following:
 - Select the entities you want to add a hatch. For details, see “Selecting entities for hatching” on page 132 in this chapter. Begin with step 2.
 - Select an area or boundary you want to add a hatch. For details, see “Selecting areas for hatching” on page 133 in this chapter. Begin with step 2.

To specify a user-defined hatch pattern


- 1 Do one of the following:
 - Choose Insert > Hatch.
 - On the Draw 2D toolbar, click the Boundary Hatch tool ().
 - Type *bhatch* and then press Enter.
- 2 From the Boundary Hatch dialog box, click the Pattern Properties tab.
- 3 In the Pattern Type list, click User Defined.
- 4 For Spacing, enter the line spacing for the pattern.
- 5 To crosshatch the pattern, select the Cross-Hatched check box.


You can choose to crosshatch the pattern. Cross-hatching imposes a copy of the specified user-defined pattern at a 90-degree angle over the first pattern you defined.
- 6 To copy the pattern properties from an existing hatch, choose Copy Hatch Properties, and select a hatch pattern from a hatched entity in the drawing.
- 7 To associate the hatch pattern to its boundary entities, under Hatch Attributes, select the Associative check box. An associative hatch updates automatically if you move any of its boundaries.
- 8 To continue, add a hatch by doing one of the following:
 - Select the entities you want to add a hatch. For details, see “Selecting entities for hatching” on page 132 in this chapter. Begin with step 2.
 - Select an area or boundary you want to add a hatch. For details, see “Selecting areas for hatching” on page 133 in this chapter. Begin with step 2.



- A** Determines how the hatch will be defined.
- B** Determines density of hatching for Predefined hatch patterns.
- C** Sets angle of hatch in relation to entity (User Defined only).
- D** Determines density of hatching for User Defined hatch patterns.
- E** Sets pen width for ISO-standard pattern.
- F** Imposes another copy of the specified pattern at a 90-degree angle over the first.
- G** Closes dialog to allow selection and copying of existing hatch pattern properties.
- H** Displays the tolerance that non-touching entities can be within and still be used to create the hatch pattern boundary.
- I** Select to update the hatch automatically if you move any of its boundaries.

To use a predefined library pattern

- 1 Do one of the following:
 - Choose Insert > Hatch.
 - On the Draw 2D toolbar, click the Boundary Hatch tool (.
 - Type *bhatch* and then press Enter.
- 2 From the Boundary Hatch dialog box, click the Pattern tab.
- 3 For Hatch File, select the *icad.pat* or *icadiso.pat* hatch pattern library file.
- 4 To select a predefined pattern, do one of the following:
 - In the Patterns list, click the pattern name.
 - Click the graphical representation of the hatch pattern.
- 5 To continue, add a hatch by doing one of the following:
 - Select the entities you want to add hatching. For details, see “Selecting entities for hatching” on page 132 in this chapter. Begin with step 2.
 - Select an area or boundary you want to add hatching. For details, see “Selecting areas for hatching” on page 133 in this chapter. Begin with step 2.



A Hatch pattern library files.

C Hatch patterns shown graphically.


B Hatch patterns listed by name.


NOTE *Hatch patterns are memory intensive and can take a considerable amount of time to draw and display. To improve performance, add hatching as one of the last steps when you create a drawing, or insert hatches on a separate layer that you can freeze as you continue to work on your drawing.*

Selecting entities for hatching

You can add hatching to any entity that forms a closed boundary, for example, a circle or rectangle. You can assign hatching to a single entity or several entities at the same time.


To select entities for hatching

- 1 Do one of the following:
 - Choose Insert > Hatch.
 - On the Draw 2D toolbar, click the Boundary Hatch tool () .
 - Type *bhatch* and then press Enter.
- 2 From the Boundary Hatch dialog box, click the Boundary tab.
- 3 Under Island Detection Options, choose one of the following:
 - **Nested Islands** The outer entity and all its islands are considered for hatching.
 - **Outer Only** Only the outer entity and its outer island are considered for hatching.
 - **Ignore Islands** Only the outer entity is considered for hatching.



Nested islands (A), with outer island (B), and with ignore islands (C).

- 4 To keep any new entities that are created for drawing the boundary hatch, select the Retain Boundaries check box. Existing entities are always retained.
- 5 Click Select Entities.
- 6 In the drawing, click the entities to be hatched individually or by choosing a selection method from the prompt box, and then press Enter when done.
- 7 In the Boundary Hatch dialog box, click OK.




- A** Choose to consider all visible entities when creating the boundary hatch.
- B** Mark the check box to keep any new entities that are created to draw the boundary hatch. Existing entities are always retained.
- C** (Display only) Indicates the boundary is created as a polyline.
- D** Determines how hatching interacts with islands.
- E** Opens the drawing area for selection of entities to be hatched.


Selecting areas for hatching

You can add hatching to an area enclosed by selected entities to form the hatch boundary. The hatch is formed in the enclosed area, not the entities themselves.

After IntelliCAD draws the hatch, the entire hatch is treated as a single entity and it is either associative or independent of the hatch boundary entities.

To select an area for hatching

- 1 Do one of the following:
 - Choose Insert > Hatch.
 - On the Draw 2D toolbar, click the Boundary Hatch tool () .
 - Type *bhatch* and then press Enter.
- 2 From the Boundary Hatch dialog box, click the Boundary tab.
- 3 Under Island Detection Options, choose one of the following:
 - **Nested Islands** The outer entity and all its islands are considered for hatching.
 - **Outer Only** Only the outer entity and its outer island are considered for hatching.
 - **Ignore Islands** Only the outer entity is considered for hatching.




Nested islands (A), with outer island (B), and with ignore islands (C).

- 4 To keep any new entities that are created for drawing the boundary hatch, select the Retain Boundaries check box. Existing entities are always retained.
- 5 Specify the entities that you want made available for boundary hatching by doing one of the following:
 - **All entities** Select All Visible Entities to have all entities in the drawing considered when creating the boundary hatch.
 - **Custom selection** Define only specific areas to be considered when creating the boundary hatch, which can improve system performance if you are working with a complex drawing. Click Select Boundary Set. In the drawing, select the entities individually or by choosing a selection method from the prompt box, and then press Enter. The Current Selection Set option becomes selected automatically, which indicates that the entities you selected with the Select Boundary Set button will be considered when creating the boundary hatch.

NOTE You can alternate between *All Visible Entities* and *Current Selection Set* without having to select entities again using the *Select Boundary Set* button. The *Current Selection Set* option uses the last set of entities you selected with the *Select Boundary Set* button.

- 6 In the Boundary Hatch dialog box, click *Select Area*.
- 7 In the drawing, click inside the closed perimeter of a boundary, not on the boundary itself. If desired, continue clicking inside additional closed perimeters.
- 8 To complete the selection, press *Enter*.
- 9 In the Boundary Hatch dialog box, click *OK*.



- | | |
|--|---|
| <p>A Opens the drawing area for selection of entities to be considered when creating the boundary hatch.</p> <p>B Choose to consider all visible entities when creating the boundary hatch.</p> <p>C Choose to use the entities you selected for the boundary set. (Becomes available after you click the <i>Select Boundary Set</i> button.)</p> | <p>D Mark the check box to keep any new entities that are created to draw the boundary hatch. Existing entities are always retained.</p> <p>E (Display only) Indicates the boundary is created as a polyline.</p> <p>F Determines how hatching interacts with islands.</p> <p>G Opens the drawing area for selection of enclosed areas to be hatched.</p> |
|--|---|

Viewing your drawing

IntelliCAD provides many ways to display and view your drawing. You can also change various display settings to speed up the display or printing of a drawing. This section explains how to:

- Navigate within a drawing by scrolling, panning, and rotating the view.
- Change the magnification of a drawing by zooming in and out.
- Work with multiple windows or views of a drawing.
- Control the display of elements to optimize performance when working with large or complex drawings.

Topics in this chapter


<i>Redrawing and regenerating a drawing</i>	138
<i>Moving around within a drawing</i>	138
<i>Changing the magnification of your drawing</i>	142
<i>Displaying multiple views</i>	146
<i>Controlling visual elements</i>	151

Redrawing and regenerating a drawing

As you work on a drawing, visual elements may remain after the completion of a command. You can remove these elements by refreshing, or redrawing, the display.

To redraw (refresh) the current window display

Do one of the following:

- Choose View > Redraw.
- On the View toolbar, click the Redraw tool (.
- Type *redraw* and then press Enter.

Information about drawing entities is stored in a database as floating point values, ensuring a high level of precision. Sometimes a drawing must be recalculated, or regenerated, from the floating-point database to convert those values to the appropriate screen coordinates. This occurs automatically. You can also manually initiate a regeneration. When the drawing is regenerated, it is also redrawn.

To regenerate the current window, type *regen* in the command bar. If more than one window is displayed, type *regenall* to regenerate all the windows.

Moving around within a drawing

You can move the view of a drawing displayed in the current viewport by scrolling, panning, or rotating the view. Doing this changes the portion of the drawing you are viewing without changing the current magnification. Scrolling lets you move around in the drawing horizontally and vertically. Panning lets you move the drawing in any direction. Rotating lets you view your drawing from any angle.

NOTE You can also move to a different view using the *Model and Layout* tabs. For more details, see “Viewing drawings in paper space and model space” on page 364.

Using scroll bars


To assist you in navigating within a drawing, horizontal and vertical scroll bars are available in each drawing window. The size of the scroll box in relation to the scroll bar indicates the current level of drawing magnification. The position of the scroll box in relation to the scroll bar indicates the location of the center of the drawing in relation to the extents of the drawing (the smallest rectangle containing all the entities in the drawing).

To turn scroll bars on or off


Do one of the following:

- Choose View > Scroll Bars.
- Choose Tools > Options > Display tab, and select Show Scroll Bars.
- Type *scrollbar*, press Enter, and then select On, Off, or Toggle.


Using the Pan command


You can move the drawing in any direction using the Pan tool () on the View toolbar. Panning shifts or slides the view of the drawing horizontally, vertically, or diagonally. The magnification of the drawing remains the same, as does its orientation in space. The only change is the portion of the drawing displayed.

To pan, you can use any of the following methods:


- For precise panning, specify two points defining the magnitude and direction of the pan. The first point, or base point, indicates the starting point of the pan. The second point indicates the amount of pan displacement relative to the first point.
- To pan in real time, press Ctrl + Shift and use the right mouse button, or use the Real-Time Pan tool () on the View toolbar.
- If you have a mouse with a wheel, press and hold the wheel, and then move the mouse.
- To pan in small increments, use the arrow keys (if the arrow keys were not selected for command history navigation in Tools > Options > Display tab).

To pan by specifying two points

- 1 Do one of the following:
 - Choose View > Pan.
 - On the View toolbar, click the Pan tool () .
 - Type *pan* and then press Enter.
- 2 Specify the pan base point either by typing the coordinates or by specifying a point in the drawing window.
- 3 Specify the pan displacement point either by typing the coordinates or by specifying a point in the drawing window.




Select the pan base point (**A**), and then select a second point (**B**) to specify the pan displacement.



Result.

To pan in real time

- 1 Do one of the following:
 - Choose View > Real-Time Motion > Real-Time Pan.
 - On the View toolbar, click the Real-Time Pan tool ().
 - Type *rtpan* and then press Enter.
- 2 Click and hold the left mouse button.
- 3 Move the cursor in the direction you want to pan.
- 4 To stop panning, release the mouse button.

TIP Hold down the right mouse button while *simultaneously pressing and holding Ctrl + Shift* to pan in real-time.

NOTE If you are working with a large drawing file, it may be helpful to set the *RTSKIPCOUNT* system variable to a higher number to reduce the number of entities that display. For example, if the value is set to 10, only the 10th entity will display when panning and rotating in real-time.

To pan using a mouse with a wheel

- Press and hold the wheel, and then move the mouse in the direction you want to pan. (The *MBUTTONPAN* system variable controls this feature.)

To pan using the arrow keys

- Press the up, down, right, or left arrow keys.


NOTE You can pan using the arrow keys if *Use Up/Down Arrows for Command History Navigation* is not marked on the *Display* tab in *Tools > Options*.

Rotating the view in real time

IntelliCAD allows you to rotate your view of a drawing in real time. This allows you to view your model from any angle while in model space. You cannot rotate the view while in paper space.

If desired, you can continue the view rotation after you release your mouse. Choose Tools > Options to enable continuous motion. For more information, see “Changing the options on the Display tab” on page 480.

To rotate the view in real time

- 1 Do one of the following:
 - Choose View > Real-Time Motion > Real-Time Sphere.
 - On the View toolbar, click the Real-Time Sphere tool ().
 - Type *rtrot* and then press Enter.
 - Press and hold Ctrl.
- 2 Click and drag the left mouse button. The view rotates according to the movement of your mouse.
- 3 To stop rotating, release the mouse button.
- 4 If the view continues to rotate, press Enter or right-click the drawing when finished.

TIP You can use the *Real-Time X*, *Real-Time Y*, and *Real-Time Z* commands to lock the rotation in the corresponding axis. You can also press Ctrl and use the right mouse button to rotate the view about the z-axis.

NOTE If you are working with a large drawing file, it may be helpful to set the *RTSKIPCOUNT* system variable to a higher number to reduce the number of entities that display. For example, if the value is set to 10, only the 10th entity will display when panning and rotating in real-time.


Changing the magnification of your drawing

You can change the magnification of your drawing at any time by zooming. The cursor changes to a magnifying glass (🔍) when a zoom tool is active. Zoom out to reduce the magnification so you can see more of the drawing, or zoom in to increase the magnification so you can see a portion of the drawing in greater detail. Changing the magnification of the drawing affects only the way the drawing is displayed; it has no effect on the dimensions of the entities in your drawing.


NOTE *If you are working in a layout viewport and cannot zoom, the layout viewport may be locked. The scale and view do not change in model space while panning or zooming in a locked layout viewport. For more details, see “Modifying layout viewports” on page 371.*

Zooming in and out

One of the easiest ways to change the magnification of the drawing is to zoom in or out by a preset increment. On the View toolbar, the Zoom In tool (🔍+) doubles the current magnification of the drawing. The Zoom Out tool (🔍-) reduces the magnification of the drawing by half. The portion of the drawing located at the center of the current viewport remains centered on the screen as you zoom in and out.



Zoom in.




Zoom out.


Zooming methods

To zoom, you can use any of the following methods:


- To define the portion of the drawing to zoom, create a window.
- To zoom in real time, press Ctrl + Shift and use the left mouse button, or use the Real-Time Zoom tool (🔍) on the View toolbar.
- If you have a mouse with a wheel, rotate the wheel to zoom in and out.

To zoom in to an area using a window

- 1 Do one of the following:
 - Choose View > Zoom > Window.
 - On the View toolbar, click the Zoom Window tool ().
 - Type *zoom* and then press Enter.
- 2 Select one corner of the window around the area you want to magnify.
- 3 Specify the opposite corner of the window around the area you want to magnify.




To specify a rectangular window around the area you want to magnify, select first one corner (A), and then select the opposite corner (B).



Result.

To zoom in real time


- 1 Do one of the following:
 - Choose View > Real-Time Motion > Real-Time Zoom.
 - On the View toolbar, click the Real-Time Zoom tool ().
 - Type *rtzoom* and then press Enter.
 - Simultaneously press and hold Ctrl + Shift.
- 2 Click and hold the left mouse button.
- 3 To zoom in, move the cursor up the screen; to zoom out, move the cursor down the screen.
- 4 To stop zooming, release the mouse button.

To zoom using a mouse with a wheel

- Rotate the wheel away from you to zoom in or toward you to zoom out.

Each rotation of the wheel away from you zooms out .8 times; each rotation toward you zooms in 1.25 times.

Displaying the previous view of a drawing

After you zoom in or pan to view a portion of your drawing in greater detail, you may want to zoom back out to see the entire drawing. On the View menu, the Zoom Previous tool () lets you restore the previous view. Selecting this tool repeatedly steps back through up to 25 successive zoomed or panned views.


Zooming to a specific scale

You can increase or decrease the magnification of your view by a precise scale factor measured relative to the overall size of the drawing or in relation to the current display. When you change the magnification factor, the portion of the drawing located at the center of the current viewport remains centered on the screen.


To change the magnification of the view relative to the overall size of the drawing, type a number representing the magnification scale factor. For example, if you type a scale factor of 2, the drawing appears at twice its original size. If you type a magnification factor of .5, the drawing appears at half its original size.

You can also change the magnification of the drawing relative to its current magnification by adding an *x* after the magnification scale factor. For example, if you type a scale factor of 2*x*, the drawing changes to twice its current size. If you type a magnification factor of .5*x*, the drawing changes to half its current size.


To zoom to a specific scale relative to the current display

- 1 Do one of the following:
 - Choose View > Zoom > Zoom In.
 - On the View toolbar, click the Zoom In tool ()
 - Type *zoom* and then press Enter.
- 2 Type the scale factor, followed by an *x* (such as 2*x*).
- 3 Press Enter.



Combining zooming and panning

You can specify the point you want at the center of the view when you change the drawing magnification. You can specify the point you want at the lower left of the view when you change the magnification of the drawing with the Zoom Left tool () on the View toolbar. With the exception of the Zoom Window tool, the other zoom tools zoom in or out from the center of the current view.

To change the center of the current view


- 1 Do one of the following:
 - Choose View > Zoom > Center.
 - On the Zoom toolbar, click the Zoom Center tool ()
 - Type *zoom*, press Enter, and then in the prompt box, choose Center.
- 2 Select the point you want located at the center of the new view.


- 3 Specify the zoom scale factor or the height of the drawing in drawing units.




Current view showing the point to be centered in the new view (**A**), and the new view zoomed using a scale factor of 2x.


Displaying the entire drawing

You can use the Zoom All tool () on the View toolbar to display an entire drawing. If you have drawn any entities outside the defined limits of the drawing, the extents of the drawing are displayed. If you drew all entities within the limits of the drawing, the drawing is displayed all the way to the drawing limits.

The Zoom Extents tool () on the View toolbar displays the drawing to its extents, making the image fill the display to the greatest possible magnification.



Zoom extents (displays all entities).



Zoom all (displays to drawing limits).

Displaying multiple views

When you begin a new drawing, it is displayed in a single window. You can view the drawing in a second window, or you can divide one window into multiple windows. You can also open and display multiple drawings.

Working with multiple views of a single drawing

You can open and work with several views of the same drawing simultaneously. There are two methods for dividing the current drawing into multiple views:

- Open a new window of the open drawing.
- Divide the current window into multiple views.

After you divide a single window into multiple windows, you can control each window separately. For example, you can zoom or pan in one window without affecting the display in any of the other windows. You can control the grid, snap, and view orientation separately for each window. You can restore named views in individual windows, draw from one window to another, and name window configurations individually so you can reuse them later.

As you draw, any changes you make in one window are immediately visible in the others. You can switch from one window to another at any time, even in the middle of a command, by clicking the window's title bar.

Opening a new window of the same drawing

You can open additional windows to create more than one view of a drawing. To open a new window, choose **Window > New Window**. After you open a new window, you can change its display without affecting any of the other windows.

When you open more than one window for a single drawing, each window is assigned a unique number (for example, `mydrawing:1`, `mydrawing:2`, and so on). If your current window is maximized, you can switch to another open window by selecting its name from the bottom of the **Window** menu.

The names of other open drawings appear at the bottom of the **Window** menu. You can also use the **Cascade**, **Tile Horizontally**, and **Tile Vertically** commands to arrange all the open windows and drawings. To arrange all the windows and drawings into a stack of identically sized windows, choose **Window > Cascade**. Arranging windows and drawings in this way makes it easy to see the title bar for each window.

To arrange all the windows and drawings horizontally so they are placed in order from top to bottom, choose **Window > Tile Horizontally**. Arranging windows and drawings in this way displays each open window. The windows are resized to fit within the available space.

To arrange all the windows and drawings vertically so they are placed side by side, choose **Window > Tile Vertically**. Arranging windows and drawings in this way displays each open window. The windows are resized to fit within the available space.

IntelliCAD uses the commands in the following table to control its windows.


IntelliCAD window-control commands


Command	Result
<i>vports</i>	Splits the current window into two, three, or four tiled windows.
<i>wcascade</i>	Cascades (overlaps) all open windows.
<i>wclose</i>	Closes the current window.
<i>wcloseall</i>	Closes all windows; also closes all drawings.
<i>whtile</i>	Tiles all windows horizontally.
<i>wiarrange</i>	Arranges window icons.
<i>wopen</i>	Opens another window of the current drawing.
<i>wvtile</i>	Tiles all windows vertically.

Dividing the current window into multiple views

You can divide a single drawing window into multiple tiled windows (called viewports) on the Model tab. You can control the number of windows created and the arrangement of the windows. You can also save and restore named window configurations and display a list of the current and saved window configurations.


To create multiple views

- Do one of the following:
 - Choose View > Viewports.
 - On the View toolbar, click the Viewports tool ().
 - Type *vports* and then press Enter.
- In the prompt box, choose Create 2 Viewports, Create 3 Viewports, or Create 4 Viewports.
- In the prompt box, choose the viewport orientation.



You can divide a drawing window into two windows arranged vertically (**A**) or horizontally (**B**); three windows arranged left (**C**), right (**D**), above (**E**), below (**F**), vertically (**G**), or horizontally (**H**); or four tiled windows (**I**).


To join two views

- 1 Do one of the following:
 - Choose View > Viewports.
 - On the View toolbar, click the Viewports tool ().
 - Type *viewports* and then press Enter.
- 2 In the prompt box, choose Join.
- 3 Click anywhere inside the window you want to keep.
- 4 Click anywhere inside the adjacent window you want to join to the first window.
- 5 Press Enter.

Saving window configurations


If you have divided the drawing window into multiple views, you can save the current window arrangement so that you can recall it to the screen later. The number and placement of the windows are saved exactly as they are currently displayed. The settings for each window are also saved.

To name and save a window configuration

- 1 Do one of the following:
 - Choose View > Viewports.
 - On the View toolbar, click the Viewports tool (.
 - Type *viewports* and then press Enter.
- 2 In the prompt box, choose Save.
- 3 Type a configuration name, and then press Enter.

The name can be up to 31 characters in length and can contain letters, numbers, the dollar sign (\$), hyphen (-), and underscore (_), or any combination.

To restore a named window configuration


- 1 Do one of the following:
 - Choose View > Viewports.
 - On the View toolbar, click the Viewports tool (.
 - Type *viewports* and then press Enter.
- 2 In the prompt box, choose Restore.
- 3 Type the name of the window configuration you want to restore.

Working with multiple drawings

With the multiple-document interface (MDI) feature, you can open more than one drawing inside of IntelliCAD. Because you can open and work on several drawings at one time, you can copy, cut, or paste an entity from one drawing to another.

Each drawing appears in a drawing window, which has the following advantages:

- You can see two or more drawings side by side.
- You can easily copy entities from one drawing to another.
- Using the IntelliCAD Explorer, you can copy such elements as layers, linetypes, and text styles from one drawing to another.
- Like viewports on the Model tab, you can tile or overlap drawing windows; unlike viewports on the Model tab, drawing windows maximize or reduce to an icon.



One session of IntelliCAD with four drawings open.

Each drawing window that you open and work on retains in the Prompt History log all the commands that you perform, but the command line does not indicate when you have switched windows.

When you work with more than one drawing open in its own window, you can easily move, cut, copy, and paste in between drawings. If you move an entity from one window to another and then want to undo this action, you must undo it in both drawings for it to take effect. If you copy an entity from one window to another and then want to undo that action, you must undo it from the drawing into which you copied the entity. If you cut and paste an entity and then want to undo that action, you must undo it in both drawings.

Controlling visual elements


The number of entities in your drawing and the complexity of the drawing affect how quickly IntelliCAD can process commands and display your drawing. You can improve overall program performance by turning off the display of certain visual elements, such as solid fills and text, while you work on the drawing. When you are ready to print your drawing, turn on the display of these elements so your drawing prints the way you want.


You can also improve performance by turning off entity-selection highlighting, turning off the display of marker blips created when you select locations in the drawing, and by turning off the display of lineweights.

Turning Fill on and off

You can reduce the time it takes to display or print a drawing by turning off the display of solid fill. When Fill is turned off, all filled entities, such as wide polylines and planes, display and print as outlines. When you turn Fill on or off, you must redraw the drawing before the change is displayed.

To turn Fill on or off

- 1 Do one of the following:
 - Choose Settings > Fill.
 - On the Settings toolbar, click the Fill tool ()
 - Type *fill* and then press Enter.
- 2 Choose View > Redraw.



Fill on.



Fill off.


TIP *On the Settings menu, a check mark appears next to the Fill command when it is turned on and the Fill tool on the Settings toolbar is activated.*

Turning Quick Text on and off

Text entities require a considerable amount of time to display and print. You can reduce the time it takes to display or print a drawing by enabling Quick Text. For example, if you're doing a preliminary check print of a drawing, you may want to turn Quick Text on to speed up printing. When Quick Text is enabled, text entities are replaced by rectangular boxes that indicate the outline of the area occupied by the text. When you turn Quick Text on or off, you must regenerate the drawing before the change is displayed.

To turn Quick Text on and off

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool ().
 - Type *qtext*, press Enter, and then in the prompt box, choose On or Off.
- 2 Click the Display tab.
- 3 Under Change Settings For, click Display.
- 4 Select or clear the Enable Quick Text check box.
- 5 Click OK.
- 6 To regenerate your drawing, do one of the following:
 - Choose View > Regen.
 - On the View toolbar, click the Regen tool ().
 - Type *regen* and then press Enter.




Quick Text off.

Quick Text on.

Turning highlighting on and off

You can improve overall program performance by turning highlighting off. When you select entities to modify, the program highlights them using a dashed linetype. This highlight disappears when you finish modifying the entities or when the entities are cleared. Sometimes highlighting entities can take a considerable amount of time.


To turn highlighting on and off


- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool ()
 - Type *highlight*, press Enter, and then in the prompt box, choose On or Off.
- 2 Click the Display tab.
- 3 Under Change Settings For, click Display.
- 4 Select or clear the Highlight Item When Selected check box.
- 5 Click OK.

Turning Blips on and off

You can turn Blips off. They are the temporary markers that appear on the screen when you select an entity or location. Blips are visible only until you redraw the drawing. You cannot select Blips; they are used only for reference and never print.

To turn Blips on and off

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool ()
 - Type *blipmode*, press Enter, and then in the prompt box, choose On or Off.
- 2 Click the Display tab.
- 3 Under Change Settings For, click Display.
- 4 Select or clear the Show Marker Blips check box.
- 5 Click OK.



Blips on.

Blips off.

Controlling the display of lineweights


You can reduce the time it takes to display a drawing by turning off the display of lineweights. When you turn off lineweights, all entities display as outlines.

You can also specify a lineweight scale. Specify a smaller scale to display thinner lines; specify a larger scale to display thicker lines. For example, a scale factor of 0.5 would display a .80 millimeter lineweight as .40 millimeter; a scale factor of 2 would increase the same lineweight to display at 1.6 millimeters. This can help you differentiate various lineweights that display in a drawing. Adjusting the lineweight display scale affects how the lineweights appear on your screen, not how they appear when printed.

NOTE *Setting the lineweight scale too high may result in slower system performance.*

You can also adjust the units for measuring lineweights, and the default lineweight.

To control the display of lineweights

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool () .
 - Type *settings* and then press Enter.
 - Type *lweight* and then press Enter.
- 2 Click the Display tab.
- 3 Under Change Settings For, click Lineweights.
- 4 Select or clear Display Lineweights.
- 5 In Units for Listing, choose Millimeters or Inches.
- 6 In Default, select the lineweight assigned to layers and entities that use the Default lineweight.
- 7 In Adjust Display Scale, move the slider to the scale you want. By default, the slider begins at 1.00.
- 8 Click OK.

TIP *On the status bar, double-click the word LWT to turn the display of lineweights on or off.*

You can turn lineweights on or off when you print. For details, see “Choosing how lineweights print” on page 377.

Working with coordinates

For accuracy in a drawing, you can locate specific points by entering coordinates as you draw or modify entities. When you create two-dimensional entities, you enter two-dimensional coordinates; for three-dimensional entities, you specify three-dimensional coordinates.

You can also specify coordinates in relation to other known locations or entities in a drawing. In particular, when you work in three-dimensional drawings, it is often easier to specify coordinates in relation to a two-dimensional working plane, called a user coordinate system (UCS).

This section explains how to work with coordinates, including how to:

- Use two-dimensional and three-dimensional coordinate systems.
- Specify absolute and relative coordinates.
- Specify polar, spherical, and cylindrical coordinates.
- Define and manipulate user coordinate systems.

Topics in this chapter


<i>Using Cartesian coordinates</i>	156
<i>Using two-dimensional coordinates</i>	159
<i>Using three-dimensional coordinates</i>	163
<i>Using xyz point filters</i>	166
<i>Defining user coordinate systems</i>	168

Using Cartesian coordinates

Many commands in IntelliCAD require that you specify points as you draw or modify entities. You can do so by selecting points with the mouse or by typing coordinate values in the command bar. The program locates points in a drawing using a Cartesian coordinate system.

Understanding how coordinate systems work

The Cartesian coordinate system uses three perpendicular axes— x , y , and z —to specify points in three-dimensional space. Every location in a drawing can be represented as a point relative to a $0,0,0$ coordinate point, referred to as the origin. To draw a two-dimensional entity, you specify horizontal coordinate positions along the x -axis and vertical coordinate positions along the y -axis. Thus, every point on a plane can be represented as a coordinate pair composed of an x -coordinate and a y -coordinate. Positive coordinates are located above and to the right of the origin; negative coordinates are located to the left and below the origin.



The three perpendicular axes of the Cartesian coordinate system.


When you work in two dimensions, you need enter only the x - and y -coordinates; the program assumes that the z -axis value is always the current elevation. When you work in three dimensions, however, you must also specify the z -axis value. When you look at a plan view of your drawing (a view from above, looking down), the z -axis extends straight up out of the screen at a 90-degree angle to the xy plane. Positive coordinates are located above the xy plane, and negative coordinates are below the plane.

All IntelliCAD drawings use a fixed coordinate system, called the World Coordinate System (WCS), and every point in a drawing has a specific x,y,z-coordinate in the WCS. You can also define arbitrary coordinate systems located anywhere in three-dimensional space. These are called user coordinate systems and can be located anywhere in the WCS and oriented in any direction.

You can create as many user coordinate systems as you want, saving or redefining them to help you construct three-dimensional entities. By defining a UCS within the WCS, you can simplify the creation of most three-dimensional entities into combinations of two-dimensional entities.

To help you keep your bearings in the current coordinate system, the program displays a coordinate system icon. When you begin a new drawing, you are automatically in the WCS, indicated by the letter *W* in the icon. When you display a drawing in plan view, you see the coordinate system icon from the top, with the z-axis directed straight toward you. When you display a three-dimensional drawing in a view other than plan view, the coordinate system icon changes to reflect your new viewpoint.

TIP *The visible portions of the axes are the positive directions.*



WCS icon.

Plan UCS icon.

3D View WCS icon.

The IntelliCAD UCS icon looks different from the UCS icon in AutoCAD, because it presents more information. Three colors represent the three axes, making it easier for you to recognize the orientation in three-dimensional space:


- x-axis: red
- y-axis: green
- z-axis: blue

If you prefer a single color for the cursor and UCS icon, you can make that change with the *config* or *options* command.

Understanding how coordinates are displayed

The current position of the cursor is displayed as x,y,z-coordinates in the status bar and, by default, updates dynamically as you move the cursor. You can toggle the coordinate display to static mode by pressing F6, so that it updates only when you select a point in the drawing.

You can also change the coordinate display to a different dynamic mode that shows the distance and angle (rather than x,y,z-coordinates) when the program displays a rubber-band line. To do this, choose Settings > Drawing Settings and select the Display tab. Under Coordinate Display, select the option for Coordinates In Polar Form For Distance And Angle Selection.




You can control the coordinate display from the Drawing Settings dialog box.

Finding the coordinates of a point

To find the x,y,z-coordinates for a point on an entity, such as the endpoint of a line, select an appropriate entity snap (such as Endpoint) before selecting the entity. If you have no entity snaps set, the x,y-coordinates of the point you specified is displayed, with the z-coordinate equal to the current elevation.

To find the coordinate of a point in the drawing

- 1 Do one of the following:
 - Choose Tools > Inquiry > ID Coordinates.
 - On the Inquiry toolbar, click the ID Coordinates tool ().
 - Type *idpoint* and then press Enter.
- 2 Select the point for which you want to find the coordinates.

If the command bar is activated, the x,y,z-coordinates for the point you selected display in the command bar.

If the command bar is not activated, the Prompt History window displays, showing the x,y,z-coordinates for the point you selected.

Using two-dimensional coordinates


When working in two dimensions, you specify points on the xy plane. You can specify any point as an absolute coordinate (or Cartesian coordinate), using the exact x-coordinate and y-coordinate locations in relation to the origin (the 0,0 coordinate point at which the two axes intersect), or as a relative coordinate in relation to the previous point. You can also specify points using relative or absolute polar coordinates, which locate a point using a distance and an angle.

Entering absolute Cartesian coordinates

To enter absolute Cartesian coordinates, type the coordinate location of the point in the command bar. For example, to use absolute Cartesian coordinates to draw a line from the origin (0,0) to a point 3 units to the right and 1 unit above the origin, start the Line command and respond to the prompts as follows:

```
Start of line: 0,0
```

```
Angle • Length • <Endpoint>: 3,1
```




Drawing a line using the absolute Cartesian coordinate method.

When using absolute Cartesian coordinates, you need to know the exact point locations for anything you draw. For instance, to use absolute Cartesian coordinates to draw an 8.5-unit square with its lower left corner at 4,5, you must determine that the upper left corner is at coordinate 4,13.5, the upper right corner at 12.5,13.5, and the lower right corner at 12.5,5.

Entering relative Cartesian coordinates

Another, simpler method is to use relative Cartesian coordinates: you specify a location in the drawing by determining its position relative to the last coordinate you specified. To use relative Cartesian coordinates, type the coordinate values in the command bar, preceded by the *at* symbol (@). The coordinate pair following the @ symbol represents the distance along the x-axis and the y-axis to the next point. For example, to draw an 8.5-unit square with its lower left corner at 4,5 using relative Cartesian coordinates, start the Line command, and then respond to the prompts as follows:

```
Start of line: 4,5
Angle • Length • <Endpoint>: @8.5,0
Angle • Length • Follow • Undo • <Endpoint>: @0,8.5
Angle • Length • Follow • Close • Undo • <Endpoint>: @-8.5,0
Angle • Length • Follow • Close • Undo • <Endpoint>: C
```



Drawing a square using the relative Cartesian coordinates method; enter *C* to close.

The first relative coordinate (@8.5,0) locates the new point 8.5 units to the right (along the x-axis) from the previous point of 4,5; the second relative coordinate (@0,8.5) locates the next point 8.5 units above (along the y-axis) the previous point, and so on. Entering *C* (for Close) draws the final line segment back to the first point specified when you started the Line command.


Entering polar coordinates

Using relative polar coordinates makes drawing a square tilted at a 45-degree angle a simple task. Polar coordinates base the location of a point on a distance and angle from either the origin (absolute coordinate) or from the previous point (relative coordinate).

To specify polar coordinates, type a distance and an angle, separated by the open angle bracket (<). For example, to use relative polar coordinates to specify a point 1 unit away from the previous point and at an angle of 45 degrees, type `@1<45`.

To draw the square from the example in the previous section, “Entering relative Cartesian coordinates,” this time tilted at a 45-degree angle, start the Line command, and then respond to the prompts as follows:

```
Start of line: 4,5
Angle • Length • <Endpoint>: @8.5<45
Angle • Length • Follow • Undo • <Endpoint>: @8.5<315
Angle • Length • Follow • Close • Undo • <Endpoint>: @8.5<225
Angle • Length • Follow • Close • Undo • <Endpoint>: C
```



Drawing a tilted square using the relative polar coordinates method; enter C to close.

NOTE This example, like all examples in this guide, assumes the program's default settings: Angles increase counterclockwise and decrease clockwise. Thus, an angle of 315 degrees is the same as -45 degrees.


Using three-dimensional coordinates

Specifying coordinates in three-dimensional space is similar to working in two dimensions, except that you also use the z-axis to locate coordinates. Three-dimensional coordinates are represented in the format x,y,z (for example, 2,3,6).

Using the right-hand rule

To visualize how IntelliCAD works with three-dimensional space, use a technique known as the right-hand rule. Hold up your right hand in a loose fist with your palm facing you. Extend your thumb in the direction of the positive x-axis and your index finger upward in the direction of the positive y-axis. Then extend your middle finger straight toward you in the direction of the z-axis. These three fingers are now pointing in the positive x, y, and z directions, respectively.

You can also use the right-hand rule to determine the positive rotation direction. Point your thumb in the positive direction of the axis about which you want to rotate, and then curl the rest of your fingers toward your palm. These fingers are curling in the positive rotation direction.



The right-hand rule helps you determine the positive direction of the x-, y-, and z-axes and the positive rotation direction.

Entering x,y,z-coordinates

When working in three dimensions, you can specify x,y,z -coordinates as absolute distances in relation to the origin (the 0,0,0 coordinate point at which the three axes intersect) or as relative coordinates based on the last point selected. For example, to specify a point 3 units along the positive x-axis, 4 units along the positive y-axis, and 2 units along the positive z-axis, specify the coordinate 3,4,2.


Entering spherical coordinates

When working in three-dimensional space, you can use spherical coordinates to specify a three-dimensional point by entering its distance from either the origin (absolute distance) or the last point (relative distance), along with its angle in the xy plane and its angle up from the xy plane. In spherical format, you separate each angle with the open angle bracket (<).

Thus, to draw a line from the origin to a point 10.2500 drawing units away, at an angle of 45 degrees from the x-axis and 35 degrees from the xy plane, start the Line command, and then respond to the prompts as follows:

```
Start of line: 0,0,0
```

```
Angle • Length • <Endpoint>: 10.2500<45<35
```




When you draw a line from a start point (**A**) to an endpoint (**B**) using spherical coordinates, you specify its length (**C**, in this case 10.2500 units), the angle in the xy plane (**D**, in this case 45 degrees), and the angle from the xy plane (**E**, in this case 35 degrees).

Entering cylindrical coordinates

When working in three-dimensional space, you can also use cylindrical coordinates to specify a three-dimensional point. You specify a point by entering its distance from either the origin (absolute distance) or the last point (relative distance), its angle in the xy plane, and its z -coordinate value.

In cylindrical format, you separate the distance and angle with the open angle bracket (<) and separate the angle and z value with a comma. For example, to draw a line from the last point to a point 7.4750 units away, at an angle of 27 degrees from the x -axis in the xy plane and 3 units up in the z direction, start the Line command, and then respond to the prompts as follows:

```
Start of line: (select point A)
Angle • Length • <Endpoint>: @7.4750<27,3
```



When you draw a line from a start point (A) to an endpoint (B) using cylindrical coordinates, you specify its length (C, in this case 7.4750), the angle in the xy plane (D, in this case 27 degrees), and the distance in the z direction (E, in this case 3 units).

Using xyz point filters

Point filters provide a method of locating a point in a drawing relative to another point without specifying the entire coordinate. Using a point filter, you can enter partial coordinates, and then the program prompts you for the remaining coordinate information. To use xyz point filters, respond to the prompt for a coordinate with a filter in the following form:


.coordinate

where *coordinate* is one or more of the letters x, y, and z. The program then prompts you for the filtered coordinate(s). For example, if you type *.xy*, the program prompts you to select a point whose xy-coordinate you want, and then prompts you for the z-coordinate. The filters *.x*, *.y*, *.z*, *.xy*, *.xz*, and *.yz* are all valid filters.

Using point filters in two dimensions

You can use point filters when you work in two dimensions to locate points in relation to existing entities. For example, to draw a circle centered in a rectangle, start the Circle command, and then respond to the prompts as follows:

```
2Point • 3Point • RadTanTan • Arc • Multiple • <Center of circle>: .y
Select Y of: mid
Snap to midpoint of: (select the left side of the rectangle)
Still need XZ of: mid
Snap to midpoint of: (select top of the rectangle)
Diameter • <Radius>: (specify radius of circle)
```



You can use point filters to center the circle by separately selecting the midpoints of two sides of the rectangle (**A** and **B**) and then specifying its radius.

Using point filters in three dimensions

You can use point filters when you work in three-dimensional space to locate points in two dimensions and then specify the z-coordinate as the elevation above the xy plane. For example, to begin drawing a line from a point with a z-coordinate 3 units above the center of a circle, insert the circle, and then start the Line command and respond to the prompts as follows:


ENTER to use last point • Follow • <Start of line>: .xy

Select XY of: cen

Snap to centerpoint of: *(select a point on the circle)*

Still need Z of: 3 *(locates the starting point 3 units above the center of the circle)*

Length of line: *(specify the length of the line)*




You can use point filters to draw a line by first selecting a point in the xy plane (**A**), specifying the z-coordinate (**B**), and then specifying the length of the line (**C**).

Defining user coordinate systems

When working in three-dimensional space, you can define a UCS with its own 0,0,0 origin and orientation separate from the WCS. You can create as many user coordinate systems as you want, and then save and recall them as you need them to simplify construction of three-dimensional entities.

For example, you can create a separate UCS for each side of a building. Then, by switching to the UCS for the east side of the building, you can draw the windows on that side by specifying only their x- and y-coordinates. When you create one or more user coordinate systems, the coordinate entry is based on the current UCS.



UCS aligned with the front wall of the house.



Defining a user coordinate system


To define a UCS, you can use any of the following methods:

- Specify a new origin and points on the positive x- and y-axes.
- Specify a new origin and point on the positive z-axis.
- Align the UCS with an existing entity.
- Rotate the current UCS around any of its axes.
- Align the UCS with its z-axis parallel to the current viewing direction.
- Align the UCS xy plane perpendicular to the current view.

When you define a new UCS, the UCS icon changes to indicate the origin and orientation of the new UCS.

To define a UCS by specifying a new origin and points on the positive x- and y-axes

- 1 Do one of the following:
 - Choose Settings > User Coordinate Systems.
 - On the Settings toolbar, click the User Coordinate Systems tool ().
 - Type *setucs* and then press Enter.
- 2 In the User Coordinate Systems dialog box, click Explore UCSs.
- 3 In the IntelliCAD Explorer, be sure that Coordinate Systems is selected, and click the New Item tool ().
- 4 In the prompt box, choose 3 Point.
- 5 Select the new origin.
- 6 Select a point on the positive x-axis.
- 7 Select a point in the positive y direction.
- 8 In the IntelliCAD Explorer - Coordinate Systems dialog box, type the name for the new UCS, and then close the dialog box.



Define the new UCS by selecting the origin (A), a point on the positive x-axis (B), and a point in the positive y direction (C).


Using a preset user coordinate system


IntelliCAD lets you select a preset UCS. The six planes defined by looking along the x,y,z-axes align the UCS with the top, left, front, bottom, right, or back, based on either the WCS or the current UCS in effect when you select the tool. You can also select the previous UCS, align the UCS to the current view, or select the WCS.

When you select a UCS, the cursor orientation and UCS icon change to reflect the new UCS. The display does not change, however, unless you select the Change View To Plan View Of The Selected UCS check box.

After you align the UCS to a preset UCS, you can use the IntelliCAD Explorer to save the UCS. To do this, in the IntelliCAD Explorer window, choose Edit > New > UCS, and then select Current.

To select a preset UCS

- Do one of the following:
 - Choose Settings > User Coordinate Systems.
 - On the Settings toolbar, click the User Coordinate Systems tool ().
 - Type *setucs* and then press Enter.
- Under Set The Selected UCS Relative To, select either Current UCS to change to the new UCS by reorienting relative to the current UCS or World Coordinate System (WCS) to base the new UCS orientation on the WCS.
- Under Select UCS, click the button corresponding to the UCS you want as the new current UCS.



- | | |
|--|--|
| <p>A Specify whether to define the new UCS relative to the current UCS or to the World Coordinate System (WCS).</p> <p>B Select to change the display to the plan view of the new UCS.</p> <p>C Click to select the previous UCS.</p> | <p>D Click one of these buttons to select the view you want of a preset UCS.</p> <p>E Click to select the WCS.</p> <p>F Click to align the UCS with the current view.</p> <p>G Click to display the IntelliCAD Explorer.</p> |
|--|--|

Working with the IntelliCAD Explorer

The IntelliCAD Explorer provides a powerful and convenient way to maintain and manage many of the features and settings of your drawings. You can use the IntelliCAD Explorer to work with layers, linetypes, text styles, coordinate systems, named views, blocks, and dimension styles within the current drawing or to copy this information between drawings.

This section explains how to use the IntelliCAD Explorer to:

- Manage elements related to settings and entities in your drawings.
- Organize information on layers and manage layers.
- Create and use linetypes.
- Load text fonts and create text styles.
- Select and control coordinate systems.
- Save and restore named views.
- Save, insert, and manage blocks.
- Copy, cut, and paste dimension styles between DWG files.

Topics in this chapter


<i>Using the IntelliCAD Explorer</i>	172
<i>Organizing information on layers</i>	177
<i>Working with linetypes</i>	190
<i>Working with text fonts and styles</i>	198
<i>Working with coordinate systems</i>	202
<i>Using named views</i>	206
<i>Working with blocks and external references</i>	209
<i>Working with dimension styles</i>	216

Using the IntelliCAD Explorer

The IntelliCAD Explorer opens in its own, separate window, which you can move or resize. The IntelliCAD Explorer window has its own menu and tools.


To display the IntelliCAD Explorer

Do one of the following:

- Choose Tools > IntelliCAD Explorer.
- On the Tools toolbar, click the IntelliCAD Explorer tool ()
- Type *explayers* and then press Enter.
- Type *la* and then press Enter.
- On the status bar, right-click on the current layer, and from the list, select the layer you want to make current.

The IntelliCAD Explorer window has two panes, a left pane and a right pane. The elements are listed in the left pane, and the drawing settings are listed and described in the right pane.

TIP *On the Settings menu, you can use the Explore Layers, Explore Blocks, Explore Views, Explore Coordinate Systems, Explore Linetypes, Explore Text Styles, and Explore Dimension Styles commands to display the layers, blocks, views, coordinate systems, linetypes, text styles, and dimension styles for the current drawing in the IntelliCAD Explorer window. Tools for these commands also appear on the Settings toolbar.*














- A Tools on the Standard toolbar provide controls common to all elements.
- B The Elements pane shows an outline view containing the name of every drawing currently open and lists the elements you can control in each drawing.

- C Click on a setting to change it.
- D The named settings for the selected element.
- E Other toolbars appear, depending on the selection in the Elements pane.

Using the IntelliCAD Explorer, you can create, delete, or modify any of the settings for the currently selected element for a given drawing. You can also copy the contents of any element from one drawing to another. The tools and menu items on the IntelliCAD Explorer provide the following functions:




IntelliCAD Explorer tools

Tool	Function
() New Item	Creates a new layer, linetype, style, coordinate system, view, block, or dimension style.
() Current	Makes the selection current.
() Cut	Cuts the selection to the Clipboard.
() Copy	Copies the selection to the Clipboard.
() Paste	Pastes the selection from the Clipboard into the appropriate list of a different drawing.
() Delete	Deletes the selection from the list.
() Properties	Displays the properties for the selection.
() World	Sets the current coordinate system to the World Coordinate System (WCS).
() Purge	Eliminates unreferenced elements from your drawing file.
() Regen	Recalculates the display for the current window.
() On/Off Regen	Turns on and off the display recalculation.

Copying settings

A particularly powerful feature of the IntelliCAD Explorer is its capability of copying many of the settings—layers, linetypes, text styles, coordinate systems, views, blocks, or dimension styles—from one drawing to another. If you have more than one drawing open, the IntelliCAD Explorer makes it easy to reuse information. For example, when you copy layers from one drawing to another, the layer names as well as their linetypes, colors, and other settings are also copied, but not the entities on those layers.

To copy layers from one open drawing to another open drawing

- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
- 2 In the Elements pane, select the drawing from which you want to copy layers.
- 3 If necessary, click the plus (+) symbol to expand the Elements list for the drawing, and then click Layers.
- 4 In the Layers Settings In Drawing list (right pane), select the layers you want to copy.
- 5 Choose Edit > Copy, or click the Copy tool ().
- 6 In the Elements pane, select the drawing to which you want to copy the layers.
- 7 If necessary, click the plus (+) symbol to expand the Elements list for the drawing, and then click Layers.
- 8 Choose Edit > Paste, or click the Paste tool (.



Deleting settings


You can use the IntelliCAD Explorer to delete many of the items that appear in the Elements list. You can delete a layer, linetype, text style, coordinate system, view, block, or dimension style.

Because you may have already created entities on a particular layer or using a particular linetype or text style, deleting one of these elements requires that you make certain choices from options the program presents. For example, if you attempt to delete a layer, the program prompts you to specify whether you want to move any entities from that layer to another layer. Every drawing has at least one layer, the default layer, named “0.” You cannot delete or rename this layer. Your drawing can also contain an unlimited number of additional layers, each of which you assign a unique name.

If you try to delete a linetype, the program prompts you to specify whether you want to convert all entities drawn using that linetype to a different linetype. If you attempt to delete a text style, the program prompts you to specify whether you want to convert all text entities created using that style to a different style.

To delete a layer and relocate its entities to another layer

- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
- 2 From the Layer Name list, select the layer that you want to delete.
If that layer is the current layer, layer 0 automatically becomes the current layer.
- 3 Choose Edit > Delete, or click the Delete tool (.
- 4 From the dialog box, click Change.
- 5 In the drop-down list, double-click the layer to which you want to relocate entities.





- A** Click to delete the layer and all entities on the layer. **C** Click to cancel the layer deletion.
- B** Click to delete the layer after first relocating all of its entities to a selected layer.

Purging elements

From within the IntelliCAD Explorer, you can eliminate unused blocks, layers, line-types, text styles, or dimension styles from your drawing file. Purging unused elements can significantly reduce the drawing file size.

To purge an element

- 1 Do one of the following:
 - Choose Tools > IntelliCAD Explorer.
 - On the Tools toolbar, click the IntelliCAD Explorer tool ().
 - Type *explayers* and then press Enter.
- 2 Select the element from which you want to purge unreferenced elements.
- 3 From the Standard toolbar, select the Purge tool ().
The main drawing window appears.
- 4 In the command bar, do one of the following:
 - Enter the name of the element to purge, and then press Enter.
 - Press Enter to purge all unused elements of the selected type without confirming the removal of each element.

Organizing information on layers

Layers in IntelliCAD are like the transparent overlays you use in manual drafting. You use layers to organize different types of drawing information. In IntelliCAD, each entity in a drawing exists on a layer. When you draw an entity, it is created on the current layer.

You can control the visibility of layers in individual viewports. When you turn a layer off, entities drawn on that layer are no longer visible, and they do not print. Although a layer may be invisible, you can still select it as the current layer, in which case new entities are also invisible until you turn the layer back on. Entities on invisible layers can also affect the display and printing of entities on other layers. For example, entities on invisible layers can hide other entities when you use the Hide command to remove hidden lines.

You can also freeze and thaw layers. Entities drawn on frozen layers do not display, do not print, and do not regenerate. When you freeze a layer, its entities do not affect the display or printing of other entities. For example, entities on frozen layers do not hide other entities when you use the Hide command to remove hidden lines. In addition, you cannot draw on a frozen layer until you thaw it, and you cannot make a frozen layer current.



You cannot freeze the current layer. If you attempt to freeze the current layer, a dialog box appears prompting you to specify a different layer. You also cannot freeze or thaw a viewport layer unless you are working in a Layout tab.


You can lock or unlock layers. The entities on a locked layer are still visible and will print, but you cannot edit them. Locking a layer prevents you from accidentally modifying entities.

Each layer has its own color, linetype, and lineweight. For drawings that use named print styles, layers can also have their own print style. Entities you draw on a particular layer are displayed in the color, linetype, and lineweight associated with that layer unless you override these settings. You control all of the associated settings for layers using the Layers elements in the IntelliCAD Explorer. You can also access layer settings for entities using the Entity Properties toolbar.

To display layers in the IntelliCAD Explorer

Do one of the following:

- Choose Settings > Explore Layers.
- Choose Tools > IntelliCAD Explorer.
- On the Tools toolbar, click the IntelliCAD Explorer tool ()
- On the Settings toolbar, click the Explore Layers tool ()
- Type *explayers* and then press Enter.



A Select Layers to display the Layers settings.

B Lists named layers in the current drawing. A check mark indicates the current layer.

C Displays the color assigned to each layer.

D Displays the linetype assigned to each layer.

E Indicates the visibility status of each layer.

F Indicates the locked or unlocked status of each layer.

G Indicates the frozen or thawed status of each layer for all viewports.

H Indicates the lineweight assigned to each layer.

I Indicates the print style assigned to each layer.




J Indicates the print status of each layer.

K Indicates the frozen or thawed status of the layer in the current viewport.


L Indicates the frozen or thawed status of the layer for new viewports on a Layout tab.

M Sorts the layers by that property when you click a column head.

When Layers are displayed, three tools on the Layer toolbar provide the following functions:

- () **Layer On/Off** toggles the selected layers on and off.
- () **Freeze/Thaw** freezes or thaws the selected layers.
- () **Lock/Unlock** locks or unlocks the selected layers.

You can change any of these settings by clicking either the tool or its current condition. You can edit the color, linetype, lineweight, and other properties of a layer by clicking the corresponding name and selecting the values you want in the dialog box. You can also edit a layer's properties by right-clicking it and choosing Properties.




- | | |
|---|--|
| <p>A Select to keep the dialog box on the screen when you switch back to the IntelliCAD Explorer.</p> <p>B Displays the name of the layer whose properties are being changed.</p> <p>C Displays the current layer color.</p> <p>D Choose the linetype assigned to the selected layer.</p> | <p>E Choose the lineweight assigned to the selected layer.</p> <p>F Choose the print style assigned to the selected layer (only for drawings that use named print style tables).</p> <p>G Click to display the Color dialog box to select a new color.</p> <p>H Select or clear check boxes to control other properties of the selected layer.</p> |
|---|--|


Creating and naming layers

You can create an unlimited number of layers in every drawing and use those layers for organizing information. When you create a new layer, it is initially assigned the color white (or black, depending on your system settings) and the linetype CONTINUOUS. By default, a new layer is also visible. After you create and name a layer, you can change its color, linetype, visibility, and other properties.


NOTE Layer names created or renamed in IntelliCAD can have up to 31 characters and cannot include spaces. IntelliCAD will, however, display longer layer names and names containing spaces, such as layers created in AutoCAD 2000.

To create a new layer

- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
- 2 Choose Edit > New > Layer.
The program adds a new layer to the Layer Name list, with the default name NewLayer1.
- 3 Type a name for the new layer over the highlighted default name, and then press Enter.
- 4 To complete the command and return to your drawing, close the window.

TIP You can also create a new layer by selecting the Layers element for a drawing and clicking the New Item tool ().

To change a layer name in the current drawing



- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
- 2 In the Layer Name list, select the layer you want to make current.
- 3 Do one of the following:
 - Choose Edit > Rename, type a new name, and then press Enter.
 - Highlight the layer name you want to change, type a new name, and then press Enter.
 - Right-click the layer name you want to change, and from the shortcut menu, select Rename, type a new name, and then press Enter.
- 4 To complete the command and return to your drawing, close the window.

NOTE You cannot rename the 0 layer.


Setting the current layer

When you create new entities, they are drawn on the current layer. To draw new entities on a different layer, you must first make that layer the current layer.

To make a layer current

- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
- 2 In the Layer Name list, select the layer you want to make current.
- 3 Do one of the following:
 - Choose Edit > Current.
 - In the Layer Name list, select the name you want to make current, and then click the Current tool (.
 - Double-click the layer name in the Layer Name list.
 - Right-click the layer name you want to change, and from the shortcut menu select Current.
- 4 To complete the command and return to your drawing, close the window.

To set the current layer to that of an existing entity

- 1 Do one of the following:
 - Choose Settings > Set Layer By Entity.
 - On the Settings toolbar, click the Set Layer By Entity tool (.
 - Type *setlayer* and then press Enter.
- 2 Select the entity to set the current layer.


Controlling layer visibility

A layer can be visible or invisible. Entities on invisible layers are not displayed and do not print. By controlling layer visibility, you can turn off unnecessary information, such as construction lines or notes. By changing layer visibility, you can put the same drawing to multiple uses.

For example, if you are drawing a floor plan, you can draw the layout of light fixtures on one layer and the location of plumbing lines on another. By selectively turning layers on and off, you can print the electrical engineering drawings and the plumbing drawings from the same drawing file. For even more convenience, you can control the visibility of layers within individual viewports, so that layers that display in one viewport are invisible in other viewports in the same drawing.

When you turn a layer off, entities drawn on that layer are no longer visible. When you turn the layer back on, the entities on that layer are redisplayed.

To turn layers on or off


- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
- 2 In the Layer Name list, select the layer you want to turn on or off.
- 3 Do one of the following:
 - Choose View > On/Off.
 - Right-click the layer you want to change, and from the shortcut menu, select Properties and turn the layer on or off.
 - Click the setting in the On/Off column.

The On/Off column shows the new setting.
- 4 To complete the command and return to your drawing, close the window.

You can also freeze layers to improve the performance of operations such as zooming and panning or producing hidden lines or shaded images. When a layer is frozen, entities drawn on that layer are no longer visible.


To control the visibility of external reference layers and save any changes made to them in the current drawing, turn on Xref Layer Visibility.

To turn on Xref Layer Visibility

- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter
- 2 Choose View > Xref Layer Visibility.

TIP You can also turn on this variable by typing *visretain*.


To freeze or thaw layers

- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
- 2 In the Layer Name list, select the layers you want to freeze or thaw.
- 3 Do one of the following:
 - Choose View > Freeze/Thaw.
 - Right-click the layer you want to change, and from the shortcut menu, select Properties and freeze or thaw the layer.
 - Click the setting in the All Viewports column.
The All Viewports column shows the new setting.
- 4 To complete the command and return to your drawing, close the window.

Locking and unlocking layers

Locking a layer makes it easy to refer to information contained on the layer, but prevents you from accidentally modifying its entities. When a layer is locked (but visible and thawed), its entities remain visible, but you cannot edit them. If you lock the current layer, you can still add new entities to it. You can also change the linetype and color associated with a locked layer. Unlocking a layer restores full editing capabilities.

To lock or unlock layers

- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
- 2 In the Layer Name list, select the layers you want to lock or unlock.
- 3 Do one of the following:
 - Choose View > Lock/Unlock.
 - Right-click the layer name you want to change, and from the shortcut menu, select Properties and lock or unlock the layer.
 - Click the setting in the Locked column.
The Locked column shows the new setting.
- 4 To complete the command and return to your drawing, close the window.

Controlling layer printing


Controlling layer printing is another way you can specify which entities print in your drawing.

By controlling layer printing, you can turn off unnecessary information during printing. For example, if you are drawing a floor plan, you can draw the layout of light fixtures on one layer and the location of plumbing lines on another. By selectively turning layers on and off when you print, you can print the electrical engineering drawings and the plumbing drawings from the same drawing file. By changing layer printing, you can put the same drawing to multiple uses.

When you turn off printing for a layer, entities drawn on that layer are still visible, but they do not print. If you turn off a layer's visibility, entities drawn on that layer do not display or print. Controlling layer printing can be especially helpful if you want layer visibility on, but do not want to print entities on that layer.

Layer visibility must be turned on in order to print entities drawn on that layer.

To turn layer printing on or off

- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
- 2 In the right pane, click the setting in the Print column for the layer you want to change. Choose Yes to print entities assigned to the layer. Choose No to omit entities assigned to the layer during printing.


You can also right-click the layer you want to change, and from the shortcut menu, select Properties and change the print setting for a layer.

Setting the layer color

Each layer in a drawing is assigned a color. IntelliCAD uses the BYLAYER color as the default color setting for entity creation so that new entities are drawn in the color of the layer on which they are inserted (set in the Drawing Settings dialog box).

Using the IntelliCAD Explorer, you can set or change the color assigned to a layer. With the direct-editing feature, you can click on the color you want to change, and then select a new color from the dialog box that appears. Changing a layer's color automatically changes the color of all entities on that layer with the BYLAYER color.

To change the layer color

- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
- 2 In the right pane, click the color swatch for the layer you want to change.

TIP *Right-click the name of the layer you want to change, and from the shortcut menu, select Properties and change the layer color.*

- 3 In the Color dialog box, select a color on one of the following tabs:
 - **Index Color** — Click BYBLOCK, BYLAYER, or one of the 255 index colors. You can also type the color number in the Index box.
 - **True Color** — Click a basic color, click a color in the color palette, enter the Hue, Saturation, and Luminance (HSL) values, or enter the Red, Green, Blue (RGB) values. There are more than 16 million true colors from which you can choose.
 - **Color Books** — Select a color book from the list, then click a color. You can select Show Only Color Book Colors Used in Drawing to limit the selection to only those color book colors that are used in the current drawing. If necessary, create or edit color books by clicking Color Book Editor. For more details, see “Using color books” on page 61.
- 4 Click OK.

NOTE *You can also assign a specific color to an entity, which overrides the layer’s color setting. When you create a new entity, use the Settings > Colors > Select Color command to change the current color. For an existing entity, select the entity, right-click for the shortcut menu, and choose Properties. You can then change the entity’s color in the Entity Properties dialog box.*

For more details about using color in the many aspects of your drawing, see “Working with colors” on page 58.

Setting a layer's linetype


Each layer uses a default linetype (a repeating pattern of dashes, dots, or blank spaces). Linetype determines the appearance of entities both on the screen and when printed.

It's a good idea to assign the BYLAYER linetype to any entities that you draw on that layer. IntelliCAD uses the BYLAYER linetype as the default linetype setting for Entity Creation (in the Drawing Settings dialog box).

Using the IntelliCAD Explorer, you can set or change the linetype assigned to a layer. With the direct-editing feature, you can click on the linetype you want to change, and then select a new linetype from the dialog box that appears. Changing the linetype assigned to a layer changes the linetype of all entities drawn on that layer with the BYLAYER linetype.

NOTE *Only those linetypes already set in the drawing can be assigned to layers. For more information about setting additional linetypes, see see "Working with linetypes" on page 190 in this chapter.*

To change the linetype assigned to one or more layers

- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
- 2 In the right pane, click the linetype for the layer you want to change.
- 3 In the Linetype dialog box, select a new linetype for the layer, or click Browse to select your linetype file.

You can also right-click the layer you want to change, and from the shortcut menu, select Properties and change the linetype assigned to a layer.

NOTE *You can also assign a specific linetype to an entity, which overrides the layer's linetype setting. When you create a new entity, use the Settings > Explore Linetypes command to change the current linetype through the IntelliCAD Explorer. For an existing entity, select the entity, right-click for the shortcut menu, and choose Properties. You can then modify the entity's linetype in the Entity Properties dialog box.*

Setting a layer's lineweight


Each layer uses a default lineweight. Lineweights determine the thickness of entities both on the screen and when printed.

All new layers are assigned the DEFAULT lineweight, which is .25 millimeters or .01 inches. If you want a different lineweight assigned to a layer, you can easily change it using IntelliCAD Explorer. For example, you may want different lineweights on each layer of your drawing to show separate elements, such as walls, dimensions, structural steel, and electrical plans. Changing the lineweight assigned to a layer changes the lineweight of all entities drawn on that layer with the BYLAYER lineweight.

When you create new entities, it's a good idea to assign the BYLAYER lineweight to any entities that you draw on that layer, unless you want to override the layer lineweight. IntelliCAD uses the BYLAYER lineweight as the default lineweight setting when you create entities (in the Drawing Settings dialog box).

TIP *To change the DEFAULT lineweight, choose Settings > Drawing Settings, click the Display tab, select Lineweights in Change Settings For, and then select a new default.*

To change the lineweight assigned to one or more layers

- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
- 2 In the right pane, click the lineweight for the layer you want to change.
- 3 In the Lineweight list, click the arrow to scroll the lineweights, and then select a new lineweight for the layer.

You can also right-click the layer you want to change, and from the shortcut menu, select Properties and change the lineweight assigned to a layer.

NOTE *You can also assign a specific lineweight to an entity, which overrides the layer's lineweight setting. When you create a new entity, use the Settings > Drawing Settings > Entity Creation tab to change the current lineweight. For an existing entity, select the entity, right-click for the shortcut menu, and choose Properties. You can then modify the entity's lineweight in the Entity Properties dialog box.*

Setting a layer's print style


If your drawing uses named print style tables, you can specify a print style for each layer. Named print style tables contain print styles that you set up to control what entities look like when they print, without actually changing the entities in the drawing.

If your drawing uses color-dependent print style tables, you cannot specify a print style for a layer. These types of print style tables automatically determine printing requirements by the color assigned to a layer or an entity. For details about converting a drawing that uses color-dependent print style table to use named print style tables, see “Changing a drawing’s print style table type” on page 387.

In drawings that use named print style tables, the default print style is Normal for all new layers. If desired, you can assign a print style using IntelliCAD Explorer. Changing the print style assigned to a layer changes the print style of all entities drawn on that layer with the BYLAYER print style.

When you create new entities, it’s a good idea to assign the BYLAYER print style to any entities that you draw on that layer, unless you want to override the layer print style. IntelliCAD uses the BYLAYER print style as the default print style setting when you create entities (in the Drawing Settings dialog box).

To change the print style assigned to one or more layers (only in a drawing that uses named print style tables)

- 1 Do one of the following:
 - Choose Settings > Explore Layers.
 - On the Settings toolbar, click the Explore Layers tool ().
 - Type *explayers* and then press Enter.
- 2 In the right pane, click the print style for the layer you want to change.
- 3 If necessary, select a different print style table in the Active Print Style Table list.
- 4 In Print Styles, select a print style.
- 5 Click OK.

You can also right-click the layer you want to change, and from the shortcut menu, select Properties and change the print style assigned to a layer.


NOTE For drawings that use named print style tables, you can also assign a specific print style to an entity, which overrides the layer’s print style setting. When you create a new entity, use the Settings > Drawing Settings > Entity Creation tab to change the current print style. For an existing entity, select the entity, right-click for the shortcut menu, and choose Properties. You can then modify the entity’s print style in the Entity Properties dialog box.

Working with linetypes

IntelliCAD provides simple and complex linetypes:

- A *simple* linetype consists of a repeating pattern of dots, dashes, or blank spaces.
- A *complex* linetype contains embedded shape and text entities along with dots, dashes, and spaces.


You can use different linetypes to represent specific kinds of information. For example, if you are drawing a site plan, you can draw roads using a continuous linetype, a fence using a using a linetype of dashes with square posts, or a gas line using a complex linetype showing the text “GAS”.




By default, every drawing has at least three linetypes: CONTINUOUS, BYLAYER, and BYBLOCK. You cannot rename or delete these linetypes. Your drawing may also contain an unlimited number of additional linetypes. You can load more linetypes into the program from a linetype library file or create and save linetypes you define.

To display the IntelliCAD Explorer Linetypes element

Do one of the following:

- Choose Settings > Explore Linetypes.
- On the Settings toolbar, click the Explore Linetypes tool ().
- Type *expltypes* and then press Enter.
- Choose Tools > IntelliCAD Explorer, and then click the Linetypes element.





- A Select Linetypes to display the Linetypes settings.
- B Lists names of linetypes loaded in the current drawing. A check mark indicates the current linetype.
- C Describes linetypes loaded in the current drawing.
- D Shows how linetypes will appear in the drawing.
- E Sorts the linetypes by that property when you click a column head.

Setting the current linetype

You normally draw an entity using the linetype assigned to the current layer, indicated as BYLAYER. You can also assign linetypes on a per-entity basis, which overrides the layer's linetype setting. A third option is to assign the BYBLOCK linetype, whereby you draw new entities using the default linetype until you group them into a block. The entities inherit the current linetype setting when you insert the block into the drawing.



To make the linetype current

- Do one of the following:
 - Choose Settings > Explore Linetypes.
 - On the Settings toolbar, click the Explore Linetypes tool ().
 - Type *expltypes* and then press Enter.
- In the Linetype Name list, select the linetype you want to make current.
- Do one of the following:
 - Choose Edit > Current.
 - Select it in the Linetype Name list and click the Current tool ().
 - Double-click the linetype name.
- To complete the command and return to your drawing, close the window.

Loading additional linetypes

Before you can select a new linetype to use in a drawing, you must either create the linetype definition or load a predefined linetype from a linetype library file (*.lin). IntelliCAD includes a linetype library file, `icad.lin`, which contains more than 100 predefined linetypes.

To load a new linetype from a linetype library



- 1 Do one of the following:
 - Choose Settings > Explore Lintypes.
 - On the Settings toolbar, click the Explore Lintypes tool ().
 - Type *expltypes* and then press Enter.
- 2 Using one of the following methods, open the New Linetype dialog box:
 - Choose Edit > New > Linetype.
 - Click the New Item tool ().
 - With the cursor in the right pane of the window, right-click to display the shortcut menu, and then choose New > Linetype.
- 3 Click Choose From File.
- 4 Click Browse.
- 5 Select the linetype library file, and then click Open.
- 6 Select the linetype you want to load.
- 7 Click OK, and then close the window.

Creating and naming linetypes

In addition to loading predefined linetypes from a linetype library file, you can create new linetypes. You can save new linetypes you create to a linetype library file for use in other drawings.

NOTE *Linetype names created or renamed in IntelliCAD can have up to 31 characters and cannot include spaces. IntelliCAD will, however, display longer linetype names and names containing spaces, such as linetypes created in AutoCAD 2000.*

To create a new simple linetype


- 1 Do one of the following:
 - Choose Settings > Explore Linetypes.
 - On the Settings toolbar, click the Explore Linetypes tool ().
 - Type *expltypes* and then press Enter.
- 2 Using one of the following methods, open the New Linetype dialog box:
 - Choose Edit > New > Linetype.
 - Click the New Item tool ().
 - With your cursor in the right pane of the window, right-click to display the shortcut menu, and choose New > Linetype.
- 3 In the Linetype Description field, type the linetype description.

You can type anything in this field that will help you remember the purpose or appearance of this linetype. For example, it is helpful to type text or symbols such as *___...* that approximate the appearance of the linetype.
- 4 In the Linetype Definition field, type the linetype definition.

The definition consists of positive and negative numbers separated by commas. A positive number draws a solid line segment for the specified number of drawing units; a negative number creates a gap for the specified number of units; a zero creates a dot.
- 5 Click OK.

The program adds the new linetype to the linetypes list with the default name, *NewLinetype1*.
- 6 To enter a name for the new linetype, type over the highlighted default text, and press Enter.



Do not use spaces between words in the new linetype name.
- 7 To complete the command and return to your drawing, close the window.



- A** Click to select a predefined linetype from a linetype library file.
- B** Type any description in this box that helps you remember the purpose or appearance of the linetype.
- C** Type the definition of the linetype, consisting of positive and negative numbers separated by commas.

To create a new complex linetype

A complex linetype can denote utilities, boundaries, contours, and so on. As with simple linetypes, complex lines are dynamically drawn as the user specifies vertices. Shapes and text entities embedded in lines are always displayed completely; they are never trimmed.

- 1 Do one of the following:
 - Choose Settings > Explore Linetypes.
 - On the Settings toolbar, click the Explore Linetypes tool ().
 - Type *expltypes* and then press Enter.
- 2 Using one of the following methods, open the New Linetype dialog box:
 - Choose Edit > New > Linetype.
 - Click the New Item tool ().
 - With your cursor in the right pane of the window, right-click to display the shortcut menu, and choose New > Linetype.
- 3 In the Linetype Description field, type the linetype description.

You can type anything in this field that will help you remember the purpose or appearance of this linetype. For complex linetypes, it is helpful to type a text description of the linetype.
- 4 In the Linetype Definition field, type the linetype definition.

As for the simple linetypes, the syntax for a complex linetype is a comma delimited list of pattern descriptors. For more details, see “Syntax for a complex linetype definition” on page 195 in this chapter.

5 Click OK.

The program adds the new linetype to the linytypes list with the default name, NewLinetype1.

6 To enter a name for the new linetype, type over the highlighted default text, and press Enter.

Do not use spaces between words in the new linetype name.

7 To complete the command and return to your drawing, close the window.*Syntax for a complex linetype definition*

Complex linytypes can include shape and text entities as pattern descriptors, as well as the dash and dot descriptors of simple linytypes.

The shape descriptor syntax

You can add a shape entity to a complex linetype using the following syntax:

[shape_name, shape_filename] or [shape_name, shape_filename, transform]

The definitions of the fields in the syntax are as follows.

shape_name The name of the shape to add to the linetype. The shape name must exist in the specified shape file (shape_filename).

shape_filename The name of a compiled shape definition file (extension *.shx). If no path is defined for the shape file name, the library path is searched for the file.

transform The transform argument is optional and can be any series of the following (each preceded by a comma):

R=value	Relative rotation
A=value	Absolute rotation
S=value	Scale
X=value	X offset
Y=value	Y offset

In this syntax, *value* represents a signed decimal number. The rotation is expressed in degrees while the other options are in linetype scaled drawing units.

rotation R=value or A=value.

R= determines a relative or tangential rotation with respect to the line's elaboration.

A= determines an absolute rotation of the shape with respect to the origin. All shapes have the same rotation regardless of their relative position to the line. The value can be appended with a *d* for degrees (default), *r* for radians, or *g* for grads. If rotation is omitted, 0 relative rotation is used.

scale S=value.

Determines a factor by which the shape's internal scale is multiplied. If the shape's internal scale is 0, the scale value is used as the scale.

X offset X=value.

Determines a shift of the shape along the X axis of the linetype computed from the end of the linetype definition vertex. If X offset is omitted or is 0, the shape is elaborated with no offset. Include this field if you want a continuous line with shapes. This value is not scaled by the scale factor defined by S.

Y offset Y=value.

Determines a shift of the shape along the Y axis of the linetype computed from the end of the linetype definition vertex. If Y offset is omitted or 0, the shape is elaborated with no offset. This value is not scaled by the scale factor defined by S.

The text descriptor syntax

You can add a text entity to a complex linetype using the following syntax:

```
["string", style_name] or ["string", style_name, transform]
```

The definitions of the fields in the syntax are as follows.

string The text to be used in the complex linetype. You cannot use the ` or the " characters in the text string. To use these characters, enter a control code (%%) with the ASCII value for the character instead.

style_name The name of the text style to be elaborated. The specified text style must be included. If it is omitted, use the currently defined style.

transform The transform argument is optional and can be any series of the following (each preceded by a comma):

R=value	Relative rotation
A=value	Absolute rotation
S=value	Scale
X=value	X offset
Y=value	Y offset

In this syntax, *value* represents a signed decimal number. The rotation is expressed in degrees while the other options are in linetype scaled drawing units.

rotation R=value or A=value.

R= determines a relative or tangential rotation with respect to the line's elaboration.

A= determines an absolute rotation of the text with respect to the origin. All text has the same rotation regardless of its relative position to the line. The value can be appended with a *d* for degrees (default), *r* for radians, or *g* for grads. If *rotation* is omitted, 0 relative rotation is used.

Rotation is centered between the baseline and the nominal cap heights box.

scale S=value.

Determines a factor by which the style's height is multiplied. If the style's height is 0, the scale value is used as the scale.

Because the final height of the text is defined by both the scale value and the height assigned to the text style, you will achieve more predictable results by setting the text style height to 0. It is recommended that you create separate text styles for text in complex linetypes to avoid conflicts with other text in your drawing.

X offset X=value.


Determines a shift of the text along the X axis of the linetype computed from the end of the linetype definition vertex. If X offset is omitted or is 0, the text is elaborated by using the lower left corner of the text as the offset. Include this field if you want a continuous line with text. This value is not scaled by the scale factor that is defined by S.

Y offset Y=value.


Determines a shift of the text along the Y axis of the linetype computed from the end of the linetype definition vertex. If Y offset is omitted or is 0, the text is elaborated by using the lower left corner of the text as the offset. This value is not scaled by the scale factor that is defined by S.

Editing linetypes

To change a linetype name

- 1 Do one of the following:
 - Choose Settings > Explore Linetypes.
 - On the Settings toolbar, click the Explore Linetypes tool ().
 - Type *expltypes* and then press Enter.
- 2 Do one of the following:
 - Select the linetype, and then choose Edit > Rename.
 - Click the linetype name you want to change, and then type the new name.
 - Right-click the linetype name you want to change, and from the shortcut menu, select Rename.
- 3 To complete the command and return to your drawing, close the window.

To change a linetype definition

- 1 Do one of the following:
 - Choose Settings > Explore Linetypes.
 - On the Settings toolbar, click the Explore Linetypes tool ().
 - Type *expltypes* and then press Enter.
- 2 Right-click on the linetype name for which you want to change the definition.
- 3 From the shortcut menu, select Properties.
- 4 In the Linetype Definition field, define the linetype using positive and negative numbers and zeros.
 A positive number draws a solid line segment for the specified number of drawing units. A negative number creates a gap for the specified number of drawing units. A zero creates a dot.
- 5 To complete the command and return to your drawing, close the Linetypes dialog box and the IntelliCAD Explorer window.

NOTE You cannot rename the *CONTINUOUS*, *BYBLOCK*, or *BYLAYER* linetypes.

Working with text fonts and styles


When you add text to a drawing, it is created using the current text style. The text style determines the font, size, angle, orientation, and other text characteristics.


Every drawing has at least one text style, named Standard, which initially uses the txt font. You cannot delete the Standard style, but you can rename it or modify it. For example, you can change the font or the oblique angle applied to the font. You also can use an unlimited number of additional text styles in your drawing.

From the IntelliCAD Explorer, you can directly edit any setting associated with a text style by using the single-click editing method to change the setting.

To display the IntelliCAD Explorer Text Styles element

Do one of the following:

- Choose Settings > Explore Text Styles.
- Choose Tools > IntelliCAD Explorer, and then click the Text Styles element.
- On the Settings toolbar, click the Explore Text Styles tool (.
- Type *expstyles* and then press Enter.



- A Select Text Styles to display the text style settings.
- B Lists names of text styles defined in the current drawing. A check mark indicates the current style.
- C Displays the height assigned to the text style.
- D Displays the width factor assigned to the text style.
- E Displays the oblique angle assigned to the text style.
- F Displays the font on which the style is based.

- G Displays the font style, such as bold or italic.
- H Displays the language on which the text style is based.
- I Displays whether Asian language big font files are used (for .shx file fonts only).
- J Indicates whether text will appear backward.
- K Indicates whether text will appear upside down.
- L Indicates whether text will appear vertically.
- M Click any column head to sort the styles by that property.


Creating and naming text styles


Fonts are character sets that consist of letters, numbers, punctuation marks, and symbols. Each font is stored in its own font file. Text styles apply additional formatting to fonts. You can create multiple text styles based on the same font, changing the various characteristics to alter the appearance of the font. To create a new text style, you assign formatting characteristics to a font.

IntelliCAD uses *.shx font files and provides a selection of fonts. These fonts are located in the IntelliCAD/Fonts directory. You can also use any font designed to work with AutoCAD. Many fonts are available from third-party vendors.


NOTE *Text style names created or renamed in IntelliCAD can have up to 31 characters and cannot include spaces. IntelliCAD will, however, display longer text style names and names containing spaces, such as text styles created in AutoCAD.*

To create a new text style

- 1 Do one of the following:
 - Choose Settings > Explore Text Styles.
 - On the Settings toolbar, click the Explore Text Styles tool ().
 - Type *expfonts* and then press Enter.
- 2 Choose Edit > New > Text Style.
- 3 Select the font on which you want to base the new style, and then click Open.
The program adds a new style to the text styles list with the default name, NewStyle1.
- 4 Type the name for the new style by typing over the highlighted default text, and then press Enter.
- 5 To complete the command, close the window.

TIP You can also create a new text style by selecting the Text Styles element and clicking the New Item tool ().

To change a text style name in the current drawing


- 1 Do one of the following:
 - Choose Settings > Explore Text Styles.
 - On the Settings toolbar, click the Explore Text Styles tool ().
 - Type *expfonts* and then press Enter.
- 2 Do one of the following:
 - Select the text style, choose Edit > Rename, type a new name, and then press Enter.
 - Click the text style name you want to change, type a new name, and then press Enter.
 - Right-click the text style name you want to change, and from the shortcut menu, select Rename, type a new name, and then press Enter.
- 3 To complete the command and return to your drawing, close the window.


Modifying text styles

A new text style is initially assigned default values for height, width factor, oblique angle, and other characteristics. You can change these values for both new and existing text styles. You can also change the font assigned to the text style. If you change the font or orientation properties of a text style assigned to text previously inserted in the drawing, all text using that style is regenerated to reflect the changes. Oblique angle and height, if specified, are given by the style definition when text is created, but are not updated for existing text when the style is changed.

A fixed text height value of 0 allows you to specify the text height at the time you insert text into the drawing. Any other value sets height of the text to that value; the program does not prompt for the text height when you insert text into the drawing. The width factor determines the horizontal scaling of text. A value less than 1 compresses the text (for example, 0.75 compresses the text 25 percent); a value greater than 1 expands the text (for example, 1.50 expands the text 50 percent). The oblique angle determines the forward or backward slant of text as an angle offset from 90 degrees. Negative values slant text to the left; positive values slant text to the right.

To modify a text style

- Do one of the following:
 - Choose Settings > Explore Text Styles.
 - On the Settings toolbar, click the Explore Text Styles tool ().
 - Type *expfonts* and then press Enter.
- Select the text characteristic of a style that you want to modify. The text characteristic either toggles its value or a dialog box appears, allowing you to make the modifications you want.
- To complete the command, close the IntelliCAD Explorer window.






- | | |
|--|--|
| <p>A Select to keep the dialog box on the screen when you switch back to the IntelliCAD Explorer or another element.</p> <p>B Displays the name of the text style whose properties are being changed.</p> <p>C Type the fixed text height.</p> <p>D Type the width factor.</p> <p>E Type the oblique angle.</p> <p>F Select to create text that displays backward.</p> | <p>G Select to create text that displays upside down.</p> <p>H Select to create text that displays vertically.</p> <p>I Displays a text preview of the text font.</p> <p>J Select the Asian language big font (for .shx file fonts only).</p> <p>K Select the text style language.</p> <p>L Select the font style.</p> <p>M Select the font name.</p> |
|--|--|

Setting the current text style

When you insert text in a drawing, the text is created using the current text style. You can also select a different text style when you create text.

To make the text style current

- 1 Do one of the following:
 - Choose Settings > Explore Text Styles.
 - On the Settings toolbar, click the Explore Text Styles tool ().
 - Type *expfonts* and then press Enter.
- 2 In the Text Style Name list, click the style you want to make current.
- 3 Use one of the following methods to make the style the current style:
 - Choose Edit > Current.
 - Click the Current tool (.
 - With the cursor in the right pane of the window, right-click to display the shortcut menu, and choose Current.
- 4 To complete the command and return to your drawing, close the IntelliCAD Explorer window.

TIP You can also make a text style current by selecting it in the Text Style Name list and clicking the Current tool () or by double-clicking the text style name in the Text Style Name list.

Working with coordinate systems

When you create entities in a drawing, they are located in relation to the drawing's underlying Cartesian coordinate system. Every drawing has a fixed coordinate system called the World Coordinate System (WCS). You cannot delete or modify the WCS.


Your drawing may contain additional coordinate systems, however, each with its own 0,0,0 origin and orientation. You can create as many user coordinate systems as you want, and then save and recall them as you need them. You can edit the origin of a coordinate system from within the IntelliCAD Explorer by single-clicking the origin coordinates and then typing new coordinates.


For example, you can create a separate user coordinate system (UCS) for each side of a building. Then, by switching to the UCS for the east side of the building, you can draw the windows on that side by specifying only their x- and y-coordinates.

You can create and then switch between various user coordinate systems by selecting Coordinate Systems in the IntelliCAD Explorer.

To display the Coordinate Systems element

Do one of the following:

- Choose Settings > Explore Coordinate Systems.
- Choose Tools > IntelliCAD Explorer, and then click the Coordinate Systems element.
- Choose Settings > User Coordinate Systems, and then click Explore UCSs.
- On the Settings toolbar, click the Explore Coordinate Systems tool ().
- Type *expucs* and then press Enter.





- A** Select Coordinate Systems to display the Coordinate Systems settings.
- B** Lists names of coordinate systems defined in the current drawing. A check mark indicates the current coordinate system.
- C** Displays the origin of the coordinate system in relation to the WCS.
- D** Displays the x-axis direction of the coordinate system in relation to the WCS.
- E** Displays the y-axis direction of the coordinate system in relation to the WCS.
- F** Click any column head to sort the coordinate systems by that property.

Defining and naming user coordinate systems

A drawing can contain as many coordinate systems as you want and can be named appropriate names so you can remember how they are used in your drawing for recalling them later.


NOTE *Coordinate system names created or renamed in IntelliCAD can have up to 31 characters and cannot include spaces. IntelliCAD will, however, display longer coordinate system names and names containing spaces, such as coordinate systems created in AutoCAD 2000.*

To define new user coordinate systems in the IntelliCAD Explorer

- 1 Do one of the following:
 - Choose Settings > Explore Coordinate Systems.
 - On the Settings toolbar, click the Explore Coordinate Systems tool ()
 - Type `expucs` and then press Enter.
- 2 Do one of the following:
 - Choose Edit > New > UCS.
 - Click the New Item tool ()
 - With your cursor in the right pane of the window, right-click to display the shortcut menu, and choose New > UCS.
- 3 Select a method from the prompt box or command bar by which to define the UCS in the drawing window.

For example, select *3 Point* and then specify three points in the drawing window to define the x, y, and z axes for your coordinate system.
- 4 Type the name for the new user coordinate system by typing over the highlighted default text, and then press Enter.
- 5 To complete the command, close the window.

To change a user coordinate system name in the current drawing


- 1 Do one of the following:
 - Choose Settings > Explore Coordinate Systems.
 - On the Settings toolbar, click the Explore Coordinate Systems tool ()
 - Type *expucs* and then press Enter.
- 2 Do one of the following:
 - Select the user coordinate system, and then choose Edit > Rename, type a new name, and then press Enter.
 - Click the user coordinate system name you want to change, type a new name, and then press Enter.
 - Right-click the user coordinate system name you want to change, and from the shortcut menu, select Rename, type a new name, and then press Enter.
- 3 Type the new user coordinate system name, and then press Enter.
- 4 To complete the command and return to your drawing, close the window.

Setting the current user coordinate system

When you draw new entities, they are created in relation to the current coordinate system. You can set the current UCS from the IntelliCAD Explorer.

To set the current UCS from the IntelliCAD Explorer

Do one of the following:


- Double-click the UCS name in the UCS Name list.
- Select the UCS in the UCS Name list, and then choose Edit > Current.
- Select the UCS in the UCS Name list, and then click the Current tool ()


Using named views

As you work on a drawing, you may find that you frequently switch among different portions of it. For example, if you are drawing the floor plan of a house, you may zoom in to particular rooms of the house and then zoom out to display the entire house. Although you can repeat the Pan and Zoom commands to do this, it is much easier to save various views of the drawing as named views. You can then quickly switch among these views. You can save and later restore named views using either the View command or the Views element in the IntelliCAD Explorer.

To display Views in the IntelliCAD Explorer

Do one of the following:

- Choose Settings > Explore Views.
- On the Settings toolbar, click the Explore Views tool ().
- Type *expviews* and then press Enter.
- Choose Tools > IntelliCAD Explorer, and then click the Views element.




- A To display the Views settings, select Views.
- B Lists names of views defined in the current drawing. A check mark indicates the current view.
- C Displays the height of the view in drawing units.
- D Displays the width of the view in drawing units.
- E Displays the direction of the view, expressed as a three-dimensional coordinate in the WCS.
- F Click any column head to sort the views by that property.

Saving and naming views



You can save the view displayed in the current window as a named view. After you save a named view, you can restore that view in the current window at any time.

NOTE *View names created or renamed in IntelliCAD can have up to 31 characters and cannot include spaces. IntelliCAD will, however, display longer view names and names containing spaces, such as views created in AutoCAD 2000.*


To save the current view as a named view

- 1 Do one of the following:
 - Choose View > Save/Restore View.
 - On the View toolbar, click the Save/Restore View tool ()
 - Type *view* and then press Enter.
- 2 In the prompt box, choose Save.
- 3 Type a name for the view, and then press Enter.
- 4 To complete the command and return to your drawing, close the window.


To save a portion of the current view as a named view

- 1 Do one of the following:
 - Choose Settings > Explore Views.
 - On the Settings toolbar, click the Explore Views tool ()
 - Type *expviews* and then press Enter.
- 2 Do one of the following:
 - Choose Edit > New > View.
 - On the IntelliCAD Explorer toolbar, click the New Item tool ()
- 3 In the prompt box, choose Window.
- 4 Specify the first corner of the view window.
- 5 Specify the opposite corner of the view window.
- 6 Rename the new view, and then press Enter.

Do not use spaces between words in the new view name.
- 7 To complete the command and return to your drawing, close the window.

TIP *You can also create a new view by selecting the Views element in the IntelliCAD Explorer and clicking the New Item tool ()*


To change a saved view name in the current drawing

- 1 Do one of the following:
 - Choose Settings > Explore Views.
 - On the Settings toolbar, click the Explore Views tool ()
 - Type *expviews* and then press Enter.
- 2 Do one of the following:
 - Select the view, choose Edit > Rename, type a new name, and then press Enter.
 - Click the view name you want to change, type a new name, and then press Enter.
 - Right-click the view name you want to change, and from the shortcut menu, select Rename, type a new name, and then press Enter.
- 3 Type the new view name, and then press Enter.
- 4 To complete the command and return to your drawing, close the window.

Restoring named views


After you save one or more named views, you can restore any of those views in the current window using either the View command or the IntelliCAD Explorer.

To restore a named view using the View command

- 1 Do one of the following:
 - Choose View > Save/Restore View.
 - On the View toolbar, click the Save/Restore View tool ()
 - Type *view* and then press Enter.
- 2 In the prompt box, choose Restore.
- 3 Type the name of the view you want to restore, and then press Enter.

To restore a named view from the IntelliCAD Explorer


Do one of the following:

- Select the view name in the list of View settings, and then choose Edit > Current.
- Select the view name in the list of View settings, and then click the Current tool ()
- Double-click the view name in the View list.

Changing named view properties

Once you create a named view you can modify its properties, such as the target direction and twist angle. This gives you access to many of the view settings after a view has been defined.

To change the view options

- 1 Do one of the following:
 - Choose Settings > Explore Views.
 - On the Settings toolbar, click the Explore Views tool ().
 - Type *expviews* and then press Enter.
- 2 Select the view whose properties you want to change.
- 3 Choose Edit > Properties.

You can also right-click the view you want to change, and from the shortcut menu, select Properties.
- 4 Change the values of the settings on any of the tabs and close the dialog box.
- 5 To complete the command and return to your drawing, close the window.

Working with blocks and external references

Blocks represent a special type of entity that, once saved, can be inserted and manipulated in the drawing as a single entity. A block can consist of visible entities such as lines, arcs, and circles as well as visible or invisible data called attributes. You can use attributes to track things such as part numbers and prices and to export attribute information to an external database. You can also track the number of parts by counting the number of times a block has been inserted into the drawing. Blocks are stored as part of the drawing file.


External references have similar uses to blocks. Using external references, you can attach entire drawings to your current drawing. Unlike a block, however, an external reference does not become part of the current drawing.

You can save blocks in the IntelliCAD Explorer. You can also use the IntelliCAD Explorer to manage and insert copies of blocks. The IntelliCAD Explorer lists the names of all blocks contained in the current drawing, along with other information about each block or external reference.


You can also rename a block, modify its insertion point, and change the path of an externally referenced drawing by single-clicking on the property and making your edits within the IntelliCAD Explorer.

To display blocks in the IntelliCAD Explorer

Do one of the following:

- Choose Settings > Explore Blocks.
- Choose Tools > IntelliCAD Explorer, and then click the Blocks element.
- On the Settings toolbar, click the Explore Blocks tool ().
- Type *expblocks* and then press Enter.




The Blocks element in the IntelliCAD Explorer defaults with images on. The Images view shows you a small image of each block or external reference.






The Images view shows an image of each block in the selected drawing. Click an image to select it.


When blocks are displayed, additional tools on the Block toolbar provide the functions described in the following table:


Additional tools on the Block toolbar

Tool	Function
() Images	Displays a small image of each block.
() Details	Displays information about each block.
() Insert	Inserts a block.

Additional tools on the Block toolbar

Tool	Function
() Insert External File Blocks	Inserts a drawing available from disk as a block.
() Save Block	Saves selected block as independent .dwg file.
() Attach Drawing	Attaches drawing as an external reference.

To see more information about each block, click the Details tool (). In the Details view, you can edit the path and the insertion point by clicking the setting and typing your changes.





- A** To display the Blocks settings, select Blocks.
- B** Lists names of blocks and external references defined in the current drawing.
- C** Displays the number of occurrences of the block in the current drawing.
- D** Displays the insertion point of the block in the current drawing.
- E** Displays the name and path for externally referenced drawings.
- F** Click any column head to sort the blocks by that property.

Creating and naming blocks


You can combine any number of entities into a single block. After you create a block, you can insert copies of it into a drawing. Each block insertion is treated as a single entity; for example, you can rotate or scale each block when you insert it. The program adds the name of the new block you insert to the Block Name list in the IntelliCAD Explorer.

NOTE *Block names created or renamed in IntelliCAD can have up to 31 characters and cannot include spaces. IntelliCAD will, however, display longer block names and names containing spaces, such as blocks created in AutoCAD 2000.*

To create a block

- 1 Do one of the following:
 - Choose Settings > Explore Blocks.
 - On the Settings toolbar, click the Explore Blocks tool ().
 - Type *expblocks* and then press Enter.
- 2 Do one of the following:
 - Choose Edit > New > Block.
 - On the IntelliCAD Explorer toolbar, click the New Item tool ().
- 3 Enter a name for the new block.
- 4 Specify the insertion point for the block.
- 5 Select the entities to be combined into the block, and then press Enter.
The program adds a new block to the blocks list, with the name you entered for it.
- 6 To complete the command and return to your drawing, close the window.



To change a block name in the current drawing

- 1 Do one of the following:
 - Choose Settings > Explore Blocks.
 - On the Settings toolbar, click the Explore Blocks tool ().
 - Type *expblocks* and then press Enter.
- 2 Do one of the following:
 - Select the block, choose Edit > Rename, type a new name, and then press Enter.
 - Click the block name you want to change, type a new name, and then press Enter.
 - Right-click the block name you want to change, and from the shortcut menu, select Rename, type a new name, and then press Enter.
- 3 To complete the command and return to your drawing, close the window.

Inserting a block

You can insert into a drawing any block listed in the Block Name list in the IntelliCAD Explorer. This includes blocks contained within any open drawing.

To insert a block

- 1 Do one of the following:
 - Choose Settings > Explore Blocks.
 - On the Settings toolbar, click the Explore Blocks tool ().
 - Type *expblocks* and then press Enter.
- 2 If you want to insert a block from another open drawing, select the drawing in the Elements pane. (If the block is contained within the same drawing, you can skip this step.)
- 3 In either the Details or Images view, select the block to be inserted.
- 4 On the IntelliCAD Explorer toolbar, click the Insert tool (.
- 5 In the drawing, specify the insertion point.
- 6 Specify the x, y, and z scale factor and the rotation angle, or in the prompt box, select Done.
- 7 To complete the command and return to your drawing, close the window.



TIP You can also insert a block by choosing Tools > IntelliCAD Explorer, and then double-clicking the name of the block you want to insert in the Block Name list.

TIP You can also insert a block from the Insert menu. see Chapter 13, “Working with blocks, attributes, and external references.”

Inserting a drawing as a block

You can insert as a block another drawing into the current drawing. After you do this, the block name is added to the Block Name list in the IntelliCAD Explorer. Changes made later to the inserted drawing will not be reflected in this drawing.



To insert a drawing as a block

- 1 Do one of the following:
 - Choose Settings > Explore Blocks.
 - On the Settings toolbar, click the Explore Blocks tool ().
 - Type *expblocks* and then press Enter.
- 2 On the IntelliCAD Explorer toolbar, click the Insert External File Blocks tool ().
- 3 In the Insert Block dialog box, select the drawing you want to insert, and then click Open.
- 4 In the drawing, specify the insertion point.
- 5 Specify the x, y, and z scale factor and the rotation angle, or in the prompt box, select Done.
- 6 To complete the command and return to your drawing, close the window.


Attaching a drawing as an external reference

You can attach another drawing to the current drawing as an external reference and insert a copy of the drawing into the current drawing. The name of the external reference drawing is added to the Block Name list. Changes made later to the referenced drawing will appear in this drawing when you reload the external reference.

To attach an external reference

- 1 Do one of the following:
 - Choose Settings > Explore Blocks.
 - On the Settings toolbar, click the Explore Blocks tool ().
 - Type *expblocks* and then press Enter.
- 2 On the IntelliCAD Explorer toolbar, click the Attach Drawing tool ().
- 3 In the Select File To Attach dialog box, select the drawing you want to attach, and then click Open.
- 4 In the drawing, specify the insertion point.
- 5 Specify the x, y, and z scale factor and the rotation angle, or in the prompt box, select Done.
- 6 To complete the command and return to your drawing, close the window.



To edit the path of an external reference

- 1 Do one of the following:
 - Choose Settings > Explore Blocks.
 - On the Settings toolbar, click the Explore Blocks tool ().
 - Type *expblocks* and then press Enter.
- 2 Click the path you want to change.
- 3 From the Insert Block dialog box, select the new drawing you want as the external reference.
- 4 Click Open.
- 5 To complete the command and return to your drawing, close the window.

Saving a block as a separate drawing

You can save a block as a separate drawing, and then you can open and modify that drawing as you would any other drawing.

To save a block as a separate drawing file

- 1 Do one of the following:
 - Choose Settings > Explore Blocks.
 - On the Settings toolbar, click the Explore Blocks tool ().
 - Type *expblocks* and then press Enter.
- 2 In either the Details or Images view, select the block you want to save.
- 3 On the IntelliCAD Explorer toolbar, click the Save Block To Disk tool ().
- 4 In the Save Block dialog box, select the folder in which you want to save the block.
- 5 In the File Name field, type a name for the new drawing file (or accept the default, in which case the new drawing name is the same as the name of the block), and then click Save.

NOTE *You can also work with external references using the Xref Manager. For details, see “Working with external references” on page 348.*

Working with dimension styles


From the IntelliCAD Explorer, you can use the Dimension Styles element to cut, copy, and paste dimension styles from one drawing to another.


TIP You can select the dimension style and use the Windows shortcut keys (*Ctrl+A* to select all, *Ctrl+X* to cut, *Ctrl+C* to copy, *Ctrl+V* to paste) to accomplish the same results. You can use these shortcut keys with all other IntelliCAD Explorer elements as well.

A dimension style contains the settings that control the appearance of a dimension. Although you cannot control these settings from within the IntelliCAD Explorer, you can use the Dimension Settings dialog box to control settings related to the appearance of arrows, lines, text, units, and other formatting characteristics.

To display the IntelliCAD Explorer Dimension Styles element

Do one of the following:

- Choose Settings > Explore Dimension Styles.
- Choose Tools > IntelliCAD Explorer, and then click the Dimension Styles element.
- On the Settings toolbar, click the Dimension Settings tool ().
- Type *setdim* and then press Enter.




- A** To display the Dimension Styles settings, select Dimension Styles.
- B** Lists the names of dimension styles defined in the current drawing.
- C** Click the Dimension Style Name column head to sort by name.

Creating and naming dimension styles


By using the Dimension Styles element in combination with the Dimension Settings dialog box, you can create new dimension styles, modify them, and copy them into a different drawing.

NOTE *Dimension style names created or renamed in IntelliCAD can have up to 31 characters and cannot include spaces. IntelliCAD will, however, display longer dimension style names and names containing spaces, such as dimension styles created in AutoCAD 2000.*


To create a dimension style

- 1 Do one of the following:
 - Choose Settings > Dimension Settings.
 - On the Settings toolbar, click the Dimension Settings tool ().
 - Type *setdim* and then press Enter.
- 2 In the Dimension Settings dialog box, click New.
- 3 Type the name of the new dimension style.
- 4 Click Create.
- 5 In the Dimension Settings dialog box, click one of the other tabs, and then change the dimension settings as necessary.
Repeat this step for each tab, as needed.
- 6 To end the command, click OK.

To change a dimension style name in the current drawing

- 1 Do one of the following:
 - Choose Settings > Dimension Settings.
 - On the Settings toolbar, click the Dimension Settings tool ().
 - Type *setdim* and then press Enter.
- 2 Do one of the following:
 - Select the dimension style, choose Edit > Rename, type a new name, and then press Enter.
 - Click the dimension style name you want to change, type a new name, and then press Enter.
 - Right-click the dimension style name you want to change, and from the shortcut menu, select Rename, type a new name, and then press Enter.
- 3 To complete the command and return to your drawing, close the window.

To copy a dimension style from one drawing to another

- 1 Do one of the following:
 - Choose Settings > Explore Dimension Styles.
 - On the Settings toolbar, click the Explore Dimension Settings tool ().
 - Type *expdimstyles* and then press Enter.
- 2 Right-click the dimension style name you want to copy.
- 3 From the shortcut menu, select Copy.
- 4 In the left pane, select the drawing to which you want to copy the dimension style.
- 5 Click the Dimension Styles element for that drawing.
- 6 In the right pane, right-click, and then from the shortcut menu, select Paste.

NOTE *Each drawing contains a dimension style named Standard. You cannot delete this dimension style, but you can rename it from within the IntelliCAD Explorer or modify its properties in the Dimension Settings dialog box.*

Getting drawing information

IntelliCAD stores accurate, detailed information about all the entities in a drawing. You can get details about an existing drawing and its entities using the tools for measuring distances and calculating areas. You can also track the amount of time you spend editing a drawing. This section explains how to:

- Measure distances along an entity.
- Measure distances and angles.
- Divide an entity into a number of equal segments.
- Calculate areas.
- Display information about entities in a drawing.
- Track the amount of time spent editing a drawing.

Many of the functions described in this section require that you set IntelliCAD to the Advanced experience level.

Topics in this chapter

<i>Specifying measurements and divisions</i>	220
<i>Calculating areas</i>	223
<i>Calculating distances and angles</i>	227
<i>Displaying information about your drawing</i>	228

Specifying measurements and divisions


You can divide a line, arc, circle, polyline, ellipse, or spline into a number of equal segments or mark off intervals of a specific length along an entity. (Note that divide is not the same as break.) For example, you may want to place station-point markers every 50 feet along the centerline of a roadway or divide the plan view of a window into three equal-width sections of glass, placing a mullion at each division point.

To specify measurements and divisions, use these commands:

- For the length of the segments, use the Measure command.
- For the number of equal-length segments, use the Divide command.

You can measure or divide arcs, circles, lines, polylines, ellipses, and splines. With either command, you can identify the segments by placing either a block or point entity at the end of each interval. If you use points, you can snap to the ends of intervals using the point entity snap. The appearance of the point entities is determined by the current point display type, which you control in the Drawing Settings dialog box.

To use a block as the marker, the block must already be defined in the current drawing. You can further indicate whether to rotate the block to align perpendicularly to the entity you are measuring or dividing.



Block not aligned with entity.

Block aligned with entity.


IntelliCAD begins measuring or dividing based on the point at which you select the entity and the type of entity with which you are working. For most entities, measuring starts from the endpoint closest to the point you used to select the entity. If you select the entity to be measured or divided using a method other than pointing (for example, using a window or fence selection), the program prompts you to specify the end from which you want to begin measuring.


Measuring intervals on entities

You can mark specified length increments along a selected entity using either a point entity or a block.

To measure intervals along an entity and mark them using point entities

Advanced experience level


- 1 Do one of the following:
 - Choose Modify > Measure.
 - On the Modify toolbar, click the Measure tool ().
 - Type *measure* and then press Enter.
- 2 Select the entity.
- 3 Specify the segment length, and then press Enter.



When you select the entity by pointing, intervals are measured from the end closest to the point at which you select the entity (A). Blocks or point entities (B) are placed along the entity at the specified interval.

To measure intervals along an entity and mark them using blocks

Advanced experience level


- 1 Do one of the following:
 - Choose Modify > Measure.
 - On the Modify toolbar, click the Measure tool ().
 - Type *measure* and then press Enter.
- 2 Select the entity.
- 3 In the prompt box, choose Insert Blocks.
- 4 Type the name of the block you want to insert as the marker.
- 5 In the prompt box, choose either Yes-Align Blocks to rotate each insertion of the block so that its vertical alignment is always perpendicular to the entity or No-Do Not Align to insert each copy of the block with a zero rotation angle.
- 6 Specify the segment length, and then press Enter.

Dividing entities into segments

You can place markers along a selected entity, dividing that entity into a specified number of equal-length segments. You can use either a point entity or a block to mark the segments.

To divide an entity into segments and mark them using point entities

Advanced experience level


- 1 Do one of the following:
 - Choose Modify > Divide.
 - On the Modify toolbar, click the Divide tool ().
 - Type *divide* and then press Enter.
- 2 Select the entity.
- 3 Specify the number of segments, and then press Enter.



When you select the entity by pointing, divisions are marked beginning from the end closest to the point at which you select the entity (A). Blocks or point entities (B) are placed along the entity to mark it in equal intervals.

To divide an entity into segments and mark them using blocks

Advanced experience level

- 1 Do one of the following:
 - Choose Modify > Divide.
 - On the Modify toolbar, click the Divide tool ().
 - Type *divide* and then press Enter.
- 2 Select the entity.
- 3 In the prompt box, choose Insert Blocks.
- 4 Type the name of the block you want to insert as the marker.
- 5 In the prompt box, choose either Yes-Align Blocks to rotate each insertion of the block so that its vertical alignment is always perpendicular to the entity or No-Do Not Align to insert each copy of the block with a zero rotation angle.
- 6 Specify the number of segments, and then press Enter.


Calculating areas

You can calculate the area and perimeter of a polygon based on a series of points you specify or enclose with a circle or closed polyline. You can also determine the area of several combined entities and add or subtract the area of one or more entities from a total combined area.

Calculating areas defined by points

You can find the area and perimeter of any closed region by specifying a series of points. The program calculates the area and perimeter of the space that is enclosed by an imaginary polygon consisting of straight-line segments connecting each point.

To calculate the area defined by points you specify


- 1 Do one of the following:
 - Choose Tools > Inquiry > Area.
 - On the Inquiry toolbar, click the Area tool ().
 - Type *area* and then press Enter.
- 2 Specify the first point.
- 3 Specify the second point.
- 4 Continue specifying points in sequence to define the perimeter of the area you want to measure.

As you select each successive point, the resulting polygon is displayed on the screen.

- 5 To complete the calculation, press Enter.

The area and perimeter of the region you defined are displayed. For example, the following type of information is displayed:

Area = 11.0583, Perimeter = 15.3092




Select the points (A, B, C) that form a polygon. The area and perimeter of the region are then calculated.

Calculating areas of closed entities

You can find the area of any closed entity. In addition, the program calculates either the circumference or the perimeter of the entity, depending on the type of entity you select.

To calculate the area of a closed entity

- 1 Do one of the following:
 - Choose Tools > Inquiry > Area.
 - On the Inquiry toolbar, click the Area tool ().
 - Type *area* and then press Enter.
- 2 In the prompt box, choose Find Area Of One Entity.
- 3 Select the entity.


The following type of information is displayed:

```
Area = 62.3837, Circumference = 27.9989
```


Calculating combined areas


You can find the total area of several combined regions by specifying points or by selecting entities. You can also subtract the areas of entities or polygons from a running total.

To add areas to calculate a combined area

- 1 Do one of the following:
 - Choose Tools > Inquiry > Area.
 - On the Inquiry toolbar, click the Area tool ().
 - Type *area* and then press Enter.
- 2 In the prompt box, choose Add Areas Together.
- 3 Using one of the following methods, identify the first area:
 - Specify points defining a polygon, and then in the prompt box, choose Done Specifying Area.
 - In the prompt box, choose Add Entities To Area, select the entities you want to add, and then press Enter to complete the calculations.
- 4 To complete the command, choose Done in the prompt box.

To subtract areas when calculating a combined area

- 1 Do one of the following:
 - Choose Tools > Inquiry > Area.
 - On the Inquiry toolbar, click the Area tool ().
 - Type *area* and then press Enter.
- 2 In the prompt box, choose Add Areas Together.
- 3 Using one of the following methods, identify the first area:
 - Specify points defining a polygon, and then in the prompt box, choose Done Specifying Area.
 - In the prompt box, choose Add Entities To Area, select the entities you want to add, and then press Enter to complete the calculations.
- 4 In the prompt box, choose Subtract Areas.
- 5 Using one of the following methods, identify the area to be subtracted:
 - Specify points defining a polygon, and then in the prompt box, choose Done Specifying Area.
 - In the prompt box, choose Subtract Entities From Area, select the entities you want to subtract, and then press Enter to complete the calculations.
- 6 To complete the command, choose Done in the prompt box.



To calculate the area of the gasket using the Area command, first add the area of the entire gasket (**A**), and then subtract the areas of the two circles (**B** and **C**).

As you select entities, the program displays the calculations. If the command bar is displayed, the information appears there. If the command bar is not displayed, the program opens the Prompt History window and displays the calculations. The following type of information is an example of what is displayed:


```
Entity • Add • Subtract • <First point>: Choose Add Areas Together
Adding: Entity • Subtract • <First point>: Choose Add Entities to Area
Adding area: <Select entities>: Select the first entity
Area = 64.6259, Perimeter = 33.3049
Total length = 33.3049
Total area = 64.6259
Adding area: <Select entities>: press Enter
Adding: Entity • Subtract • <First point>: Choose Subtract Areas
Subtracting: Entity • Add • <First point>: Choose Subtract Entities from
Area
Subtracting area: <Select entities>: Select the first entity to subtract
Area = 3.1597, Circumference = 6.3012
Total length = 27.0036
Total area = 61.4662
Subtracting area: <Select entities>: Select the second entity to subtract
Area = 3.1597, Circumference = 6.3012
Total length = 20.7024
Total area = 58.3066
Subtracting area: <Select entities>: Press Enter
Subtracting: Entity • Add • <First point>: Choose Done
```


Calculating distances and angles

You can calculate the distance between any two points you select. The following information is displayed:


- The distance between the points, measured in drawing units.
- Their angle in the xy plane.
- Their angle measured from the xy plane.
- The change (delta) in the x, y, and z distances between the two points.

To calculate the distance between two points and their angle

- 1 Do one of the following:
 - Choose Tools > Inquiry > Distance.
 - On the Inquiry toolbar, click the Distance tool () .
 - Type *distance* and then press Enter.
- 2 Specify the first point.
- 3 Specify the second point.

The following type of information is displayed:

Distance = 13.2850, Angle in XY Plane = 31°, Angle from XY Plane = 0°
Delta X = 11.3878, Delta Y = 6.8418, Delta Z = 0.0000



Use the Distance command to calculate the distance (A) between two points (B and C), the angle in the xy plane (D), the angle from the xy plane, and the delta x (E), delta y (F), and delta z distances between the two points.

TIP To use specific points on selected entities, use entity snaps to select the precise points on the entities.

Displaying information about your drawing

You can display a variety of information about a drawing and the entities it contains, including:

- Information in the drawing database about selected entities.
- The current drawing status.
- The time spent working on the drawing.

This information is displayed in the Prompt History window and in the command bar.


Displaying information about entities

You can display information about the selected entities. The information varies, depending on the type of entities you select. All of the listings display the following information:

- Entity type.
- Layer.
- Color.
- Linetype.
- The location of the entity (its xyz-coordinates relative to the current user coordinate system [UCS]).
- The current space (model space on the Model tab or paper space on a Layout tab).
- The size of the entity (the information varies, depending on the entity type).

To display information about an entity

Advanced experience level

- 1 Do one of the following:
 - Choose Tools > Inquiry > List Entity Info.
 - On the Inquiry toolbar, click the List Entity Info tool ().
 - Type *list* and then press Enter.
- 2 Select one or more entities.
- 3 Press Enter.

TIP To return to the drawing window, press *F2*.

The following type of information is displayed:

```

----- Circle -----
Handle: 2C
Current space: Model
Layer: 0
Color: BYLAYER
Linetype: CONTINUOUS
Handle: 4C
Current space: Model
Center point: X= -5.8583 Y= 7.2752 Z= 0.0000
Radius: 4.4562
Circumference: 27.9989
Area: 62.3837

```

Displaying the drawing status

You can display information about the current status of a drawing, including:

- Drawing name.
- Limits.
- Insertion base point.
- Snap and grid settings.
- Current layer, color, and linetype.
- Current settings for various modes (fill, grid, orthogonal, snap, blips, and so on).

To display the drawing status

Advanced experience level

Do one of the following:

- Choose Tools > Inquiry > Drawing Status.
- Type *status* and then press Enter.

The following type of information is displayed:

```

Current drawing name: Site Plan
    Drawing limits are: X=0.0000 Y=0.0000 Z=0.0000
        X=12.0000 Y=9.0000 Z=0.0000
    Paper space limits are: X=0.0000 Y=0.0000 Z=0.0000
        X=12.0000 Y=9.0000 Z=0.0000
    Screen width (pixels): 971
    Screen height (pixels): 569
    Insertion base is: X=0.0000 Y=0.0000 Z=0.0000
    Snap resolution is: X=0.5000 Y=0.5000 Z=0.0000
    Grid spacing is: X:0.5000 Y:0.5000 Z=0.0000
    Current layer: 0
    Current color: BYLAYER
    Current linetype: BYLAYER
    Current elevation: 0.0000
    Current thickness: 0.0000
    Fill: on
    Grid: off
    Ortho: off
    Snap: off
    Blips: off
    Drag: on
    Command echo: on
    Positive angle direction: Counterclockwise
    Angular units: Decimal degrees
    Dimension units: Decimal
    Pick box height: 3
    Entities in drawing: 288
  
```

Tracking time spent working on a drawing


You can display information about the amount of time you have spent working on a drawing, including:

- The date and time the drawing was created.
- The date and time the drawing was most recently saved.
- The total amount of time spent working on the drawing.
- The time spent working on the drawing during the current editing session.

You can turn the elapsed-time timer on and off or reset it to zero.

To display the timer information

Advanced experience level

- 1 Do one of the following:
 - Choose Tools > Inquiry > Time Variables.
 - On the Inquiry toolbar, click the Time Variables tool ()
 - Type *time* and then press Enter.
- 2 Select any of the prompt box options:
 - Choose Timer On to turn the elapsed timer on.
 - Choose Timer Off to turn the elapsed timer off.
 - Choose Display Timer to redisplay the timer information.
 - Choose Reset Timer to reset the elapsed timer to zero.
- 3 In the prompt box, choose Cancel to exit the command.

Each time you display the timer information, the following type of information is displayed:

```
The current time is Fri Dec 19 09:58:43 1997
Drawing was created on: Wed 17 Dec 1997 at 16:17:59.8090
Drawing was last updated on: Thur 18 Dec 1997 at 09:58:43.3040
Total editing time: 1 2: 35:4.2345
Elapsed timer (on): 0 1: 21:5.6324
```


Modifying entities

IntelliCAD provides many editing tools for modifying a drawing. You can easily move, rotate, or stretch drawing entities, or change their scale. When you want to remove an entity, you can delete it with a few clicks of the mouse. You can also make multiple copies of any entity and copy entities from one drawing to another.

You can modify most entities using general-purpose editing commands, many of which are located on the Modify toolbar and the Modify menu. Some complex entities require special commands. This section explains how to:

- Select entities using entity-selection methods and grips.
- Change the properties of entities.
- Rearrange entities by moving, rotating, or changing the display order.
- Resize entities by stretching, scaling, extending, trimming, or editing their lengths.
- Break and join entities.
- Group entities.
- Edit polylines.
- Explode entities.
- Create chamfers and fillets.

Topics in this chapter

<i>Selecting entities</i>	234
<i>Modifying the properties of entities</i>	240
<i>Deleting entities</i>	242
<i>Copying entities</i>	242
<i>Rearranging entities</i>	248
<i>Resizing entities</i>	251
<i>Breaking and joining entities</i>	259
<i>Grouping entities</i>	261
<i>Editing polylines</i>	264
<i>Exploding entities</i>	270
<i>Chamfering and filleting entities</i>	271

Selecting entities


You can create a selection set that consists of one or more entities before you modify them. Use any of the following methods to create a selection set:

- Choose a command or tool first, and then select entities.
- Select entities first, and then choose a command or tool (most entities).
- Select entities by pointing, and then use grips to modify them.

Displaying selected entities highlighted

You can specify whether to display selected entities highlighted, which makes the selection set easier to see. By default, the highlighting feature is turned on.

To turn the highlighting feature on or off

- 1 Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool () .
 - Type *settings* and then press Enter.
- 2 Click the Display tab.
- 3 In the Change Settings For box, select Display.
- 4 Select or clear the Highlight Item When Selected check box.
- 5 Click OK.

Entity-selection methods

When you choose a command that requires you to select entities (when you're deleting or changing entity properties, for example), you can use any of the following selection methods by choosing them in the prompt box or entering them in the command bar:


- **Select all entities (ALL)** Selects all entities in the current drawing.
- **Add to set (+ or A)** Adds one or more entities to the selection set.
- **Subtract from set (- or R)** Removes one or more entities from the selection set.
- **Previous selection (P)** Selects entities included in the previous selection set.
- **Last entity in drawing (L)** Selects the entity most recently added to the drawing.
- **Window-Inside (W)** Selects entities contained entirely within a rectangular selection window.
- **Crossing window (C)** Selects entities contained within or crossing the boundary of a rectangular selection window.
- **Outside window (O)** Selects entities falling completely outside a rectangular selection window.

- **Window polygon (WP)** Selects entities contained entirely within a polygon selection window.
- **Crossing polygon (CP)** Selects entities contained within or crossing the boundary of a polygon selection window.
- **Outside polygon (OP)** Selects entities falling completely outside a polygon selection window.
- **Window circle (WC)** Selects entities contained entirely within a circular selection window.
- **Crossing circle (CC)** Selects entities contained within or crossing the boundary of a circular selection window.
- **Outside circle (OC)** Selects entities falling completely outside a circular selection window.
- **Point (PO)** Selects any closed entities that surround the selected point.
- **Fence (F)** Selects entities crossing a line or line segments.
- **Select by Properties (PRO)** Selects entities that match a particular set of properties—for example, all entities on a particular layer or drawn in a certain color.

You can also use a few selection methods automatically, without displaying the prompt box. For example, you can simply click to select entities, or you can use a Window-Inside or Crossing Window by defining the opposite corners of a rectangular selection window. The direction in which you define the points of the rectangle (left-to-right or right-to-left) determines which type of window you create.

To create a Window-Inside

- 1 Click to select a point in the drawing.
- 2 Click to the right of the first point to select a second point in the drawing.




Window-Inside by selecting the first (A) and second (B) points.

Resulting selection.

This method is most commonly referred to as simply a *window* or *selection window*.

To create a Crossing Window

- 1 Click to select a point in the drawing.
- 2 Click to the left of the first point to select a second point in the drawing.




Crossing Window by selecting the first (A) and second (B) points.

Resulting selection.

In addition to a rectangular window, you can define a selection window using other shapes such as a polygon, circle, or fence (a multisegmented line that selects entities it crosses).

To select entities using Window Polygon

- 1 Activate an entity-modification command.
- 2 In the prompt box, choose Window Polygon.
- 3 Specify the vertices of the polygon.
- 4 To complete the selection polygon, press Enter.




Window Polygon by specifying the vertices of the polygon (A, B, and C).

Resulting selection.

To select entities using Fence

- 1 Activate an entity-modification command.
- 2 In the prompt box, choose Fence.
- 3 Specify the endpoints of the Fence segments.
- 4 To complete the Fence, press Enter.



Fence by specifying the endpoints of the fence segments (A, B, and C).

Resulting selection.

To select entities using their properties

- 1 Activate an entity-modification command.
- 2 In the prompt box, choose Select by Properties.
- 3 Choose an option for selection: Color, Layer, Linetype, Name, Thickness, Type, Value (of attributes, text, or multi-line text), Width (of polylines), or Location.
- 4 Make your selections, depending on the option you chose.
- 5 To complete the selection, press Enter.

Choosing the command first


When you choose an entity-modification tool or command, the program prompts you to select entities and displays a prompt box from which you can choose a selection method. You can select individual entities or use other techniques such as selection windows to select multiple entities.

When you select entities, you add them to the selection set. After you select at least one entity, you can remove entities from the selection set. To finish adding entities to the selection set, press Enter. Most entity-modification commands then act on the entire selection set.

Selecting entities first

You can select entities first and then choose how to modify them. As you select each entity, it is highlighted with small squares called grips, which appear at strategic points on the entity.

The locations of the grips depend on the type of entity selected. For example, grips appear at the endpoints and midpoint of a line, at the quadrant points and center point of a circle, and at the endpoints, midpoint, and center of an arc.



Examples of grip locations.

After you select one or more entities, you can choose an entity-modification command, such as Copy or Move, from the Modify menu or toolbar. You can also click the right mouse button to display a shortcut menu containing the entity-modification commands appropriate for the selected entities, and then choose the command from the menu.

When you select entities and then issue a command, the program immediately acts on the entities you've selected. In many cases, a command-specific prompt box provides additional options for that editing operation. If you want to modify the selection set at that point, right-click to display the prompt box with the selection options and choose the option you want. To redisplay the command-specific prompt box, right-click again.

Deselecting entities

If an entity is no longer needed in a selection set, you can deselect it to remove it from the selection set.

To remove an entity from the selection set

- 1 Press Shift, and then select the entity again.

NOTE Pressing Shift while selecting entities using a crossing window removes all entities from the specified selection set.


To remove all entities from the selection set


- 1 Press Escape.

Turning grips on and off

You can turn the use of grips on and off and control the size and color of grips.

To change grip settings

- Do one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool () .
 - Type *ddgrips* and then press Enter.
- In the Drawing Settings dialog box, click the Display tab.
- In the Change Settings For list, click Grips.
- Change the desired settings, and then click OK.



- | | |
|---|--|
| A Click to activate grips for all selected entities. | C Specify the grip size. |
| B Click to assign the color for grips. | D Displays the current grip size. |

Editing with grips

To use grips for editing, you select an entity to display the grips, and then click a grip to make it active. The grip you select depends on the type of entity you're modifying and the editing operation you're performing. For example, to move a line entity, drag it by its midpoint grip. To stretch the line, drag one of the endpoint grips. You do not need to enter a command when using grips.


Modifying the properties of entities

You can change the layer, thickness, linetype, color, and linetype scale of one or more entities. Depending on the type of entity or entities you select, you can also change other properties, such as the start point and endpoint of lines, the center point and radius of circles, and the vertices of polylines.

You can modify all the properties of all entities simultaneously. For example, using the *entprop* command, select all entities on a particular layer, and then move the entities to another layer by simply selecting a name from the Layer text box. Additionally, using the *select* command and the Select by Properties option, select all blue entities and change their color to green.

In the Entity Properties dialog box, changes that you make in the Layer, Color, Thickness, Lineweight, Linetype, Linetype Scale, and Print Style (if using named print style tables) fields affect all selected entities. If you select several entities that all have different properties, the default value initially is *Varies*. Changes that you make in the entity tabs, such as Circle, Line, and Arc, affect all selected entities of that type. You can select the entities to be changed using any entity-selection method.


To modify properties of entities

- 1 Do one of the following:
 - Choose Modify > Properties.
 - On the Modify toolbar, click the Properties tool ().
 - Type *entprop* and then press Enter.
- 2 Select the entities, and then press Enter.
- 3 Make changes to the desired properties, and then click OK.

TIP Use the Entity Properties toolbar to change the properties of selected entities. Note that the Entity Properties toolbar settings that display when no entities are selected determine the properties of new entities when you draw them.

The Entity Properties dialog box, shown in the following illustration, has two sections. The All Selected Entities section (the upper part of the dialog box) displays properties common to all selected entities, such as Layer, Color, Lineweight, Linetype, Linetype Scale, Thickness, and Print Style (if using named print style tables). This portion of the dialog box is equivalent to the dialog box displayed by the AutoCAD *ddchprop* command.

The lower section of the Entity Properties dialog box contains options specific to the selected entities. Each tab displays the properties appropriate for the entity. This feature is equivalent to repeatedly applying the AutoCAD *ddmodify* command to one entity at a time




The IntelliCAD Entity Properties dialog box.

Deleting entities

You can remove entities from a drawing. You can delete entities using any of the entity-selection methods.

To delete a selection set

- 1 Do one of the following:
 - Choose Edit > Delete.
 - On the Standard toolbar, click the Delete tool (.
 - Type *delete* and then press Enter.
- 2 Select the entities, and then press Enter.

TIP *Typing the Undelete command restores the most recently deleted selection set. If you have made additional modifications since deleting the entities, use Undelete rather than Undo to restore those entities without reversing those modifications.*

Copying entities

You can copy one or more entities, making one copy or multiple copies within the current drawing. You can also copy entities between drawings.


Use any of the following methods to copy entities within the current drawing:


- Create a copy at a location referenced from the original.
- Create a copy aligned parallel to the original.
- Create a copy as a mirror image of the original.
- Create several copies in a rectangular or circular pattern.

Copying entities within a drawing

You can duplicate entities within the current drawing. The default method is to create a selection set and then specify a starting point, or base point, and an endpoint, or displacement point, for the copy. You can also make multiple copies or copy the selection set to a location you specify, using a direction vector.


To copy a selection set

- 1 Do one of the following:
 - Choose Modify > Copy.
 - On the Modify toolbar, click the Copy tool (.
 - Type *copy* and then press Enter.
- 2 Select the entities, and then press Enter.
- 3 Specify the base point.
- 4 Specify the insertion point.
- 5 Continue specifying insertion points to place additional copies.
- 6 To complete the command, press Enter.



To make a single copy of an entity, select the entity to copy (**A**), base point (**B**), and then displacement point (**C**).

Result.



To make multiple copies of an entity, select the entity to copy (**A**), specify the base point (**B**), and then specify the displacement points (**C**, **D**, and **E**).


Result.

NOTE The *COPYMODE* system variable controls whether you are prompted for multiple copies.


Copying between drawings

You can use the Clipboard to cut or copy entities from one drawing to another. Cutting removes the selected entities from a drawing and stores them on the Clipboard. Copying duplicates the selected entities from a drawing and places them on the Clipboard.

To cut entities to the Clipboard


- 1 Select the entities you want to cut.
- 2 Do one of the following:
 - Choose Edit > Cut.
 - On the Standard toolbar, click the Cut tool ().
 - Type *cutclip* and then press Enter.

To copy entities to the Clipboard

- 1 Select the entities you want to copy.
- 2 Do one of the following:
 - Choose Edit > Copy.
 - On the Standard toolbar, click the Copy tool ().
 - Type *copyclip* and then press Enter.

Anything that you can copy to the Clipboard can be pasted into a drawing. The format in which the program adds the Clipboard contents to the drawing depends on the type of information in the Clipboard. For example, if you copy IntelliCAD drawing entities to the Clipboard, the program pastes them into the drawing as IntelliCAD entities. If you copy items to the Clipboard from other programs, they are pasted into the current drawing as embedded ActiveX® objects.

To paste entities from the Clipboard


- 1 Do one of the following:
 - Choose Edit > Paste.
 - On the Standard toolbar, click the Paste tool ().
 - Type *pasteclip* and then press Enter.
- 2 Specify the insertion point.


Making parallel copies

You can use the parallel feature to copy selected entities and align them parallel to the original entities at a specified distance. You can make parallel entities using arcs, circles, ellipses, elliptical arcs, lines, two-dimensional polylines, rays, and infinite lines.

Making parallel copies of curved entities creates larger or smaller curves, depending on which side of the original entity you place the copy. For example, placing a parallel copy of a circle outside the circle creates a larger concentric circle; positioning the copy inside the circle creates a smaller concentric circle.

To make a parallel copy by specifying the distance


- 1 Do one of the following:
 - Choose Modify > Parallel.
 - On the Modify toolbar, click the Parallel tool ().
 - Type *parallel* and then press Enter.
- 2 Specify the distance by selecting two points or by entering a distance.
- 3 Select the entity to copy.
- 4 Specify on which side of the entity to place the parallel copy.
- 5 Select another entity to copy, or press Enter to complete the command.




To make a parallel copy, specify the distance between copies by entering a distance or selecting two points (**A** and **B**), select the entity to copy (**C**), and specify on which side to place the copy (**D**).

Result.

To make a parallel copy passing through a point

- 1 Do one of the following:
 - Choose Modify > Parallel.
 - On the Modify toolbar, click the Parallel tool ().
 - Type *parallel* and then press Enter.
- 2 In the prompt box, choose Through Point.
- 3 Select the entity to copy.
- 4 Specify the point for the entity to pass through.
- 5 Repeat steps 3 and 4, or press Enter to complete the command.





To make a parallel copy passing through a point, select the entity to copy (**A**) and then specify the through point (**B**).

Mirroring entities

You can create a mirror image of an entity. You mirror the entity about a mirror line, which you define by specifying two points in a drawing. You can delete or retain the original entities.

To mirror entities

- 1 Do one of the following:
 - Choose Modify > Mirror.
 - On the Modify toolbar, click the Mirror tool ().
 - Type *mirror* and then press Enter.
- 2 Select the entity, and then press Enter.
- 3 Specify the first point of the mirror line.
- 4 Specify the second point of the mirror line.
- 5 In the prompt box, choose one of the following:
 - Yes, Delete Entities – deletes the original entities.
 - No, Keep Entities – retains the original entities.




To mirror an entity, select it (A), and then specify the first point (B) and second point (C) of the mirror line.

Result.

Arraying entities


You can copy an entity in a rectangular or polar (circular) pattern, creating an array. For a rectangular array, you control the number of copies in the array by specifying the number of rows and columns. You also specify the distance between each row and column. For a polar array, you control the number of copies that compose the array and whether to rotate the copies.

To create a polar array

- 1 Do one of the following:
 - Choose Modify > Array.
 - On the Modify toolbar, click the Array tool ().
 - Type *array* and then press Enter.
- 2 Select the entities, and then press Enter.
- 3 In the prompt box, choose Polar.
- 4 Specify the center point of the array.
- 5 Specify the number of items to array, including the original selection set.
- 6 Specify the angle the array is to fill, from 0 to 360 degrees.


The default setting for the angle is 360 degrees. Positive values create the array in a counterclockwise direction; negative values create the array in a clockwise direction.


- 7 In the prompt box, choose one of the following:
 - Yes, Rotate Entities – rotates entities as they are arrayed.
 - No, Do Not Rotate – retains the original orientation of each copy as it is arrayed.



To create a polar array, select the entity to copy (**A**), specify the center point of the array (**B**), and then specify the number of items to array, the angle the array is to fill, and whether to rotate the items.

To create a rectangular array

- 1 Do one of the following:
 - Choose Modify > Array.
 - On the Modify toolbar, click the Array tool ().
 - Type *array* and then press Enter.
- 2 Select the entities, and then press Enter.
- 3 In the prompt box, choose Rectangular.
- 4 Type the number of rows.
- 5 Type the number of columns.
- 6 Specify the distance between the rows.
- 7 Specify the distance between the columns.



To create a rectangular array, select the entity to copy (**A**), type the number of rows and columns, and then specify the distance between each row (**B**) and column (**C**).


Rearranging entities


You can move one or more entities, and you can also rotate entities about a specified point. If you have entities that overlap, you can also change the display order.

Moving entities

You can move entities around within the current drawing or from one drawing to another. The default method is to create a selection set and then specify a starting point, or base point, and an endpoint, or displacement point, to define the relocation of the entities. You can also relocate the entities using a direction vector.

To move a selection set

- 1 Do one of the following:
 - Choose Modify > Move.
 - On the Modify toolbar, click the Move tool ().
 - Type *move* and then press Enter.
- 2 Select the entities, and then press Enter.
- 3 Specify the base point.
- 4 Specify the displacement point.



To move an entity, select it (**A**), and then specify the base point (**B**) and the displacement point (**C**).

Result.

You can also move entities using grips. To move an entity using grips, select the entity to display its grips, and then click a grip and drag it. The grip you select depends on the type of entity you're modifying. For example, to move a line entity, select the midpoint grip. To move a curved entity, such as an arc, circle, or ellipse, select the center point grip. Not all entities can be moved using grips.


To move an entity using grips


- 1 Select the entity.
- 2 Click a grip to select it.
- 3 Drag the entity to where you want to relocate it.
- 4 Click to release.

Rotating entities

You can rotate entities about a specified point at a specified rotation angle or by an angle referenced to a base angle. The default method rotates the entities using a relative rotation angle from their current orientation.


To rotate a selection set


- 1 Do one of the following:
 - Choose Modify > Rotate.
 - On the Modify toolbar, click the Rotate tool () .
 - Type *rotate* and then press Enter.
- 2 Select the entities, and then press Enter.
- 3 Specify the rotation point.
- 4 Specify the rotation angle.



To rotate an entity, select the entity to rotate (**A**), and then specify the rotation point (**B**) and the rotation angle (**C**).

To rotate a selection set in reference to a base angle

- 1 Do one of the following:
 - Choose Modify > Rotate.
 - On the Modify toolbar, click the Rotate tool () .
 - Type *rotate* and then press Enter.
- 2 Select the entities, and then press Enter.
- 3 Specify the rotation point.
- 4 In the prompt box, choose Base Angle.
- 5 Specify the base angle.
- 6 Specify the new angle.




To rotate an entity in reference to a base angle, select the entity (**A**), specify the rotation point (**B**), select the base angle and pick point (**B**) again (or type the @ symbol), specify the second point (**C**), and then specify the point representing the new angle (**D**).

Reordering entities

When multiple entities overlap, you can change the order in which they are displayed and printed. You can move entities to the front, back, or on top or below of another entity.

To reorder entities:

- 1 Do one of the following:
 - Choose Tools > Draw Order.
 - On the Tools toolbar, click the Draw Order tool () .
 - Type *draworder* and then press Enter.
- 2 Select the entity you want to reorder, and then press Enter.
- 3 In the prompt box, specify the new drawing order, and then press Enter.
- 4 If you are reordering above or under, select the entity you want the first entity to be above or below, and then press Enter.

NOTE The *SORTENTS* system variable automatically turns on, which may affect system performance.


Resizing entities


You can change the size of an entity or set of entities by stretching, scaling, extending, trimming, or editing their lengths.

Stretching entities

You can change the size of entities by stretching them. When you stretch entities, you must select the entities using either a crossing window or a crossing polygon. You then specify a displacement distance or select a base point and a displacement point. Entities that cross the window or polygon boundary are stretched; those completely within the crossing window or crossing polygon are simply moved.

To stretch an entity

- 1 Do one of the following:
 - Choose Modify > Stretch.
 - On the Modify toolbar, click the Stretch tool ().
 - Type *stretch* and then press Enter.
- 2 In the prompt box, choose Crossing Window or Crossing Polygon.
- 3 Select the entities, and then press Enter.
- 4 Specify the base point.
- 5 Specify the second point of displacement.




To stretch entities, select them using a crossing window (A) or crossing polygon, and then specify the base point (B) and displacement point (C).

To stretch an entity using grips, you select it to display its grips and then select a grip to make it the active grip. This becomes the base point. Then you move the active grip to a new location. The grip you select depends on the type of entity you're modifying. For example, to stretch one corner of a rectangle, select the corner point grip. To stretch a line, select an endpoint grip. Not all entities can be stretched using grips.

To stretch an entity using grips

- 1 Select the entity.
- 2 Click a grip to activate it.
- 3 Drag the grip.
- 4 Click to release.




To stretch an entity using grips, select the entity (A), select a grip (B), and drag the grip to its new location (C).


Result.

Scaling entities

You can change the size of a selected entity by scaling it in relation to a base point. You can change the size of an entity by specifying a base point and a length, which is used as a scale factor based on the current drawing units, or by specifying a scale factor. You can also use a scale factor referenced to a base scale factor, for example, by specifying the current length and a new length for the entity.

To scale a selection set by a scale factor

- 1 Do one of the following:
 - Choose Modify > Scale.
 - On the Modify toolbar, click the Scale tool ().
 - Type *scale* and then press Enter.
- 2 Select the entities, and then press Enter.
- 3 Specify the base point.
- 4 Specify the scale factor.




To scale an entity by a scale factor, select the entity (A), and then specify the base point (B) and the scale factor.

Result.

You can also scale some entities using grips. To scale an entity, you select the entity, and then click a grip. You then change the size of the entity by moving the grip. The grip you select depends on the type of entity you're modifying. For example, to scale a circle, select a quadrant point grip.

To scale an entity using grips

- 1 Select the entity.
- 2 Click a grip to select it.
- 3 Drag the grip.
- 4 Click to release.



To scale using grips, select the entity (A), click a grip (B), and scale the entity by dragging the grip to its new location (C).


Result.


Extending entities

You can extend entities so that they end at a boundary defined by other entities. You can also extend entities to the point at which they would intersect an implied boundary edge. When extending entities, you first select the boundary edges, and then specify the entities to extend, selecting them either one at a time or using the fence selection method.

You can extend arcs, lines, two-dimensional polylines, and rays. Arcs, circles, ellipses, lines, splines, polylines, rays, infinite lines, and viewports on a Layout tab can act as boundary edges.

To extend an entity


- 1 Do one of the following:
 - Choose Modify > Extend.
 - On the Modify toolbar, click the Extend tool (.
 - Type *extend* and then press Enter.
- 2 Select one or more entities as boundary edges, and then press Enter.
- 3 Select the entity to extend.
- 4 Select another entity to extend, or press Enter to complete the command.



To extend entities, select the boundary edge (A), and then select the entities to extend (B).

Result.

To extend an entity to an implied boundary


- 1 Do one of the following:
 - Choose Modify > Extend.
 - On the Modify toolbar, click the Extend tool ().
 - Type *extend* and then press Enter.
- 2 Select one or more boundary edges, and then press Enter.
- 3 In the prompt box, choose Edge Mode.
- 4 In the prompt box, choose Extend.
- 5 Select the entity to extend.
- 6 Select another entity to extend, or press Enter to complete the command.




Select the boundary edge (A), and then select the entities to extend (B).

Result.

To extend several entities using the fence selection method


- 1 Do one of the following:
 - Choose Modify > Extend.
 - On the Modify toolbar, click the Extend tool ().
 - Type *extend* and then press Enter.
- 2 Select one or more boundary edges, and then press Enter.
- 3 In the prompt box, choose Fence.
- 4 Specify the first point of the fence.
- 5 Specify the second point of the fence.
- 6 Specify the next fence point, or press Enter to complete the command.



Select the boundary edge (A), and then specify the first point (B) and second point (C) of the fence.

Result.

When you extend a wide polyline, its centerline intersects the boundary edge. Because the end of the polyline is always cut at a 90-degree angle, part of the polyline may extend past the boundary edge. A tapered polyline continues to taper until it intersects the boundary edge. If this would result in a negative polyline width, the ending width changes to 0.



A tapered polyline (A) continues to taper until it intersects the boundary edge (B).


Result.

Trimming entities

You can clip, or trim, entities so they end at one or more implied cutting edges defined by other entities. You can also trim entities to the point at which they would intersect an implied cutting edge. When trimming entities, you first select the cutting edges and then specify the entities to trim, selecting them either one at a time or using the fence selection method.

You can trim arcs, circles, lines, open two-dimensional and three-dimensional polylines, and rays. Arcs, circles, lines, polylines, rays, infinite lines, and viewports on a Layout tab can act as cutting edges. An entity can be both a cutting edge and one of the entities being trimmed.

To trim an entity


- 1 Do one of the following:
 - Choose Modify > Trim.
 - On the Modify toolbar, click the Trim tool ().
 - Type *trim* and then press Enter.
- 2 Select one or more cutting edges, and then press Enter.
- 3 Select the entity to trim.
- 4 Select another entity to trim, or press Enter to complete the command.




To trim entities, select the cutting edge (A), and then select the entities to trim (B).

Result.

To trim an entity to an implied boundary

- 1 Do one of the following:
 - Choose Modify > Trim.
 - On the Modify toolbar, click the Trim tool ().
 - Type *trim* and then press Enter.
- 2 Select one or more cutting edges, and then press Enter.
- 3 In the prompt box, choose Edge Mode.
- 4 In the prompt box, choose Extend.
- 5 Select the entity to trim.


- 6 Select another entity to trim, or press Enter to complete the command.




Select the implied boundary edge (A), and then select the entities to trim (B).

Result.

To trim several entities using the fence selection method

- 1 Do one of the following:
 - Choose Modify > Trim.
 - On the Modify toolbar, click the Trim tool ().
 - Type *trim* and then press Enter.
- 2 Select one or more cutting edges, and then press Enter.
- 3 In the prompt box, choose Fence.
- 4 Specify the first point of the fence.
- 5 Specify the second point of the fence.
- 6 Specify the next fence point, or press Enter to complete the command.



Select the boundary edge (A), and then specify the first point (B) and second point (C) of the fence.

Result.


Editing the length of entities


You can change the length of entities or the included angle of arcs. Use any of the following methods to change the length of an entity:

- Dynamically drag the endpoint or angle.
- Specify an incremental length or angle measured from an endpoint.
- Specify the new length as a percentage of the total length or angle.
- Specify a new length or included angle.

You can change the length of arcs, lines, and open polylines.

To change the length of an entity by dragging

- 1 Do one of the following:
 - Choose Modify > Edit Length.
 - On the Modify toolbar, click the Edit Length tool ().
 - Type *editlen* and then press Enter.
- 2 In the prompt box, choose Dynamic.
- 3 Select the entity you want to change.
- 4 Specify the new endpoint or included angle.



Select the entity (A), and then select the new endpoint (B).

Result.


Breaking and joining entities

You can break an entity into two parts, removing a portion of the entity in the process. You can also join two entities into a single entity.

Breaking entities

You can break arcs, circles, ellipses, lines, polylines, rays, and infinite lines. When breaking entities, you must specify two points for the break. By default, the point you use to select the entity becomes the first break point; however, you can use the First option to select a break point different from the one that selects the entity.


To break an entity


- 1 Do one of the following:
 - Choose Modify > Break.
 - On the Modify toolbar, click the Break tool ().
 - Type *break* and then press Enter.
- 2 Select the entity.
- 3 Specify the second break point.



Select the entity (A), and then specify the second break point (B). Result.

To select an entity and then specify the two break points

- 1 Do one of the following:
 - Choose Modify > Break.
 - On the Modify toolbar, click the Break tool ().
 - Type *break* and then press Enter.
- 2 Select the entity.
- 3 In the prompt box, choose First.
- 4 Specify the first break point.
- 5 Specify the second break point.



Select the entity (A), and then specify the first (B) and second (C) break points.

Result.


TIP To break an entity in two without removing a portion of the entity, specify the same point for the first and second break points by typing the at sign (@) and pressing Enter instead of specifying the second break point.


Joining entities

You can join two entities into a single entity. You can join either two lines or two arcs. The two lines must be parallel; the two arcs must share the same center point and radius.

When you join two lines, the farthest endpoints remain at their existing locations; the program draws a new line between these points. Arcs are joined counterclockwise, from the first arc you select to the second.

To join two entities

- 1 Do one of the following:
 - Choose Modify > Join.
 - On the Modify toolbar, click the Join tool (.
 - Type *join* and then press Enter.
- 2 Select the first arc or line.
- 3 Select the second arc or line.




Select the first arc or line (A), and then select the second arc or line (B).

Result.

Grouping entities

A group is a collection of entities saved together as one unit. After you select the entities that belong in the group, you can later add more entities, remove entities, and reorder the entities. If necessary, you can also ungroup the entities at any time to work with the entities separately.


The Group dialog box controls the settings for all groups in a drawing.



Creating groups

When you create a group, you enter a group name and description, and then select the entities for the group.

To create a group


- Do one of the following:
 - Choose Tools > Group.
 - On the Tools toolbar, click the Group tool ().
 - Type *group* and then press Enter.
- Under Create New Group, enter the name and description of the group.
- Click Selectable if you want all entities in the group to be selected when you select one entity of the group in the drawing.

- 4 Click Select Entities and Create Group.
- 5 Select the entities for the group, and then press Enter.
- 6 In the Group dialog box, click OK.


TIP You can enter the name of a group in the command bar when selecting entities.

Modifying groups

To modify a group and its entities

- 1 Do one of the following:
 - Choose Tools > Group.
 - On the Tools toolbar, click the Group tool ().
 - Type *group* and then press Enter.
- 2 Select the group you want to modify.
- 3 Under Modify Selected Group, do one or more of the following:
 - Enter a new name, and then click Rename Group.
 - Enter a new description, and then click Change Group Description.
 - Select whether you want the group to be selectable in the drawing.
 - Click Add Entities to Group, select the entities to add to the group, and then press Enter.
 - Click Remove Entities from Group, select the entities to remove from the group, and then press Enter.
- 4 In the Group dialog box, click OK.

To change the order of entities in a group

- 1 Do one of the following:
 - Choose Tools > Group.
 - On the Tools toolbar, click the Group tool () .
 - Type *group* and then press Enter.
- 2 Under Modify Selected Group, click Reorder Entities.
- 3 In the Reorder Grouped Entities dialog box, select the group you want to reorder.
- 4 To see the order of entities in the group, click Highlight. Follow the prompts that display to view the entities one by one.
- 5 To reverse the order of all entities in the group, click Reverse Order.
- 6 To change the order of specific entities or a range of entities:
 - In Remove from Position, enter the current position of the entity.
 - In Place to Position, enter the new position of the entity.
 - In Number of Entities, enter the number of entities or range of entities to reorder. For example, if you are changing the order of only one entity, enter 1.
 - Click Reorder.


NOTE *The entities in a group are numbered 0, 1, 2, 3, and so on.*

- 7 Click OK, and then click OK again.

Ungrouping entities

When you ungroup entities, the entities remain in the drawing but the group is deleted from the drawing.

To ungroup entities

- 1 Do one of the following:
 - Choose Tools > Group.
 - On the Tools toolbar, click the Group tool () .
 - Type *group* and then press Enter.
- 2 Select the group to delete.
- 3 Under Modify Selected Group, click Ungroup Entities.
- 4 Click OK.


Editing polylines

You can modify any type of two-dimensional or three-dimensional polyline. Entities such as rectangles, polygons, and donuts, as well as three-dimensional entities such as pyramids, cylinders, and spheres, are all variations of polylines that you can edit.

You can edit a polyline by opening or closing it, by changing its overall width or the widths of individual segments, and by converting a polyline with straight line segments into a flowing curve or an approximation of a spline. In addition, you can use the Edit Polyline tool to edit individual vertices, adding, removing, or moving vertices. You can also add new segments to an existing polyline, change the linetypes of a polyline, and reverse the direction or order of the vertices.

To modify a polyline, you first select the polyline, and then select a polyline editing option. The available options vary depending on whether the selected polyline is a two-dimensional or three-dimensional entity. If the selected entity is not a polyline, the Edit Polyline tool provides the option of turning it into one. You can convert only arcs and lines into polylines. If several arcs or lines are joined endpoint to endpoint, they can all be selected and turned into one polyline.


To convert an entity into a polyline


- 1 Do one of the following:
 - Choose Modify > Edit Polyline.
 - On the Modify toolbar, click the Edit Polyline tool ().
 - Type *editpline* and then press Enter.
- 2 Select the entity.
- 3 In the prompt box, choose Yes-Turn Into Polyline.
- 4 In the prompt box, choose another option, or choose Done to complete the command.

Opening and closing polylines

When you close a polyline, the program draws a straight polyline segment from the last vertex of the polyline to the first vertex. Opening a polyline removes the closing segment. When you select a polyline for editing, the prompt box displays either the Open or Close option, depending on whether the polyline you select is closed or open.

To close an open polyline

- 1 Do one of the following:
 - Choose Modify > Edit Polyline.
 - On the Modify toolbar, click the Edit Polyline tool ().
 - Type *editpline* and then press Enter.
- 2 Select the polyline.
- 3 In the prompt box, choose Close.
- 4 In the prompt box, choose another option, or choose Done to complete the command.




Closing an open polyline adds a straight polyline segment between the first (A) and last (B) vertices.


Result.

Curving and decurving polylines

You can convert a multisegment polyline into a smooth curve using either the Fit or Spline option. The Fit option creates a smooth curve connecting all the vertices. The Spline option computes a smooth curve that is pulled toward the vertices but passes through only the first and last vertices. The Decurve option removes Fit or Spline curves and arcs, leaving straight segments between the vertices.

To fit a curve to a polyline

- 1 Do one of the following:
 - Choose Modify > Edit Polyline.
 - On the Modify toolbar, click the Edit Polyline tool ().
 - Type *editpline* and then press Enter.
- 2 Select the polyline.
- 3 In the prompt box, choose Fit.
- 4 In the prompt box, choose another option, or choose Done to complete the command.



Original polyline.

After applying Fit curve.

After applying Spline.


Joining polylines

You can add an arc, line, or polyline entity to an existing open polyline, forming one continuous polyline entity. To join an entity to a polyline, that entity must already share an endpoint with an end vertex of the selected polyline.

When you join an entity to a polyline, the width of the new polyline segment depends on the width of the original polyline and the type of entity you are joining to it:

- A line or an arc assumes the same width as the polyline segment for the end vertex to which it is joined.
- A polyline joined to a tapered polyline retains its own width values.
- A polyline joined to a uniform-width polyline assumes the width of the polyline to which it is joined.


To join an arc, line, or polyline to an existing polyline

- 1 Do one of the following:
 - Choose Modify > Edit Polyline.
 - On the Modify toolbar, click the Edit Polyline tool ().
 - Type *editpline* and then press Enter.
- 2 Select the polyline.
- 3 In the prompt box, choose Join.
- 4 Select the arc, line, or polyline to join.
- 5 In the prompt box, choose another option, or choose Done to complete the command.


Changing the polyline width

You can change the width of an entire polyline, applying a uniform width to the entire entity or tapering the polyline uniformly along its entire length.

To apply a uniform width to an entire polyline

- 1 Do one of the following:
 - Choose Modify > Edit Polyline.
 - On the Modify toolbar, click the Edit Polyline tool ().
 - Type *editpline* and then press Enter.
- 2 Select the polyline.
- 3 In the prompt box, choose Width.
- 4 Specify the new polyline width.
- 5 In the prompt box, choose another option, or choose Done to complete the command.

To taper a polyline uniformly along its length

- 1 Do one of the following:
 - Choose Modify > Edit Polyline.
 - On the Modify toolbar, click the Edit Polyline tool ().
 - Type *editpline* and then press Enter.
- 2 Select the polyline.
- 3 In the prompt box, choose Taper.
- 4 Specify the starting width.
- 5 Specify the ending width.
- 6 In the prompt box, choose another option, or choose Done to complete the command.


Editing polyline vertices


You can use the Edit Vertices option to modify individual polyline vertices. When you select this option, the program switches into a special vertex editing mode and places an *x* on the first vertex. The *x* indicates the vertex you are editing. The Next and Previous options move the *x* to the next or previous vertex. You can edit only one vertex at a time.

When editing vertices, you can modify the polyline in the following ways:

- Convert a polyline segment into a curve by specifying a new tangent angle.
- Break a polyline into two separate polylines.
- Insert a new vertex after the current vertex.
- Move the current vertex.
- Straighten the polyline segment between two vertices.
- Change the width of the polyline segment between two vertices.

To move a polyline vertex


- 1 Do one of the following:
 - Choose Modify > Edit Polyline.
 - On the Modify toolbar, click the Edit Polyline tool ().
 - Type *editpline* and then press Enter.
- 2 Select the polyline.
- 3 In the prompt box, choose Edit Vertices.
- 4 In the prompt box, choose Next Vertex.
Repeat until the *x* reaches the vertex you want to move.
- 5 In the prompt box, choose Move.
- 6 Specify the new location for the vertex.
- 7 In the prompt box, choose another option, or choose Exit to stop editing vertices.
- 8 In the prompt box, choose another option, or choose Done to complete the command.




Select the polyline (A), move the current vertex marker to the vertex you want to move (B), and then specify the new vertex location (C).

Result.

To taper the width of an individual polyline segment

- 1 Do one of the following:
 - Choose Modify > Edit Polyline.
 - On the Modify toolbar, click the Edit Polyline tool ().
 - Type *editpline* and then press Enter.
- 2 Select the polyline.
- 3 In the prompt box, choose Edit Vertices.
- 4 In the prompt box, choose Next Vertex.
Repeat until the *x* reaches the first vertex of the segment you want to taper.
- 5 In the prompt box, choose Width.
- 6 Specify the starting width.
- 7 Specify the ending width.
- 8 In the prompt box, choose another option, or choose Exit to stop editing vertices and update the display.
- 9 In the prompt box, choose another option, or choose Done to complete the command.



Select the polyline (**A**), move the current vertex marker to the first vertex of the segment you want to taper (**B**), and then specify the new starting and ending widths for that segment.

Result.


Exploding entities

You can convert a complex entity, such as a block or polyline, from a single entity into its component parts. Exploding a polyline, rectangle, donut, polygon, dimension, or leader reduces it to a collection of individual line and arc entities that you can then modify individually. Blocks are converted to the individual entities, possibly including other, nested blocks that composed the original entity.

With the following exceptions, exploding an entity usually has no visible effect on a drawing:

- If the original polyline had a width, the width information is lost when you explode it. The resulting lines and arcs follow the centerline of the original polyline.
- If you explode a block containing attributes, the attributes are lost, but the original attribute definitions remain.
- Colors, linetypes, lineweights, and print styles assigned BYBLOCK may be different after exploding an entity, because they will adopt the default color, linetype, lineweight, and print style until inserted into another block.


To explode an entity

- 1 Do one of the following:
 - Choose Modify > Explode.
 - On the Modify toolbar, click the Explode tool ().
 - Type *explode* and then press Enter.
- 2 Select the entities to explode.
- 3 Press Enter.

Chamfering and filleting entities

You can chamfer or fillet entities. A chamfer connects two nonparallel entities with a line to create a beveled edge. A fillet connects two entities with an arc of a specified radius to create a rounded edge. If both entities you are working with are on the same layer, the chamfer or fillet is drawn on that layer. If they are on different layers, the chamfer or fillet is drawn on the current layer.

The Chamfer/Fillet settings in the Drawing Settings dialog box control the chamfer and fillet settings. The portions of the entities that extend beyond the chamfer or fillet are normally deleted when you create the chamfer or fillet. You can retain these original entities, however, by changing the settings in the dialog box.




- A** Click to remove or retain portions of entities that extend beyond the chamfer or fillet.
- B** Click to create a chamfer using two chamfer distances (distance-distance method).
- C** Specify the first and second chamfer distances when using the distance-distance method.
- D** Specify the chamfer length and angle when using the distance-angle method.
- E** Click to create a chamfer using the chamfer length and angle (distance-angle method).
- F** Click to specify the fillet radius by selecting two points in the drawing.
- G** Specify the fillet radius.


Chamfering entities

You can connect two nonparallel entities by extending or trimming them and then joining them with a line to create a beveled edge. You can chamfer lines, polylines, rays, and infinite lines. When creating a chamfer, you can specify how far to trim the entities back from their intersection (distance-distance method), or you can specify the length of the chamfer and the angle it forms along the first entity (distance-angle method).

When chamfering a polyline, you can chamfer multiple segments between two selected polyline segments, or you can chamfer the entire polyline.


To chamfer two entities using the distance-distance method


- 1 Do one of the following:
 - Choose Modify > Chamfer.
 - On the Modify toolbar, click the Chamfer tool ().
 - Type *chamfer* and then press Enter.
- 2 In the prompt box, choose Chamfer Settings.
- 3 In the Drawing Settings dialog box, click the Entity Modification tab.
- 4 Under Chamfer Distances And Angles, click Distance-Distance.
- 5 Under Chamfer Distances And Angles, specify the first and second chamfer distances.
- 6 Click OK.
- 7 Select the first entity.
- 8 Select the second entity.



Select the first (A) and second (B) entities. The chamfer is drawn, based on the first (C) and second (D) chamfer distances.


To chamfer two entities using the distance-angle method


- 1 Do one of the following:
 - Choose Modify > Chamfer.
 - On the Modify toolbar, click the Chamfer tool ().
 - Type *chamfer* and then press Enter.
- 2 In the prompt box, choose Chamfer Settings.
- 3 In the Drawing Settings dialog box, click the Entity Modification tab.
- 4 Under Chamfer Distances And Angles, click Distance-Angle.
- 5 Under Chamfer Distances And Angles, specify the chamfer distance and angle.
- 6 Click OK.
- 7 Select the first entity.
- 8 Select the second entity.



Select the first (A) and second (B) entities. The chamfer is drawn, based on the distance measured along the first entity (C) and the angle (D) formed with the first entity.

To chamfer all vertices in a polyline


- 1 Do one of the following:
 - Choose Modify > Chamfer.
 - On the Modify toolbar, click the Chamfer tool ().
 - Type *chamfer* and then press Enter.
- 2 In the prompt box, choose Polyline.
- 3 Select the polyline.




Original polyline.

Result after chamfering.

To chamfer selected vertices in a polyline

- Do one of the following:
 - Choose Modify > Chamfer.
 - On the Modify toolbar, click the Chamfer tool ().
 - Type *chamfer* and then press Enter.
- Select the polyline along the segment where you want to begin the chamfer.
- Select the polyline along the segment where you want to end the chamfer.




Select the polyline along the (A) and (B) segments.


Result after chamfering.

Filleting entities

You can connect two entities with an arc of a specified radius to create a rounded edge. You can fillet pairs of line segments, straight polyline segments, arcs, circles, rays, and infinite lines. You can also fillet parallel lines, rays, and infinite lines. When filleting a polyline, you can fillet multiple segments between two selected segments, or you can fillet the entire polyline.

To fillet two entities


- Do one of the following:
 - Choose Modify > Fillet.
 - On the Modify toolbar, click the Fillet tool ().
 - Type *fillet* and then press Enter.
- In the prompt box, choose Fillet Settings.
- In the Drawing Settings dialog box, specify the fillet radius.
- Click OK.
- Select the first entity.
- Select the second entity.




Select the first (A) and second (B) entities.

Result after filleting.

To fillet an entire polyline


- 1 Do one of the following:
 - Choose Modify > Fillet.
 - On the Modify toolbar, click the Fillet tool ().
 - Type *fillet* and then press Enter.
- 2 In the prompt box, choose Polyline.
- 3 Select the polyline.




Select the polyline (A).

Result after filleting.

To fillet selected vertices in a polyline


- 1 Do one of the following:
 - Choose Modify > Fillet.
 - On the Modify toolbar, click the Fillet tool ().
 - Type *fillet* and then press Enter.
- 2 Select the polyline along the segment where you want to begin the fillet.
- 3 Select the polyline along the segment where you want to end the fillet.



Select the polyline along the (A) and (B) segments.

Result after filleting.


When you fillet circles and arcs, more than one fillet can exist between the entities. The point at which you select the entities determines the fillet.



Select entities (A and B).

Results after filleting.

You can fillet parallel lines, rays, and infinite lines. The first entity must be a line or ray; the second entity can be a line, ray, or infinite line. The diameter of the fillet arc is always equal to the distance between the parallel entities. The current fillet radius is ignored.



Original entities.

Result after filleting.

Working with text

You can insert text into your drawing and control its appearance, allowing you to provide additional information for your IntelliCAD drawings. This section explains how to:

- Create line text.
- Create paragraphs.
- Create text styles.
- Format text.
- Change text.
- Change paragraph text.
- Check the spelling of text.
- Use an alternate text editor.
- Working with text written in different languages.


Topics in this chapter

<i>Creating line text</i>	278
<i>Creating paragraph text</i>	279
<i>Working with text styles</i>	281
<i>Formatting text</i>	282
<i>Changing text</i>	285
<i>Using an alternate text editor</i>	293
<i>Working with text written in different languages</i>	295

Creating line text

When you create text, you end each line of text by pressing Enter. Each line of text is created as a separate entity that you can modify.

To create text

- 1 Do one of the following:
 - Choose Insert > Text.
 - On the Draw 2D toolbar, click the Text tool ().
 - Type *dtext* and then press Enter.
- 2 Specify the insertion point for the first character.
- 3 Specify the height of the text.
- 4 Specify the text rotation angle.
- 5 Type the text, and then press Enter at the end of each new line.
- 6 To complete the command, press Enter again.


TIP *If you've already created text and want new text to appear immediately below the previous text, choose Insert > Text. When prompted for an insertion point, press Enter. The new text will keep the same height and rotation angle as the previous text.*

Creating paragraph text

Paragraph text consists of one or more lines of text or paragraphs that fit within a boundary width that you specify. Each paragraph text entity you create is treated as a single entity regardless of the number of individual paragraphs or lines of text it contains.

When you create paragraph text, you first determine the paragraph's boundary width by specifying the opposite corners of a rectangle. The paragraph text automatically wraps so that it fits within this rectangle. The first corner of the rectangle determines the default attachment point of the paragraph text. You can change the location of the attachment point in reference to the rectangle, and you can determine the direction in which text flows within the rectangle. You can also select the text and paragraph format, text style, text height, and the rotation angle of the entire paragraph text entity.

To create paragraph text


- 1 Do one of the following:
 - Choose Insert > Multiline Text.
 - On the Draw 2D toolbar, click the Multiline Text tool ().
 - Type *mtext* and then press Enter.
- 2 Select the first corner of the text area.
- 3 In the MTEXT prompt box, select the properties you want to change, or proceed directly to step 4.

You can select these properties in steps 7 and 8.
- 4 Select the second corner of the text area.
- 5 In the Multiline Text dialog box, click the Text tab.
- 6 In the window, type the text you want.


To create paragraphs, press Enter and continue typing.
- 7 Make any selections or changes you want to the following:
 - Font, text height, bold, italic, underline, and color.
 - Indents on the ruler. Move the upper left arrow to define the first line indent, move the lower left arrow to define the paragraph indent, and move the right arrow to define the right indent.
 - Tabs on the ruler. Click the ruler to create tabs, move any tab marker to modify its location, and drag any tab off the ruler to delete it.

Your selections affect highlighted text, or if no text is highlighted, new text when you type it.
- 8 Click the Properties tab, and make selections or changes you want to the text Style, Justification, Width, and Rotation.
- 9 Click OK.

TIP You can paste text from the Clipboard into the Multiline Text dialog box.



- A Click to view and select text attributes.
- B Select the text font.
- C Mark the first line indent, paragraph indent, right indent, and tabs.
- D Type and select text.
- E Select or type a zoom magnification.
- F Select BYBLOCK, BYLAYER, the color of your choice, or choose Select Color to select from additional colors.
- G Click to undo the previous action.
- H Click to bold, italicize, and underline text.
- I Select or type the text height.



- A Click to view and select text style and text box properties.
- B Select a text style.
- C Mark the first line indent, paragraph indent, right indent, and tabs.
- D Type and select text.
- E Select or type the text box angle.
- F Select or type the text width.
- G Select the text box justification.

Working with text styles

When you add text to a drawing, it uses the current text style. Text style determines the font, size, angle, orientation, and other characteristics.


Every drawing has a default text style, named Standard, which initially uses the *icad.fnt* font. You cannot delete the Standard style, but you can rename it or modify it. You can change the font, the size of the font, and the obliquing angle applied to it. If you change the font or orientation of an existing style, all existing text entities created using that style are automatically updated to reflect the new font or orientation. Changing any other characteristic has no effect on existing text. You also can create and use an unlimited number of additional text styles.

The text style determines the characteristics shown in the following table.

Style characteristics

Characteristic	Default	Description
Style name	Standard	The name of the style, up to 31 characters.
Font file	icad.fnt	The font file on which the style is based.
Text height	0	The character height. A value of 0 prompts for text height upon insertion.
Width factor	1	The horizontal expansion or compression of the text. Values less than 1 compress the text; values greater than 1 expand the text.
Obliquing angle	0	The slant of the text, in degrees. Negative values slant the text to the left; positive values slant the text to the right.
Backward	No	Determines whether text appears backward.
Upside down	No	Determines whether text appears upside down.
Vertical	No	Determines whether text has a vertical orientation.

To create a text style

- Do one of the following:
 - Choose Settings > Explore Text Styles.
 - On the Settings toolbar, click the Explore Text Styles tool ().
 - Type *expfonts* and then press Enter.
- Choose Edit > New > Style.
- Type a new text style name, or press Enter to accept the default name.
- Choose Edit > Properties to open the Styles dialog box.
- Under Text Font, select the name, style, and language of the font you want to use.
- Under Text Measurements, enter the Fixed Text Height, Width Factor, and Oblique Angle measurement.
- Under Text Generation, select the check boxes you want to indicate the direction for printed text to appear.

- 8 Close the Styles dialog box, then close the IntelliCAD Explorer dialog box.
- 9 To begin using the new style, choose Insert > Text.
- 10 In the prompt box, select Use Defined Style.


Formatting text

When you create text, you choose the text style and set the alignment. The style determines the font characteristics for the text. For line text, the alignment determines how the text aligns with the text insertion point. For paragraph text, the alignment determines the location of the attachment point in relation to the paragraph text boundary and the direction in which text flows within the boundary.

Setting the line text style

You can set the text style before you specify the insertion point. You select the text style by typing the name of a previously defined style.

To specify a line text style


- 1 Do one of the following:
 - Choose Insert > Text.
 - On the Draw 2D toolbar, click the Text tool ().
 - Type *dtext* and then press Enter.
- 2 In the prompt box, choose Use Defined Style.
- 3 Type the name of a previously defined text style, and then press Enter.

To display a list of available text styles, type a question mark (?), and then press Enter.
- 4 Specify the text insertion point.
- 5 Specify the text height.
- 6 Specify the rotation angle.
- 7 Type the text line, and then press Enter.
- 8 To complete the command, press Enter again.

Setting the paragraph text style


You can set the paragraph text style before you specify the insertion point. You select the text style by typing the name of a previously defined style.

To specify a paragraph text style

- 1 Do one of the following:
 - Choose Insert > Multiline Text.
 - On the Draw 2D toolbar, click the Multiline Text tool ().
 - Type *mtext* and then press Enter.
- 2 Specify the first point of the Multiline Text box.
- 3 In the prompt box, choose Text Style.
- 4 Type the name of a previously defined text style, and then press Enter.
- 5 Specify the text height.
- 6 Specify the rotation angle.
- 7 Specify the opposite corner of the Multiline Text box.
- 8 Type the text, and then press Enter.
- 9 To complete the command, press Enter again.

Setting the line text alignment

When you create text, you can set the text alignment before you specify the insertion point. You set the alignment by choosing it in the prompt box. By default, text is left justified. You can align text at the left, center, or right and at the top, middle, or baseline of the text or at the bottom of descending letters.



- | | |
|-----------------|-----------------|
| A Top left | H Baseline |
| B Middle left | I Right |
| C Left | J Middle right |
| D Bottom left | K Top right |
| E Center | L Middle |
| F Bottom center | M Middle center |
| G Bottom right | N Top center |

You can also align text so that it fits or aligns between two points. The Align option creates text that scales up or down while maintaining a constant height/width ratio; the Fit option expands or compresses the text to fit between the two points.


Ut wisi enim ad minim veniam

Text aligned between two points maintains a constant height/width ratio.

Ut wisi enim

Text fit between two points expands or compresses to fit.

To specify the line text alignment

- 1 Do one of the following:
 - Choose Insert > Text.
 - On the Draw 2D toolbar, click the Text tool () .
 - Type *dtext* and then press Enter.
- 2 In the prompt box, choose an alignment option, or choose Justification Options to display all the justification options.
- 3 Specify the text insertion point, and then continue creating the line text.

Setting the paragraph text alignment

When you create paragraph text, you can set the text alignment by specifying the attachment point location in relation to the paragraph text boundary and the direction in which text flows within the boundary. You can set the paragraph text alignment either in the prompt box displayed after you specify the first corner of the paragraph text boundary or from the Multiline Text dialog box. You can specify the attachment point at the top left, top center, top right, middle left, middle center, middle right, bottom left, bottom center, or bottom right. The paragraph text can flow left to right, right to left, top to bottom, or bottom to top.

Including special text characters

You can use control codes to overscore or underscore text or to include special characters. Both overscore and underscore can be active at the same time. To include control codes, as you type text, type two percent symbols (%%) followed by the special control code or character. A single percent sign is treated as a normal text character. A triple-percent control code is provided for those instances where a control-code sequence must follow a percent sign in the text.

Special text characters

Control code	Function
%%o	Toggles overscore mode on and off.
%%u	Toggles underscore mode on and off.
%%d	Draws a degree symbol (°).
%%p	Draws the plus-or-minus symbol (±).
%%c	Draws the circle diameter symbol (Ø).
%%%	Forces a single percent sign.
%%nnn	Draws special character number <i>nnn</i> .

Ut wisi enim[°] ad± minim Ø veniam


Text created using special text characters: Ut wisi %%uenim%%d ad%%p%%u minim %%c %%oveniam.

Changing text


Changing line text


You can edit and modify the text as you would any other drawing entity. That is, you can delete, move, rotate, and scale text.

To edit text

- 1 Do one of the following:
 - Choose Modify > Edit Text.
 - On the Modify toolbar, click the Edit Text tool ().
 - Type *ddedit* and then press Enter.
- 2 Select the text entity.
- 3 In the Text field, edit the text, and then click OK.

To change text properties

- 1 Do one of the following:
 - Choose Modify > Edit Text.
 - On the Modify toolbar, click the Edit Text tool().
 - Type *ddedit* and then press Enter.
- 2 Select the text entity.
- 3 Under Text Settings, change the text properties you want.
- 4 Click OK.




- | | |
|---|---|
| <p>A Click to change layer.</p> <p>B Click to change color.</p> <p>C Click to change print style (available only for drawings that use named print style tables).</p> <p>D Specify new text insertion point or justification.</p> <p>E Specify text height.</p> <p>F Specify text rotation angle.</p> <p>G Edit the existing text.</p> <p>H Specify the width factor.</p> | <p>I Specify the obliquing angle.</p> <p>J Select to insert backward text.</p> <p>K Select to insert upside-down text.</p> <p>L Click to change text style.</p> <p>M Click to change text justification.</p> <p>N Click to select a new text insertion point. or justification</p> <p>O Click to attach a hyperlink to the text.</p> |
|---|---|


Changing paragraph text


You can modify the text as you would any other drawing entity. That is, you can delete, move, rotate, and scale text.

To edit paragraph text

- 1 Do one of the following:
 - Choose Modify > Edit Text.
 - On the Modify toolbar, click the Edit Text tool ().
- 2 Select the text entity.
- 3 Edit the text in the Contents field of the Entity Properties dialog box.
- 4 To apply font style changes to the text, click Full Editor.
- 5 Click OK.

To change paragraph text properties

- 1 Do one of the following:
 - Choose Modify > Edit Text.
 - On the Modify toolbar, click the Edit Text tool ().
- 2 Select the text entity.
- 3 Change the text properties you want under the Text section of the Entity Properties dialog box.
- 4 To apply font style changes to the text, click Full Editor.
- 5 Click OK.




- | | |
|--|---|
| <p>A Click to change layer.</p> <p>B Click to change color.</p> <p>C Click to change print style (available only for drawings that use named print style tables).</p> <p>D Specify new attachment point.</p> <p>E Specify text height.</p> <p>F Specify width of text boundary rectangle.</p> <p>G Specify text rotation angle.</p> | <p>H Edit the existing text.</p> <p>I Click to change font styles.</p> <p>J Click to change text style.</p> <p>K Click to change direction in which text flows.</p> <p>L Click to change attachment point in relation to text boundary rectangle.</p> <p>M Click to select a new attachment point.</p> <p>N Click to attach a hyperlink to the text.</p> |
|--|---|


Checking the spelling

Checking the spelling of text

You can use the Spell command to check the spelling of single-line text, multiline text, paragraph text, attributes, attribute definitions, and dimension text.

To check the spelling of text

- 1 Do one of the following:
 - Choose Tools > Spelling.
 - On the Standard toolbar, click the Spelling tool ().
 - Type *spell* and then press Enter.
- 2 Select one or more text entities.
- 3 In the Check Spelling dialog box, misspelled words display one at a time. Do one of the following for each found word:
 - Keep text unchanged — Click Ignore to keep the found word unchanged in the drawing, or click Ignore All to keep all instances of the found word unchanged in the drawing.
 - Change text — Select or type a word in the Suggestions box, then click Change to change the found word in the drawing to the new text, or click Change All to change all instances of the found word in the drawing.
- 4 Click Add if you want to add the currently found word to a list of custom spelling words. The Check Spelling dialog will recognize the added word as spelled correctly the next time the word is checked for spelling.




- A** Displays the current dictionary.
- B** Displays the misspelled word and its context in the drawing.
- C** Displays (or you can type) a new word to replace the misspelled word in the drawing.
- D** Click to select a new word to replace the currently found misspelled word.
- E** Click to select a new dictionary or modify a custom dictionary.
- F** Click to add the suggested word to the custom dictionary.
- G** Click to suggest additional words based on the selected word in the Suggestions list.
- H** Click to change all instances of the misspelled word to the suggested word.
- I** Click to change a single instance of the misspelled word to the suggested word.
- J** Click to skip all instances of the misspelled word.
- K** Click to skip a single instance of the misspelled word without changing it.
- L** Move the slider to zoom in or out on the text.


Customizing the spelling words

Most drawings contain text that is not recognized as spelled correctly, even though it is spelled correctly. For example, if your company name Zaffer, Inc. appears in all of your drawings, the company name will appear as misspelled every time you check the spelling of drawing text. You can easily add words to a custom dictionary so that any word in the custom dictionary is recognized as spelled correctly.

The custom dictionary is independent of any spelling dictionary you have chosen to use. You can check the spelling of text using one dictionary, check the spelling of the same or other text using a different dictionary, and in both cases your custom dictionary is used.

To create and manage a custom dictionary

- 1 Do one of the following:
 - Choose Tools > Spelling.
 - On the Standard toolbar, click the Spelling tool ().
 - Type *spell* and then press Enter.
- 2 Select one or more text entities.
- 3 In the Check Spelling dialog box, click Change Dictionaries.
- 4 To add a custom word, type a word in Custom Dictionary Words, then click Add.
- 5 To delete a custom word, select a word in Custom Dictionary Words, then click Delete.
- 6 Click OK.



- | | |
|---|--|
| <p>A Type a word for the custom dictionary.</p> <p>B Displays the words in the custom dictionary.</p> <p>C Click to delete the currently selected word from the custom dictionary.</p> <p>D Click to add the current word in the edit box (A) to the custom dictionary.</p> | <p>E Click to select a different custom dictionary.</p> <p>F Displays the custom dictionary filename. You can type a new path and filename or click Browse to select a file.</p> |
|---|--|


***TIP** You can also add custom words to the custom dictionary directly during spell checking of text. In the Check Spelling dialog, click Add to add the currently found word to the custom dictionary.*

Changing the dictionary

The Spell command compares text found in the drawing with correctly spelled words in an installed dictionary (.dic file). There are many different dictionaries that can be used with IntelliCAD, including dictionaries in different languages. You can download and install a new dictionary or use a dictionary already installed on your computer.

To download and install a new dictionary

- 1 Choose Tools > Spelling, select one or more text entities, then in the Check Spelling dialog box, click Change Dictionaries.
- 2 Click Download.
- 3 From the web page that displays (or from a different web page), download the desired dictionary.
- 4 Unzip the contents of the downloaded file to \MyDocuments\Spelling, or the location where you installed spelling dictionaries for IntelliCAD.
- 5 Click Change Dictionaries again, which will load the newly installed dictionary.
- 6 In Main Dictionary, select the desired dictionary.
- 7 Click OK.



A Select the desired spelling dictionary.

B Click to open the default Internet browser to a web page where you can download spelling dictionaries in different languages.

To use a dictionary already installed on your computer

- 1 Do one of the following:
 - Copy the existing dictionary (.dic file) to \MyDocuments\Spelling, or to the location where you install spelling dictionaries for IntelliCAD.
 - Add the folder of the existing dictionary to the list of folders where IntelliCAD searches for dictionaries. Choose Tools > Options, click Paths/Files and add the folder location to the Dictionary paths. For more details, see “Changing the options on the Paths/Files tab” on page 478.
- 2 Choose Tools > Spelling, select one or more text entities, then in the Check Spelling dialog box, click Change Dictionaries.
- 3 In Main Dictionary, select the desired dictionary.
- 4 Click OK.

Using an alternate text editor

IntelliCAD includes a built-in text editor for creating paragraph text using the Multiline Text command. You can also specify an alternate text editor for the Multiline Text command.

Selecting an alternate text editor

Before you can use an alternate text editor, you must specify the editor by setting the MTEXTED system variable.


To select an alternate text editor

- 1 Type *mtexted* and then press Enter.
- 2 Enter the path and name of the executable file for the text editor you want to use to create or edit multiline text. For example, to use Microsoft® Wordpad, you would type something similar to the following (adjusting the path name as necessary):
C:\Program Files\Windows\Accessories\Wordpad.exe

Creating paragraph text in an alternate text editor

After you set up IntelliCAD to use an alternate text editor, you can start using it to include text in your drawings.

To use an alternate text editor

- 1 Do one of the following:
 - Choose Insert > Multiline Text.
 - On the Draw 2D toolbar, click the Multiline Text tool ().
 - Type *mtext* and then press Enter.
- 2 Select the first and second corners of the text area.
- 3 In the Multiline Text dialog box, click the Text tab.
- 4 In the window, type the text you want, using the special characters from the table shown next to achieve special formatting. Enter \P to end a paragraph and start a new paragraph on the next line. For example, to use an alignment value of 1 and stack two numbers to display them as a fraction:


```
{\A1;\S1/2;}\P
```
- 5 When your text is complete, save the changes and exit the text editor.

Special formatting characters

Format characters	Function
\O...o	Toggles overscore mode on and off.
\L...l	Toggles underscore mode on and off.
\~	Inserts a nonbreaking space.
\\	Inserts a backslash.
{...}	Inserts an opening and closing brace.
\Cvalue;	Sets the color to a specified value.
\File name;	Sets the font based on a specified font file name.
\Hvalue;	Sets the text height to a specified value.
\HvalueX;	Sets the text height to a multiple of the current text height.
\S...^...;	Stacks the subsequent text at the /, #, or ^ symbol.
\Tvalue;	Adjusts the space between characters, from 0.75 to 4 times.
\Qangle;	Changes obliquing angle.
\Wvalue;	Changes width factor to produce wide text.
\A	Sets the alignment value.
\P	Ends paragraph.
\p[i],[l],[tX1,X2,...,X32]	Formats paragraph: i = first line indent; l = paragraph offset; t = tab positions.

Working with text written in different languages

You can include text in your drawings that is written in different languages.

Using Unicode characters

IntelliCAD supports the Unicode character encoding standard, which enables you to display and write text in different languages using different letters. Unicode fonts contain many more characters than typically defined in a system.

Special Unicode characters

Control code	Function
\U+00B0	Draws a degree symbol (°).
\U+00B1	Draws the plus-or-minus symbol (±).
\U+2205	Draws the circle diameter symbol (∅).

For more details about using special characters, see “Including special text characters” on page 285 in this chapter. You can also use a different text editor; see “Using an alternate text editor” on page 293 in this chapter.

Specifying character sets for drawings

The character set used to display text in drawings typically depends on the character set specified by your operating system, for example, ANSI_1252 is Latin 1, ANSI_1253 is Greek, and ANSI_1254 is Turkish. This is also called the *code page*.

IntelliCAD allows you to manage which code page is assigned to a drawing when you open the drawing or after you open it. This unique feature is usually not necessary if you distribute drawings within the same geographic region, but it can be very helpful when sharing or distributing drawings between different geographic regions. Changing the code page is highly desirable especially in geographic regions where several languages are used that require different character sets to display text properly.

Setting the code page doesn’t change the language of your text; instead it specifies the character set in which the text displays. Some fonts can display its characters several different ways depending on the code page setting.


There are two system variables that relate to the code page of a drawing:

- SYSCODEPAGE — Character set defined for your operating system.
- DWGCODEPAGE — Character set defined for an individual drawing that overrides the operating system code page.

To manage how code pages are assigned to drawings

- 1 Type *codepage* and then press Enter.
The Code Page Manager dialog box opens.
- 2 If you want to convert the drawing to use a different code page, in Drawing Code Page, select the desired code page.
- 3 Select one of the following options:
 - **No conversion when a drawing is opened** — Keeps the drawing code page unchanged when you open a drawing.
 - **Always open this dialog when a drawing is opened** — Opens the Code Page Manager dialog box every time you open a drawing.
 - **Only open this dialog when the drawing and system code pages differ** — Opens the Code Page Manager dialog box only when the operating system code page is different from the drawing code page. This setting can be helpful if you sometimes send or receive drawings created using a code page that is different from the one used by your operating system.
 - **Automatically convert the code page when a drawing is opened** — Always use the same code page when opening drawings (the Code Page Manager dialog box will not open).
- 4 If you selected to automatically convert the code page, select one of the following:
 - **Use alternate code page** — When converting drawings automatically, always use the code page that you select.
 - **Use system code page** — When converting drawings automatically, use the code page defined for the operating system (this is the code page displayed for the SYSCODEPAGE system variable).

TIP *If you want to always use the code page assigned to a drawing, choose No Conversion when a Drawing is Opened (this is the default setting). You can change the drawing code page after opening a drawing, if necessary. If you want to always use the code page specified for your operating system, choose Automatically Convert the Code Page, and then choose Use System Code Page.*



- A** Displays the code page for your operating system.
- B** Select the code page for the current drawing.
- C** Choose to keep the drawing code page unchanged when you open a drawing.
- D** Choose to open the Code Page Manager dialog box every time you open a drawing.
- E** Choose to open the Code Page Manager dialog box only when the operating system code page is different from the drawing code page.
- F** Choose to always use the same code page when opening drawings (the Code Page Manager dialog box will not open).
- G** Choose to always use the operating system code page when opening drawings (available only if you selected to automatically convert drawings).
- H** Choose to always use the selected code page when opening drawings (available only if you selected to automatically convert drawings).
- I** Click to preview the first text entity using the current code page settings.
- J** Click to preview the next text entity using the current code page settings.

Dimensioning your drawing

The IntelliCAD dimensioning tools let you add measurements to a drawing. You can quickly add dimensions by simply pointing to entities. You can also add tolerance symbols to your drawings.

The program's many dimensioning variables let you control the appearance of the dimensions. With dimension styles, you can save dimension variable settings so you can reuse them without having to re-create them.

This section explains how to:


- Create dimensions as linear, angular, diametral, radial, and ordinate.
- Create leaders and annotations.
- Edit dimensions.
- Use dimension styles and variables.
- Add geometric tolerances.
- Control dimension tolerance.
- Control alternate dimension units.

Topics in this chapter

<i>Understanding dimensioning concepts</i>	300
<i>Creating dimensions</i>	302
<i>Editing dimensions</i>	313
<i>Understanding dimension styles and variables</i>	316
<i>Adding geometric tolerances</i>	327

Understanding dimensioning concepts

You can create five basic types of dimensions: linear, angular, radial, diametral, and ordinate. You can create dimensions for existing entities by selecting them, or you can create dimensions by selecting points within a drawing. For example, you can create a linear dimension either by selecting the entity to be dimensioned or by specifying the first and second extension line origins.




- | | |
|---------------------------------------|---------------------------------------|
| A Radial dimension. | E Aligned dimension. |
| B Vertical linear dimension. | F Diametral dimension. |
| C Angular dimension. | G Horizontal linear dimension. |
| D Linear continued dimensions. | H Linear baseline dimension. |

When you create a dimension, the program draws it on the current layer, using the current dimension style. Each dimension has an associated dimension style, which controls the appearance of the dimension, such as the types of arrowheads, text style, and colors of various components. You can modify existing dimension styles by changing one of the dimension variable settings and then updating the dimension style to reflect the new settings.

Each dimension you create consists of several parts. A dimension line shows where a dimension begins and ends. When you create an angular dimension, the dimension line is a dimension line arc that subtends the measured angle.


Extension lines, also called projection lines, are lines that extend away from the entity for which you are creating a dimension, so that you can place the dimension line away from the entity. Arrowheads form the termination at each end of the dimension line.

Dimension text contains the measured dimension and can also include prefixes, suffixes, tolerances, and other optional text. As you insert dimensions, you can control the dimension text and specify its position and orientation.



- A** Extension line.
- B** Arrowhead.
- C** Dimension line.
- D** Dimension text.

Dimensions can also contain other optional components. A leader is a line leading from a feature of the drawing to an annotation. Leaders begin with an arrowhead, and you can use them to place a dimension away from the dimension line or to add notes. When you create a radial dimension, you can add a center mark, which is a small cross that marks the center of a circle or an arc, or you can add centerlines, which are crossing lines that extend out from the center of a circle or an arc.



- Leader.
- Center mark.
- Centerlines.

Creating dimensions

You can create dimensions by:

- Selecting the entity to dimension and specifying the dimension line location.
- Specifying the extension line origins and the dimension line location.

When you create dimensions by selecting an entity, the program automatically places the extension line origins at the appropriate definition points based on the type of entity you select. For example, the definition points are located at the endpoints of arcs, lines, and polyline segments. When you create dimensions by specifying the extension line origins, the points you specify determine the definition points. To establish these points precisely, use entity snaps.


You can create dimensions in model space or paper space.

Creating linear dimensions

Linear dimensions annotate linear distances or lengths and can be oriented horizontally, vertically, or aligned parallel to an existing entity or to the selected extension origin points. After you create a linear dimension, you can add a baseline dimension or a continued dimension. A linear baseline dimension inserts an additional dimension from a common first extension line origin of a previous linear dimension. A linear continued dimension continues a linear dimension from the second extension line of a previous linear dimension.

TIP *To select precise ordinate points, use entity snaps.*


To create a horizontal or vertical dimension

- 1 Do one of the following:
 - Choose Insert > Dimensions > Linear.
 - On the Dimensioning toolbar, click the Linear tool ().
 - Type *dimlinear* and then press Enter.
- 2 Press Enter, and then select the entity to dimension.
 Or, you can insert the dimension by specifying the first and second extension line origins.
- 3 Specify the dimension line location.



To insert a linear dimension by selecting the entity, select the entity (**A**) to dimension, and then specify the dimension line location (**B**).


Result.




To insert a linear dimension by selecting the extension line origins, select the first extension origin (**A**), select the second extension origin (**B**), and then specify the dimension line location (**C**).

Result.

To create an aligned dimension

- 1 Do one of the following:
 - Choose Insert > Dimensions > Aligned.
 - On the Dimensioning toolbar, click the Aligned tool ().
 - Type *dimaligned* and then press Enter.
- 2 Press Enter, and then select the entity to dimension.
 Or, you can insert the dimension by specifying the first and second extension line origins.
- 3 Specify the dimension line location.



To insert an aligned dimension by selecting the entity, select the entity (**A**) to dimension, and then select the dimension line location (**B**).

Result.




To insert an aligned dimension by selecting the extension line origins, select the first extension origin (**A**), select the second extension origin (**B**), and then specify the dimension line location (**C**).

Result.


To create a linear baseline dimension

NOTE Before you can use this procedure, you must first create a dimension.


- 1 Do one of the following:
 - Choose Insert > Dimensions > Baseline.
 - On the Dimensioning toolbar, click the Baseline tool ().
 - Type *dimbaseline* and then press Enter.
- 2 To select a starting dimension, press Enter.
- 3 Select the next extension line origin, and then press Enter.

Or press Enter, and then select an existing dimension for the baseline. Select the origin of the next extension line, and then press Enter.

The program automatically places the new baseline dimension above or below the previous dimension line. The distance between the two dimension lines is determined by the Baseline Offset value in the Dimension Settings dialog box.




To add a baseline dimension to an existing linear dimension, select the existing dimension (**A**), select the next extension line origin (**B**), and select as many additional points as you want (**C**).




Result.


To create a linear continued dimension

NOTE Before you can use this procedure, you must first create a dimension.

- 1 Do one of the following:
 - Choose Insert > Dimensions > Continue.
 - On the Dimensioning toolbar, click the Continue tool ()
 - Type *dimcontinue* and then press Enter.
- 2 To select a starting dimension, press Enter.
- 3 Select the next extension line origin, and then press Enter.
Or press Enter, and then select an existing dimension to continue.
- 4 To add continued dimensions, continue selecting extension line origins.
- 5 To end the command, press Enter twice.



To add a continued dimension to an existing linear dimension, select the existing dimension (**A**), select the next extension line origin (**B**), and select another extension line origin (**C**).





Result.

Creating angular dimensions

Angular dimensions annotate the angle measured between two lines. You can also dimension an angle by selecting an angle vertex and two endpoints. After you create an angular dimension, you can add a baseline dimension or a continued dimension. An angular baseline dimension inserts an additional dimension from a common first extension line origin of a previous angular dimension. An angular continued dimension continues an angular dimension from the second extension line of a previous angular dimension.

To dimension an angle encompassed by an arc


- 1 Do one of the following:
 - Choose Insert > Dimensions > Angular.
 - On the Dimensioning toolbar, click the Angular tool () .
 - Type *dimangular* and then press Enter.
- 2 Select the arc.
- 3 Specify the dimension arc location.



To dimension the angle subtended by an arc, select the arc (**A**), and then specify the dimension arc location (**B**).

Result.

To dimension an angle between two lines

- 1 Do one of the following:
 - Choose Insert > Dimensions > Angular.
 - On the Dimensioning toolbar, click the Angular tool () .
 - Type *dimangular* and then press Enter.
- 2 Select one line.
- 3 Select the other line.
- 4 Specify the dimension line location.




Select one line (A), select the other line (B), and then specify the dimension line location (C).


Result.

Creating diametral and radial dimensions

Diameter and radius dimensions annotate the radii and diameters of arcs and circles. You can optionally include centerlines or center marks.

To create a diametral dimension


- 1 Do one of the following:
 - Choose Insert > Dimensions > Diameter.
 - On the Dimensioning toolbar, click the Diameter tool () .
 - Type *dimdiameter* and then press Enter.
- 2 Select the arc or circle.
- 3 Specify the dimension line location.




Select the circle (A), and then specify the dimension line location (B).

Result.

To create a radial dimension

- 1 Do one of the following:
 - Choose Insert > Dimensions > Radius.
 - On the Dimensioning toolbar, click the Radius tool ().
 - Type *dimradius* and then press Enter.
- 2 Select the arc or circle.
- 3 Specify the dimension line location.




Select the circle (A), and then specify the dimension line location (B).

Result.

Creating ordinate dimensions


An ordinate dimension annotates the perpendicular distance from an origin or base point (the origin of the current user coordinate system [UCS]). Ordinate dimensions consist of an x- or y-coordinate and a leader. An x-ordinate dimension measures distances along the x-axis; a y-ordinate dimension measures distances along the y-axis.


As you select ordinate points, the program automatically determines whether the point is an x- or y-ordinate based on which direction you drag the second point. You can also specify whether the ordinate represents an x- or y-ordinate. Ordinate dimension text is always aligned with the ordinate leader lines, regardless of the text orientation specified by the current dimension style.



Ordinate dimensions measure the distance along the x- or y-axis from an origin to a selected ordinate point.

To create an ordinate dimension

- 1 Do one of the following:
 - Choose Insert > Dimensions > Ordinate.
 - On the Dimensioning toolbar, click the Ordinate tool ()
 - Type *dimordinate* and then press Enter.
- 2 Select the point for ordinate dimension.
- 3 Specify the ordinate leader endpoint.




Select the ordinate point (A), and then specify the ordinate leader endpoint (B).


TIP To select precise ordinate points, use entity snaps.

Creating leaders and annotations

Leaders consist of a line or series of lines that connects a feature in a drawing to an annotation. Generally, you place an arrowhead at the first point. An annotation, created as dimension text, is placed immediately adjacent to the last point. By default, the text placed at the end of the leader line consists of the most recent dimension. You can also type an annotation as a single line of text.

To create a leader and an annotation

- 1 Do one of the following:
 - Choose Insert > Dimensions > Leader.
 - On the Dimensioning toolbar, click the Leader tool ()
 - Type *dimleader* and then press Enter.
- 2 Specify the starting point of the leader.
- 3 Specify the endpoint of the leader line segment.
- 4 Specify additional leader line segment endpoints.
- 5 After you specify the last endpoint, press Enter.
- 6 Type the annotation, or press Enter to accept the most recent dimension as the default annotation.



Specify the starting point of the leader (A) and the endpoint of the leader line segment (B).

Result.

Dimensioning model space entities in paper space

To increase efficiency, you can separate your drawing model from annotations using the Model and Layout tabs.

It takes time to display dimensions, title blocks, keynotes, and other annotations. If you draw these on a Layout tab, display-time and visual clutter are reduced when you work on your model (on the Model tab). IntelliCAD allows you to dimension model space entities on either the Model tab or a Layout tab — you can make the choice depending on the method that works best for your needs.

To dimension model space entities in paper space

- 1 Click a Layout tab.
- 2 Create at least one layout viewport. For details, see “Creating layout viewports” on page 368.
- 3 Lock the desired layout viewport by doing the following:
 - Right-click the edge of the layout viewport that you want to use for creating dimensions.
 - Choose Properties.
 - Mark Lock Viewport, and then click OK.

Locking the viewport is not required, but it is extremely helpful when you zoom or pan in the layout viewport; it prevents the viewport scale and view center from changing.

TIP *You may want to place the layout viewports on their own layer and after locking the layout viewports, hide the layer that contains them. This allows you to work within the layout viewport without it cluttering your display or selections.*

- 4 Make sure you are working in paper space by verifying that the Model/Paper Space toggle in the status bar begins with “P.” If necessary, switch to paper space by double-clicking the Model/Paper Space toggle in the status bar.
- 5 Create a dimension. You can select the model space entities directly, specify definition points, or use entities snaps to help accurately select the definition points.

The dimension is created in paper space.

For more details about using paper space and model space, see “Understanding paper space and model space” on page 362.


Editing dimensions

You can use grips to edit entity dimensions. You can also edit the dimension text. You can rotate dimension lines and dimension text at any angle, and you can reposition the dimension text anywhere along the dimension line.

Making dimensions oblique

Extension lines are normally created at a perpendicular angle to the dimension line. You can change the angle of the extension lines, however, so that they tilt relative to the dimension line.

To make oblique extension lines

- Do one of the following:
 - Choose Insert > Dimensions > Make Oblique.
 - On the Dimensioning toolbar, click the Make Oblique tool () .
 - Type *dimedit*, press Enter, and then in the prompt box, choose Oblique Lines.
- Select the linear dimension, and then press Enter.
- Type the obliquing angle, and then press Enter.



Select the dimension to be made oblique (**A**), and then type the obliquing angle.

Result.

TIP To align the oblique angle if you don't know the exact measurement, use snaps to pick two points on the entity.


Editing dimension text

You can rotate the text of an existing dimension, move the dimension text to a new position, or replace selected dimension text with new text. You can also restore dimension text to its original position as defined by the current dimension style.

When you rotate or replace selected text, you specify the change first, and then select one or more dimensions to which to apply the change. All the selected dimensions are updated simultaneously.

To rotate dimension text

Advanced experience level

- 1 Do one of the following:
 - Choose Insert > Dimensions > Rotate Dimension Text.
 - On the Dimensioning toolbar, click the Rotate Dimension Text tool ()
 - Type *dimedit*, press Enter, and then in the prompt box, choose Rotate Text.
- 2 Type the new dimension text angle, and then press Enter.
- 3 Select the dimension to be rotated, and then press Enter.




Select the dimension to be rotated (**A**), and then type the rotation angle.

Result.


NOTE *The dimension text angle is relative to the dimension line. If the dimension text rotation is set to zero, the text angle is defined by the dimension type and the dimension style.*

To move dimension text

Advanced experience level

- 1 Do one of the following:
 - Choose Insert > Dimensions > Reposition Dimension Text.
 - On the Dimensioning toolbar, click the Reposition Dimension Text tool ()
 - Type *dimtedit* and then press Enter.
- 2 Select the dimension to reposition text.

- 3 Select the new text position.




Select the dimension to be moved (A), and then select the new text position (B).

Result.


To restore dimension text to its home position

Advanced experience level

- 1 Do one of the following:
 - Choose Insert > Dimensions > Restore Text Position.
 - On the Dimensioning toolbar, click the Restore Text Position tool (.
 - Type *dimedit*, press Enter, and then in the prompt box, choose Restore Text.
- 2 Select the dimension text to restore, and then press Enter.

To replace existing dimension text with new text

Advanced experience level

- 1 Do one of the following:
 - Choose Insert > Dimensions > Edit Dimension Text.
 - On the Dimensioning toolbar, click the Edit Dimension Text tool (.
 - Type *dimedit* and then in the prompt box, choose Edit Text.
- 2 Type the new dimension text, and then press Enter.
- 3 Select the dimension to be replaced, and then press Enter.


Understanding dimension styles and variables

Dimensions that you insert are created using the current dimension style. You can create, save, restore, and delete named dimension styles.

To display information about the current dimension style and compare it with other style names, you can use the `dimstyle` command.

Dimension styles provide a way for you to change various settings that control the appearance of dimensions. You can then save those settings for reuse. If you don't define a dimension style before creating dimensions, the program uses the Standard dimension style, which stores the default dimension variable settings. Each option in the Dimension Settings dialog box relates to a variable that you can set manually. See the online Command Reference for more information.


To create a dimension style

- 1 Do one of the following:
 - Choose Settings > Dimension Settings.
 - On the Settings toolbar, click the Dimension Settings tool () .
 - Type `setdim` and then press Enter.
- 2 In the Dimension Settings dialog box, click New.
- 3 Type the name of the new dimension style.
- 4 Click Create.
- 5 In the Dimension Settings dialog box, click one of the other tabs, and then change the dimension settings as necessary.
Repeat this step for each tab, as needed.
- 6 To end the command, click OK.


To select a dimension style

- 1 Do one of the following:
 - Choose Settings > Dimension Settings, select a dimension style from the list, and then click OK.
 - On the Dimensioning toolbar, select a dimension style from the list.
 - Type `setdim`, press Enter, select a dimension style from the list, and then click OK.

To rename a dimension style

- 1 Do one of the following:
 - Choose Settings > Dimension Settings.
 - On the Settings toolbar, click the Dimension Settings tool ().
 - Type *setdim* and then press Enter.
- 2 In the Dimension Settings dialog box, click Rename.
- 3 In the Rename list, click the dimension style to be renamed.
- 4 In the To box, type the new dimension style name.
- 5 Click Rename.
- 6 Click OK.

To delete a named dimension style

- 1 Do one of the following:
 - Choose Settings > Dimension Settings.
 - On the Settings toolbar, click the Dimension Settings tool ().
 - Type *setdim* and then press Enter.
- 2 In the Dimension Settings dialog box, click Delete.
- 3 Select the dimension style to delete.
- 4 Click Delete.
- 5 Click OK.

To display information about the current style

- 1 Type *dimstyle* and then press Enter.
- 2 Type *v* and then press Enter to display information about the variables.
- 3 Type the dimension style name, and press Enter.


Controlling dimension arrows

You can control the appearance and size of arrowheads or tick marks placed at the ends of dimension lines. Any changes you make affect the current dimension style. The arrowheads you choose display in the image tile on the right side of the Dimension Settings dialog box.


You can choose from a number of arrowhead types. You can specify different arrowheads for each end of a dimension line and for leader lines. The Starting arrow corresponds to the first extension line; the Ending arrow corresponds to the second extension line. Blocks defined in the drawing also display in the three Arrowhead lists as user-defined arrows. You can use these blocks to create and assign your own arrowheads.

The Arrow Size value determines the size of the arrowhead, measured in drawing units. You can also use tick marks instead of arrowheads.

To choose an arrowhead

- 1 Do one of the following:
 - Choose Settings > Dimension Settings.
 - On the Settings toolbar, click the Dimension Settings tool ()
 - Type *setdim* and then press Enter.
- 2 Click the Arrows tab.
- 3 In the Starting Arrowhead or Ending Arrowhead list, click to select the Starting or Ending arrowhead, respectively.
- 4 In the Leader Arrowhead list, click to select a leader arrowhead for leader lines.
- 5 Click OK.

NOTE You can also specify leader arrow types using the *DIMLDRBLK* system variable.




- | | |
|---|--|
| <p>A Type or select arrowhead size.</p> <p>B Click to select a starting arrowhead, or click the arrowhead picture to scroll the list automatically.</p> <p>C Click to select an ending arrowhead, or click the arrowhead picture to scroll the list automatically.</p> | <p>D Click to select a leader arrowhead, or click the arrowhead picture to scroll the list automatically.</p> <p>E Select to enable tick marks instead of arrowheads.</p> <p>F Type or select tick mark size.</p> |
|---|--|

Controlling dimension format

You can control the way dimension text and arrowheads are placed in relation to the dimension lines. Any changes you make affect the current dimension style. The image tile on the right side of the Dimension Settings dialog box shows the appearance of dimensions based on the current dimension style settings.

The program determines whether both dimension text and arrowheads will fit between the extension lines by comparing the distance between the extension lines to the size of the dimension text, the size of the arrowheads, and the amount of space required around dimension text. The program applies the best fit method based on the available space. If possible, both the dimension text and arrowheads are placed between the extension lines. If both will not fit between the extension lines, you can determine how text and arrowheads are placed using the Fit Method settings on the Dimension Settings dialog box.




Text and arrowheads placed outside extension lines.


Text placed between extension lines and arrowheads outside extension lines.

Text placed above dimension line with a leader connecting the text to the dimension line.

To format dimensions

- 1 Do one of the following:
 - Choose Settings > Dimension Settings.
 - On the Settings toolbar, click the Dimension Settings tool ()
 - Type *setdim* and then press Enter.
- 2 Click the Format tab.
- 3 Click the Fit option that you want.
- 4 Specify the Distance option that you want.
- 5 Click OK.


NOTE You can also specify how dimension text and arrows are arranged using the *DIMATFIT* system variable. You can specify how dimension text is moved using the *DIMTMOVE* system variable.



- A** Click to place both text and arrowheads inside the extension lines when both do not automatically fit between them.
- B** Click to place text only between extension lines and arrowheads outside extension lines when both do not fit between them.
- C** Click to fit either text or arrowheads between extension lines when both do not fit between them.
- D** Click to automatically determine the best fit method.
- E** Click to place text beside the dimension line with a leader when both text and arrowheads do not fit between the extension lines.
- F** Click to place text above the dimension line with a leader connecting the text to the dimension line when both text and arrowheads do not fit between the extension lines.
- G** Click to place text above the dimension line without a leader when both text and arrowheads do not fit between the extension lines.
- H** Type or select the distance around the dimension text.

Controlling line settings

You can control settings affecting dimension lines, extension lines, and center marks. Any changes you make affect the current dimension style. The image tile on the right side of the Dimension Settings dialog box shows the appearance of the dimensions based on the current dimension style settings.





A Extend past dimension.

C Offset from origin.

B Baseline offset.

To set the color for dimension lines


- 1 Do one of the following:
 - Choose Settings > Dimension Settings.
 - On the Settings toolbar, click the Dimension Settings tool () .
 - Type *setdim* and then press Enter.
- 2 Click the Lines tab.
- 3 Make your selections.
- 4 Click OK.



- A Type or select center mark size. Positive values create a center mark. Negative values create centerlines.
- B Type or select the baseline offset distance (the distance to offset successive dimension lines when creating baseline dimensions) and the offset from origin (the distance extension lines are offset from their origin points).
- C In Dimensions, type or select the distance that extension lines extend beyond dimension lines. In Obliques, type or select the distance that dimension lines extend beyond extension lines.
- D Select the dimension lineweight and the dimension line color.
- E Select the extension lineweight and the extension line color.
- F Select to prevent the creation of the first and second dimension lines.
- G Select to prevent the creation of the first and second extension lines.
- H Select to prevent the creation of dimension lines outside extension lines.
- I Select to draw dimension lines between extension lines when text and arrows are placed outside extension lines.

Controlling dimension text


You can control the settings affecting the appearance of dimension text. Any changes you make affect the current dimension style. The image tile on the right side of the Dimension Settings dialog box shows the appearance of the dimensions based on the current dimension style settings.




Text between extension lines aligned horizontally.

Text between extension lines aligned with dimension line.

To align dimension text with the dimension line


- 1 Do one of the following:
 - Choose Settings > Dimension Settings.
 - On the Settings toolbar, click the Dimension Settings tool ().
 - Type *setdim* and then press Enter.
- 2 Click the Text tab.
- 3 Make your selections.
- 4 Click OK.



- A** Click to select the text style used for dimension text.
- B** Type or select the text height, measured in drawing units.
- C** Type a prefix or suffix to be appended to dimension text.
- D** Click to display the IntelliCAD Explorer, Text Styles element.
- E** Click to select the dimension text color.
- F** Select to align text placed between the extension lines with the dimension line.
- G** Select to align text placed outside the extension lines with the dimension line.
- H** Select to force text between the extension lines.
- I** Type or select the vertical text offset distance.
- J** Click to select the horizontal or vertical justification of dimension text.
- K** Formats integers in superscript after the specified number of decimal places.

Controlling dimension units

You can determine the appearance and format of the primary and alternate dimension units. The image tile on the right side of the Dimension Settings dialog box shows the appearance of the dimensions based on the current dimension style settings.




Round off distance set to .0100
(original dimension before
rounding).


Round off distance set to 0.2500.

Round off distance set
to 1.0000.

To round off dimensions

- 1 Do one of the following:
 - Choose Settings > Dimension Settings.
 - On the Settings toolbar, click the Dimension Settings tool ().
 - Type *setdim* and then press Enter.
- 2 Click the Units tab.
- 3 In the Round Linear Distances field, type or select the nearest value to which you want to round off dimensions.
- 4 Click OK.

NOTE You can also specify units for linear dimensions using the *DIMLUNIT* system variable. You can specify fraction formats using the *DIMFRAC* system variable.

















- A Select the linear dimension format.
- B Type or select the number of decimal places you want displayed in linear dimension text.
- C Enter the marker symbol used for decimals.
- D Type or select the nearest value to which you want to round off linear distances.
- E Select to prevent the inclusion of leading zeros or the inclusion of feet in dimension text when the dimension is less than one foot.
- F Select to prevent the inclusion of trailing zeros or the inclusion of inches in dimension text when the number of inches is zero.
- G Select the angular dimension format.
- H Type or select the number of decimal places you want displayed for angular dimension text. Select whether to suppress leading or trailing zeros.
- I Type or select the scale factor applied to all dimensions.
- J Type or select the linear scale factor applied to all lengths measured by dimensioning commands.

Adding geometric tolerances

Geometric tolerances indicate the maximum allowable variations in the geometry defined by a drawing. IntelliCAD draws geometric tolerances using a feature control frame, which is a rectangle divided into compartments.

Each feature control frame consists of at least two compartments. The first compartment contains a geometric tolerance symbol that indicates the geometric characteristic to which the tolerance is applied, such as location, orientation, or form. For example, a form tolerance may indicate the flatness or roundness of a surface. The geometric tolerance symbols and their characteristics are shown in the following table.

Geometric tolerance symbols


Symbol	Characteristic	Type
	Position	Location
	Concentricity or coaxiality	Location
	Symmetry	Location
	Parallelism	Orientation
	Perpendicularity	Orientation
	Angularity	Orientation
	Cylindricity	Form
	Flatness	Form
	Circularity or roundness	Form
	Straightness	Form
	Profile of a surface	Profile
	Profile of a line	Profile
	Circular runout	Runout
	Total runout	Runout

The second compartment contains the tolerance value. When appropriate, the tolerance value is preceded by a diameter symbol and followed by a material condition symbol. The material conditions apply to features that can vary in size. The material condition symbols and their meanings are shown in the following table.

Material conditions

Symbol	Definition
Ⓜ	At maximum material condition (MMC), a feature contains the maximum amount of material stated in the limits.
Ⓛ	At least material condition (LMC), a feature contains the minimum amount of material stated in the limits.
Ⓢ	Regardless of feature size (RFS) indicates that the feature can be any size within the stated limits.

The tolerance value can then be followed by primary, secondary, and tertiary datum reference letters, along with the material conditions of each datum. Datum reference letters are generally used as reference tolerances to one of up to three perpendicular planes from which a measurement is made, although datum reference letters can also indicate an exact point or axis.



A Geometric characteristic symbol.

B Diameter symbol.


C Tolerance value.


D Material condition symbol.

E Datum reference.

When two tolerances apply to the same geometry, you can also add a composite tolerance consisting of a primary tolerance value followed by a secondary tolerance value. To make a tolerance even more specific, it can also contain a projected tolerance consisting of a height value followed by a projected tolerance symbol. For example, you can use a projected tolerance to indicate the perpendicularity of an embedded part.

To add a geometric tolerance


- 1 Do one of the following:
 - Choose Insert > Dimensions > Tolerance.
 - On the Dimensions toolbar, click the Tolerance tool (.
 - Type *tolerance* and then press Enter.
- 2 To display the geometric tolerance symbols, on the first line, click the Sym box.
- 3 Click to select a geometric tolerance symbol.
- 4 Under Tolerance 1, click the Dia box to add a diameter symbol.
- 5 In the field, type the first tolerance value.
- 6 To display the material condition symbols, click the M.C. box.
- 7 Click to select a material condition.
- 8 Under Tolerance 2, repeat steps 4 through 7 to add a secondary tolerance value, if appropriate.
- 9 Under Datum 1, type the primary datum reference letter.
- 10 To display the material condition symbols, click the M.C. box.
- 11 Click to select a material condition.
- 12 Repeat steps 9 through 11 to add secondary and tertiary datum, if appropriate.
- 13 In the second row, repeat steps 2 through 12 to add composite tolerances, if appropriate.
- 14 In the Height box, type a projected tolerance zone height value, if appropriate.
- 15 To insert a projected tolerance zone symbol, click the Projected Tolerance Zone box, if appropriate.
- 16 Click OK.
- 17 In the drawing, specify the location of the feature frame.



- A Use this row to include composite tolerances.
- B Type a projected tolerance height value.
- C Type a datum identifier.
- D Click to include a projected tolerance symbol.
- E Click to select the material condition symbol for tertiary data.
- F Type the tertiary datum reference letter.
- G Click to select the material condition symbol for secondary datum.
- H Type the secondary datum reference letter.
- I Click to select the material condition symbol for primary datum.
- J Type the primary datum reference letter.
- K Click to select the material condition symbol for the second tolerance value.
- L Type the second tolerance value.
- M Click to include a diameter symbol for the second tolerance value.
- N Click to select the material condition symbol for the first tolerance value.
- O Type the first tolerance value.
- P Click to include a diameter symbol for the first tolerance value.
- Q Click to select a geometric tolerance symbol.

Controlling dimension tolerance


You can create dimensions as either tolerance or limits dimensions. When creating a tolerance dimension, you can control the upper and lower tolerance limits as well as the number of decimal places of the dimension text. The image tile on the right side of the Dimension Settings dialog box shows the appearance of tolerance and limits dimensions based on the current dimension style settings.




Tolerance dimension.

Limits dimension.

To create a tolerance dimension


- 1 Do one of the following:
 - Choose Settings > Dimension Settings.
 - On the Settings toolbar, click the Dimension Settings tool ().
 - Type *setdim* and then press Enter.
- 2 Click the Tolerance tab.
- 3 Select the Append Dimension Tolerances check box.
- 4 Type or select the lower tolerance limit.
- 5 Type or select the upper tolerance limit.
- 6 Click OK.
- 7 Insert the dimension.



- A Select to insert dimensions as upper and lower tolerance limits.
- B Select to include plus and minus tolerance values with the dimension text.
- C Type or select the minimum tolerance or lower limit value.
- D Type or select the maximum tolerance or upper limit value.
- E Type or select the number of decimal places displayed in limits or tolerance dimensions.
- F Select to prevent the inclusion of leading zeros or the inclusion of feet in dimension limits when the dimension is less than one foot.
- G Select to prevent the inclusion of trailing zeros or the inclusion of inches in dimension limits when the number of inches is zero.


Controlling alternate dimension units


You can include alternate dimensions in addition to the primary dimension text. You can also determine the appearance and format of the alternate dimensions, including the scale factor applied to generate alternate dimensions. The image tile on the right side of the Dimension Settings dialog box shows the appearance of the dimensions based on the current dimension style settings.



Alternate dimension created using a scale factor of 25.4, with an appended suffix.

To create an alternate dimension

- 1 Do one of the following:
 - Choose Settings > Dimension Settings.
 - On the Settings toolbar, click the Dimension Settings tool ()
 - Type *setdim* and then press Enter.
- 2 Click the Alternate Units tab.
- 3 Select the Enable Alternate Units check box.
- 4 Type or select the scale factor.
- 5 In the Suffix field, type a suffix to be appended to the alternate dimension.
- 6 Click OK.
- 7 Insert the dimension.



- A** Select to include alternate dimensions.
- B** Select to prevent the inclusion of leading zeros or the inclusion of feet in alternate dimensions when the dimension is less than one foot.
- C** Select to prevent the inclusion of trailing zeros or the inclusion of inches in alternate dimensions when the number of inches is zero.
- D** Type or select the number of decimal places displayed in alternate dimensions.
- E** Type or select any rounding for alternate dimensions.
- F** Type or select the scale factor applied to measured dimensions to generate the alternate dimensions.
- G** Click to select the format for alternate dimensions.
- H** Type a prefix or suffix to be appended to alternate dimensions.
- I** Type or select the number of decimal places displayed in limits or tolerances included as part of alternate dimensions.
- J** Select to prevent the inclusion of leading zeros or the inclusion of feet in limits or tolerances included as part of alternate dimensions.
- K** Select to prevent the inclusion of trailing zeros or the inclusion of inches in limits or tolerances included as part of alternate dimensions.

Working with blocks, attributes, and external references

Blocks, attributes, and external references provide mechanisms for managing entities in your drawings and for including additional information with the standard drawing entities. With blocks, you can combine numerous entities into a single entity, and then reuse it, inserting multiple copies. With attributes, you can associate text, such as part numbers or prices, with blocks, and then extract the text-attribute information to a separate file, such as a database, for further analysis. With external references, you can link separate reference drawing files to a drawing to combine information without adding the contents of the reference drawings to the current drawing. If you make changes to the referenced file, all references are updated automatically.

This section explains how to:

- Create, insert, and redefine blocks.
- Create, edit, and insert attributes.
- Extract attribute data to a separate file.
- Attach and work with external references.

Topics in this chapter

<i>Working with blocks</i>	336
<i>Working with attributes</i>	342
<i>Working with external references</i>	348

Working with blocks

Usually, blocks are several entities combined into one that you can insert into a drawing and manipulate as a single entity. A block can consist of visible entities such as lines, arcs, and circles, as well as visible or invisible data called attributes. Blocks are stored as part of the drawing file.

Blocks can help you better organize your work, quickly create and revise drawings, and reduce drawing file size. Using blocks, you can create a library of frequently used symbols. Then you can insert a symbol as a block rather than redraw the symbol from scratch.

After you create a block from multiple entities, you save it once, which also saves disk space. You insert only multiple references to a single block definition. You can change the block definition to quickly revise a drawing, and then update all instances of the block.

If you insert a block that contains entities originally drawn on layer 0 and assigned color and linetype `BYLAYER`, it is placed on the current layer and assumes the color and linetype of that layer. If you insert a block that contains entities originally drawn on other layers or with explicitly specified colors or linetypes, the block retains the original settings.

If you insert a block that contains entities originally assigned color and linetype `BYBLOCK`, and the block itself has the color and linetype `BYLAYER`, those entities adopt the color and linetype of the layer onto which they are inserted. If the block is assigned an explicit color or linetype, such as red or dashed, those entities adopt those qualities.

A procedure called nesting occurs when you include other blocks in a new block that you are creating. Nesting is useful when you want to combine and include small components, such as nuts and bolts, into a larger assembly and you need to insert multiple instances of that assembly into an even larger drawing.

Creating blocks

The tools and commands for creating blocks appear on the Tools toolbar and the Tools menu, respectively, when you set the program to the Advanced experience level. You can also use the IntelliCAD Explorer to create blocks.


You can create blocks in two ways:

- By saving a block for use within the current drawing only.
- By saving the block as a separate drawing file that you can insert into other drawings.

When you create a block, you specify its name, its insertion point, and the entities that compose the block. The insertion point is the base point for the block and serves as the reference point when you later insert the block into a drawing.

To create a block for use within a current drawing

Advanced experience level

- 1 Do one of the following:
 - Choose Tools > Create Block.
 - On the Tools toolbar, click the Create Block tool ().
 - Type *block* and then press Enter.
- 2 Type a name for the block, and then press Enter.
- 3 Specify the insertion point for the block.
- 4 Select the entities that you want in the block, and then press Enter.


The block is created and exists only in the current drawing. The entities you select are removed from the display, because they are now part of the block.
- 5 To restore the original entities to the drawing while retaining the new block, type *undelete* or *oops*.

NOTE *If you frequently restore original entities after you define a block, you can customize the program to add the Undelete command to a menu or toolbar.*

You can create a block as a separate drawing file that you can insert into other drawings.

To save a block as a separate drawing file

Advanced experience level

- 1 Do one of the following:
 - Choose Tools > Save Block To Disk.
 - On the Tools toolbar, click the Save Block To Disk tool ().
 - Type *wblock* and then press Enter.
- 2 In the File Name field, type the name of the drawing file you want to create.
- 3 Click Save.
- 4 In the prompt box, choose one of the following:
 - **Multiple Blocks** This option saves one or more existing block entities to a separate drawing file. When prompted, type the name of the block(s).
 - **All Entities** This option immediately saves the entire drawing to a separate drawing file.
 - **Select Entities** This option saves those entities you select to a separate drawing file. When prompted, specify the insertion point for the block, select the entities for the block, and then press Enter.

NOTE *When saving multiple blocks or saving the entire drawing as a separate drawing file, the program assigns the 0,0,0 coordinate as the insertion base point. You can change the base point by opening the drawing and redefining the block.*


Inserting blocks

You can insert blocks and other drawings into the current drawing. When you insert a block, it is treated as a single entity. When you insert a drawing, it is added to the current drawing as a block. You can then insert multiple instances of the block without reloading the original drawing file. If you change the original drawing file, those changes have no effect on the current drawing unless you redefine the block by reinserting the changed drawing.


You can also insert blocks from another drawing into the current drawing, using the IntelliCAD Explorer. Both drawings must be open at the same time to do this. see Chapter 8, “Working with the IntelliCAD Explorer.”

When you insert a block or drawing, you must specify the insertion point, scale, and rotation angle. The block’s insertion point is the reference point specified when you created the block. When you insert a drawing as a block, the program takes the specified insertion point as the block insertion point. You can change the insertion point, however, by first opening the original drawing and redefining the block.


To insert a block

- 1 Display the Insert Block dialog box by doing one of the following:
 - Choose Insert > Block.
 - On the Draw 2D toolbar, click the Block tool ().
 - Type *ddinsert* and then press Enter.
- 2 In the Insert Block dialog box, under Insert, click Block Name.
- 3 In the Block Name box, select the name of the block you want to insert.
- 4 Click Insert.
- 5 Specify the insertion point for the block.
- 6 Specify the x, y, and z scale factors and the rotation angle, or press Enter to accept the default values.

To insert an entire drawing into the current drawing

- 1 Do one of the following:
 - Choose Insert > Block.
 - On the Draw 2D toolbar, click the Block tool ().
 - Type *ddinsert* and then press Enter.
- 2 In the Insert Block dialog box, under Insert, click From File.
- 3 Type the path and the drawing file name, or click Browse to specify the file from the Insert Drawing dialog box, and click Open.
- 4 Click Insert.
- 5 Specify the insertion point for the block.
- 6 Specify the x, y, and z scale factors and the rotation angle, or press Enter to accept the default values.

NOTE *You can specify the insertion point, scale factors, and rotation angle in the Insert Block dialog box before inserting the block. You can also control whether the block is exploded back into its original component entities after insertion. Under Positioning, clear the Position Block When Inserting check box, and specify the appropriate coordinates. If you want to explode the block immediately, select the Explode Upon Insertion check box.*




- A** Click and then enter the path and drawing file name to insert the entire drawing file as a block.
- B** Click to position the block when inserting.
- C** Specify the insertion point, scale factors, and rotation angle before you insert the block (available only when Position Block When Inserting is cleared).
- D** Click to explode the block on insertion.
- E** Specify columns, column spacing, rows, and row spacing.
- F** Click to insert the block.
- G** Click to select the block insertion point in the drawing before inserting the block (available only when the Position Block When Inserting check box is cleared).

Redefining blocks

You can redefine all instances of a block within the current drawing. To redefine a block that was created in the current drawing, you create a new block using the same name. You can update all the blocks in the current drawing by redefining the block. If the block was inserted from a separate drawing file that was subsequently updated, reinsert that block to update all other instances in the current drawing.

To redefine a block in the current drawing

Advanced experience level

- 1 Do one of the following:
 - Choose Tools > Create Block.
 - On the Tools toolbar, click the Create Block tool ()
 - Type *block* and then press Enter.
- 2 Type the name of the block you want to redefine, and then press Enter.
- 3 In the prompt box, choose Yes-Redefine Block.
- 4 Specify the insertion point for the block.
- 5 Select the entities for the block, and then press Enter.

The block is immediately redefined, and all instances of the block in the drawing are updated. The entities you select for inclusion in the block are removed from the drawing, because they are now part of the block.

TIP *To restore the original entities to the drawing while retaining the new block, type undelete or oops.*


You can update all instances of a block inserted from a separate drawing by reinserting the drawing.

Exploding blocks

You can explode an inserted block to its original component entities. When you explode a block, only that single instance of the block is affected. The original block definition remains in the drawing, and you can still insert additional copies of the original block. If you explode a block that contains attributes, the attributes are lost, but the original attribute definitions remain.

Exploding dissociates component entities to their next simplest level of complexity; blocks or polylines in a block become blocks or polylines again

To explode a block

- 1 Do one of the following:
 - Choose Modify > Explode.
 - On the Modify toolbar, click the Explode tool ()
 - Type *explode* and then press Enter.
- 2 Select the block.
- 3 Press Enter.

Working with attributes

An attribute is a particular entity that you can save as part of a block definition. Attributes consist of text-based data. You can use attributes to track such things as part numbers and prices. Attributes have either fixed or variable values. When you insert a block containing attributes, the program adds the fixed values to the drawing along with the block, and you are prompted to supply any variable values.

After you insert blocks containing attributes, you can extract the attribute information to a separate file and then use that information in a spreadsheet or database to produce a parts list or bill of materials. You can also use attribute information to track the number of times a particular block is inserted into a drawing.


Attributes can be visible or hidden. Hidden attributes are neither displayed nor printed, but the information is still stored in the drawing and written to a file when you extract it.


Defining attributes

You add an attribute to a drawing by first defining it and then saving it as part of a block definition. To define an attribute, you specify the characteristics of the attribute, including its name, prompt, and default value; the location and text formatting; and optional modes (hidden, fixed, validate, predefined, and locked).

To define an attribute

Advanced experience level

- 1 Do one of the following:
 - Choose Tools > Define Attributes.
 - On the Tools toolbar, click the Define Attributes tool ().
 - Type *ddattdef* and then press Enter.
- 2 In the Define Attribute dialog box, type the name, prompt, and default value.
- 3 Under Insert Coordinates, specify the location of the attribute, or click Select to select a point in the drawing.
- 4 Under Attribute Flags, select the optional attribute modes.
- 5 Under Text, specify the text characteristics.
- 6 To add the attribute to the drawing, do one of the following:
 - Click Define to add the attribute and keep the dialog box active so you can define another attribute.
 - Click Define And Exit to add the attribute and end the command.




- A Type the name you want to assign to the attribute.
- B Enter the identifying prompt information displayed when you insert a block containing the attribute.
- C Enter the default or constant value. For variable attributes, the default value is replaced by the actual value when you later insert a block containing the attribute.
- D Specify the x-, y-, and z-coordinates for the attribute insertion point.
- E Select to create a hidden attribute.
- F Select to create a fixed-value attribute.
- G Select to create an attribute whose value must be validated when you later insert a block containing the attribute.
- H Select to create an attribute whose value is defined and not requested when you later insert a block containing the attribute, but that you can edit after the block is inserted.
- I Select to lock the position of the attribute within the block.
- J Click to add the attribute and keep the dialog box active so you can define another attribute.
- K Click to add the attribute and end the command.
- L Specify the text rotation angle, or click to specify the rotation angle by selecting two points in the drawing.
- M Specify the text height, or click to specify the height by selecting two points in the drawing.
- N Choose the text justification.
- O Choose the text style from those styles already defined in the drawing.
- P Click to specify the attribute insertion point by selecting a point in the drawing.


Editing attribute definitions

You can edit an attribute definition before you associate it with a block and before it is saved as part of a block definition.

To edit an attribute definition

Advanced experience level

- 1 Do one of the following:
 - Choose Modify > Edit Text.
 - On the Modify toolbar, click the Edit Text tool ().
 - Type *ddedit* and then press Enter.
- 2 Select the attribute definition text to edit.
- 3 Modify the attribute name, prompt string, default value, and other attribute definition characteristics.
- 4 Click OK.



- | | |
|--|---|
| <p>A Modify the name assigned to the attribute.</p> <p>B Modify the prompt that displays when you insert the attribute into the drawing.</p> <p>C Modify the identifying prompt information displayed when you insert a block containing the attribute.</p> | <p>D Modify the attribute insertion point.</p> <p>E Modify the attribute text style and appearance.</p> <p>F Modify the attribute insertion flags to create hidden, fixed-value, locked, validated, or defined attributes.</p> |
|--|---|

Attaching attributes to blocks

You can attach attributes to a block after you define it and select it as one of the entities to include. Include the attributes when the program prompts you for the entities to include in the selection set for a block. After the attribute is incorporated into a block, the program prompts you each time you insert the block, so you can specify different values for the attributes each time you insert it into a new drawing.


Editing attributes attached to blocks

You can edit the attribute values of a block that has been inserted into a drawing.

To edit an attribute attached to a block

Advanced experience level

1 Do one of the following:

- Choose Tools > Edit Block Attributes.
- On the Tools toolbar, click the Edit Block Attributes tool ()
- Type *ddatte* and then press Enter.


2 Select the block to edit.

The Edit Block Attributes dialog box displays all the attributes attached to the block you select.

3 Edit the attribute values as necessary.

4 Click OK.

- A** Identifies the name of the block.
B Displays the names of all attributes attached to the block.
C Click to select attribute.
D Type the new value for the selected attribute.
E Click to update the attribute values and exit.
F Displays the value of each attribute attached to the block.
G Displays the prompt for each attribute attached to the block.



Extracting attribute information

You can extract attribute information from a drawing and save it to a separate text file for use with a database program. You can save the file in any of the following formats:

- **Comma Delimited Format (CDF)** Contains one line for each instance of a block, with individual attribute fields separated by commas. Character string fields are enclosed with single quotation marks. You must specify a template file when extracting to a CDF file.
- **Space Delimited Format (SDF)** Contains one line for each instance of a block. Each attribute field has a fixed length; there are no separators or character string delimiters. You must specify a template file when extracting to a SDF file.
- **Drawing Exchange Format (DXF)** Creates a subset of a standard DXF file (a *.dxx file) containing all the information about each block, including the insertion points, rotation angles, and attribute values. No template file is required.

Before extracting attributes to a CDF or SDF file, you must create a template file. The template file is an ASCII text file that specifies the attribute data fields to be written in the extract file. Each line of the template file specifies one attribute field. IntelliCAD recognizes 15 different fields, which contain elements such as the block name, the x-, y-, and z-coordinates of its insertion point, the layer on which it is inserted, and so on. You can include any of these fields. The template file must include at least one attribute name.

Each line in the template file must start with the field name. Block name and insertion-point values must begin with *BL:*. The next nonblank character must be either a *C* (indicating a character string field) or an *N* (indicating a numeric field). This character is then followed by three digits indicating the width of the field (in characters). The final three digits indicate the number of decimal places (for numeric fields). In the case of character fields, the last three digits must be zeros (000). A typical template file is similar to the one shown here:


- A Field name.
- B Block name. Block names must begin with *BL:*.
- C Insertion point. Insertion-point values must begin with *BL:*.
- D Attribute tags.
- E Number of decimal places for numeric fields or *000* for character fields.
- F Field width for character or numeric fields.
- G C for character fields; N for numeric fields.


	A		
B	BL:DESK		
	C	BL:X	C008000
		BL:Y	N007001
		TYPE	N007001
D	MANUFACTURER		C050000
	MODELNUMBER		C050000
	COST		C025000
			N005002

To create a template file

- 1 Create a template file using any ASCII text editor (such as Microsoft® Notepad or Microsoft® WordPad) or a word-processing program such as Microsoft® Word.
- 2 Include the necessary fields in the template file.
- 3 Save the template file in ASCII text format.

To extract attribute information

- 1 Do one of the following:
 - Choose Tools > Extract Attributes.
 - On the Tools toolbar, click the Extract Attributes tool ().
 - Type *dattext* and then press Enter.
- 2 Click Select, specify the entities from which to extract attributes, and then press Enter.
- 3 Specify the format of the extracted file.
- 4 For CDF and SDF formats, specify the template file.
- 5 Specify the extract output file.
- 6 Click Extract.



- | | |
|--|--|
| <p>A Click to select blocks in the drawing containing attributes you want to extract.</p> <p>B Click to specify the format of the extracted file.</p> <p>C Specify the template file for CDF and SDF extracts.</p> <p>D Specify the extract output file.</p> | <p>E Click to extract attributes.</p> <p>F Click to specify the output file using a file dialog box.</p> <p>G Click to specify the template file using a file dialog box.</p> <p>H Indicates the number of blocks with attributes selected for extraction.</p> |
|--|--|


Working with external references

You can link entire drawings to the current drawing as external references. Unlike inserting a drawing as a block, in which you add all the entities from the separate drawing into the current drawing, external references attach a pointer to the external file. The entities in the external reference appear in the current drawing, but the entities themselves are not added to the drawing. Thus, attaching an external reference does not significantly increase the size of the current drawing file.

External references provide additional capabilities not available when you insert a drawing as a block. When you insert a drawing as a block, the entities are stored in the drawing. Any changes you make to the original drawing are not reflected in the drawing in which you inserted it. When you attach an external reference, however, any changes you make to the original drawing file are reflected in the drawings that reference it. These changes appear automatically each time you open the drawing containing the external reference. If you know that the original drawing was modified, you can reload the external reference anytime you're working on the drawing.

External references are useful for assembling master drawings from component drawings. Use external references to coordinate your work with others in a group. External references help reduce drawing file size and ensure that you are always working with the most recent version of a drawing. However, if you send or receive drawings that contain external references, it is important to include with the master drawing all of the external references attached to it. When you open a drawing that contains external references, the source external reference files must be accessible for the external references to display in the drawing.

The Xref Manager helps you easily attach and work with external references.



- A Click to display a detailed list or hierarchical tree.
- B Select an external reference to modify its attachment.
- C Type or click Browse to specify the external reference location.
- D Type or click Browse to specify other search directories where external references may be located.
- E Click to open the source drawing for the external reference.
- F Click to make the external reference a permanent part of the drawing.
- G Click to remove the external reference, but keep elements and path information for easy reloading.
- H Click to update with changes from the external reference.
- I Click to completely remove the external reference.
- J Click to link a drawing.

Attaching external references

Attaching a separate drawing to the current one creates an external reference. The external reference appears in the drawing as a block definition, but the drawing entities are linked rather than added to the current drawing. If you modify the linked drawing, the current drawing that contains the external reference is updated automatically when you open it, or you can reload the external reference manually so it reflects the latest version of the external reference.


When you attach an external reference, its layers, linetypes, text styles, and other elements are not added to the current drawing. Rather, these elements are also linked from the referenced file.


There are two ways you can attach an external reference:

- An attachment is an inserted drawing that contains a link to the original file. Attachments can themselves contain other, nested reference files. When you attach an external reference, any nested references contained in the file also appear in the current drawing.
- An overlay is an inserted drawing that contains a link to the original file. Overlays allow you to lay a drawing on top of another drawing, similar to the way you work manually with transparencies. When a drawing that contains overlaid external references is itself attached or overlaid as an external reference in another drawing, the overlays do not appear as part of the external reference. Use overlaying when you want to see reference geometry in a drawing but you do not need to include that geometry in drawings that will be used by others (nested external references).

You can attach as many copies of an external reference file as you want. Each copy can have a different position, scale, and rotation angle.

To attach an external reference

- 1 Do one of the following:
 - Choose Insert > Xref Manager.
 - On the Tools toolbar, click the Xref Manager tool ()
 - Type *xrm* and then press Enter.
- 2 Click Attach.
- 3 Specify the drawing file to attach as an external reference, and then click Open.
- 4 In Reference Type, choose how you want to insert the drawing:
 - Attachment – inserts a copy of the drawing and includes any other drawings that are externally referenced within the referenced drawing.
 - Overlay – lays a copy of a drawing over your original drawing; it does not include any nested external references from the externally referenced drawing.
- 5 Make any additional selections.
- 6 Click OK.
- 7 If you marked Specify On-Screen for any items, follow the prompts to attach the external reference.






- A** Displays the external reference to attach, or select one from the list.
- B** Select to save the folder location of the referenced drawing. If not selected, the referenced drawing must be located in the same folder as the current drawing.
- C** Click Attachment to link a drawing, including any of its own external references. Click Overlay to link a drawing, omitting any of its own nested external references.
- D** Choose to specify the insertion point in the drawing, or enter x-, y-, and z-coordinates.
- E** Choose to specify the scale in the drawing, or enter x-, y-, and z-scale factors.
- F** Choose to specify the rotation angle in the drawing, or enter a rotation angle.
- G** Click to locate and select a different external reference.

Viewing the list of external references

You can view a list of the external references that are linked to the current drawing two different ways using the Xref Manager:

- **List View** displays the external references in a list, which allows you to sort the list of references by name, status, size, type, date, or saved path.
- **Tree View** displays a hierarchical representation of the external references and the relationships between them. The tree view shows the level of nesting relationships of the attached external references.


To view a list of external references

- 1 Do one of the following:
 - Choose Insert > Xref Manager.
 - On the Tools toolbar, click the Xref Manager tool (.
 - Type *xrm* and then press Enter.
- 2 Click List View () or Tree View (.

Opening external references

From the Xref Manager you can quickly open the source drawing for any external reference. This is especially helpful if you are working with nested external references, which you cannot bind or detach. From the Xref Manager, open the source drawing, make changes, and then save and close the source drawing. When the Xref Manager displays again, simply reload the external reference.

To open an external reference


- 1 Do one of the following:
 - Choose Insert > Xref Manager.
 - On the Tools toolbar, click the Xref Manager tool ()
 - Type *xrm* and then press Enter.
- 2 Select the external reference to open.
- 3 Click Open.

Removing external references


Removing external references from the current drawing is easy with the Xref Manager. You can unload an external reference, which keeps some information about the external reference in the current drawing for easy reloading later, or you can detach the external reference entirely.

When you unload an external reference, you remove it from the current drawing. However, its elements, such as layers and linetypes, remain in the drawing and it is still listed in the Xref Manager. By detaching an external reference you remove it and all of its elements from the current drawing, and it is no longer listed in the Xref Manager.

To unload an external reference

- 1 Do one of the following:
 - Choose Insert > Xref Manager.
 - On the Tools toolbar, click the Xref Manager tool ()
 - Type *xrm* and then press Enter.
- 2 Select the external reference to unload.
- 3 Click Unload.

To detach an external reference

- 1 Do one of the following:
 - Choose Insert > Xref Manager.
 - On the Tools toolbar, click the Xref Manager tool ()
 - Type *xrm* and then press Enter.
- 2 Select the external reference to detach.
- 3 Click Detach.


NOTE Only the external references that are attached directly to the current drawing can be detached; nested external references cannot be detached.

Reloading external references

When you open or print a drawing, any external references in the drawing are updated automatically. If a drawing is already open and a referenced drawing is modified, you can update the current drawing manually to display the latest version of the referenced drawing.

You may also want to reload an external reference that has been unloaded temporarily.

To reload an external reference


- 1 Do one of the following:
 - Choose Insert > Xref Manager.
 - On the Tools toolbar, click the Xref Manager tool ()
 - Type *xrm* and then press Enter.
- 2 Select the external reference to reload.
- 3 Click Reload.

Changing the path for external references

If the file associated with an external reference is moved to a different directory or renamed, the program displays a message indicating that it cannot load the external reference. You can re-establish the link to the file by doing any of the following:

- Change the path for the external reference.
- Specify additional directories for IntelliCAD to search. This is especially helpful if you have several external references that have moved to a new directory.


To change the path for a single external reference

- 1 Do one of the following:
 - Choose Insert > Xref Manager.
 - On the Tools toolbar, click the Xref Manager tool ()
 - Type *xrm* and then press Enter.
- 2 Select the external reference whose path you want to change.
- 3 In Xref Path, do one of the following:
 - Enter a new filename or location.
 - Click Browse to locate and select the referenced drawing.

IntelliCAD reloads the specified external reference automatically.

NOTE You cannot recursively reference a drawing from the same original drawing.

To change the search paths for all external references in the drawing

- 1 Do one of the following:
 - Choose Insert > Xref Manager.
 - On the Tools toolbar, click the Xref Manager tool ()
 - Type *xrm* and then press Enter.
- 2 In Additional Xref Search Paths, do one of the following:
 - Enter a new directory and its path. Separate multiple paths with a semicolon, for example, c:\My Drawings;d:\My Drawings\Backup.
 - Click Browse to locate and select a directory.

IntelliCAD searches the specified directories; any found external references are reloaded automatically.


Binding external references to drawings

External references are not part of the drawing. Rather, they are links to an externally referenced file. To provide a copy of a drawing containing external references to someone else, you must also provide all the external reference files. In addition, the person receiving the drawings must either re-create the same paths you used when linking the external references or change the paths for the external references.

To provide a copy of a drawing that contains external references, it is often easier to first bind the external references to the drawing. Binding the external references makes them a permanent part of the drawing, which is similar to inserting a separate drawing as a block.

You can bind external references that are attached directly to the current drawing; you cannot bind nested external references.

To bind an existing external reference to a drawing


- 1 Do one of the following:
 - Choose Insert > Xref Manager.
 - On the Tools toolbar, click the Xref Manager tool ().
 - Type *xrm* and then press Enter.
- 2 Select the external reference to bind.
- 3 Click Bind.
- 4 Choose one of the following:
 - **Bind** Binds the external reference and creates a unique name for each named entity, such as a layer or block, that is located in the external reference. For example, a layer named Electric in the external reference will be named Xref\$0\$Electric in the current drawing. If the current drawing already has a layer or block with the same name, the name is changed incrementally, for example, Xref\$1\$Electric.
 - **Insert** Binds the external reference, but does not change the names of any named entities in the external reference. For example, a layer named Electric in the external reference will have the same name, Electric, in the current drawing. If the current drawing has a layer or block with the same name, the named entity in the external reference takes on the properties of the named entity in the current drawing.
- 5 Click OK.

Clipping external references

When you attach a drawing as an external reference, all of the referenced drawing displays in the current drawing. However, after you attach an external reference, you can define a clipping boundary that determines which portion of the referenced drawing is visible or hidden.

You can edit, move, or copy clipped external references the same way you modify unclipped external references. The boundary moves with the reference. If an external reference contains nested clipped external references, they also appear clipped in the drawing.

TIP *In addition to clipping external references, you can also partially hide blocks using clipping boundaries.*



Example of an external reference clipped using a clipping boundary. The clipping boundary is the rectangle in the top window.

Adding a clipping boundary

When you create a clipping boundary, it affects only the display of the referenced drawing; it does not affect the original referenced drawing or any referenced geometry. The portion of the external reference within the clipping boundary is visible and the remainder of the external reference becomes hidden.

To define a rectangular clipping boundary

- 1 Do one of the following:
 - Choose Modify > Xref Clip.
 - Type *xclip* and then press Enter.
- 2 Select the external references to clip. If desired, you can also select blocks.
- 3 Press Enter.
- 4 Press Enter to create a new clipping boundary.
- 5 If prompted, press Enter to delete any existing boundaries.
- 6 Choose Rectangular.
- 7 Define the first corner of the clipping rectangle.
- 8 Define the second corner of the clipping rectangle.
The selected external references are clipped by the rectangle.

TIP You can first select all external references, right-click the selection, and then select *Xref Clip* from the shortcut menu.

To define a clipping boundary using a polyline

- 1 Draw a polyline where you want to clip external references.
- 2 Do one of the following:
 - Choose Modify > Xref Clip.
 - Type *xclip* and then press Enter.
- 3 Select the external references to clip. If desired, you can also select blocks.
- 4 Press Enter.
- 5 Press Enter to create a new clipping boundary.
- 6 If prompted, press Enter to delete any existing boundaries.
- 7 Choose Select Polyline.
- 8 Select the polyline to use as clipping boundary.

Turning clipping boundaries on and off

You can turn xref clipping on or off. When a clipping boundary is turned off, the boundary does not display and the entire external reference is visible, provided that the geometry is on a layer that is on and thawed. When a clipping boundary is turned off, it still exists and can be turned on. However, deleting a clipping boundary is permanent.

To turn clipping boundaries on and off

- 1 Do one of the following:
 - Choose Modify > Xref Clip.
 - Type *xclip* and then press Enter.
- 2 Select the desired external references.
- 3 Press Enter.
- 4 To turn off clipping boundaries, choose Off. To turn on existing clipping boundaries, choose On.
- 5 Press Enter.

If you are turning off a clipping boundary, click the clipped portion of the external reference to view the previously hidden portion of the referenced drawing.

TIP When the *XCLIPFRAME* system variable is on (set to 1), you can select and print the clipping boundary frame.

Deleting a clipping boundary

If you no longer need a clipping boundary for an external reference, you can delete it.

To delete a clipping boundary

- 1 Do one of the following:
 - Choose Modify > Xref Clip.
 - Type *xclip* and then press Enter.
- 2 Select the desired external references.
- 3 Press Enter.
- 4 Choose Delete, and then press Enter.
- 5 Click the clipped portion of the external reference.

The previously hidden portion of the referenced drawing displays.

Printing drawings

You can print a copy of your drawing exactly as you created it, or you can add formatting and specify print controls to change how your drawing looks when it is printed.

Sometimes you may require multiple printed drawings, each with a different look or layout. For example, you may need one printed drawing for a client presentation, along with several other variations for production contractors. For each type of printed drawing that you require, you can create a layout that defines its characteristics, including scale, area to print, print style tables, and more.

This section explains how to:

- Start printing right away.
- Set up a drawing to print multiple layouts from paper space on a Layout tab.
- Define how you want your drawing to look when it is printed.
- Print or plot your drawing.

Topics in this chapter


<i>Getting started printing</i>	360
<i>Defining layouts for printing</i>	361
<i>Customizing print options</i>	373
<i>Printing or plotting your drawing</i>	391

Getting started printing

When you create a drawing, you do most of your work on the Model tab. At any time you can print your drawing to see how it looks on paper. It's easy to get started printing, and then later create layouts and custom print settings to enhance your printed output.

To start printing

1 From the Model tab, do one of the following:

- Choose File > Print.
- On the Standard toolbar, click the Print tool ().

If you click the Print tool, the Print dialog box does not display. Your drawing will be sent directly to the selected printer.

- Type *print* and then press Enter.

2 Click Print.

There are many options that you can set before printing, such as the scale of the drawing, print area, print style tables, and more. For details, see “Customizing print options” on page 373 in this chapter.

NOTE Type *qprint* and then press Enter to print the current viewport. The Print dialog box is bypassed and the drawing is sent directly to the selected printer.

Defining layouts for printing

You can print your drawing directly from the Model tab where you created it, or you can create custom layouts for printing on Layout tabs.

When printing from the Model tab, you can print your drawing exactly the way it appears, or you can modify the drawing before printing by adding dimensions, a legend, or a title block.

You typically use the Layout tabs for printing if you require multiple print layouts. You may also want to use a Layout tab for printing even if you want your drawing printed only one way. For example, if you want to include large amounts of text on your printed drawing, you can add the text to a Layout tab so it does not clutter your drawing while you work on the Model tab.

Understanding layouts

When you create a drawing, you do most of your work on the Model tab. Each drawing that you create can contain numerous layouts that simulate the paper on which you will print a copy of the drawing. Each of these layouts is created on a Layout tab.

You can prepare a separate layout for each way you want to print your drawing. The layout allows you to organize different views to control which portion of your drawing prints and at what scale.

Before you print, you can also include additional entities and layout settings that control how your drawing prints. Additional items only appear on the Layout tab, not on the Model tab. For example, a layout can contain dimensions, title blocks, legends, or keynotes that print with your model, but do not clutter the screen when you work with your model on the Model tab.


Use these general steps to prepare your drawing for printing multiple layouts:

- 1 On the Model tab, create your drawing.
- 2 Create a new layout. You can use an existing Layout1 or Layout2 tab, or you can create a new Layout tab. For details about creating a new layout, see “Creating a new layout” on page 365 in this chapter.
- 3 Create at least one layout viewport on the Layout tab. Use each viewport to help control which portion of the drawing prints and at what scale. For details, see “Working with layout viewports” on page 368 in this chapter.
- 4 Include any additional items that may be required for the specific layout, such as dimensions, a legend, or a title block.
- 5 Specify additional settings for the layout, such as the scale of the drawing, print area, print style tables, and more. For details, see “Customizing print options” on page 373 in this chapter.
- 6 Print or plot your drawing. For more details, see “Printing or plotting your drawing” on page 391 in this chapter.

Understanding paper space and model space

When you start a drawing session, your initial working area is called model space. Model space is an area in which you create two-dimensional and three-dimensional entities based on either the World Coordinate System (WCS) or a user coordinate system (UCS). You view and work in model space while using the Model tab.

Your view of this area is a single viewport that fills the screen. You can create additional views on the Model tab, called viewports, which can show the same or different two-dimensional or three-dimensional views, all of which are displayed in a tiled manner. You can work in only one of these viewports at a time on the Model tab, and you can print only the current viewport.




Model space with two viewports.

IntelliCAD provides an additional work area, called paper space. The contents of paper space represent the paper layout of your drawing. In this work area, you can create and arrange different views of your model similar to the way you arrange detail drawings or orthogonal views of a model on a sheet of paper. You can also add dimensions, keynotes, annotations, borders, title blocks, and other print-related entities in paper space, which reduces clutter when you work with your model in model space.

You view and work in paper space while using a Layout tab. Each view, or layout viewport, that you create in paper space provides a window of your drawing in model space. You can create one layout viewport or several. You can place layout viewports anywhere on the screen; their edges can be touching or not; and you can print them all at the same time.

You do not need to use paper space to print your drawing, but it offers several advantages:

- Print the same drawing with different print settings that you save with each layout, for example, printer configuration files, print style tables, lineweight settings, drawing scale, and more.
- Add print-related entities that are not essential to the model itself, such as keynotes or annotations, to reduce clutter when you work with your model in model space on the Model tab.
- For a single layout, create multiple layout viewports that print the model at different views and scales.



Paper space with layout viewports.

Viewing drawings in paper space and model space

When you work in paper space on a Layout tab, you can still view your drawing in model space. First you need to create a layout viewport in paper space; this allows you to view your model space entities from paper space.

Within a layout viewport you can modify and snap to model space entities while working in model space and even snap to model space entities from paper space. Snapping to model space entities from paper space allows you to accurately dimension model space entities in paper space. And although it is generally more convenient to modify entities on the Model tab, there are often times when it is convenient to make modifications from a layout viewport on a Layout tab.

Zooming or panning the drawing in model space or paper space affects the entire drawing, unless you use multiple windows or viewports. Additionally, if you are working from paper space, you can lock the layout viewport so the viewport scale and view center do not change while panning and zooming in the layout viewport.

To view a drawing in model space on the Model tab

Do one of the following:

- Click the Model tab.
- Right-click the Model/Paper Space toggle in the status bar, and then choose Model.

To view a drawing in paper space on a Layout tab

Do one of the following:

- Click one of the Layout tabs.
- Type *layout* and then press Enter. In the prompt box, choose Set. Type a name for the layout you want to make current, and then press Enter.
- Double-click the Model/Paper Space toggle in the status bar. For example, double-click “Model” or “M:Tab Name” in the status bar to switch to paper space.
- While using a Layout tab, type *pspace* and then press Enter.
- While using a Layout tab, double-click outside of the layout viewport.

The first time you switch to a Layout tab, your drawing seems to disappear. This is normal. You must create at least one layout viewport to see your model. For details, see “Working with layout viewports” on page 368 in this chapter.

To view a drawing in model space on a Layout tab

Do one of the following:

- Click the desired Layout tab, and then create and view a layout viewport. For more details, see “Working with layout viewports” on page 368 in this chapter.
- Double-click the Model/Paper Space toggle in the status bar. For example, double-click “P:Tab Name” in the status bar to switch to model space on the current Layout tab.
- Type *mspace* and then press Enter.
- While using a Layout tab, double-click inside of the layout viewport.

Displaying the Model and Layout tabs

The Model and Layout tabs can be hidden, if desired. You may want to hide the tabs if you only work on the Model tab or if you use the command bar and status bar to switch between tabs.

To turn the Model and Layout tabs display on or off

Do one of the following:

- Choose View > Model and Layout tabs.
- Choose Tools > Options > Display tab, and choose Show Tabs.

Creating a new layout

In IntelliCAD, you can create multiple layouts for a single drawing. Each layout represents a sheet of paper. For each layout you can specify the print area, print styles, print scale, lineweight scale, pen mappings, and add viewports, dimensions, a title block, and other geometry specific to the layout. The entities you add to a layout in paper space do not appear in model space.

Each layout requires at least one layout viewport. This viewport displays the drawing’s model space entities.


When you create a new drawing, the drawing automatically contains two default layouts: Layout1 and Layout2. You can start by using one of the default layouts, you can create your own, or you can create a new layout from another template (.dwt) file, drawing (.dwg) file, or drawing interchange (.dxf) file.

Each drawing can contain up to 255 layouts.


To create a new layout using the Layout1 or Layout2 tab

- 1 Click the Layout1 or Layout2 tab.
- 2 Set up at least one layout viewport. For details, see “Working with layout viewports” on page 368 in this chapter.
- 3 If desired, rename the layout. For details, see “To rename a layout” on page 367 in this chapter.

To create a new layout using a new Layout tab

- 1 Do one of the following:
 - Choose Insert > Layout > New Layout.
 - On the Layouts toolbar, click the New Layout tool ().
 - Type *layout*, press Enter, and choose New.
- 2 Type a unique name for your layout and then press Enter.
The name can be up to 255 characters in length and can contain letters, numbers, the dollar sign (\$), hyphen (-), and underscore (_), or any combination.
- 3 Set up at least one layout viewport. For details, see “Working with layout viewports” on page 368 in this chapter.

To create a new layout from an existing file

- 1 Do one of the following:
 - Choose Insert > Layout > Layout from Template.
 - On the Layouts toolbar, click the Layout from Template tool ().
 - Type *layout*, press Enter, and choose Template.
- 2 Select the desired template, drawing, or drawing interchange file that contains the layout you want, and then click Open.
- 3 Select the layout(s), and then click OK. You can choose multiple layouts by holding down Ctrl while selecting layout names.

Reusing layouts from other files

Save time by re-using layouts that you have already created. Within the same drawing, you may want to make a copy of a layout that contains most of the settings you want, and then make changes to the new copy. If you created layouts that you want to use again when you create new drawings, you can save the layouts as a drawing template.

To make a copy of a layout

- 1 Type *layout* and then press Enter.
- 2 In the prompt box, choose Copy.
- 3 Type the name of the layout you want to copy, and then press Enter.
- 4 Type a name for the new layout, and then press Enter.

To save a layout as a drawing template

- 1 Type *layout* and then press Enter.
- 2 In the prompt box, choose Save.
- 3 Type the name of the layout that you want to save, and then press Enter.
- 4 Specify the file name and location for the template, and then click Save.

After you save a layout as a template, you can use the template when you create new drawings. You can also import the template's layouts into another drawing.

Managing layouts in a drawing

You can rename layouts, delete layouts, and view a list of all layouts available in a drawing. You can also change the order in which the Layout tabs appear; the Model tab is always stationary.

If you want to rename, delete, or reorder a layout when the Layout tabs are hidden, you can type *layout* to make your changes or choose View > Model and Layout Tabs to display the tabs.

To rename a layout

- 1 Right-click the Layout tab to rename.
- 2 Type a new name for the layout.
- 3 Click OK.

The name can be up to 255 characters in length and can contain letters, numbers, the dollar sign (\$), hyphen (-), and underscore (_), or any combination.

To delete a layout

- 1 Right-click the Layout tab to delete.
- 2 Click OK to confirm the deletion.

NOTE You cannot delete the Model tab or the last remaining Layout tab. To delete all geometry from the Model tab or a Layout tab, first select all geometry and then use the Erase command.

To reorder the Layout tabs

- 1 Right-click the Layout tab you want to move.
- 2 Do one of the following:
 - Choose Move Right, and then choose a new location.
 - Choose Move Left, and then choose a new location.

To view a list of all layouts

- 1 Type *layout* and then press Enter.
- 2 In the prompt box, choose ? to list all layouts.
- 3 Type *s* or press Enter to scroll through the layouts.

Working with layout viewports

When you begin working in a drawing on the Model tab, it consists of a single view of your model. You may have created additional views by dividing the drawing space into multiple windows; each window is a separate viewport on the Model tab.

On a Layout tab, you must create at least one layout viewport to see your model. However, you can create multiple layout viewports that display unique views of your model located in model space. Each layout viewport functions as a window into your model space drawing — with each window looking different from the next. You can customize the view center, scale, layer visibility, and contents of each layout viewport. Each layout viewport is created as a separate entity that you can move, copy, or delete.

Click any layout viewport to make it the current viewport, and then add or modify model space entities in that viewport, even while snapping to model space entities from paper space. Any changes you make in one layout viewport are immediately visible in the other viewports (if the other layout viewports are displaying that portion of the drawing). Zooming or panning in the current viewport affects only that viewport.


This section focusses on working with layout viewports in paper space on a Layout tab. For additional information about viewports in model space, see “Dividing the current window into multiple views” on page 147.

Creating layout viewports


The first time you switch to a Layout tab, all of your model space entities disappear. You must create at least one layout viewport on the Layout tab to see your work.

You can create layout viewports anywhere inside the drawing area. You can control the number of viewports created and the arrangement of the viewports.

To create layout viewports

- 1 Do one of the following:
 - Choose View > Layout Viewports.
 - On the Views toolbar, click the Layout Viewports tool ().
 - Type *mview* and then press Enter.
- 2 In the prompt box, choose Fit To View, Create 2 Viewports, Create 3 Viewports, or Create 4 Viewports, or specify two opposing corners to create a custom viewport.
- 3 In the prompt box, choose the viewport orientation.
- 4 Do one of the following:
 - To arrange the viewports to fill the current graphic area, in the prompt box, choose Fit To Screen.
 - To fit the viewports within a bounding rectangle, specify the corners of a rectangle.

TIP When you create a layout viewport, the layout viewport border is created on the current layer. You can make layout viewport borders invisible by creating a new layer before you create layout viewports and then turning off that layer after you create the layout viewports. To select a layout viewport's borders, you must turn that layer back on before you can rearrange or modify the layout viewport.




You can create a single layout viewport, or you can divide the graphic area into two viewports arranged vertically (**A**) or horizontally (**B**); three viewports arranged left (**C**), right (**D**), above (**E**), below (**F**), vertically (**G**), or horizontally (**H**); or four viewports (**I**).

Viewing and scaling layout viewports


If you have created numerous layout viewports, your system performance may be affected. If necessary, you can turn a layout viewport on or off. Turning off a layout viewport does not delete the viewport or its contents; it simply turns off its display.

You can also change how you view items within a layout viewport by specifying a scale factor, which changes how large or small model space entities appear within the layout viewport.

To turn layout viewports on or off

- 1 Click the desired Layout tab.
- 2 Do one of the following:
 - Choose View > Layout Viewports.
 - On the View toolbar, click the Layout Viewports tool ().
 - Type *mview* and then press Enter.
- 3 Choose On or Off.
- 4 Select the edge of the layout viewport to turn on or off, and then press Enter.

To change the layout viewport scale

- 1 Do one of the following:
 - Choose Modify > Properties.
 - On the Modify toolbar, click the Properties tool ().
 - Type *entprop* and then press Enter.
- 2 Select the edge of the layout viewport.
- 3 In Scale, enter the scale at which you want to view model space entities from within the layout viewport.
- 4 Click OK.

To change the scale of model space entities relative to paper space

- 1 Click the Model tab.
- 2 Click a viewport to make it current.
- 3 Choose View > Zoom > Zoom.
- 4 Type the zoom scale factor relative to paper space by appending the suffix *xp* to the scale factor, and then press Enter.

For example, to increase the scale of the entities in the viewport on the Model tab to twice the size of paper space units, type *2xp*. To decrease the scale to half the size of paper space units, type *.5xp*.

Modifying layout viewports


After you create layout viewports, you can modify them as needed. On the Layout tab, you can snap to the viewport borders using entity snaps. You can copy, delete, move, scale, and stretch layout viewports as you would any other drawing entity.

Additionally, you can lock a layout viewport so the viewport scale and view center do not change in model space while panning or zooming in the layout viewport. If you are working on model space entities from a Layout tab, locking the layout viewport prevents you from constantly changing the layout viewport scale and view center.


And assigning a UCS to each viewport allows you to quickly switch between layout viewports and immediately draw in a different UCS. This can greatly increase productivity, especially when creating complex 3D models.

Modifying a layout viewport on a Layout tab does not affect the model space entities within the layout viewport.

To modify layout viewport properties

- 1 Click the desired Layout tab.
- 2 Do one of the following:
 - Choose Modify > Properties.
 - On the Modify toolbar, click the Properties tool ().
 - Type *entprop* and then press Enter.
- 3 Select the edge of the layout viewport you want to modify.
- 4 Adjust the center point, width, or height of the viewport.
- 5 In Scale, enter the scale at which you want to view model space entities from within the layout viewport.
- 6 Mark Lock Viewport to lock the viewport scale and view in model space while panning or zooming in the layout viewport.
- 7 Mark UCS per Viewport if you want to use a unique UCS for each layout viewport.
- 8 Click OK.

NOTE *You can select only layout viewports for modification. If you click a viewport on the Model tab, it makes that viewport active, not available for modification.*



- A** Enter the center point of the layout viewport.
- B** Enter the width of the layout viewport.
- C** Enter the height of the layout viewport.
- D** Enter the scale used for viewing model space entities from within the layout viewport.
- E** Mark to use a unique UCS for each layout viewport.
- F** Mark to lock the viewport scale and view in model space while panning or zooming in the layout viewport.
- G** Click to select the center of the layout viewport in the drawing.

Customizing print options

Before you print, you can set up many aspects of printing:

- Specify paper size and orientation.
- Select and configure a printer or plotting device.
- Specify the view and scale of a printed drawing, including which portion of a drawing to print, the print scale, and the origin of the print area.
- Choose whether to print and scale lineweights.
- Choose whether to implement print style tables to control colors, pen widths, line-types, and lineweights.
- Open printer configuration (PCP) files; create and save PCP files.

Setting the paper size and orientation

You can specify a paper size and paper orientation for all drawings.

To select the paper size and orientation

- 1 Do one of the following:
 - Choose File > Print Setup.
 - Type *psetup* and then press Enter.
 - Type *print* and press Enter, and then click Print Setup.
- 2 Select the paper size and paper orientation, and then click OK.

You can also adjust the orientation by printing a drawing upside down on the paper. Each layout in your drawing can specify whether to print upside down.

To print a drawing upside down

- 1 If necessary, click the desired Layout tab or the Model tab.
- 2 Do one of the following:
 - Choose File > Print.
 - Type *print* and then press Enter.
- 3 Click the Advanced tab.
- 4 Select Print Upside Down.
- 5 Select Save Changes to Layout, and then click Apply to save your changes.

Selecting a printer or plotter

You can specify a printer or plotter to be used when printing any drawing. You can print your drawing on any printer or plotter that is compatible with Windows, including raster printers.

To select a printer or plotter

- 1 Do one of the following:
 - Choose File > Print Setup.
 - Type *psetup* and then press Enter.
 - Type *print* and press Enter, and then click Print Setup.
- 2 From the Printer Name list, select a printer or plotter, and then click OK.

Setting the scale and view

You can print or plot the entire drawing or a selected portion, depending on which options you select in the Print dialog box. You can choose to print what is visible on the screen, or you can specify to print an area of the drawing.

You can control the position of the drawing on the paper by specifying the origin of the print area, the location of the lower left corner of the print area, in relation to the lower left corner of the paper. The origin is normally set to 0,0, which places the lower left corner of the print area as close to the lower left corner of the paper as the printer or plotter will allow. You can specify a different origin, however, by specifying different coordinates.

When you create a drawing, you generally draw entities full-size. When you print the drawing, you can specify the scale of the resulting print or let the program adjust the size of the drawing to fit the paper. To print the drawing at a specific scale, specify the scale as a ratio of drawing units to printed units.

If you are printing from a Layout tab, the scale and view options you specify can be different for each layout that you create.

To automatically scale the drawing for printing

- 1 If necessary, click the desired Layout tab or the Model tab.
- 2 Do one of the following:
 - Choose File > Print.
 - Type *print* and then press Enter.
- 3 Click the Scale/View tab.
- 4 To scale the drawing to fit on one printed page, in Print Scale, select Scale to Fit.
- 5 Select Save Changes to Layout, and then click Apply to save your changes.

To specify the scale factor yourself

- 1 If necessary, click the desired Layout tab or the Model tab.
- 2 Do one of the following:
 - Choose File > Print.
 - Type *print* and then press Enter.
- 3 Click the Scale/View tab.
- 4 In Print Scale, do one of the following:
 - Select a pre-defined scale. For example, choose 1:2 if you want 1 printed unit (inch or millimeter) to equal 2 drawing units.
 - Select Custom, and then under User Defined Scale, type the ratio of printed units of measure (inches or millimeters) to drawing units.
- 5 To specify the printed units of measure, click Inches or Millimeters.
- 6 Select Save Changes to Layout, and then click Apply to save your changes.

To specify a portion of the drawing to print


- 1 If necessary, click the desired Layout tab or the Model tab.
- 2 Do one of the following:
 - Choose File > Print.
 - Type *print* and then press Enter.
- 3 Click the Scale/View tab.
- 4 Under Print Area, click one of the following:
 - Current View – prints the view on the screen.
 - Saved View – prints the selected saved view.
 - Extents – prints the area that contains entities in the drawing.
 - Limits – prints to the limits defined for the layout or drawing.
 - Window – prints the portion of the drawing contained in the specified window, maintaining the aspect ratio of the windowed area to the drawing.

If you clicked Window, you must specify the window. Under Windowed Print Area, enter the diagonal x- and y-coordinates of the window, or select the area on the screen.

To print only the area in the window without considering whether there is extra space on the screen, select the Print Only Area Within Specified Window check box.

- 5 Under Entities To Print, click one of the following:
 - All Entities Within Print Area – prints all drawing entities contained within the specified print area.
 - Selected Entities Within Print Area – prints only the entities you select from within the specified print area.

- 6 Select Save Changes to Layout, and then click Apply to save your changes.



- A** Displays either "Model" or the layout name to which the print settings apply.
- B** Click to select the area of the drawing that you want to print.
- C** Type the x- and y-coordinates of the two opposing corners of the rectangular area to print; or, to specify coordinates in the drawing window, click Select Print Area.
- D** Select to print the area of the window while ignoring the aspect ratio to the remainder of the drawing.
- E** Click to specify drawing units and paper size in millimeters or inches.
- F** Specify the custom scale for the print area by typing the ratio of drawing units to printed inches or printed millimeters. (Available only if Custom is selected for Print Scale.)
- G** Select to fit the specified print area to the current paper size, select a scale ratio, or select to specify your own custom scale in User Defined Scale.
- H** Click to print only selected entities within the specified print area.
- I** Click to print all entities within the specified print area.
- J** Select to save the print settings for the model or layout.
- K** Select to print using the current print settings or using the settings from the last time you printed.

NOTE IntelliCAD saves your print settings each time you print. To restore the IntelliCAD default print settings, click Reset in the Print dialog box.

To specify the print area origin

- 1 If necessary, click the desired Layout tab or the Model tab.
- 2 Do one of the following:
 - Choose File > Print.
 - Type *print* and then press Enter.
- 3 Click the Advanced tab.
- 4 Under Origin of Print Area, do one of the following:
 - To center the specified print area on the printed page, select the Center on Page check box.
 - To specify an origin for the print area, type the x- and y-coordinates, or click Select Origin and then specify a point on the drawing.
- 5 Select Save Changes to Layout, and then click Apply to save your changes.

Choosing how lineweights print


If entities are assigned lineweights, you can control whether they print with the assigned lineweights. If you turn off lineweight printing, entities print with a default outline. You can also control whether lineweights print in proportion to the scale you set on the Scale/View tab.

Each layout in your drawing can specify whether to print and scale lineweights.

To set lineweight options

- 1 If necessary, click the desired Layout tab or the Model tab.
- 2 Do one of the following:
 - Choose File > Print.
 - Type *print* and press Enter.
- 3 Click the Advanced tab.
- 4 Choose how you want to print lineweights:
 - Print Lineweights – prints entities with their assigned lineweights. If not selected, entities print with a default outline.
 - Scale Lineweights – prints lineweights in proportion to the scale you set on the Scale/View tab. If not selected, lineweights print at their assigned size without adjustments for the print scale. (A Layout tab must be active to scale lineweights.)
- 5 Select Save Changes to Layout, and then click Apply to save your changes.

NOTE *Print styles can also affect how lineweights print. For details, see the next section.*



- A** Displays either "Model" or the layout name to which the print settings apply.
- B** Select a print style table.
- C** Click to load print settings from a PCP file.
- D** Click to save the current configuration as a PCP file.
- E** Select to print the drawing upside down on your printer.
- F** Select to print entities with their assigned lineweights.
- G** Select to print lineweights in proportion to the scale you set on the Scale/View tab. (A Layout tab must be active.)
- H** Click to specify the print area origin by selecting a point within the drawing.
- I** Type x- and y-coordinates to specify the origin of the print area.
- J** Select to center the print area on the page.
- K** Click to make changes to the selected print style table.
- L** Click to create a new print style table.
- M** Select to save the print settings for the model or layout.
- N** Select to load print settings from the current layout (or model) or the last time you printed.

NOTE *IntelliCAD saves your print settings each time you print. To restore the IntelliCAD default print settings, click Reset in the Print dialog box.*

Using print styles

IntelliCAD uses print styles to change the appearance of your printed drawing without modifying the actual entities in your drawing. Assigning print styles allows you to customize the color, pen width, linetype, and lineweight that are used to print your drawing.

Print styles help you control what your drawing looks like when it is printed. Rather than describe what an entity looks like on your screen, print styles describe what an entity will look like when you print it. For example, you can map all yellow entities in your drawing to print in blue without modifying the actual entities. You could also map all yellow entities to print with whatever lineweight, linetype, or pen width that you specify.

Because print styles are saved in print style tables, which are files located on your computer, disk, or server, you can reuse them to help eliminate the need to reconfigure your print settings each time you print a drawing. For example, you may have multiple clients who have their own printing preferences. You can save print styles in a named file for each of your clients. You can even share the file with co-workers, or store the files on a network to ensure that everyone in your office uses the same standards.

Understanding print style tables

A print style table is a collection of print styles that allows you to change the appearance of your printed drawing without modifying the actual entities in your drawing. Each print style table is saved in a file that can be located on your computer, disk, or server.

A drawing can use one type of print style table at a time. There are two types of print style tables:

- **Color-dependent print style tables (CTB)** contain a collection of print styles based on each of the 255 index colors available in a drawing. True colors and color books are not applicable to color-dependent print style tables.
- **Named print style tables (STB)** contain a collection of print styles that you define. They can vary regardless of color.

With color-dependent print style tables, you cannot assign print styles to individual entities or layers. To use these print styles, you assign a specific color to an entity or layer. When you specify a color-dependent print style table at printing time, the entity colors and layer colors map to color-based print styles in the print style table that you specify.

With named print style tables, you can assign named print styles to individual entities and layers. Entities and layers assigned print styles are printed according to the print style table that you specify at printing time. If you specify a print style for a specific entity, that print style overrides any print style assigned to the layer on which the entity resides.

Sometimes a named print style assigned to an entity or layer is not located in the print style table that is assigned to a layout or drawing. This can happen if the print style has been deleted from the named print style table or if you assign a different named print style table to the drawing that does not contain the named print style. In this case, the entity is printed using its default properties, which is similar to assigning the Normal print style to an entity or layer. If you plan on interchanging named print style tables within the same drawing, it's a good idea to coordinate the tables to use the same print style names.

If a new drawing is based on a template, the new drawing uses the same type of print style table as the template. If a new drawing is created without a template, the type of print style table is specified in the New Drawing Wizard; by default, the new drawing uses the print style table type specified in Tools > Options on the Printing tab. Every drawing is designed to use print style tables, but you decide whether to implement them.

Comparison of print style table types

	Color-dependent print style table (CTB)	Named print style table (STB)
Description	Contains pre-defined print styles according to color; there is one print style for each of the 255 index colors available in the drawing. Entities with the same color are printed the same way.	Contains unique print styles that you create. Entities with the same color can have different print settings.
Example	All blue entities print with a .5 millimeter lineweight.	One entity prints with a .7 millimeter lineweight; a second blue prints with a .5 millimeter lineweight.
Number of print styles	255 (fixed).	At least one (varies).
Print style names	Print style names range from "Color_1" to "Color_255". You cannot rename print styles.	You define new print style names. You can rename all print styles except the Normal print style.
Add, delete, and modify print styles	You can modify the existing print styles, but you cannot add or delete print styles.	You can add and delete print styles. You can modify all print styles except the Normal print style, which uses the default characteristics of the entity.

Comparison of print style table types

	Color-dependent print style table (CTB)	Named print style table (STB)
Create additional tables	Yes.	Yes.
Assignment	Current print style: New entities always assigned BYCOLOR. Print styles: Assigned to colors in the print style table. Print style tables: Assigned to a Layout tab or the Model tab.	Current print style: Assigned to new entities. Print styles: Assigned to entities and layers. Print style tables: Assigned to a Layout tab or the Model tab.
Legacy file support	You can import existing printer configuration files (PCP) files into the print style table. CTB files are similar to PCP files primarily used in previous versions of IntelliCAD.	Not applicable.

Implementing print style tables

Every drawing is designed to use print style tables, but you decide whether to implement them. Even if you use one of the default print style tables available with IntelliCAD, using print style tables requires planning ahead of time to ensure that your drawing prints as planned.

For example, a single drawing of a floor plan might require the printing of the following drawing sheets:

- **Main Floor Plan** Walls print with thick, black lines.
- **Electrical Plan** Walls print with normal gray lines, indicating that they are not the focus.
- **HVAC Plan** Walls print with normal gray lines, indicating that they are not the focus.
- **Roof Plan** Walls print with thin, gray lines and a hidden linetype, indicating that they are hidden under the roof in a plan view.

In this example, you can create four named print style tables, each containing a print style named “WallPstyle”. Each print style table contains its own settings for “WallPstyle” to control how the walls print. Assign WallPstyle to either the wall entities or to a wall layer. Then, assign a different named print style table each time you print, or create four layouts and assign a different print style table to each layout.

The following table describes, in order, the steps to get you started using both color-dependent and named print style tables.

Getting started using print style tables

Color-dependent	Named	Task	Command	Where to get details
X	X	Create a new drawing. Select a drawing template that uses the desired print style table type or choose it in the New Drawing Wizard.	File > New	Creating a new drawing, page 40
X	X	(Optional) Create a new print style table.	File > Print Styles Manager	Creating new print style tables, page 384
X		Assign colors to entities and layers that correspond with print style table settings.	Modify > Properties Tools > IntelliCAD Explorer	Setting the current entity color, page 45; Modifying the properties of entities, page 240; Setting the layer color, page 185
	X	Set the current print style assigned to new entities.	Settings > Drawing Settings > Entity Creation tab; status bar; <i>printstyle</i>	Setting the current print style, page 49
	X	Assign print styles to entities.	Modify > Properties; Entity Properties toolbar; <i>printstyle</i>	Modifying the properties of entities, page 240
	X	Use IntelliCAD Explorer to assign print styles to layers.	Tools > IntelliCAD Explorer	Setting a layer's print style, page 189
X	X	Assign a print style table to the Model tab, a layout, or to all layouts in the drawing.	File > Print > Advanced tab	Assigning print style tables, page 383
X	X	(Optional) Make changes to the assigned print style table.	File > Print Styles Manager File > Print > Advanced tab	Modifying print style tables, page 385
X	X	Print the drawing.	File > Print	Printing or plotting your drawing, page 391

The following table describes how to further customize how print styles work within your drawings.

Further customizing print style tables

Task	Command	Where to get details
Copy, rename, or delete print style tables.	File > Print Styles Manager	Copy, rename, or delete print style tables, page 387
Change a drawing to use another type of print style table, for example, change a drawing that uses color-dependent print style tables to one that uses named print style tables.	<i>convertpstyles</i>	Changing a drawing's print style table type, page 387
Convert a color-dependent print style table to a named print style table.	<i>convertctb</i>	Converting print style tables, page 388
Change the default location where print style tables are stored.	Tools > Options > Paths/Files tab	Changing the options on the Paths/Files tab, page 478
Customize how print styles work with new drawings that you create and older drawings that you open.	Tools > Options > Printing tab	Changing the options on the Printing tab, page 488

Assigning print style tables

Select a print style table before printing if you want to change how your drawing appears when you print it. Print style tables can modify how colors, pen widths, line-types, and lineweights look when they are printed.

You can assign print style tables globally for all layouts (including the Model tab), or individually for the Model tab or a Layout tab. Assigning a print style table to an individual layout allows you to further customize the layouts you use to print a drawing.

However, assigning different named print style tables to various layouts may result in mismatched print style names; a named print style assigned to an entity or layer may not be located in the assigned print style table at print time. In this case, entities are printed using their default properties, which is similar to assigning the Normal print style to an entity or layer.

To assign print style tables

- 1 If necessary, click the desired Layout tab, or click the Model tab.
- 2 Do one of the following:
 - Choose File > Print.
 - Type *print* and then press Enter.
- 3 Click the Advanced tab.
- 4 Under Print Style Table (Pen Assignments), select a print style table that you created or one of the following:
 - **None** — Applies no print style table. Entities print according to their own properties.
 - **Icad** — Uses the default print style table and its color assignments.
 - **Monochrome** — Prints all colors as black.
- 5 At the prompt, choose Yes to assign the print style table to all layouts in the drawing, including the Model tab, or choose No to assign the print style table only to the individual layout listed in Layout Name on the Print dialog box.
- 6 Select Save Changes to Layout, and then click Apply to save your changes.

NOTE *When your drawing was first created it was set up to use either color-dependent or named print style tables. For details on converting a drawing to use a different type of print style table, see “Understanding print style tables” on page 379 in this chapter.*

Creating new print style tables

IntelliCAD offers several print style tables to help you get started. If you want to customize your print output further, you can create your own print style table. You can create a new print style table entirely from scratch, based on IntelliCAD registry settings, or by importing a printer configuration file (PCP file).

To create new print style tables

- 1 Do one of the following:
 - Choose File > Print Styles Manager.
 - Type *stylesmanager* and then press Enter.
- 2 Double-click Create a Print Style Table.
- 3 Complete the setup wizard.

On the last wizard page, you can click Print Style Table Editor to set up the print styles for the table. For more details about the Print Style Table Editor options, see the next section.

Modifying print style tables

When your drawing was created, it was set up to use color-dependent or named print style tables.

Color-dependent print style tables (.ctb files) You can modify individual print styles within the table, but you cannot add, rename, or delete print styles. Color-dependent print style tables always have 255 print styles, each named for a specific color. Your changes affect all entities and layers assigned that color.

Named print style tables (.stb files) You can add, modify, rename, and delete individual print styles within the table. However, you cannot modify, rename, or delete the Normal print style. Your changes affect all entities and layers that are assigned that print style name.

TIP *If you can't remember what type of print style table is assigned to your drawing, use the `PSTYLEMODE` system variable to determine the print style table type.*

Each print style within a print style table specifies a color, pen numbers, linetype, and lineweight. IntelliCAD recognizes additional characteristics for compatibility with AutoCAD only, including: dither, grayscale, screening, adaptive, line end style, line join style, and fill style.


When specifying print style characteristics, be sure to consider the limitations of your output device.

NOTE *It is recommended that you only modify print style tables that you have created. If you modify a default print style table that came with IntelliCAD, you overwrite the original information which is then lost.*

To modify print style tables

- 1 Do one of the following:
 - Choose File > Print Styles Manager.
 - Type `stylesmanager` and then press Enter.
- 2 Double-click the print style table you want to modify.
- 3 Click the General tab, and then do any of the following:
 - Enter a new table description.
 - Select Apply Global Scale Factor to Non-ISO Linetypes to apply the scale factor to non-ISO linetypes used for any print style in the current print style table. This also applies to fill patterns, which are not used in IntelliCAD, but are recognized for compatibility with AutoCAD.
 - Enter a scale factor to apply to non-ISO linetypes used for any print style in the current print style table.

- 4 Click the Properties tab, and then do any of the following:
 - Make format changes to a print style by selecting it in the Print Styles list, then make color, pen map, linetype, or lineweight changes for the print style. Your changes are saved automatically for the selected print style.
 - Add a new print style by clicking Add Style. Enter a new name, and then click OK. Select the options for the print style. (Available for named print styles only.)
 - Rename a print style by selecting it in the Print Styles list. Single-click the print style again, and then enter a new name. (Available for named print styles only.)
 - Delete a print style by selecting it in the Print Styles list. Click Delete Style. (Available for named print styles only.)
- 5 Click OK.



- | | |
|--|--|
| <p>A Select a print style to modify it.</p> <p>B Enter a description for the selected print style.</p> <p>C Click to create a new print style. (Named print style tables only.)</p> <p>D Click to delete the selected print style. (Named print style tables only.)</p> <p>E Click to modify the list of available lineweights for the current print style table.</p> <p>F Click to save the print style table with a new name or in a new location.</p> | <p>G Choose a lineweight for the selected print style.</p> <p>H Choose a linetype for the selected print style.</p> <p>I Type or scroll to the width of the virtual pen for the selected print style (for printers that don't have physical pens, such as laser or inkjet printers).</p> <p>J Type or scroll to the width of the physical pen for the selected print style.</p> <p>K Choose a color for the selected print style.</p> |
|--|--|

Copy, rename, or delete print style tables

Copy, rename, or delete a print style table just as you would any other file on your computer. Regardless of which print style table type your drawing uses, you can use the Print Style Manager to manage both color-dependent and named print style tables.

To copy, rename, or delete print style tables

- 1 Do one of the following:
 - Choose File > Print Styles Manager.
 - Type *stylesmanager* and then press Enter.
- 2 Select a print style table.
Color-dependent print style tables are .ctb files and named print style tables are .stb files.
- 3 Copy, rename, or delete the print style table just as you would any other file on your computer.

Changing a drawing's print style table type

When your drawing was created, it was set up to use color-dependent print style tables (.ctb files) or named print style tables (.stb files). A drawing can use one type of print style table at a time. If necessary, after a drawing is created you can convert the drawing to use the other type of print style table.

If you can't remember what type of print style table is assigned to your drawing, use the PSTYLEMODE system variable to determine the print style table type.

To change a drawing to use named print style tables

- 1 If you want to reuse any of the existing print style information, convert your color-dependent print style tables to named print style tables. For details, see “To convert a color-dependent print style table to a named print style table” on page 388 in this chapter.
- 2 Open the drawing that uses color-dependent print style tables (.ctb files).
- 3 Type *convertstyles*, and then press Enter.
- 4 If you have already converted your individual color-dependent print style tables to named tables, click OK in the prompt that displays.
If you have not converted the tables, click Cancel. First use *convertctb* to convert your color-dependent print style tables to named tables. If you do not, all of the print style information you specified in your drawing will be lost.
- 5 Select a named print style table (.stb file) that you want to use with the drawing.
- 6 Click Open.

NOTE *If you have not converted a color-dependent print style table to a named print style table, you will be warned that the table you have selected does not contain color mapping and the drawing cannot be converted.*

To change a drawing to use color-dependent print style tables

- 1 Open the drawing that uses named print style tables (.stb files).
- 2 Type *convertpstyles*, and then press Enter.
- 3 If you are sure you want to convert the drawing and lose all print style assignments, click OK in the prompt that displays.

If you do not want to lose the print style assignments, click Cancel.

NOTE *Converting a drawing to use color-dependent print style tables will remove all of the named print style information from entities and layers. However, the named print style tables are not deleted from your computer.*

Converting print style tables

You can convert a color-dependent print style table to a named print style table. You cannot convert a named print style table to a color-dependent print style table because color-dependent tables contain only print styles that are named after the 255 colors to which they map.

Converting a color-dependent print style table to a named print style table can be helpful in the following situations:

- You don't want to create a named print style table from scratch.
- You want to create a named print style table that has the same settings as a color-dependent print style table, but with some new print styles or other custom settings.
- You want to convert a drawing to use named print style tables and you want to reuse most of print styles already defined in a color-dependent print style table.

To convert a color-dependent print style table to a named print style table

- 1 Type *convertctb*, and then press Enter.
- 2 Select the color-dependent print style table (.ctb file) that you want to convert.
- 3 Click Open.
- 4 Enter a name for the new named print style table (.stb file).
- 5 Click Save.

The print styles in the new table are named Style 1, Style 2, and so on. If you want to use different print style names, rename the print styles before you assign them to entities and layers in your drawing. If you rename the print styles after assigning them, they will not match when you print your drawing. For information about renaming print styles, see “Modifying print style tables” on page 385 in this chapter.

Turning off print style tables

When you turn off print style tables, entities print according to their own properties. However, all of the print style information is saved so you can easily turn on print styles again. Actual print style table files are not deleted, and for drawings that use named print style tables, entities and layers retain their assigned print styles.

To turn off print style tables

- 1 If necessary, click the desired Layout tab, or click the Model tab.
- 2 Do one of the following:
 - Choose File > Print.
 - Type *print* and then press Enter.
- 3 Click the Advanced tab.
- 4 Under Print Style Table (Pen Assignments), select None.
- 5 At the prompt, choose Yes to turn off print style tables for all layouts in the drawing, including the Model tab, or choose No to turn off print style tables only for the individual layout listed in Layout Name on the Print dialog box.
- 6 Select Save Changes to Layout, and then click Apply to save your changes.

Reusing print settings

After you set up print settings for a drawing or layout, you can save them and reuse them again using printer configuration files.

Printer configuration files store the printer information you create for specific drawings or layouts, which eliminates the need to completely reconfigure your print settings each time you print a drawing. Printer configuration files also allow you to share and reuse print settings between different drawings and layouts.

IntelliCAD supports the printer configuration (PCP) file format used by AutoCAD. This feature makes it possible to use existing PCP files saved in AutoCAD, as well as to save your IntelliCAD print configuration settings to a PCP format.

TIP *You can convert an AutoCAD PC2 file to PCP format using the Device And Default selection feature in the AutoCAD Print dialog box.*

The printer configuration files that you specify can be different for each layout that you create.

To save print settings in a PCP file

- 1 If necessary, click the desired Layout tab or the Model tab.
- 2 Do one of the following:
 - Choose File > Print.
 - Type *print* and then press Enter.
- 3 Click the Advanced tab.
- 4 Specify the desired print settings.
- 5 Under Printer Configuration File, click Save.
- 6 Name the file, and then click Save.

To assign a PCP file

- 1 If necessary, click the desired Layout tab or the Model tab.
- 2 Do one of the following:
 - Choose File > Print.
 - Type *print* and then press Enter.
- 3 Click the Advanced tab.
- 4 Under Printer Configuration File, click Open.
- 5 Locate and select the PCP file, and then click Open.
- 6 Select Save Changes to Layout, and then click Apply to save your changes.

PCP files created before IntelliCAD 6 contain obsolete PenMap/Width settings that you can convert to use with print style tables. Import the PCP file to create a new color-dependent print style table. For details, see “Creating new print style tables” on page 384 in this chapter.

TIP *It is easy to reuse print settings from the last time you printed. In the Print dialog box under Use Settings, choose Previous Print.*

Printing or plotting your drawing


After you have configured your drawing and any layouts for printing, you are ready to print. If desired, you can preview your page before printing.


Previewing a drawing before printing

Viewing a drawing before printing gives you a preview of what your drawing will look like when it is printed. This helps you see if there are any changes you want to make before actually printing the drawing.

If you are using print style tables, the preview shows how your drawing will print with the assigned print styles. For example, the preview may display different colors or lineweights than those used in the drawing because of assigned print styles.

To preview a drawing before printing

- 1 If necessary, click the desired Layout tab or the Model tab.
- 2 Do one of the following:
 - Choose File > Print Preview.
 - On the Standard toolbar, click the Print Preview tool ()
 - Type *ppreview* and then press Enter.
- 3 After checking the preview image, do one of the following:
 - To print the drawing, click Print Settings to display the Print dialog box.
 - To return to the drawing, click Close.



- A** Click to zoom in.
- B** Click to zoom out. If you have zoomed in several times, click multiple times to restore the entire preview image.
- C** Click to display the Print Settings dialog box.
- D** Click to print the drawing.
- E** Click to close the preview and return to the drawing.

Printing a drawing


The Print dialog box is organized by tabs into two functional areas: scaling and viewing, and advanced printing options. The print setting options available under each tab were described in the previous sections.

NOTE *You cannot print a rendered image directly to a printer. To print a rendered image, you must first save the drawing to a different format and then print it from another graphics program.*

To print a drawing

1 If necessary, click the desired Layout tab or the Model tab.

2 Do one of the following:

- Choose File > Print.
- On the Standard toolbar, click the Print tool ().

If you click the Print tool, the Print dialog box does not display. Your drawing will be sent directly to the selected printer.

- Type *print* and then press Enter.

3 From the Print dialog box, make any adjustments to the settings.

4 Click Print.

NOTE *Instead of using the print settings you saved with your layout, you can select Previous Print in the Use Settings list to print according to the settings used the last time you printed. If necessary, you can click Reset to restore the IntelliCAD default print settings.*

Drawing in three dimensions

Paper drawings typically represent two-dimensional views of three-dimensional objects. With IntelliCAD, you can create three-dimensional models of three-dimensional objects.

This section explains how to:

- View entities in three dimensions.
- Create three-dimensional entities.
- Edit entities in three-dimensional space.
- Edit three-dimensional solids.
- Display hidden-line and shaded views of three-dimensional entities.

The tools and commands for many of the functions described in this section appear on the Draw 3D toolbar and the Insert menu, respectively, when you set the program to the Advanced experience level.

Topics in this chapter

<i>Viewing entities in three dimensions</i>	396
<i>Creating three-dimensional entities</i>	399
<i>Editing in three dimensions</i>	425
<i>Editing three-dimensional solids</i>	430
<i>Hiding, shading, and rendering</i>	441




Viewing entities in three dimensions

You can view an IntelliCAD drawing from any position in three-dimensional space. From any selected viewing position, you can add new entities and modify existing entities. You can also generate hidden-line and shaded views from any viewing position.

Setting the viewing direction


You view three-dimensional drawings by setting the viewing direction. The viewing direction establishes the viewing position, the Cartesian coordinate corresponding to the viewpoint looking back at the origin point, the 0,0,0 coordinate. When you view a drawing from the default viewpoint (0,0,1), you see a plan view of the drawing.


On the View toolbar, you can view a three-dimensional drawing using any of the following methods:

- Preset Viewpoints ()
- Dynamic View Control ()
- Plan View ()

You can change the viewing direction to look at the drawing from a different vantage point or to work on a three-dimensional model from a different orientation.

To set a new viewing direction

- 1 Do one of the following:
 - Choose View > Preset Viewpoints.
 - On the View toolbar, click the Preset Viewpoints tool ()
 - Type *setvpoint* and then press Enter.
- 2 Click the preset view you want to use.




A Click to select a non-axis viewpoint.


C Click to select a viewpoint aligned with an axis.

B Click to select the previous viewpoint.

You can dynamically rotate the viewpoint within the xy plane and relative to the xy plane, and you can pan and zoom the drawing. As you change the viewpoint settings, the drawing display automatically updates.

To dynamically set a view direction


- 1 Do one of the following:
 - Choose View > Dynamic View Control.
 - On the View toolbar, click the Dynamic View Control tool (.
 - Type `viewctl` and then press Enter.
- 2 Click the appropriate tools to dynamically change the viewpoint.
- 3 To complete the command, click OK.



- | | |
|---|--|
| A Indicates the current viewpoint. | F Click to zoom out. |
| B Click to pan the drawing. | G Click to zoom in. |
| C Click to display the Preset Viewpoints dialog box. | H Shows the current viewpoint orientation. |
| D Click to update the drawing display whenever you click a tool. | I Type or select the rotation angle increment. |
| E Click to zoom extents. | J Click to rotate the view about a predefined axis. |

You can set the current viewing direction to the plan view of the current user coordinate system (UCS), a previously saved UCS, or the World Coordinate System (WCS).

To display a plan view of the current drawing

- 1 Do one of the following:
 - Choose View > Plan View.
 - On the View toolbar, click the Plan View tool ().
 - Type *plan* and then press Enter.
- 2 In the prompt box, choose one of the following:
 - Current displays the plan view of the current UCS.
 - UCS displays the plan view of a saved UCS. The program prompts you for the name of the UCS.
 - World displays the plan view of the WCS.

Creating three-dimensional entities

IntelliCAD supports the following types of three-dimensional models:


- Wire-frame models, which consist of lines and curves that define the edges of a three-dimensional entity. You can create a wire-frame model by drawing lines, arcs, polylines, and other two-dimensional entities anywhere in three-dimensional space. Wire-frame models have no surfaces; they always appear as outlines. Because you must individually draw and position each entity that makes up a wire-frame model, creating one can be exacting and time-consuming.
- Surface models, which consist of both edges and the surfaces between those edges. You can create a surface model by applying elevation and thickness to two-dimensional planar entities or by using specific three-dimensional entity-creation commands. Surface models consist of individual planes forming a faceted, polygonal mesh.
- 3D solids, which are three-dimensional ACIS entities that consist of faces and edges. 3D solids appear to have volume and are easier to work with than wire-frame and surface models. IntelliCAD supports viewing and limited editing of 3D solids, including moving, rotating and scaling. Additionally, some versions of IntelliCAD allow you to create and more completely edit 3D solids.

Applying elevation and thickness

By default, the program creates new two-dimensional entities with a zero elevation and thickness. The easiest way to create a three-dimensional entity is to change the elevation or thickness property of an existing two-dimensional entity.

The elevation of an entity is its z-coordinate position in relation to the xy plane in which the entity is drawn. An elevation of 0 indicates that the entity is drawn on the xy plane of the current UCS. Positive elevations are above this plane; negative elevations are below it.

The thickness of an entity is the distance it is extruded above or below its elevation. A positive thickness extrudes the entity upward in the positive z direction of the entity; a negative thickness extrudes it downward in the negative z direction. The thickness is applied uniformly to the entire entity. You can extrude any two-dimensional entity into a three-dimensional entity by changing the thickness of the entity to a nonzero value. For example, a circle becomes a cylinder, a line becomes a three-dimensional plane, and a rectangle becomes a box.



Two-dimensional entities.

Two-dimensional entities with thickness added.


You can create three-dimensional entities using any of the following methods:

- Draw two-dimensional entities in three-dimensional space.
- Convert two-dimensional planar entities into three-dimensional entities by applying elevation and thickness.
- Convert two-dimensional planar entities into three-dimensional entities by revolving or extruding.
- Create three-dimensional entities such as boxes, cylinders, cones, domes, spheres, and wedges.


NOTE *Three-dimensional solids are drawn as true solids with versions of IntelliCAD that support three-dimensional ACIS solids. Three-dimensional solids that you can create include: box, cone, cylinder, dish, dome, pyramid, sphere, torus, and wedge.*

You can change the default elevation and thickness values to create new entities with an elevation and thickness already applied.


To set the current elevation


- 1 Display the current elevation setting by doing one of the following:
 - Choose Settings > Elevation.
 - On the Settings toolbar, click the Elevation tool ()
 - Type *elev* and then press Enter.
- 2 Specify the New Current Value For Elevation, and then press Enter.

To set the current thickness

- 1 Display the current thickness setting by doing one of the following:
 - Choose Settings > Thickness.
 - On the Settings toolbar, click the Thickness tool ()
 - Type *thickness* and then press Enter.
- 2 Specify the New Current Value For Thickness, and then press Enter.

To set the current elevation and thickness using a dialog box


- 1 Display the Drawing Settings dialog box by doing one of the following:
 - Choose Settings > Drawing Settings.
 - On the Settings toolbar, click the Drawing Settings tool ()
 - Type *settings* and then press Enter.
- 2 Click the 3D Settings tab.
- 3 In the Change Settings For list, click Surfaces.
- 4 To change the current thickness, in the Current 3D Thickness box, type a new thickness value or click the arrows to select a new thickness.
- 5 To change the current elevation, in the Current 3D Elevation box, type a new elevation value or click the arrows to select a new elevation.
- 6 Click OK.




A Type or select the current three-dimensional thickness.

B Type or select the current three-dimensional elevation.

To change the thickness and elevation of an existing entity

- 1 Do one of the following:
 - Choose Modify > Properties.
 - On the Modify toolbar, click the Properties tool ().
 - Type *entprop* and then press Enter.
- 2 Select the entity, and then press Enter.
IntelliCAD displays the Entity Properties dialog box. The exact appearance of the dialog box depends on the type of entity you select.
- 3 To change the thickness, in the Thickness box, type a new thickness value or click the arrows to select the new thickness.
- 4 To change the elevation, in the Z coordinate box, type a new elevation value or click the arrows to select the new elevation.
- 5 Click OK.

NOTE When you change the thickness of an entity, you do not change the entity type. If you want to extrude an entity and convert it to a three-dimensional solid, use the *Extrude* command.



A Type or select the new thickness.


B Type or select the new elevation.

Creating three-dimensional faces


You can create a three-dimensional face, which consists of a section of a plane in three-dimensional space. You define a three-dimensional face by specifying the x,y,z coordinates of three or more corners. After you specify the fourth point, the program continues to prompt you for additional faces by alternating prompts for the third point and fourth point to allow you to build a complex three-dimensional entity. Each three- or four-sided plane is created as a separate three-dimensional face entity.

To create a three-dimensional face

Advanced experience level

- 1 Do one of the following:
 - Choose Insert > 3D Entities > Face.
 - On the Draw 3D toolbar, click the Face tool ().
 - Type *face* and then press Enter.
- 2 Specify the first point of the three-dimensional face.
- 3 Specify the second, third, and fourth points.
- 4 Specify the third and fourth points for additional faces.
- 5 To complete the command, press Enter.

TIP Any or all edges of a three-dimensional face can be invisible to allow you to more accurately model entities with holes in them. As the program prompts you for the corner points, in the prompt box, choose *Invisible Edge* to make the next edge invisible.




An example of a three-dimensional model created using three-dimensional faces.

Creating rectangular meshes

You can create a three-dimensional rectangular mesh consisting of four-sided polygons. You determine the size of the mesh by specifying the number of vertices along the primary (M-direction) and secondary (N-direction) mesh axes and then specifying the coordinates for each vertex.


To create a rectangular mesh

Advanced experience level

- 1 Do one of the following:
 - Choose Insert > 3D Entities > Mesh.
 - On the Draw 3D toolbar, click the Mesh tool ().
 - Type *mesh* and then press Enter.
- 2 Specify the number of vertices along the primary mesh axis.
- 3 Specify the number of vertices along the secondary mesh axis.
- 4 Specify the coordinates for each vertex.

Specifying the coordinates for the last vertex completes the mesh and ends the command.

TIP Although creating rectangular meshes manually can be exacting, they are useful for representing complex surfaces such as three-dimensional terrain models. The Mesh tool is most useful when combined with scripts or LISP programs that mathematically calculate the coordinates of the vertices.




An example of a three-dimensional terrain model created using rectangular meshes.

Creating polyface meshes

You can create a polygon mesh consisting of faces connecting three or more vertices. You first determine the coordinates of each vertex and then define each face by entering the vertex numbers for all the vertices of that face. As you create each face, you can control the visibility and color of each edge and assign each edge to specific layers.

To create a polyface mesh

Advanced experience level

- 1 Do one of the following:
 - Choose Insert > 3D Entities > Polyface Mesh.
 - On the Draw 3D toolbar, click the Polyface Mesh tool () .
 - Type *pface* and then press Enter.
- 2 Specify the coordinates of each vertex.

After each vertex that you specify, the next vertex number is displayed, and you are prompted for the coordinates of the vertex. Specify the coordinates, and then press Enter. Continue to specify the coordinates for each numbered vertex.
- 3 To finish specifying vertex coordinates, press Enter.
- 4 Specify the vertex numbers that define the first face.

You specify the face by entering the vertex numbers that were defined when you specified coordinates in step 2. Each face can be composed of three or more numbered vertices.
- 5 To finish defining the first face, press Enter.
- 6 Specify the next face by entering its vertex numbers.
- 7 To complete the command, press Enter.


TIP *To make an edge invisible, type the vertex number as a negative value.*


Creating ruled surface meshes

You can create a ruled surface, which is a three-dimensional polygon mesh that approximates the surface between two existing entities. You select the two entities that define the ruled surface. These entities can be arcs, circles, lines, points, or polylines.

To create a ruled surface mesh


Advanced experience level

- 1 Do one of the following:
 - Choose Insert > 3D Entities > Ruled Surface.
 - On the Draw 3D toolbar, click the Ruled Surface tool ().
 - Type *rulesurf* and then press Enter.
- 2 Select the first defining entity.
- 3 Select the second defining entity.



Select the first (A) and second (B) defining entities.

The resulting ruled surface mesh.


TIP To control the density of the mesh, change the values for the Number of M-Direction Surfaces. Choose Settings > Drawing Settings, and then click the 3D Settings tab. Under Change Settings For, select Surfaces. Under Surface Settings, change the Number Of M-Direction Surfaces value. Or, on the Settings toolbar, use the Drawing Settings tool () to display that dialog box.


Creating extruded surface meshes

You can create an extruded surface, which is a three-dimensional polygon mesh that approximates the surface generated by extruding a path curve along a direction vector. You select the two entities that define the path curve and direction vector. The length of the direction vector determines the distance the path curve is moved along the direction vector. The extruded entity can be an arc, circle, line, or polyline. You can choose a line or open polyline as the direction vector. The resulting mesh consists of a series of parallel polygonal planes running along the specified path.

To create an extruded surface mesh


Advanced experience level

- 1 Do one of the following:
 - Choose Insert > 3D Entities > Extruded Surface.
 - On the Draw 3D toolbar, click the Extruded Surface tool () .
 - Type *tabsurf* and then press Enter.
- 2 Select the entity to extrude.
- 3 Select the extrusion path.



Select the entity to extrude (A) and the extrusion path (B).

The resulting extruded surface mesh.

TIP To control the density of the mesh, change the values for the Number of M-Direction Surfaces. Choose Settings > Drawing Settings, and then click the 3D Settings tab. Under Change Settings For, select Surfaces. Under Surface Settings, change the Number Of M-Direction Surfaces. Or, on the Settings toolbar, use the Drawing Settings tool () to display that dialog box.

NOTE An extruded mesh is different from an extruded solid. If you want to extrude an entity and convert it to a three-dimensional solid, use the Extrude command.


Creating revolved surface meshes


You can create a surface of revolution, which is a three-dimensional polygon mesh that approximates the surface generated by rotating a two-dimensional profile around an axis. You select the two entities that define the profile and the axis. You also specify the starting angle and the number of degrees to revolve the profile.

Revolving the profile 360 degrees creates a closed three-dimensional mesh. The Number Of M-Direction Surfaces value determines the mesh density (the number of mesh segments) in the M-direction (around the axis of revolution). The N-Direction Mesh Density value determines the mesh density (the number of mesh segments) in the N-direction (along the axis of revolution).

To create a revolved surface mesh


Advanced experience level

- 1 Do one of the following:
 - Choose Insert > 3D Entities > Revolved Surface.
 - On the Draw 3D toolbar, click the Revolved Surface tool () .
 - Type *revsurf* and then press Enter.
- 2 Select the entity to revolve.
- 3 Select the entity to be used as the axis of revolution.
- 4 Specify the starting angle.
- 5 Specify the number of degrees to revolve the entity.



Select the entity to be revolved (**A**) and the axis of revolution (**B**).

The resulting revolved surface mesh.


TIP To control the density of the mesh, change the values for the Number Of M-Direction Surfaces and N-Direction Mesh Density. Choose Settings > Drawing Settings, and then click the 3D Settings tab. Under Change Settings For, select Surfaces. Under Surface Settings, change the Number Of M-Direction Surfaces and N-Direction Mesh Density values. Or on the Settings toolbar, use the Drawing Settings tool () to display that dialog box.


Creating edge-defined Coons surface patch meshes

You can create a surface called a Coons surface patch, a mesh connecting four edges. You select the entities that define the edges. Edge entities can be arcs, lines, or polylines. The four edge entities must form a closed loop and share endpoints. A patch is a bicubic surface (one curve extends in the M-direction and the other in the N-direction) interpolated between the four adjoining edges. You can select the edges in any order. The first edge you select determines the M-direction of the mesh.

To create an edge-defined Coons surface patch mesh


Advanced experience level

- 1 Do one of the following:
 - Choose Insert > 3D Entities > Coons Surface.
 - On the Draw 3D toolbar, click the Coons Surface tool ().
 - Type *edgesurf* and then press Enter.
- 2 Select the first edge.
- 3 Select the second, third, and fourth edges.



Select the entities to be used as the four edges (A, B, C, and D).

The resulting Coons surface patch mesh.


TIP To control the density of the mesh, change the value for the Number of M-Direction Surfaces and N-Direction Mesh Density. Choose Settings > Drawing Settings, and then click the 3D Settings tab. Under Change Settings For, select Surfaces. Under Surface Settings, change the Number Of M-Direction Surfaces and N-Direction Mesh Density values. Or on the Settings toolbar, use the Drawing Settings tool () to display that dialog box.


Creating boxes

You can create rectangular boxes, or cubes. A box consists of six rectangular surface planes. The base of the box is always parallel with the xy plane of the current UCS. You position the box by specifying either a corner or the center of the box. You determine the size of the box by either specifying a second corner and the height; defining the box to be a cube and then providing its length; or specifying the length, width, and height.

NOTE *The box is created as a three-dimensional ACIS solid.*

To create a box


- 1 Do one of the following:
 - Choose Insert > 3D Entities > Box.
 - On the Solids toolbar, click the Box tool ().
 - Type *box* and then press Enter.
- 2 Specify the first corner of the base.
- 3 Specify the opposite corner of the base.
- 4 Specify the height.



First corner of the base (**A**), the opposite corner of the base (**B**), and the height (**C**).

To create a box as a three-dimensional surface

To create a box as a surface instead of as a solid, the procedure is similar.


- 1 Do one of the following:
 - On the Draw 3D toolbar, click the Box tool ().
 - Type *ai_box* and then press Enter.
- 2 Specify the first corner of the base.
- 3 Specify the opposite corner of the base.
- 4 Specify the height.


Creating wedges

You can create three-dimensional wedges consisting of five surface planes. The base of the wedge is always parallel with the xy plane of the current UCS with the sloped face opposite the first corner. The height is always parallel with the z-axis. You position the wedge by specifying either a corner or the center of the wedge. You determine the size of the wedge by either specifying a second corner and the height; defining the wedge based on a cube having a given length; or specifying the length, width, and height.

NOTE *The wedge is created as a three-dimensional ACIS solid.*

To create a wedge


- 1 Do one of the following:
 - Choose Insert > 3D Entities > Wedge.
 - On the Solids toolbar, click the Wedge tool ().
 - Type *wedge* and then press Enter.
- 2 Specify the first corner of the base.
- 3 Specify the opposite corner of the base.
- 4 Specify the height.



First corner of the base (A), the opposite corner of the base (B), and the height (C).

To create a wedge as a three-dimensional surface

To create a wedge as a surface instead of as a solid, the procedure is similar.


- 1 Do one of the following:
 - On the Draw 3D toolbar, click the Wedge tool ().
 - Type *ai_wedge* and then press Enter.
- 2 Specify the first corner of the base.
- 3 Specify the opposite corner of the base.
- 4 Specify the height.


Creating cones

You can create three-dimensional cones defined by a circular base and tapering to a point perpendicular to the base. The base of the cone is always parallel with the xy plane of the current UCS; the height of the cone is always parallel with the z-axis. You position the cone by specifying the center of the base. You determine the size of the cone by specifying either the radius or the diameter of the base and the height.

NOTE *The cone is created as a three-dimensional ACIS solid.*

To create a cone


- 1 Do one of the following:
 - Choose Insert > 3D Entities > Cone.
 - On the Solids toolbar, click the Cone tool ().
 - Type *cone* and then press Enter.
- 2 Specify the center of the base of the cone.
- 3 Specify the radius or diameter.
- 4 Specify the height.



Center of the base (**A**), the radius of the base (**B**), and the height (**C**).

To create a cone as a three-dimensional surface

To create a cone as a surface instead of as a solid, the procedure is similar.


- 1 Do one of the following:
 - On the Draw 3D toolbar, click the Cone tool ().
 - Type *ai_cone* and then press Enter.
- 2 Specify the center of the base of the cone.
- 3 Specify the radius or diameter.
- 4 Specify the height.


Creating pyramids

You can create tetrahedrons (three-sided pyramids) or four-sided pyramids. The sides of the resulting pyramid can meet at a point (the apex) or can form a three- or four-sided top. The sides of a four-sided pyramid can also meet along a ridge defined by two points. The base of the pyramid is always parallel with the xy plane of the current UCS. You position the pyramid by specifying a corner of the base. You determine the size of the pyramid by specifying the base points and either the apex, the corners of the top surface, or the endpoints of the ridge.

NOTE *The tetrahedron and pyramid are created as three-dimensional ACIS solids.*


To create a tetrahedron


- 1 Do one of the following:
 - Choose Insert > 3D Entities > Pyramid.
 - On the Solids toolbar, click the Pyramid tool ().
 - Type *pyramid* and then press Enter.
- 2 Specify the first point for the base of the pyramid.
- 3 Specify the second and third points.
- 4 In the prompt box, choose Tetrahedron.
- 5 Specify the apex of the tetrahedron.



The first point (**A**), second point (**B**), and third point (**C**) of the base, and the apex (**D**).

To create a pyramid with a planar top


- 1 Do one of the following:
 - Choose Insert > 3D Entities > Pyramid.
 - On the Solids toolbar, click the Pyramid tool ().
 - Type *pyramid* and then press Enter.
- 2 Specify the first point for the base of the pyramid.
- 3 Specify the second, third, and fourth points.
- 4 In the prompt box, choose Top Surface.
- 5 Specify the first point on the top surface of the pyramid.
- 6 Specify the second, third, and fourth points.



The first point (A), second point (B), third point (C), and fourth point (D) of the base, and the first point (E), second point (F), third point (G), and fourth point (H) of the top surface.

To create a pyramid as a three-dimensional surface

To create a pyramid as a surface instead of as a solid, the procedure is similar.


- 1 Do one of the following:
 - On the Draw 3D toolbar, click the Pyramid tool ().
 - Type *ai_pyramid* and then press Enter.
- 2 Specify the points as described previously.


Creating cylinders

You can create cylinders defined by a circular base. The base of a cylinder is always parallel with the xy plane of the current UCS; the height of a cylinder is always parallel with the z-axis. You position a cylinder by specifying the center of the base. You determine the size of a cylinder by specifying either the radius or diameter of the base and the height.

NOTE *The cylinder is created as a three-dimensional ACIS solid.*

To create a cylinder


- 1 Do one of the following:
 - Choose Insert > 3D Entities > Cylinder.
 - On the Solids toolbar, click the Cylinder tool ().
 - Type *cylinder* and then press Enter.
- 2 Specify the center of the base of the cylinder.
- 3 Specify the radius or diameter.
- 4 Specify the height.



Center of the base (**A**), radius of the base (**B**), and the height (**C**).

To create a cylinder as a three-dimensional surface

To create a cylinder as a surface instead of as a solid, the procedure is similar.


- 1 Do one of the following:
 - On the Draw 3D toolbar, click the Cylinder tool ().
 - Type *ai_cylinder* and then press Enter.
- 2 Specify the center, radius, and height as described previously.


Creating spheres

You can create spheres. The latitude lines of a sphere are always parallel with the xy plane of the current UCS; the central axis is always parallel with the z-axis. You position a sphere by specifying its center point. You determine the size of a sphere by specifying either its radius or its diameter.

NOTE *The sphere is created as a three-dimensional ACIS solid.*

To create a sphere

- 1 Do one of the following:
 - Choose Insert > 3D Entities > Sphere.
 - On the Solids toolbar, click the Sphere tool ().
 - Type *sphere* and then press Enter.
- 2 Specify the center of the sphere.
- 3 Specify the radius or diameter.




Center (A) and radius (B) of the sphere.

The resulting sphere.

To create a sphere as a three-dimensional surface

To create a sphere as a surface instead of as a solid, the procedure is similar.


- 1 Do one of the following:
 - On the Draw 3D toolbar, click the Sphere tool ().
 - Type *ai_sphere* and then press Enter.
- 2 Specify the center of the sphere.
- 3 Specify the radius or diameter.
- 4 Specify the number of longitudinal sections that are perpendicular to the xy plane.
- 5 Specify the number of latitudinal sections that are parallel to the xy plane.


Creating dishes

You can create a three-dimensional dish. The latitude lines of a dish are always parallel with the xy plane of the current UCS; the central axis is always parallel with the z-axis. You position a dish by specifying its center point. You determine the size of a dish by specifying either its radius or its diameter.

NOTE *The dish is created as a three-dimensional ACIS solid.*

To create a dish


- 1 Do one of the following:
 - Choose Insert > 3D Entities > Dish.
 - On the Solids toolbar, click the Dish tool ().
 - Type *dish* and then press Enter.
- 2 Specify the center of the dish.
- 3 Specify the radius or diameter.



Center (A) and radius (B) of the dish.

To create a dish as a three-dimensional surface

To create a dish as a surface instead of as a solid, the procedure is similar.


- 1 Do one of the following:
 - On the Draw 3D toolbar, click the Dish tool ().
 - Type *ai_dish* and then press Enter.
- 2 Specify the center and radius or diameter as described previously.


Creating domes

You can create a three-dimensional dome. The latitude lines of a dome are always parallel with the xy plane of the current UCS; the central axis is always parallel with the z-axis. You position a dome by specifying its center point. You determine the size of a dome by specifying either its radius or its diameter.

NOTE *The dome is created as a three-dimensional ACIS solid.*

To create a dome


- 1 Do one of the following:
 - Choose Insert > 3D Entities > Dome.
 - On the Solids toolbar, click the Dome tool (.
 - Type *dome* and then press Enter.
- 2 Specify the center of the dome.
- 3 Specify the radius or diameter.



Center (A) and radius (B) of the dome.

To create a dome as a three-dimensional surface

To create a dome as a surface instead of as a solid, the procedure is similar.


- 1 Do one of the following:
 - On the Draw 3D toolbar, click the Dome tool (.
 - Type *ai_dome* and then press Enter.
- 2 Specify the center and radius or diameter as described previously.


Creating tori

You can create a three-dimensional donut or ring-shaped entity known as a torus. The diameter of a ring is always parallel with the xy plane of the current UCS. A torus is constructed by revolving a circle about a line drawn in the plane of the circle and parallel with the z-axis of the current UCS. You position a torus by specifying its center point. You determine the size of a torus by specifying its overall diameter or radius and the diameter or radius of the tube (the circle being revolved).

NOTE *The torus is created as a three-dimensional ACIS solid.*

To create a torus


- 1 Do one of the following:
 - Choose Insert > 3D Entities > Torus.
 - On the Solids toolbar, click the Torus tool (.
 - Type *torus* and then press Enter.
- 2 Specify the center of the whole torus.
- 3 Specify the radius or diameter of the whole torus.
- 4 Specify the radius or diameter of the body of the torus.



Center (**A**) and radius of the whole torus (**B**), and the radius of the body (**C**).

To create a torus as a three-dimensional surface

To create a torus as a surface instead of as a solid, the procedure is similar.

- 1 Do one of the following:
 - On the Draw 3D toolbar, click the Torus tool ().
 - Type *ai_torus* and then press Enter.
- 2 Specify the center of the whole torus.
- 3 Specify the radius or diameter of the whole torus.
- 4 Specify the radius or diameter of the body of the torus.
- 5 Specify the number of longitudinal sections that are perpendicular to the xy plane.
- 6 Specify the number of latitudinal sections that are parallel to the xy plane.


Creating regions

You can convert a closed entity into a two-dimensional region. After you create a region, you can modify it using the various three-dimensional tools. For example, you can create a region from a square, and then extrude the square to create a three-dimensional cube.

You can create regions from closed entities, such as polylines, polygons, circles, ellipses, closed splines, and donuts.

Creating regions typically has no visible effect on a drawing. However, if the original entity had a width or lineweight, that information is lost when you create the region.

To create a region

- 1 Do one of the following:
 - Choose Modify > Region.
 - On the Modify toolbar, click the Region tool ().
 - Type *region* and then press Enter.
- 2 Select the entities to create the region.
- 3 Press Enter.


The command bar displays a message that describes how many regions were created.

Creating extruded solids

You can create three-dimensional solids by extruding closed entities, such as polylines, polygons, circles, ellipses, closed splines, donuts, and regions. You can extrude the entity along a selected path, or you can specify its height and taper angle.

To create an extruded solid

- 1 Do one of the following:
 - Choose Insert > 3D Entities > Extrude.
 - Type *extrude* and then press Enter.
- 2 Select the entity to extrude.
- 3 Select the extrusion path, or specify the height.



Select the entity to extrude (A) and the extrusion path (B).


The resulting extruded solid.

Creating revolved solids

You can create three-dimensional solids by revolving closed entities, such as polylines, polygons, circles, ellipses, and regions. You can revolve the entity about a defined axis, line, polyline, or two points.

To create a revolved solid

- 1 Do one of the following:
 - Choose Insert > 3D Entities > Revolve.
 - Type *revolve* and then press Enter.
- 2 Select the entity to revolve.
- 3 Do one of the following to define the axis of revolution:
 - Specify a start point and an end point.
 - Type *o* and press Enter to select an entity that determines the axis.
 - Type *x* and press Enter to select the x-axis.
 - Type *y* and press Enter to select the y-axis.
- 4 Specify the angle of revolution.




Select the entity to revolve (**A**) and the axis (**B**) about which to revolve it., followed by the angle of revolution.


The resulting revolved solid.

Creating composite solids

You can create composite three-dimensional solids by combining, subtracting, and finding the intersection of two or more solids.

To combine solids


- Do one of the following:
 - Choose **Modify > Solids Editing > Union**.
 - On the Solids Editing toolbar, click the Union tool ().
 - Type *union* and then press Enter.
- Select the entities to combine.




Select the entities to combine (**A** and **B**).

The resulting combined solid.

To subtract solids

- Do one of the following:
 - Choose **Modify > Solids Editing > Subtract**.
 - On the Solids Editing toolbar, click the Subtract tool ().
 - Type *subtract* and then press Enter.
- Select the entities to subtract from one another.




Select the entities to subtract (**A** and **B**).


The resulting solid.

To intersect solids

1 Do one of the following:

- Choose Modify > Solids Editing > Intersect.
- On the Solids Editing toolbar, click the Intersect tool ()
- Type *intersect* and then press Enter.

2 Select the entities to intersect.



Select the entities to combine (**A** and **B**).

The resulting combined solid.


Editing in three dimensions


You can copy, move, rotate, array, mirror, and align two-dimensional and three-dimensional entities in both two-dimensional and three-dimensional space. You can also change and edit properties of three-dimensional entities much like you change and edit properties for two-dimensional entities. When you modify three-dimensional entities in two-dimensional space, you modify the entity in relation to the current UCS.

Rotating in three dimensions

You can rotate selected entities about a specified axis in three-dimensional space. You select the entities to rotate and then define the axis of rotation either by specifying two points; selecting an existing entity; aligning the axis with the x-, y-, or z-axis of the current UCS; or aligning the axis with the current view.

To rotate an entity about an axis in three dimensions

- 1 Do one of the following:
 - Choose Modify > 3D Rotate.
 - On the Modify toolbar, click the 3D Rotate tool () .
 - Type *rotate3D* and then press Enter.
- 2 Select the entities to rotate, and then press Enter.
- 3 Choose from one of the following options: Entity, Last, View, Xaxis, Yaxis, Zaxis.
- 4 Specify the rotation angle.
- 5 Specify the reference angle.




Select the entities to rotate (**A**), specify the endpoints of the axis of rotation (**B** and **C**), and then specify the rotation angle (**D**).


Result after rotating the entities.

Arraying in three dimensions

You can copy selected entities and arrange them in a three-dimensional rectangular or polar (circular) pattern. For a rectangular array, you control the number of copies in the array by specifying the number of rows and columns and the number of levels. You also specify the distance between each. For a polar array, you specify the axis around which to array the entities, the number of copies of the entities to create, and the angle subtended by the resulting array.


To create a three-dimensional rectangular array

- 1 Do one of the following:
 - Choose Modify > 3D Array.
 - On the Modify toolbar, click the 3D Array tool () .
 - Type *3Darray* and then press Enter.
- 2 Select the entities, and then press Enter.
- 3 In the prompt box, choose Rectangular.
- 4 Type the number of rows in the array.
- 5 Type the number of columns.
- 6 Type the number of levels.
- 7 Specify the vertical distance between the rows.
- 8 Specify the horizontal distance between the columns.
- 9 Specify the depth between the levels.




To create a three-dimensional rectangular array, select the entity to copy (A), type the number of rows, columns, and levels, and then specify the distance between each row (B), column (C), and level (D).

To create a three-dimensional polar array

- 1 Do one of the following:
 - Choose Modify > 3D Array.
 - On the Modify toolbar, click the 3D Array tool ().
 - Type *3Darray* and then press Enter.
- 2 Select the entities, and then press Enter.
- 3 In the prompt box, choose Polar.
- 4 Type the number of copies to make, including the original selection set.
- 5 Specify the angle the array is to fill, from 0 to 360 degrees.

The default setting for the angle is 360 degrees. Positive values create the array in a counterclockwise direction; negative values create the array in a clockwise direction.
- 6 In the prompt box, choose one of the following:
 - Yes-Rotate Entities to rotate entities as they are arrayed.
 - No-Do Not Rotate to retain the original orientation of each copy as it is arrayed.
- 7 Specify the center point of the array.
- 8 Specify a second point along the central axis of the array.





To create a three-dimensional polar array, select the entity to copy (**A**), type the number of copies to make, specify the angle the array is to fill (**B**), and then specify the center point of the array (**C**) and a second point along the central axis of the array (**D**).

Mirroring in three dimensions

You can create a mirror image of selected entities in three-dimensional space. You mirror the entities about a mirror plane that you define by either specifying three points; selecting an existing two-dimensional planar entity; aligning the plane parallel with the xy, yz, or xz plane of the current UCS; or aligning the plane with the current view. You can delete or retain the original entities.

To mirror an entity about a three-dimensional plane

- 1 Do one of the following:
 - Choose Modify > 3D Mirror.
 - On the Modify toolbar, click the 3D Mirror tool () .
 - Type *mirror3D* and then press Enter.
- 2 Select the entities, and then press Enter.
- 3 In the prompt box, choose 3 Points, or press Enter to select the default.
- 4 Specify the first point on the mirror plane.
- 5 Specify the second and third points on the plane.
- 6 In the prompt box, choose one of the following:
 - Yes-Delete Entities to delete the original entities.
 - No-Keep Entities to retain the original entities.




Select the entity to mirror (**A**), and then specify the first point (**B**), second point (**C**), and third point (**D**) defining the mirror plane.


The resulting mirrored entity.

Aligning in three dimensions

You can align selected entities with other entities in three-dimensional space. You select the entities you want to align, and specify one, two or three pairs of points to align the selected entities.

To align an entity with another

- 1 Do one of the following:
 - Choose Modify > Align.
 - On the Modify toolbar, click the Align tool ().
 - Type *align* and then press Enter.
- 2 Select the entities, and then press Enter.
- 3 Specify the first source point.
- 4 Specify the first destination point
- 5 Specify additional source and destination points if desired (up to three pairs).



Select the entities to align, and then specify the first source point (**A**), the first destination point (**B**), the second destination point (**C**), and the second destination point (**D**). You can specify up to three pairs of source/destination points.

The resulting mirrored entity.

Editing three-dimensional solids


You can edit three-dimensional solids in several unique ways, including: chamfer, fillet, section, and slice. You can also modify individual faces and edges of solids, as well as imprint, separate, shell, and check solids.

You can edit three-dimensional ACIS solids, including: boxes, cones, cylinders, dishes, domes, pyramids, spheres, tori, and wedges.


Chamfering and filleting solids

You can chamfer or fillet a three-dimensional solid much like you chamfer or fillet a two-dimensional entity.

To chamfer a solid

- 1 Do one of the following:
 - Choose Modify > Chamfer.
 - On the Modify toolbar, click the Chamfer tool ().
 - Type *chamfer* and then press Enter.
- 2 Select the edge of the base surface to chamfer. (One of two surfaces adjacent to the selected edge will be highlighted.)
- 3 Do one of the following:
 - To select a different surface, type *n* and press Enter.
 - To use the current surface, press Enter.
- 4 Specify the base surface distance (measured from the selected edge to the base surface).
- 5 Specify the adjacent surface distance (measured from the selected edge to the adjacent surface).
- 6 Do one of the following:
 - Specify the edges to chamfer.
 - To select all edges around the base surface, type *l* and press Enter.

To fillet a solid

- 1 Do one of the following:
 - Choose Modify > Fillet.
 - On the Modify toolbar, click the Fillet tool ().
 - Type *fillet* and then press Enter.
- 2 Select the edge of the solid to fillet.
- 3 Specify the fillet radius.
- 4 Select additional edges to fillet, and press Enter to fillet.


Sectioning and slicing solids

You can section or slice a three-dimensional solid, region, or body (typically a sheet).


When you section a solid, you obtain an “inside view” by creating a cross-section through the solid as a region or block. When you section a region or body, the resulting intersections are curves.

When you slice a solid, region, or body, you create a new entity by cutting the original entity and removing a specific side.

To section an entity

- 1 Do one of the following:
 - Choose Insert > 3D Entities > Section.
 - On the Solids toolbar, click the Section tool ().
 - Type *section* and then press Enter.
- 2 Select the entities to cross-section.
- 3 Do one of the following:
 - Specify three points to define the cross-section plane. (The first point defines the origin, while the second point defines the x-axis and the third point defines the y-axis.)
 - Type *o* and press Enter to select an entity that defines the cross-sectional plane.
 - Specify an axis by typing the appropriate letter and pressing Enter.


To slice an entity


- 1 Do one of the following:
 - Choose Insert > 3D Entities > Slice.
 - On the Solids toolbar, click the Slice tool ().
 - Type *slice* and then press Enter.
- 2 Select the entities to slice.
- 3 Do one of the following:
 - Specify three points to define the cross-section plane. (The first point defines the origin, while the second point defines the x-axis and the third point defines the y-axis.)
 - Type *o* and press Enter to select an entity that defines the cross-sectional plane.
 - Specify an axis by typing the appropriate letter and pressing Enter.
- 4 Specify which side to retain, or type *b* to retain both sides.

Modifying faces

You can edit three-dimension solids by extruding, moving, rotating, offsetting, tapering, deleting, or copying individual faces. You can also change the color of individual faces.

To extrude a solid face


- 1 Do one of the following:
 - Choose Modify > Solids Editing > Extrude Face.
 - On the Solids Editing toolbar, click the Extrude Face tool (.
- 2 Select the entity with the face you want to extrude.
- 3 Select the face(s) to extrude, and press Enter.
- 4 Do one of the following:
 - Specify the height of extrusion.
 - Type *p* and press Enter to select a path for extrusion.
- 5 If you specified a height, specify a taper angle.




Select the entity to extrude, and then specify the face(s) to extrude (**A**), and the height of extrusion or path.

The resulting entity with the face extruded to position (**B**).

To move a solid face


- 1 Do one of the following:
 - Choose Modify > Solids Editing > Move Face.
 - On the Solids Editing toolbar, click the Move Face tool ().
- 2 Select the entity with the face you want to move.
- 3 Select the face(s) to move, and press Enter.
- 4 Specify a base point.
- 5 Specify an end point.




Select the entity, and then specify the face(s) to move (**A**), the base point (**B**), and the end point (**C**).

The resulting entity with the face moved to the new position.

To rotate a solid face


- 1 Do one of the following:
 - Choose Modify > Solids Editing > Rotate Face.
 - On the Solids Editing toolbar, click the Rotate Face tool ()
- 2 Select the entity with the face you want to rotate.
- 3 Select the face(s) to rotate, and press Enter.
- 4 Specify a base point.
- 5 Specify another point on the rotation axis.
- 6 Specify the rotation angle.




Select the entity, and then specify the face(s) to rotate (A), the base point (B), a second point on the rotation axis (C), and a rotation angle.

The resulting entity with the face rotated to position (D).

To offset a solid face


- 1 Do one of the following:
 - Choose Modify > Solids Editing > Offset Face.
 - On the Solids Editing toolbar, click the Offset Face tool ().
- 2 Select the entity with the face you want to offset.
- 3 Select the face(s) to offset, and press Enter.
- 4 Specify an offset distance.




Select the entity, and then specify the face(s) to offset (**A**) and the distance to offset.

The resulting entity with the face offset to position (**B**).

To taper a solid face


- 1 Do one of the following:
 - Choose Modify > Solids Editing > Taper Faces.
 - On the Solids Editing toolbar, click the Taper Face tool ().
- 2 Select the entity with the face you want to taper.
- 3 Select the face(s) to taper, and press Enter.
- 4 Specify a base point.
- 5 Specify another point along the axis.
- 6 Specify a taper angle.




Select the entity, and then specify the face(s) to taper (**A**), a base point, a second point along the taper axis, and a taper angle.

The resulting entity with the face tapered to position (**D**).

To delete a solid face


- 1 Do one of the following:
 - Choose Modify > Solids Editing > Delete Face.
 - On the Solids Editing toolbar, click the Delete Face tool ().
- 2 Select the entity with the face you want to delete.
- 3 Select the face(s) to delete, and press Enter.




Select the entity, and then specify the face(s) to delete (**A**).

The resulting entity with the face deleted.

To copy a solid face


- 1 Do one of the following:
 - Choose Modify > Solids Editing > Copy Face.
 - On the Solids Editing toolbar, click the Copy Face tool ().
- 2 Select the entity with the face you want to copy.
- 3 Select the face(s) to copy, and press Enter.
- 4 Specify a base point.
- 5 Specify an end point.




Select the entity, and then specify the face(s) to copy (A), the base point (B), and the end point (C).

The resulting entity with the face copied.

To color a face

- 1 Do one of the following:
 - Choose Modify > Solids Editing > Color Face.
 - On the Solids Editing toolbar, click the Color Face tool ().
- 2 Select the entity with the face you want to color.
- 3 Select the face(s) to color, and press Enter.
- 4 Specify a color.




Select the entity, and then specify the face(s) to color (A).


The resulting entity with the face colored.

Modifying edges

In addition to modifying faces of solids, you can modify individual edges. You can copy individual edges or change the color of individual edges.

To copy an edge


- 1 Do one of the following:
 - Choose Modify > Solids Editing > Copy Edge.
 - On the Solids Editing toolbar, click the Copy Edge tool ().
- 2 Select the entity with the edge you want to copy.
- 3 Select the edge(s) to copy, and press Enter.
- 4 Specify a base point.
- 5 Specify an end point.



Select the entity, and then specify the edge(s) to copy (A), the base point (B), and the end point (C).

The resulting entity with the edge copied.


To color an edge

- 1 Do one of the following:
 - Choose Modify > Solids Editing > Color Edge.
 - On the Solids Editing toolbar, click the Color Edge tool ().
- 2 Select the entity with the edge you want to color.
- 3 Select the edge(s) to color, and press Enter.
- 4 Specify a color.

Imprinting solids

You can modify the face of a solid by imprinting another entity on it. For example, you can imprint a line, arc, or polyline onto the face of a box.


To imprint a solid entity

- 1 Do one of the following:
 - Choose Modify > Solids Editing > Imprint.
 - On the Solids Editing toolbar, click the Imprint tool ().
- 2 Select the solid entity you want to imprint.
- 3 Select the entity you want to imprint on the solid.

Separating solids

You can separate solids that have been combined. After you separate them, they are separated into individual solids.


To separate solids


- 1 Do one of the following:
 - Choose Modify > Solids Editing > Separate.
 - On the Solids Editing toolbar, click the Separate tool ().
- 2 Select the solid you want to separate.

Shelling solids

You can create a shell or a hollow thin wall from your 3D solid entity. IntelliCAD offsets existing faces to create new faces.

To shell a solid

- 1 Do one of the following:
 - Choose Modify > Solids Editing > Shell.
 - On the Solids Editing toolbar, click the Shell tool ()
- 2 Select the entity you want to shell.
- 3 Remove any faces you don't want to include.
- 4 Specify an offset distance.




Select the entity, and then select faces to remove (A) and (B), then specify an offset distance.

The resulting shelled entity.

Cleaning solids

You can remove redundant edges or vertices from solids when they are not needed.


To clean a solid

- 1 Do one of the following:
 - Choose Modify > Solids Editing > Clean.
 - On the Solids Editing toolbar, click the Clean tool ()
- 2 Select the entity you want to clean.

Checking solids

You can check whether a selected entity is a valid three dimensional ACIS solid. If it is a valid 3D solid, you can modify the entity using the 3D solid editing commands; if not, you cannot edit the entity using these commands.

To check a solid


- 1 Do one of the following:
 - Choose Modify > Solids Editing > Check.
 - On the Solids Editing toolbar, click the Check tool ().
- 2 Select the entities to check.

Hiding, shading, and rendering

As you create three-dimensional entities, the program displays both wire-frame and surface models in wire-frame view, which makes it difficult to visualize your three-dimensional models. To better visualize the model, you can remove all the lines that are hidden behind other entities or surfaces when seen from the current viewpoint.

Shading goes a step further by removing hidden lines and then assigning flat colors to the visible surfaces, making them appear solid. Shaded images are useful when you want to quickly visualize your model as a solid entity, though they lack depth and definition.

Rendering provides an even more realistic image of your model, complete with light sources, shadows, surface material properties, and reflections, giving your model a photo-realistic look. As shown in the following illustrations, when you render a model, the program removes hidden lines and then shades the surfaces as though they were illuminated from imaginary light sources.



Wire-frame model.

Hidden-line image.

Shaded image.


Rendered image.


Creating hidden-line images

Creating a hidden-line view of your drawing removes all the lines that are hidden behind other surfaces when seen from your vantage point. When you remove hidden lines or shade a model, the program treats the entities differently, depending on how you created them. Wire-frame models always appear transparent, because they have no surfaces. Surface models appear filled, with surfaces applied to all visible sides.

To create a hidden-line image

Do one of the following:

- Choose View > Rendering > Hide.
- On the Rendering toolbar, click the Hide tool ()
- Type *hide* and then press Enter.



Before creating a hidden-line image.


After removing hidden lines.

Creating shaded images

Creating a shaded image of your drawing removes hidden lines and then applies shading to the visible surfaces based on their entity color. Because they are intended to provide a quick visualization, shaded images do not have a light source and use continuous colors across surfaces, causing them to appear flat and unrealistic.

To create a shaded image

Do one of the following:

- Choose View > Rendering > Shade.
- On the Rendering toolbar, click the Shade tool ()
- Type *shade* and then press Enter.

To control the appearance of the shaded image, choose Settings > Drawing Settings, and then click the 3D Settings tab and select the options you want. You can shade the surfaces and edges of the model in four ways:

- Faces shaded; edges not highlighted.
- Faces shaded; edges highlighted in the background color.
- Faces filled in the background color; edges drawn using the entity color (similar to a hidden-line view).
- Faces filled using the entity color; edges highlighted in the background color.

Creating rendered images

Creating a rendered image of your drawing removes hidden lines and then shades the surface as though it were illuminated from multiple light sources.


Full rendering creates a photo-realistic image of your model, complete with light sources, shadows, surface material properties, and reflections. You can illuminate your image with spotlights, distant lighting to simulate sunshine, and ambient light. If you choose not to customize the light sources, the program generates default light sources for you.

Rays from these imaginary light sources are traced as they reflect off and refract through the surfaces of the model, a process called *ray tracing*. Ray tracing determines where shadows fall and how reflections on shiny materials such as metal and glass appear. You can modify the reflective properties of the materials that make up your model to control how the light rays reflect off its surfaces.

Full rendering automatically creates a base on which your model is displayed, if you don't already have one, so it does not appear suspended in space. A background is also automatically added to the image. A background such as a cloudy sky or an imported raster graphic such as a stone wall can also be added behind the image, making it even more realistic.


To create a quickly rendered image


Do one of the following:

- Choose View > Rendering > Render.
- On the Rendering toolbar, click the Render tool (.
- Type *render* and then press Enter.

To create a fully rendered image

Do one of the following:

- Choose View > Rendering > Full Render.
- On the Rendering toolbar, click the Full Render tool (.
- Type *fullrender* and then press Enter.






Fully rendered image.

Creating custom rendered images

IntelliCAD allows you to create custom rendered images by applying materials, backgrounds, and lighting (including shadows) to your drawing:

- **Materials** Specify materials for different surfaces and define how the materials map to those surfaces. Predefined materials are available in the materials library, which can be customized further using the built-in editor. You can choose to use procedural or bitmap materials.
- **Backgrounds** Specify the background or backdrop for a rendered image. Several predefined backgrounds are available. By default, no background is used and it appears black. The background is an infinite, planar surface and reflects off of any reflective surfaces in your model. The background is not affected by lighting however, so no shadows or highlights are seen on the background.
- **Lighting** Specify the placement of lights, light color, and light intensity to determine how your drawing or scene is lit, including shadows and reflections in the scene. Lights can be placed either outside the field of view or inside to illuminate different areas of the scene. Several predefined lighting controls are available, including ambient lighting, diffuse lighting, specular reflections, specular highlights, and transparency.

To apply materials, backgrounds, and lighting


- 1 Do one of the following:
 - Choose View > Rendering, and then choose Materials, Backgrounds, or Lighting.
 - On the Rendering toolbar, click the Materials tool () , Backgrounds () , or Lighting tool () .
 - Type *materials*, *backgrounds*, or *lighting* and then press Enter.
- 2 Make your selections.

NOTE You can specify additional options by choosing View > Rendering > Render Settings. For more information about creating custom rendered images, click Help in any of the Render dialog boxes.

Printing a rendered image

You cannot print a rendered image directly to a printer. Instead, you must first save the drawing to a different format — either a bitmap (.bmp), JPEG (.jpg), TIFF (.tif), TrueVision TGA (.tga), or Portable Network Graphic (.png). After you save a rendered image, you can print it from another graphics program.

To save a rendered image of your drawing

- 1 Create a rendered image of the drawing.
- 2 Do one of the following:
 - Choose View > Rendering > Render Settings.
 - On the Rendering toolbar, click the Render Settings tool ().
 - Type *setrender* and then press Enter.
- 3 On the Rendering tab, click Save Last Image.
- 4 Enter a file name and path.
- 5 In Save As Type, choose the file format.
- 6 Click Save.

Working with other programs

IntelliCAD offers great flexibility in its capability to be used with other programs. You can include an IntelliCAD drawing in a Microsoft® Word document or insert a Microsoft® Excel spreadsheet containing a parts list into an IntelliCAD drawing. To include IntelliCAD drawings in other programs and documents from other programs in IntelliCAD drawings, you either link or embed them. You can also save IntelliCAD drawings in other file formats that can be used directly with other programs or send IntelliCAD drawings to coworkers via e-mail.

This section explains how to:

- Save and view snapshots.
- Use images in your drawings.
- Use object linking and embedding.
- Export IntelliCAD drawings to other file formats.
- Send drawing files via e-mail.
- Use IntelliCAD with the Internet.

Topics in this chapter

<i>Saving and viewing snapshots</i>	<i>448</i>
<i>Using images in a drawing.....</i>	<i>449</i>
<i>Using data from other programs in IntelliCAD drawings.....</i>	<i>458</i>
<i>Using IntelliCAD data in other programs</i>	<i>464</i>
<i>Using IntelliCAD with the Internet.....</i>	<i>472</i>

Saving and viewing snapshots

You can save snapshots of a drawing to view later. A snapshot saves the current drawing in either *.emf, *.wmf, or *.sld format exactly as it appears on the screen. A snapshot is not a drawing file. You cannot edit or print the snapshot; you can only view it.


You can use snapshots in the following ways:

- Make presentations by showing snapshots of your drawings.
- Reference a snapshot of a drawing while working on a different drawing.
- Present a number of snapshots as a slide show by using scripts.

When you view a snapshot, it temporarily replaces the current drawing. When you refresh the display of the current drawing (by redrawing, panning, zooming, minimizing, maximizing, or tiling), the snapshot image disappears, and you are returned to the current drawing.


You create a snapshot by saving the current view as a snapshot. A snapshot does not include any entities on layers that are not currently visible. The contents of the snapshot also depend on the current drawing space. In model space, the snapshot shows only the current viewport. In paper space, the snapshot contains all visible viewports.

To create a snapshot

- 1 Display the drawing exactly as you want to capture it as a snapshot.
 - Choose Tools > Make Snapshot.
 - On the Tools toolbar, click the Make Snapshot tool ().
 - Type *msnapshot* and then press Enter.
- 2 In the Create Snapshot dialog box, specify the name of the snapshot file you want to create.
- 3 From the Files Of Types list, choose either *.emf, *.wmf, or *.sld.
- 4 Click Save.

The current drawing remains on the screen, and the snapshot is saved to the directory that you specify. You can view previously saved snapshots, and you can also view snapshots created using AutoCAD.

To view a snapshot

- 1 Do one of the following:
 - Choose Tools > View Snapshot.
 - On the Tools toolbar, click the View Snapshot tool ().
 - Type *vsnapshot* and then press Enter.
- 2 In the View Snapshot dialog box, specify the name of the snapshot file you want to view.
- 3 Click Open.

IntelliCAD displays the snapshot in the current drawing window.

Using images in a drawing

You can modify and view raster images directly inside of IntelliCAD. You can load, edit, and modify multiple images as overlays or underlays to your IntelliCAD drawings. The images can be selected for use with IntelliCAD commands by selecting the image frame, which can be turned on or off for printing or selection purposes.


IntelliCAD support numerous image file formats, including BMP, JPG, GIF, EMF, TIF, PNG, WMF, and many more.

Attaching images

When you attach an image to a drawing, the image displays in the drawing but is not saved in the drawing. The image file remains saved in its original location on your computer, network, or other media.

If you send or receive drawings that contain images, it is important to include with the drawing all of the image files attached to it. When you open a drawing that contains images, the source image files must be accessible for the images to display in the drawing.


To attach an image

- 1 Do one of the following:
 - Choose Image > Attach Image.
 - On the Image toolbar, click the Attach Image tool ().
 - Type *imageattach* and then press Enter.
- 2 Specify a file to attach, and then click Open.

- 3 In Image Path will be Saved As, enter a different image file location, if necessary. You can click [>] to choose how you want to save the image path:
 - Full Path — The image is referenced using its full path, for example, c:\My Pictures\MyImage.jpg. Use this option if the image is saved in a folder unrelated to the current drawing folder.
 - Relative Path — The image is referenced using a path relative to the current drawing folder, for example, ..\My Pictures\MyImage.jpg. Use this option if the image is stored in a subfolder of the current drawing folder.
 - File Name Only — The image is referenced using its file name in the current drawing folder, for example, MyImage.jpg. Use this option if the image is saved in the same folder as the current drawing.
- 4 In the Attach Image dialog box, specify the position, scale, rotation, transparency, and clipping options, and then click OK.

NOTE *Transparency works for images that support alpha transparency, that is, images that have at least one color that can be viewed as a transparent color.*

- 5 In the drawing, specify an insertion point, scale, and rotation if you chose to specify those on the screen.



- A** Enter a different image file location, if necessary.
- B** Choose to place the image automatically in the drawing using specifications located in a positioning file. Enter the TWF file associated with the image or click [...] to select it.
- C** Choose to specify the insertion point in the drawing upon insertion, or enter coordinates.
- D** Choose to specify the size of the image in the drawing upon insertion, or enter the size values.
- E** Choose whether to turn clipping display on or off for the image.
- F** Choose whether entities located under the image are visible (for images that support alpha transparency).
- G** Choose to specify rotation in the drawing upon insertion, or enter how many degrees to rotate the image to the left.
- H** Click to view image information, including color depth and resolution.
- I** Choose to save the image path as its full path, relative path to the current drawing folder, or file name in the current drawing folder.

TIP You can also attach images using the Image Manager. Choose *Image > Image Manager*, and then click *Attach* to specify an image and then attach it, or if you want to quickly add another occurrence of an image already located in the drawing, select the image in the Image Manager and then click *Add*.


Modifying images

You can modify an image by changing its brightness, contrast, fade, size, rotation, or transparency. These changes affect the image in the drawing only — not the original image file.

In addition to modifying a single image or multiple images that you select, you can also modify all occurrences of an image within a drawing. For example, if your company logo appears in multiple locations throughout a drawing, you can use the Image Manager to specify the changes once and apply them to all occurrences of the logo.

You can use other IntelliCAD commands for typical modifications, such as Delete, Move, Layer, and more.

To modify images

- 1 Do one of the following:
 - Choose Image > Image Manager.
 - On the Image toolbar, click the Image Manager tool ().
 - Type *image* and then press Enter.


TIP *You can also modify images by selecting one or more images in a drawing, and then choosing Modify > Properties.*

- 2 In the Images list, select the image you want to modify. If there is more than one occurrence of the image in the drawing, do one of the following:
 - To modify all occurrences of the image, select a top-level image in the list.
 - To modify a single occurrence of the image, expand a top-level image in the list, and then select the individual image.
- 3 Adjust the Brightness, Contrast, and Fade by moving the slider to the setting you want or by entering an exact number. The image preview shows how your changes will affect the image.

TIP *If you want to restore the image to the default brightness, contrast, and fade settings, click Reset.*

- 4 Adjust the Size by making changes to the width (X) and height (Y) in drawing units. Mark Keep Aspect Ratio if you want the width and height to change together to retain the aspect ratio of the image.
- 5 Adjust the Rotation by entering the number of degrees you want to rotate the image to the left. Zero degrees indicates no rotation.
- 6 Mark Use Transparency if you want entities located under the image to be visible (for images that support alpha transparency, that is, images that have at least one color that can be viewed as a transparent color).

- 7 Mark Show Clipping Boundary if you want to show the image clipped, if a clipping boundary is defined for the image. Unmarking this option displays the whole image, even if a clipping boundary is defined.
- 8 Click OK.



- A Click a top-level image to modify all occurrences located in the drawing. Expand a top-level image and click an individual image to modify that occurrence only.
- B Move the slider or enter an exact number for image brightness.
- C Move the slider or enter an exact number for image contrast.
- D Move the slider or enter an exact number for image fade, which fades the image without displaying entities located under the image.
- E Click to return to the default brightness, contrast, and fade settings.
- F Enter the width (X) and height (Y) in drawing units. Mark Keep Aspect Ratio to change width and height together.
- G Choose whether to turn clipping display on or off for the image.
- H Choose whether entities located under the image are visible (for images that support alpha transparency).
- I Enter how many degrees to rotate the image to the left.

Changing the display of images


You can change the following for how all images display in a drawing:

- Image quality — Images can display in high or low resolution.
- Image frames — Images can display with or without frames on their edges.

Changing the display quality for all images

High quality displays images in high resolution and requires more system resources. Draft quality displays images in low resolution and consumes fewer system resources. Changing the quality setting affects all images in the drawing.

To change the display quality for all images


- 1 Do one of the following:
 - Choose Image > Image Quality.
 - On the Image toolbar, click the Image Quality tool ().
 - Type *imagequality* and then press Enter.
- 2 Choose High or Draft.

Turning image frames on or off for all images

When image frames are turned on, a frame displays and prints on the edge of all images in the drawing. When image frames are turned off, none of the images display or print with a frame, which also makes images unselectable. Each image frame displays with the properties (layer, color, linetype, etc.) that are assigned to the image.

Turning image frames off may be helpful, for example, if the images are part of a background in the drawing.

To turn image frames on or off for all images

- 1 Do one of the following:
 - Choose Image > Display Image Frame.
 - On the Image toolbar, click the Display Image Frame tool ().
 - Type *imageframe* and then press Enter.
- 2 Choose On or Off.


Clipping images

You can clip images so that only a portion of the image is visible in a drawing. The visible portion can be in the shape of a rectangle or polygon.

Image clipping can be turned on or off. If you turn off clipping for an image, the entire image is visible provided that the image is on a layer that is on and thawed. The clipping information is retained however, and you can turn clipping back on at any time.


If you delete clipping from an image, the clipping is removed permanently but the image itself remains in the drawing.

To clip an image in the shape of a rectangle

- 1 Make sure that image frames are turned on — so you can select images — by choosing Image > Display Image Frame, and then choose On.
- 2 Do one of the following:
 - Choose Image > Clip Image.
 - On the Image toolbar, click the Clip Image tool ().
 - Type *imageclip* and then press Enter.
- 3 Select the edge of the image you want to clip.
- 4 If prompted, choose New to create a new clipping boundary.
- 5 Choose Rectangle.
- 6 Define the first corner of the clipping rectangle.
- 7 Define the opposite corner of the clipping rectangle.


Only the portion of the image located within the clipping rectangle is visible.

To clip an image in the shape of a polygon


- 1 Make sure that image frames are turned on — so you can select images — by choosing Image > Display Image Frame, and then choose On.
- 2 Do one of the following:
 - Choose Image > Clip Image.
 - On the Image toolbar, click the Clip Image tool ().
 - Type *imageclip* and then press Enter.
- 3 Select the edge of the image you want to clip.
- 4 If prompted, choose New to create a new clipping boundary.
- 5 Choose Polygon.
- 6 Select the points for the polygon, and then press Enter when the polygon is complete.

Only the portion of the image located within the clipping polygon is visible.

To turn clipping on or off for an image

- 1 Make sure that image frames are turned on — so you can select images — by choosing Image > Display Image Frame, and then choose On.
- 2 Do one of the following:
 - Choose Image > Clip Image.
 - On the Image toolbar, click the Clip Image tool ().
 - Type *imageclip* and then press Enter.
- 3 Select the edge of the image for which you want to turn clipping on or off.
- 4 Choose On or Off.


To remove clipping from an image

- 1 Make sure that image frames are turned on — so you can select images — by choosing Image > Display Image Frame, and then choose On.
- 2 Do one of the following:
 - Choose Image > Clip Image.
 - On the Image toolbar, click the Clip Image tool ().
 - Type *imageclip* and then press Enter.
- 3 Select the edge of the image for which you want to remove clipping.
- 4 Choose Delete.

Unloading and reloading images

If you find that including an image affects system performance, you can unload it so only the image frame displays to mark its location. If you want an unloaded image to print, reload it before printing. You may also want to reload an image if the original file contains new content.

To unload and reload an image


- 1 Do one of the following:
 - Choose Image > Image Manager.
 - On the Image toolbar, click the Image Manager tool ().
 - Type *image* and then press Enter.
- 2 In the Images list, select the desired image. If there is more than one occurrence of the image in the drawing, do one of the following:
 - To unload or reload all occurrences of the image, select a top-level image in the list.
 - To unload or reload a single occurrence of the image, expand a top-level image in the list, and then select the individual image.

- 3 Do one of the following:
 - To unload the image so only its outer edge displays, click Unload.
 - To reload the image so its contents display and print, click Reload.

Changing the path for images

If the file associated with an image is renamed or moved to a different location, the program displays a message indicating that it cannot load the image. You can re-establish the link to the file by changing the path for the image.


To change the path for an image

- 1 Do one of the following:
 - Choose Image > Image Manager.
 - On the Image toolbar, click the Image Manager tool () .
 - Type *image* and then press Enter.
- 2 In the Images list, select the desired image. If there is more than one occurrence of the image in the drawing, do one of the following:
 - To change the path for all occurrences of the image, select a top-level image in the list.
 - To change the path for a single occurrence of the image, expand a top-level image in the list, and then select the individual image.
- 3 Click the [...] button.
- 4 Select the file with its new name or in its new location, and then click Open.
- 5 Click Set Path.

Deleting images

Once an image is no longer required in the drawing, you can delete it from the drawing. Deleting an image removes it from the drawing, and from the list of images in the Image Manager dialog box.

To delete an image

- 1 Do one of the following:
 - Choose Image > Image Manager.
 - On the Image toolbar, click the Image Manager tool ().
 - Type *image* and then press Enter.
- 2 In the Images list, select the image you want to delete. If there is more than one occurrence of the image in the drawing, do one of the following:
 - To delete all occurrences of the image, select a top-level image in the list.
 - To delete a single occurrence of the image, expand a top-level image in the list, and then select the individual image.
- 3 Click Detach.

Using data from other programs in IntelliCAD drawings

You can include data from other programs in IntelliCAD drawings by using either embedding or linking. The method you choose depends on the type of object or file you want to include in your IntelliCAD drawing and what you want to do with it after it is there.

Embedding objects into drawings


Embed an object into your IntelliCAD drawing when you want to keep all the data you work with in one file or if you want to transfer the file to other computers. You can embed data from programs that support object linking and embedding.

For example, if you want to distribute data about a department's computer equipment along with an IntelliCAD drawing of the department's floor plan, you can embed a Microsoft® Excel spreadsheet into the floor plan.

When you embed data from another program, IntelliCAD becomes the container for that data. The object embedded in the IntelliCAD drawing becomes part of the IntelliCAD file. When you edit the data, you open its program from within the IntelliCAD drawing.

Any changes you make to the embedded data exist only in the IntelliCAD drawing, so it is not necessary to keep that data in a separate file. If the data does exist in a separate file, the original file does not change when you modify the embedded object in IntelliCAD. Also, changes to the original file do not affect the embedded object in the IntelliCAD drawing.

To embed another program's object into an IntelliCAD drawing

- 1 Open the file that contains the data you want.
- 2 In the file, select the data you want to embed in the IntelliCAD drawing.
- 3 Choose that program's command to place data on the Clipboard.
Usually, you choose Edit > Copy.
- 4 In the IntelliCAD window, display the drawing in which you want to embed the object.
- 5 Choose Edit > Paste, or click the Paste tool () on the Standard toolbar.
The data on the Clipboard is pasted into the drawing as an embedded object. The object appears in the center of the view, but you can select and move it by moving the cursor.

To embed an object from an existing file within IntelliCAD

- 1 Do one of the following:
 - Choose Insert > Object.
 - Type *insertobj* and then press Enter.
- 2 In the Insert Object dialog box, click Create From File.
- 3 Specify the file by doing one of the following:
 - Type a path and file name in the File box.
 - Click Browse to select a file.
- 4 Select Display As Icon if you want that program's icon to appear in the drawing instead of the data.
- 5 Click OK.

The first page of the file appears in the IntelliCAD drawing, unless you chose to display it as an icon. You can select the object and drag to reposition it.

To create a new embedded object from within IntelliCAD

- 1 Do one of the following:
 - Choose Insert > Object.
 - Type *insertobj* and then press Enter.
- 2 In the Insert Object dialog box, click Create New.
- 3 From the Object Type list, select the type of object you want to create, and then click OK.

The program for creating that object opens within IntelliCAD. If the program is compatible with ActiveX, it opens in place (within the other program) in the IntelliCAD drawing; otherwise, the program opens in its full window.
- 4 Create the object in the other program.
- 5 If the program is running within the other document (in place), click anywhere outside the embedded object to close the program.

If the program is running in its full window, choose File > Exit.

Linking objects to drawings

If another program supports ActiveX, you can link its data to IntelliCAD drawings. Use linking when you want to include the same data in many files. When you update the data, all links to other files reflect the changes.

For example, if you created your company logo in an ActiveX-compatible drawing program, and you want to include it in the title block of every drawing you create with IntelliCAD, you can link it to each IntelliCAD drawing. When you change the original logo in the drawing program, the IntelliCAD drawing updates automatically.

When you link data from another program, the IntelliCAD drawing stores only a reference to the location of the file in which you created the data. You link data from a saved file, so IntelliCAD can find the data and display it.

Because linking adds only a reference to a file, the data does not significantly increase the file size of the IntelliCAD drawing. However, links require some maintenance. If you move any of the linked files, you need to update the links. In addition, if you want to transport linked data, you must include all linked files.

You can update a linked object automatically every time you open the drawing, or you can do so only when you specify. Anytime a link is updated, changes made to the object in its original file also appear in the IntelliCAD drawing, and the changes also appear in the original file if they were made through IntelliCAD.

To link a file to an IntelliCAD drawing

- 1 Save the original file.
Because a link consists of a reference to the original file, you must save the file before you can link to it.
- 2 In the original file, select the data you want in the IntelliCAD drawing.
- 3 Choose that program's command to place data on the Clipboard.
Usually, you choose Edit > Copy.
- 4 Display the IntelliCAD drawing to which you want to link the file.
- 5 In IntelliCAD, choose Edit > Paste Special.
- 6 In the Paste Special dialog box, select Paste Link.
- 7 Click OK.

To create a linked object from within IntelliCAD

- 1 Display the IntelliCAD drawing in which you want to display the linked object.
 - Choose Insert > Object
 - Type *insertobj* and then press Enter.
- 2 In the Insert Object dialog box, click Create From File.
- 3 Specify the file by doing one of the following:
 - Type a path and file name in the File box.
 - Click Browse to select the file using a file dialog box.
- 4 Select the Link check box.
- 5 Select Display As Icon if you want that program's icon to appear in the drawing instead of the data.
- 6 Click OK.

The first page appears in the IntelliCAD drawing, unless you chose to display it as an icon. To reposition the object, select and drag it.

Editing an embedded or linked object from within IntelliCAD

You can modify an embedded or linked object in its original program from within IntelliCAD. When you modify an embedded object, you change the object only in IntelliCAD, not its original file (if you pasted the object from an existing file). When you modify a linked file, however, you open and change the original file.

Most programs include a submenu of actions you can perform on an embedded or linked ActiveX object. Usually, the commands for editing ActiveX objects are Edit and Open. If the object is embedded and its program supports in-place editing, the Edit command opens the object in place. The Open command opens the object in the full program window. In IntelliCAD, this command appears at the bottom of the Edit menu.

To edit an embedded or linked object

- In the IntelliCAD drawing, double-click the object.

If the object is embedded and the program in which you created the object supports in-place editing, the object opens in place.

If the object is linked, or if its program does not support in-place editing, the other program opens in its full window and displays the object.

Importing files created in other formats


You can import the following files:

- Drawing Exchange Format files with a .dxf file extension. This file type is an ASCII or binary description of a drawing file.
- Design Web Format files with a .dwf file extension. DWF™ files are used to distribute a drawing for others to view in a Web browser, review, and edit using free Autodesk® software and tools.
- Drawing templates with a .dwt file extension. This file type contains predefined settings that you can reuse when you create new drawings.
- Three-dimensional entities saved with an .sat file extension. This file type contains three-dimensional ACIS solids saved as an .sat file.

Importing a DXF, DWF, or DWT file

Importing DXF files, two-dimensional DWF files, and DWT files is similar to opening a standard drawing file.

To import a DXF, DWF, or DWT file

- 1 Use one of the following methods:
 - Choose File > Open.
 - On the Standard toolbar, click the Open tool () .
 - Type *open* and then press Enter.
- 2 Choose the folder that contains the drawing.
- 3 In Files of Type, choose the type of drawing you want to import.
- 4 Choose the file you want to open.
- 5 Click Open.

Importing an ACIS file

An ACIS file contains three-dimensional solids, regions, or bodies that are saved as an ASCII .sat file.

To import an ACIS file

- 1 Do one of the following:
 - Choose File > Acis In.
 - Type *acisin*, and then press Enter.
- 2 Choose the directory containing the SAT file.
- 3 Choose the SAT file you want to open.
- 4 Click Open.

Using IntelliCAD data in other programs

You can use any of the following methods to include IntelliCAD data in a document created in another program:

- Embedding
- Linking
- Dragging
- Exporting
- E-mailing

The method you choose depends on the capabilities of the other program and how you want to work with the IntelliCAD data after you've placed it in the other document.

NOTE *Each method except exporting uses ActiveX to integrate data from different programs. With ActiveX, you can open IntelliCAD drawings from within the other program to modify the IntelliCAD drawings.*

Embedding drawings

When you embed an IntelliCAD drawing, it becomes part of the other program's document file. When you edit the drawing, you edit only the version that is embedded in the other document.

Embedding is useful when you don't want to maintain a link to the IntelliCAD drawing for the data you include in the other document. Edits made to the new drawing do not affect the original drawing. To transfer the file to other computers, you can transfer all the data in one file, but embedded objects increase the file size.

From within a document in a program that supports ActiveX, such as Microsoft® Word, you can either create a new embedded IntelliCAD drawing or embed an existing IntelliCAD drawing.

To create an IntelliCAD drawing in another document

- 1 In the document, choose Insert > Object (or the equivalent command for that program).
- 2 In the dialog box, click the options for creating a new file.
- 3 Under Object Type, choose IntelliCAD Drawing, and then click OK.
- 4 Create the IntelliCAD drawing.
- 5 If IntelliCAD is running in its own window, choose File > Exit.

If IntelliCAD is running within the other document (in place), click somewhere in the document outside the IntelliCAD drawing to close IntelliCAD.

- 6 To edit the IntelliCAD drawing from within the document, double-click the drawing.

TIP You can also embed an existing IntelliCAD drawing from within another document. Follow step 1 in the preceding procedure, and then click the option for creating an object from an existing file.

To embed selected IntelliCAD entities

- 1 In IntelliCAD, select the entities you want to embed.
- 2 Choose Edit > Copy (or press Ctrl+C).
- 3 Open the document in which you want to embed the entities.
- 4 Choose Edit > Paste (or the equivalent command).

To embed an entire IntelliCAD drawing

- 1 Open the document in which you want to embed the drawing.
- 2 Choose Insert > Object.
- 3 Click Create From File.
- 4 Click Browse, and then choose the file you want to embed.
- 5 Click Insert, and then click OK.

Editing an embedded IntelliCAD object in place

In many ActiveX-compatible programs you can edit an embedded IntelliCAD object without leaving the program (or container application). This is called in-place editing. A different set of IntelliCAD menus and toolbars temporarily replaces most of the menus and controls in the active window while you edit the IntelliCAD object.

To edit an embedded IntelliCAD object in place

- 1 In the container application, double-click the embedded IntelliCAD object.
A different set of IntelliCAD menus and controls appears.
- 2 Edit the IntelliCAD drawing.
- 3 Click anywhere outside the drawing window to exit the in-place editing controls.

Linking drawings

When you link an IntelliCAD drawing to another document, the other document contains only a reference to the IntelliCAD drawing file, rather than the actual drawing. You link data in a saved IntelliCAD file so that the other program can find the data and display it.

Linking works well when you want to include the same IntelliCAD data in more than one document. When you update the data, you need update it in only one location. The versions that are linked to other documents reflect the changes automatically.

Linking an IntelliCAD file to another document does not increase the file size the way embedding an IntelliCAD object does. However, links require more maintenance. To transport the data, you must make sure to transfer all linked files to the other computer.

To link an IntelliCAD file to another document

- 1 Open the drawing you want to link.

NOTE Because a link is a reference to a file, you can link only files that are saved to a location on a disk. If you haven't saved the drawing you want to link, choose *File > Save*.

- 2 In the other program, open the document in which you want to include the IntelliCAD drawing.
- 3 Choose that program's command for inserting objects.

In Microsoft® Office programs, choose *Insert > Object*. In the Object dialog box, click the *Create From File* tab. Specify the name of the drawing file you want to link. Select the *Link To File* check box, and then click *OK*.



The drawing appears in the document, with a link to the original IntelliCAD file.

Dragging IntelliCAD drawings into other programs

If the other program in which you want to include IntelliCAD drawings is compatible with ActiveX, an alternative to pasting drawings with menu commands is to drag drawing file icons from Windows Explorer into the other document. Dragging and dropping drawings does not use the Clipboard, so data on the Clipboard is not affected.

When you drag an IntelliCAD drawing file from Windows Explorer, you link or embed the entire drawing in the other document. When you drag the file, the cursor changes in response to the action you take.

How the cursor changes

Cursor appearance	Action
	Drag to embed the selected file to the other document.
	Cannot drop drawings in that document.

TIP Before you drag a drawing, position the Windows Explorer window and the other program's window so you can see the file icon and the document in which you want to drop it.

To drag and embed drawings into another document

- Select the icon for the drawing file, and then drag the drawing into the document.

Exporting drawings

You can save or export IntelliCAD drawings in a number of different formats for use with other programs. When you save a drawing in a different format, the program saves all the entities in the drawing to the new file. Or, you can choose which entities are included in the new file.

Export formats

Format	File extension	Details
AutoCAD Drawing	DWG	AutoCAD versions 2007, 2004, 2000, R14, R13, or R11/12
ASCII AutoCAD Drawing Exchange Format	DXF	AutoCAD versions 2007, 2004, 2000, R14, R13, or R11/12
Binary AutoCAD Drawing Exchange Format	DXF	AutoCAD versions 2007, 2004, 2000, R14, R13, or R11/12
Bitmap	BMP	Graphics file
Enhanced Windows Metafile	EMF	Graphics file
Windows Metafile	WMF	Graphics file
Portable Document Format	PDF	Distribute your drawing to others for using with Adobe® Acrobat® Reader® and Adobe® Acrobat
Design Web Format	DWF	Distribute your drawing to others for using with Autodesk® software and tools
Scalable Vector Graphics	SVG	Graphics file format and Web development language

You can also export ACIS solids, regions, and surfaces to an ASCII file (*.sat) that you can use in other programs.

Exporting to a DWG, DXF, BMP, EMF, WMF, or SVG file

Exporting to a file is similar to saving a standard drawing file.

To export a drawing to a DWG, DXF, BMP, EMF, WMF, or SVG file


- 1 Do one of the following:
 - Choose File > Export To File.
 - Type *export* and then press Enter.
- 2 In the Export Drawing As File dialog box, under Save As Type, choose the file format.
- 3 Specify the name of the file you want to create.
- 4 Click Save.
- 5 If the selection prompt box displays, choose the entity-selection method, and then create the selection set.
- 6 When you have finished selecting entities, press Enter.

Exporting to a PDF file

PDF files allow you to distribute your drawing to others for viewing in Adobe® Acrobat® Reader®, which is free software that users can download. PDF files can also be viewed, reviewed, and edited in Adobe® Acrobat.

To export a drawing to a PDF file

- 1 Do one of the following:
 - Choose File > Export To File.
 - Type *export* and then press Enter.
- 2 In Save As Type, choose Portable Document Format (pdf).
- 3 Specify the name of the file you want to create.
- 4 Click Save.
- 5 Choose the entity-selection method, and then create a selection set that contains the entities you want to export.
- 6 When you have finished selecting entities, press Enter.
- 7 Choose the options for how you want to export to the PDF file.
- 8 Click Export.



- A** Click to include fonts within the PDF file, otherwise system fonts are used. If selected, TrueType fonts are embedded within the exported PDF file, which can cause very large file sizes in some cases.
- B** Click to export TrueType font text as geometry instead of text.
- C** Click to export SHX font text as geometry instead of text.
- D** Click to optimize geometry processing, for example, save arcs as bezier curves instead of an enumeration of lines, save separated segments with equal ends and equal attributes as one polyline, and save rectangles as rectangles instead of four lines.
- E** Choose whether to export only the current, active layout, or all layouts in the drawing.
- F** Enter details if you want to save the information as properties for the PDF file.
- G** Enter the width and height of the paper for the layouts you are exporting. This will be the width and height of the page in the PDF file.
- H** Choose the desired unit of measure for the paper size: millimeters or inches.
- I** Select a paper size for the layouts you are exporting. This will also be the page size in the PDF file. If you want to specify your own custom paper size, choose Custom Size.
- J** Click to use the same paper size that is defined for the exported layouts. If this check box is unmarked, specify a different paper size in the Size list.

Exporting to a DWF file

DWF files allow you to publish your drawings so they can be viewed on the Internet using a Web browser. IntelliCAD exports your drawing to a Design Web Format (.dwf) file, which can be viewed in a Web browser if Autodesk® DWF Viewer is also installed on the computer. DWF Viewer is a free tool from Autodesk®.

You can export your drawing to a 2D DWF file or a 3D DWF file. 2D DWF files have smaller file sizes, but cannot be viewed in three dimensions. 3D DWF files can be viewed in three dimensions using the Autodesk® DWF Viewer, but have larger file sizes.

To export a drawing to a 2D DWF file

- 1 Do one of the following:
 - Choose File > Export To File.
 - Type *export* and then press Enter.
- 2 In Save As Type, choose Design Web Format (dwf).
- 3 Specify the name of the file you want to create.
- 4 Click Save.
- 5 Choose how you want to export:
 - **DWF File Version** — Choose the DWF file version you want. Version 4.2 can export entities on the Model tab only (no layouts). Version 5.5 can export the current layout only. Version 6.0 can export the current layout or all layouts.
 - **DWF File Format** — Choose the desired file format. Compressed binary files have a smaller file size than uncompressed binary files. ASCII files have the largest file size.
 - **Layout to Export** — Choose whether to export the current layout only, or all layouts in the drawing.
- 6 Click OK.
- 7 Choose the entity-selection method, and then create a selection set that contains the entities you want to export.
- 8 When you have finished selecting entities, press Enter.

To export a drawing to a 3D DWF file

- 1 Do one of the following:
 - Choose File > Export To File.
 - Type *export* and then press Enter.
- 2 In Save As Type, choose 3D DWF.
- 3 Specify the name of the file you want to create.
- 4 Click Save.
- 5 Choose the entity-selection method, and then create a selection set that contains the entities you want to export.
- 6 When you have finished selecting entities, press Enter.

Exporting to an ACIS file

You can export ACIS entities such as surfaces, regions, and solids to an ACIS file in ASCII (SAT) format.

To export an ACIS file

- 1 Do one of the following:
 - Choose File > Acis Out.
 - Type *acisout* and then press Enter.
- 2 Select the ACIS entities you want to save.
- 3 Specify the name of the file you want to create.
- 4 Click Save.

Sending drawings through e-mail

You can send an IntelliCAD drawing to another user via e-mail. IntelliCAD is compatible with e-mail programs that support the Messaging Application Program Interface (MAPI) protocol.

To include a drawing file in an e-mail message

- 1 While the drawing file is open, choose File > Send Mail.
If your mail program is not already running, it starts; a new e-mail message containing the IntelliCAD icon and file name appears.
- 2 Address the e-mail, type a message, and send the e-mail message as you would any other message.

To view an IntelliCAD file sent by e-mail

- Open the e-mail message, and then double-click the IntelliCAD icon.

NOTE *IntelliCAD software must be installed on the computer used to open drawings in e-mail.*

Using IntelliCAD with the Internet

You can use IntelliCAD to access the Internet and exchange drawing information and perform other tasks, including:

- Add hyperlinks to a drawing.
- Publish drawings to the Internet.
- Drag drawings (.dwg files) directly from a Web site into IntelliCAD.
- Access the Internet during a drawing session.

NOTE *You will need Internet Explorer Version 5.0 or later and access to the Internet to fully use these features.*

Add hyperlinks to a drawing


In your IntelliCAD drawings, you can include hyperlinks, which are pointers that take you to another location, such as a Web address or a file on a particular computer. You can attach a hyperlink to any entity in your drawing. Then, when you select that entity, you can open the link and jump to the specific Web address or file location. You can create *absolute* hyperlinks, which store the full path to a file, or *relative* hyperlinks, which store a partial path relative to a base folder or a Uniform Resource Locator (URL).

NOTE *To open files associated with hyperlinks, the PICKFIRST system variable must be set to On.*

To create a hyperlink

- 1 Type *hyperlink* and then press Enter.
- 2 Select an entity or entities that you would like to associate with a hyperlink; then press Enter to display the Edit Hyperlink dialog box.
- 3 Do one of the following:
 - Click Browse to specify a file.
 - In the Link to File or URL box, type a Web address.
- 4 If you want to use a common path for all hyperlinks in the drawing, select the Use relative path for hyperlinks check box. Relative paths provide flexibility if you move files to a different folder, since you can change multiple hyperlink paths at once, rather than change them all individually.

- 5 Click OK to close the Edit Hyperlink dialog box.



NOTE The *HYPERLINKBASE* system variable defines the relative path used for all hyperlinks in the current drawing. To use the default drawing path, leave the value blank by entering a period (".").

To remove a hyperlink

- 1 Type *hyperlink* and then press Enter.
- 2 Select an entity or entities with a hyperlink; then press Enter to display the Edit Hyperlink dialog box.
- 3 Click Remove Link.
- 4 Click OK to close the Edit Hyperlink dialog box.

To access a hyperlink

- 1 Select an entity with a hyperlink.
- 2 Right-click anywhere in the drawing area.
- 3 In the pop-up menu, choose Open Link.

Publishing drawings to the Internet

You can publish your drawings so they can be viewed on the Internet using a Web browser. IntelliCAD exports your drawing to a Design Web Format (.dwf) file, which can be viewed in a Web browser if DWF Viewer is also installed on the computer. DWF Viewer is a free tool from Autodesk®.

For details about creating a DWF file, see “Exporting to a DWF file” on page 470 in this chapter.

Inserting drawings from a Web site

Some Web sites are configured to allow you to drag drawings from the Web site directly into your drawing. You can drag-and-drop drawings from any Web site that supports the Autodesk® i-drop® technology.

To insert a drawing from a Web site

- 1 Open your Web browser.
- 2 Navigate to a Web site that supports Autodesk® i-drop.
- 3 Position the Web browser and IntelliCAD windows so they are both visible.
- 4 Click the drawing in your Web browser and drag it to your drawing in IntelliCAD.

The drawing file is downloaded and inserted into your drawing in IntelliCAD.

Accessing the IntelliCAD Web site during a drawing session

In addition to using hyperlinks to access the Internet, you can access a company Web site at any time. At the Web site, you can obtain company information as well as product information and news.

To access the IntelliCAD Web site

- 1 Do one of the following:
 - Choose Help > IntelliCAD on the Web.
 - Type *onweb* and then press Enter.
- 2 Navigate to the section of your choice on the IntelliCAD Web site.

Customizing IntelliCAD

You can customize IntelliCAD in a number of ways. For example, you can change the appearance of many aspects of the program and modify the existing menus and toolbars or create new ones. This section explains how to:

- Set the program's preferences.
- Customize menus and toolbars.
- Customize the keyboard.
- Create aliases for frequently used commands.
- Customize entities.
- Create and use scripts.
- Use add-on programs with IntelliCAD.
- Use a digitizer tablet for menu selection and calibrated drawing.

Topics in this chapter

<i>Setting and changing options</i>	476
<i>Customizing menus</i>	491
<i>Customizing toolbars</i>	498
<i>Customizing the keyboard</i>	508
<i>Creating aliases</i>	511
<i>Customizing entities</i>	514
<i>Creating and replaying scripts</i>	518
<i>Programming IntelliCAD</i>	521
<i>Using a digitizer tablet</i>	526

Setting and changing options

You can change many of the options that control the program's behavior and appearance, such as setting the experience level, specifying file paths and default files, and configuring display features.

Changing the options on the General tab

In the Options dialog box, the General tab contains settings for experience level and save options. You can also set VBA security.

Setting the experience level You can control which menus and tools are available by setting the experience level. You can choose from the following experience levels:

- **Beginner** Menus and toolbars display only basic commands.
- **Intermediate** Menus and toolbars display most two-dimensional entity creation and modification commands.
- **Advanced** Menus and toolbars display all available commands.

Saving your drawings automatically To avoid losing data in the event of a power failure or other system error, save your drawing files often. You can configure the program to periodically save your drawings automatically. The Minutes setting determines the interval between automatic saves. The program restarts this interval timer whenever you save the drawing file.

When AutoSave is enabled, the program creates a copy of your drawing. The file is saved in the folder specified in Options > Paths/Files for Temporary Files, with the file extension specified in the AutoSave Drawing Extension box (by default, .SV\$).

Setting the default Save As format You can control the default file format that you want to display in the Save Drawing As dialog box. For example, if you use the Save As command to save most of your drawings in a legacy file format, you can select that file format as the default so you don't have to select it each time you save a drawing using the Save As command. This setting has no effect on saving existing or new drawings using commands other than Save As — IntelliCAD always saves existing drawings in their current file format and saves new drawings with the most current file format.

Setting how drawings are opened If you regularly open drawings that contain errors or damaged data, for example, if you are a new IntelliCAD user and your original drawings were created using different CAD software, you can enable Open Drawings using Recover. This option automatically checks all drawings for errors when using the Open command, and attempts recovery, as needed. Viewing warning messages when opening drawings allows you to know which files are being fixed by IntelliCAD and what errors have occurred; however, you can also choose to hide the warnings.


Disabling VBA CommonProject macros Each time you start IntelliCAD, macros are automatically loaded for the Visual Basic Application (VBA) CommonProject. If you do not plan to use VBA, disabling the macros may improve performance. In addition, disabling the macros can enhance security if you are running IntelliCAD at a low security level.

To change the options on the General tab

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the General tab.
- 3 Under Experience level, select Beginner, Intermediate, or Advanced.
- 4 Under AutoSave, select the check box to enable the AutoSave feature, and select the frequency.

If you want to change the default extension assigned to your AutoSave files, type the new extension in AutoSave Drawing Extension.
- 5 Under Save As, select the default drawing format that displays when using the Save As command. You can always specify a different format in the Save Drawing As dialog box.
- 6 If you want to use the Recover command automatically each time you use the Open command, mark the check box for Open Drawings using Recover.

If you want to hide warnings when errors are found in a drawing, mark the check box for Hide Warnings when Opening Drawings using Recover. Errors will still be logged in an ASCII file with an .adt extension.
- 7 If you do not want the CommonProject macros to be loaded when you start IntelliCAD, under VBA Security, click the check box for Disable VBA CommonProject Macros On Startup.
- 8 When you have finished, click OK.



- | | |
|--|---|
| <p>A Click to enable AutoSave feature.</p> <p>B Select the default file format that displays when saving drawings using the Save As dialog box.</p> <p>C Select to check all drawings for errors when using the Open command, and attempt recovery, as needed.</p> <p>D Select to hide warning messages when opening drawings, if the check box Open Drawings using Recover is marked.</p> | <p>E Click to disable VBA CommonProject macros on startup. (Available if supported by your version of IntelliCAD.)</p> <p>F Type the file extension for AutoSaved files.</p> <p>G Enter frequency of AutoSave in minutes.</p> <p>H Select the experience level.</p> |
|--|---|

Changing the options on the Paths/Files tab

You can specify locations for various file types such as those used for drawings, fonts, and menus in the Options dialog box on the Paths/Files tab. You can even specify multiple paths for the same file type. In addition, you can change the names of the default system files that are used for functions such as font mapping and error logging.

Specifying the user paths

You can enter paths to your IntelliCAD directories by typing them into a Location field in the Options dialog box. This feature includes directories for drawings, fonts, help, external references, menus, hatch patterns, blocks, print style tables, print output files, temporary files, templates, and color books. IntelliCAD searches directories for support files in the following order:

- The IntelliCAD program directory.
- The current drawing directory.
- The Windows search path.
- The search path specified in the Options dialog box.

You can enter multiple paths for each item. If, for example, the Drawings item has more than one directory associated with it, you can specify multiple paths by separating them with a semicolon. IntelliCAD searches the directories in the order in which they are listed.

To specify a user path

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Paths/Files tab.
- 3 Under Location, click the item in the User Paths list whose path you want to specify, and type the path.

If you do not know the path or directory name, click Browse, and then browse to the location of the directory you want.
- 4 When you have finished, click OK.

Changing the default system files


You can change the default system files, including the log file, default template, alternate font, and font mapping file.

To change a default system file

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Paths/Files tab.
- 3 In the lower half of the dialog box, under File, click the file name for the default system file you want to change, and type in a new file name.

If you don't know the file name, click Browse, and then browse to the location of the file you want.
- 4 Type a new name.
- 5 When you have finished, click OK.

The following figure shows the Options dialog box with the User Paths and System Files sections identified.



- A** Click to select a new default file. **C** Click to select new default folder.
B Select the default file to change. **D** Directory path specified by user.

Changing the options on the Display tab

In the Options dialog box, the Display tab contains settings for displaying the command bar, IntelliCAD window, menus, and real-time view rotation.

Setting the command lines to track IntelliCAD tracks the commands and command prompts you used most recently. You can control the number of lines that the program keeps in memory as you work. The default value is 256. You can display the commands in the Prompt History window. To display the Prompt History window, press F2. To close the window, press F2 again.

Enabling Up/Down arrows in command history By default, using the keyboard arrows pans your view of the drawing. If you prefer to scroll the command history using the up and down arrows, you can mark the Use Up/Down Arrows for Command History Navigation check box. Then when you use the up and down arrows, previous commands display and the other prompt input is skipped. This can be a convenient way to review and even repeat previous commands.

Displaying tabs and scroll bars Hiding window elements if you do not use them can help increase drawing space in the IntelliCAD window.

To show or hide the Model tab and Layout tabs, select the Show Tabs check box. You may want to hide the tabs if you only work on the Model tab or if you use the command bar and status bar to switch between tabs.

To show or hide the scroll bars that display on the right side and bottom of the IntelliCAD window or viewport, select the Show Scroll Bars check box. You may want to hide the scroll bars if you only use the Pan command to scroll drawings.

Enabling continuous view rotation When you use the Real-Time Sphere command to rotate your view of entities, you typically move the mouse to rotate the view. If you want the rotation to continue after you release the mouse, turn on the Continuous Inertial Motion in Real Time check box. The rotation also continues when you use the Real-Time X, Real-Time Y, and Real-Time Z commands.

Changing the zoom direction of the mouse wheel By default when working in a drawing and using the mouse wheel, you spin the mouse wheel forward to zoom in and spin it backward to zoom out. If you want to reverse the zoom direction relative to the zoom wheel, that is, spin the wheel forward to zoom out and spin it backward to zoom in, enable the Reverse Mouse Wheel Zoom Direction check box. This can be especially helpful if you use the mouse with your left hand.


Setting the graphics screen color By default, drawings are displayed on a black background. You can change this color and specify the background screen color that you want.

Displaying prompt boxes When a command offers several options, a prompt box is displayed with those options. If you prefer to select options by typing, you can turn off the prompt boxes by clearing the Display Prompt Boxes check box.

Setting automatic menu loading The first time you start IntelliCAD, a default menu is loaded, and the Automatic Menu Loading check box in the Options dialog box is checked. The Automatic Menu Loading feature allows you to load drawings with associated menus without overwriting the default menu. You can turn off the Automatic Menu Loading option.

To change the options on the Display tab

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Display tab.
- 3 Select the options you want.
- 4 When you have finished, click OK.




- A Type or select the maximum number of command lines to track.
- B Click to show or hide the Model and Layout tabs.
- C Click to show or hide scroll bars.
- D Click to show or hide prompt boxes.
- E Click to toggle automatic menu loading on or off.
- F Select to zoom out when spinning the mouse wheel forward and zoom in when spinning the mouse wheel backward.
- G Select to continue rotating the view when using the Real-Time Sphere, Real-Time X, Real-Time Y, and Real-Time Z commands.
- H Click to select screen color.
- I Select to use Up and Down arrows for scrolling the command history instead of panning.

Changing the options on the Crosshairs tab

In the Options dialog box, on the Crosshairs tab, you can control how the crosshairs display. To help you differentiate the x-, y-, and z-axes, a different color is assigned to each. You can change the default axes colors to any color you want. In addition, you can specify the size of the crosshairs display, enable grips attraction for the cursor, and you can elect to use crosshairs as the default pointer shape.

To change the options on the Crosshairs tab

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Crosshairs tab.
- 3 Select the options you want.
- 4 When you have finished, click OK.



- | | |
|---|---|
| <p>A For each axis, click Color and select an axis color from the palette.</p> <p>B Select to always display the pointer as the crosshairs (instead of the small box).</p> <p>C Select to move the crosshairs automatically to grips within a certain range.</p> | <p>D Enter or scroll to a number for the grips attraction range. Higher points increase the range of the attraction.</p> <p>E Enter or scroll to a number for the percentage of the screen to be used by the crosshairs cursor.</p> |
|---|---|

Changing the options on the Profiles tab

IntelliCAD allows you to customize the settings that control your drawing environment, and then save and restore those settings in a profile. For example, if you prefer working with custom menus and toolbars, you can save these settings as your own profile.

Profiles can be helpful if you have multiple users with different preferences, or if you are a single user who works on various projects that require unique settings. You can even export your profile and bring it with you when you work on a different computer.

Understanding the settings saved in profiles

Profiles save many settings that control the drawing environment. Once you start using a profile, it automatically tracks and stores changes that you make to your drawing environment.

Some settings are saved immediately, but some require that you exit IntelliCAD and then start IntelliCAD again. This is because profiles save settings from your computer's registry and some settings are only saved to the registry when you exit IntelliCAD.

Settings saved in profiles

Setting	Location	When saved
Toolbar settings	Tools > Customize, Toolbars tab	Exit and restart of IntelliCAD
Menu settings	Tools > Customize, Menus tab	Immediately
Keyboard settings	Tools > Customize, Keyboard tab	Immediately
Alias settings	Tools > Customize, Aliases tab	Immediately
Window elements on/off status and their various settings	View > Command Bar View > Model and Layout Tabs View > Prompt History Window View > Scroll Bars View > Status Bar	Exit and restart of IntelliCAD
Tablet configurations	Settings > Tablet	Immediately
User paths	Tools > Options, Paths/Files tab	Immediately
System variables	Typed in command bar	Varies — some saved immediately and some upon exit and restart of IntelliCAD

Creating profiles


Create profiles if you want to save your custom drawing environment settings. This can be helpful if you have two or more drawing environments that you use regularly.

When you create a new profile, the current drawing environment settings are automatically saved with the new profile.

To create a profile

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Profiles tab.
- 3 Click Create.
- 4 Enter a name, a description (optional), and then click OK.
- 5 In the Options dialog box, click OK.
- 6 Make changes to your drawing environment.
IntelliCAD automatically saves the settings to the new profile.

NOTE *In some cases, for example, with toolbars, you need to exit and restart IntelliCAD before the settings are saved with the profile. This is because profiles save settings from your computer's registry and some settings are only saved to the registry when you exit IntelliCAD.*



- | | |
|--|---|
| A Displays the name of the currently loaded profile. | G Click to delete the selected profile. |
| B Select a profile to load it or modify it. | H Click to rename the selected profile. |
| C Displays a description of the profile. | I Click to make a copy of the selected profile. |
| D Click to restore the selected profile to the system default settings. | J Click to load the selected profile and make it the active profile. |
| E Click to open a profile stored in an .arg file. | K Click to create a new profile. |
| F Click to save the selected profile in an .arg file. | |

Loading a profile

While you work in IntelliCAD, you can load the custom settings of any profile. The current profile when you exit IntelliCAD is automatically loaded when you start IntelliCAD again.

To load a profile

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Profiles tab.
- 3 Select the desired profile.
- 4 Click Set Current.

Restoring the default settings

At any time you can return to the default drawing environment settings that were installed with IntelliCAD.

If the Default profile is unchanged, simply load it to restore the default settings. If the Default profile is deleted or changed, reset an existing profile (one that you no longer need) to replace its contents with the default settings.

To restore default settings using an unchanged Default profile

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Profiles tab.
- 3 Select the Default profile.
- 4 Click Set Current.

To restore default settings without using the Default profile

NOTE *Resetting a profile erases all of the profile's custom settings. Do this only if you are certain you no longer need the selected profile.*

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Profiles tab.
- 3 Select a profile that you no longer need; all of its custom settings will be erased. If necessary, create or copy a profile to use for restoring the default settings.
- 4 Click Reset.

Managing profiles

Once you start using profiles, you may need to rename, copy, or delete them. Copying a profile is a quick way to create a new profile based on an existing profile.

To rename a profile

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Profiles tab.
- 3 Select the profile you want to rename.
- 4 Click Rename.
- 5 Make any necessary changes to the name or description, and then click OK.

To copy a profile

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Profiles tab.
- 3 Select the profile you want to copy.
- 4 Click Copy.
- 5 Enter a new name, a description (optional), and then click OK.

To delete a profile

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Profiles tab.
- 3 Select the profile you want to delete.
- 4 Click Delete.

Working with profiles on multiple computers

If you use multiple computers and you like to work with our own drawing environment settings, save time by bringing your profile with you.

On your computer, export your profile to an .arg file. Bring the file with you to the other computer using a disk, E-mail, network, or some other method. When you start working at another computer, simply open and load your profile instead of recreating your preferred drawing environment.

To export a profile to a file

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Profiles tab.
- 3 Select the profile to export.
- 4 Click Export.
- 5 Specify a location and name for the exported file, and then click Save.

To open a profile from a file

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Profiles tab.
- 3 Click Import.
- 4 Locate and select the profile (.arg file), and then click Open.
- 5 Make any necessary changes to the name or description, and then click OK.
- 6 (Optional) To load the imported profile, select it, and then click Set Current.

Changing the options on the Printing tab

In the Options dialog box, on the Printing tab, you can determine several printing settings, including headers, footers, and print style tables.


Creating headers and footers You can include header and footer information such as a date and time stamp, your name and company name, or other information that you want to appear at the top or bottom of printed drawings. Header and footer settings are set globally for all drawings.

Specifying print style settings Print styles change the appearance of your printed drawing without modifying the actual entities in your drawing. Use the Printing tab to specify initial print style settings for new drawings created without a template and for older drawings when opened (older drawings that were created before print styles were available, for example, before AutoCAD 2000). Drawings that are already open are not affected.

For more details about print styles and print style tables, see “Using print styles” on page 379.

To change the options on the Printing tab

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
- 2 Click the Printing tab.
- 3 Select the options you want.
- 4 When you have finished, click OK.




- | | |
|---|---|
| <p>A Type the content for the header and footer, or select it from the lists.</p> <p>B Select to use color-dependent or named print style tables for new drawings created without a template.</p> <p>C Select a print style table to use with new drawings.</p> <p>D For color-dependent tables, displays BYCOLOR (not selectable); for named tables, select the print style to assign to layer zero.</p> | <p>E For color-dependent tables, displays BYCOLOR (not selectable); for named tables, select the print style to assign to new entities.</p> <p>F Click to create or change print style tables that can be selected on the Printing tab or elsewhere in IntellCAD.</p> |
|---|---|

Changing the options on the Snapping tab

In the Options dialog box, on the Snapping tab, you can control how entity snaps work, including fly-over snapping. Fly-over snapping is a visual aid to help you see and use entity snaps more efficiently.

To change the options on the Snapping tab

- 1 Do one of the following:
 - Choose Tools > Options.
 - Type *config* and then press Enter.
 - Choose Settings > Entity Snap > Entity Snap Settings and click Fly-Over.
- 2 Click the Snapping tab.
- 3 Select the options you want.
- 4 When you have finished, click OK.




- Select to display an extra image on the cursor to show which entity snap is active. (Available even if fly-over snapping is turned off.)
- Select to turn on fly-over snapping.
- Select to turn on fly-over snap tooltips, which indicate the type of snap that was used to select the marked location.
- Select to turn on the fly-over snap aperture box. Entities found within the aperture box are available for selection, making it easier to find and select entity snap points.
- Type or scroll to the tolerance size for the fly-over snap aperture box. Higher numbers increase the distance from the cursor in which entities are found.
- Type or scroll to the thickness of the fly-over snap marker.
- Type or scroll to the size of the fly-over snap marker.
- Click to choose the color of the fly-over snap marker.
- Select to turn on the display of fly-over snap markers in all views when you are using more than one viewport.
- Select to turn on fly-over snap markers, which mark snap points on entities.

Customizing menus

You can customize a current menu and save your changes as an IntelliCAD menu file. You can also load both existing IntelliCAD (*.icm) and AutoCAD (*.mnu, *.mns) menu files. You customize menus using the Customize dialog box.

To display the Customize dialog box

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Menus tab.



- | | |
|--|---|
| <p>A To make a menu item current, choose it from the list.</p> <p>B Contains the command string assigned to the current menu item.</p> <p>C Contains the text displayed in the status bar for the current menu item.</p> <p>D Click to import an existing menu file from another source.</p> <p>E Click to save the current menu to a different location.</p> | <p>F Click to reset the current menu, rejecting any changes you have made.</p> <p>G Click to display the Options dialog box for further customization options.</p> <p>H Click to add the selected command to the current menu item.</p> <p>I Click to rename the current menu item.</p> <p>J Click to insert a Menu Item, a Menu Sub-Item, a Spacer, or Context Menu Item, or a Context Menu Sub-Item.</p> |
|--|---|

Understanding menu compatibility

MNU files are menu files created by all AutoCAD releases, and MNS files are included in AutoCAD Releases 13, 14, and 2000. IntelliCAD reads both file formats, even when menu macros include AutoLISP code. This feature allows you to continue using your existing AutoCAD menus.

IntelliCAD support of specific sections in AutoCAD MNU and MNS files

Menu section	Definition	IntelliCAD support
***POPO	Cursor menu	Supported
***POP n	Pull-down menus	Supported
***AUX n	Auxiliary menus	Not supported
***BUTTON n	Button menus	Not supported
***ICON	Icon menus	Not supported
***SCREEN	Screen menus	Not supported
***TABLET n	Tablet menus	Not supported

To see how IntelliCAD reads AutoCAD menu source files

- 1 Type *menu* and then press Enter.
- 2 Under Files Of Type, select AutoCAD Menu File (mnu).
- 3 In the Open Menu dialog box, go to the AutoCAD Support folder and select the Acad.mnu file (or Acad.mns for Releases 13, 14, and 2000).
- 4 To load the AutoCAD menu file into IntelliCAD, click Open.
The IntelliCAD menu bar now looks identical to the AutoCAD menu bar.
- 5 To see how it works, choose a few commands from the menu bar, such as File > Open or Draw > Line.
- 6 To restore IntelliCAD to its default menu, choose Tools > Customize, and then click the Menus tab and click Reset.
- 7 To restore the IntelliCAD default toolbars, choose Tools > Customize, and then click the Toolbars tab and click Reset.

Creating new menus and commands

You can create a new menu by inserting a menu item at the top level of the Menu Tree. Then you can add commands to the new menu item. You can also add sub-menus and modify existing menu names and commands by adding, deleting, and rearranging them.

NOTE A green bullet in front of a menu item or command indicates that the menu item or command is available for you to use at the experience level you have set. A red bullet in front of a menu item or command indicates that the menu item or command is not available for you to use at the experience level you have set. To change your experience level, choose Tools > Options.

To create a new menu

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Menus tab.
- 3 In the Menu Tree, select the menu name above which you want to add a new menu.
- 4 Choose Insert > Menu Item.
- 5 Type a name for the new pull-down menu, and then press Enter.
- 6 Click Close.

To see the new menu, you must perform the following steps for adding a command to the menu.

To add a command to a menu

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Menus tab.
- 3 In the Menu Tree, select the menu to which you want to add the new command.
- 4 Choose Insert > Menu Sub-Item.
- 5 Type a name for the new command, and then press Enter.
- 6 Assign a command string to the command you added by doing one of the following:
 - In the Available Commands list, choose the command, and then click Add Command.
 - In the Command box, type the command string, and then click Add Command.
- 7 In the Help String box, type the text to be displayed in the status bar when the cursor is positioned over the new command.
- 8 To add another command, repeat steps 3 through 7.
- 9 When you have finished, click Close.

TIP When you type a name for a new command, you can specify an access key by including an ampersand (&) immediately preceding the letter you want to use as the access key. Be sure not to assign the same access key to more than one menu or command within a menu. For example, if you add a command named *Quick Line* to the *Insert* menu, including an ampersand immediately preceding the letter *Q* causes that letter to appear underlined in the menu. You can then select that command by displaying the menu and pressing the *Q* key.

To rename a menu item

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Menus tab.
- 3 In the Menu Tree, select the menu item you want to rename.
- 4 Click Rename.
- 5 Type a new name for the menu item by typing over the highlighted name, and then press Enter.
- 6 Click Close.

To delete a menu item

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Menus tab.
- 3 In the Menu Tree, select the menu item you want to delete.
- 4 Click Delete.
- 5 In the Confirmation dialog box, click Yes to delete the menu item.
- 6 Click Close.

NOTE Deleting a menu item that has sub-items below it in the Menu Tree also deletes all those sub-items.

Setting the experience levels for menus

You can set the experience levels for menu items you create, and you can change the experience levels for existing commands.

To set the experience levels for a command

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Menus tab.
- 3 In the Menu Tree, select the command.
- 4 Click Options.
- 5 In the Menu Customization Options dialog box, under Experience Level, select the experience levels that you want for the command.
- 6 Click OK.
- 7 Click Close.

NOTE *Select all the experience levels above the lowest level you want to use. Commands appear in the menu only at the experience levels you specify. If you select Intermediate without also selecting Advanced, the commands will appear only when you set the experience level to Intermediate.*

Saving menu files

IntelliCAD automatically saves any changes you make to the current menu. You can also create and save your custom menus. The program automatically saves all menu files with the *.icm file extension.

To save the current menu to a file

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Menus tab.
- 3 Click Export.
- 4 In the Select Menu File dialog box, specify the directory and file name you want to use to save the menu file.
- 5 Click Save.
- 6 Click Close.

NOTE *Saving a menu does not save any toolbars that you created or modified.*

Loading menu files

You can replace the current menu file with other custom menus. The program loads both AutoCAD (*.mnu, *.mns) and IntelliCAD (*.icm) menu files.

To load a menu file

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Menus tab.
- 3 Click Import.
- 4 From the Files Of Type list, choose either *.icm, *.mnu, or *.mns.
- 5 Select the menu to load.
- 6 Click Open.
- 7 Click Close.

NOTE *Loading a new menu replaces only the menu. It does not replace any custom toolbars you may have defined.*

Creating custom shortcut menus

With IntelliCAD, you can create a custom shortcut menu for commands you want to use frequently. You access the shortcut menu by holding down the Shift key and clicking the right mouse button or by clicking the mouse wheel (if you have one). Using any ASCII text editor, you construct the menu to conform to the Custom shortcut menu syntax and definitions as shown here:

```

***MENUGROUP=group_name
***POPO
**menu_name
[menu_name]
ID_item_name [item_string]command
***HELPSTRINGS
ID_item_name[help_string]

```

Shortcut menu syntax and explanations

Item	Explanation
<i>group_name</i>	Menu group name.
<i>menu_name</i>	Shortcut menu name.
<i>item_name</i>	Menu item name.

Shortcut menu syntax and explanations

Item	Explanation
<i>item_string</i>	Menu item string (typically, the command name). The menu item string appears in the shortcut menu. To specify an access key for a command, insert an ampersand (&) immediately before the letter you want to use as the access key. Do not assign the same access key to more than one command.
<i>command</i>	Command string. Begin the command string with "^C^C" (e.g., ^C^C_LINE) unless the command is transparent.
<i>help_string</i>	Help string. The text in the help string appears in the status bar when you place the cursor over the menu item.

To create a custom shortcut menu

The following example describes how to build a custom menu that includes *line*, *hatch*, *dtext*, *circle*, and *erase* commands.

- 1 Open any ASCII text editor.
- 2 Type the following characters exactly as shown here:

```

***MENUGROUP=example
***POPO
**IntelliCAD
[IntelliCAD]
ID_Line [Line]^C^C_line
ID_Hatch [Hatch]^C^C_hatch
ID_Dtext [Dtext]^C^C_dtext
ID_0 [Circle Rad]^C^C_circle
ID_Erase [erase]^C^C_erase

***HELPSTRINGS
ID_LINE [Draws a line]
ID_HATCH [Fills an enclosed area with a nonassociative hatch pattern]
ID_DTEXT [Displays text on screen as it is entered]
ID_CIRCLE [Creates a circle]
ID_ERASE [Removes objects from a drawing]

```

- 3 Save the file as *example.mnu* to the IntelliCAD 6.1 folder.

To use the custom shortcut menu

- 1 Open IntelliCAD.
- 2 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and press Enter.
- 3 Click the Menus tab.
- 4 Click Import.
- 5 Select the custom shortcut menu file.
- 6 Select the Append To Current Menu check box, and then click Open.
If you don't select this box, the custom shortcut menu deletes all current menus.
- 7 Click Close.
- 8 Select an entity in your drawing, and then hold down Shift and click the right mouse button.
- 9 Click the shortcut command that you want.

To restore the shortcut menu defaults


- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and press Enter.
- 2 Click Reset.

Customizing toolbars

IntelliCAD provides toolbars so that you can access frequently used commands. You can customize these toolbars by adding or removing tools or by rearranging the organization of tools. You can also create custom toolbars. Toolbars are saved as integral parts of the program. Although you cannot export custom toolbars for use by others, you can load toolbars created as part of AutoCAD menus. You customize toolbars using the Customize dialog box and clicking the Toolbars tab.

To display the Customize dialog box

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Toolbars tab.
- 3 Customize the toolbars using the procedures that follow the illustration here.



- A** The Categories list shows available toolbar categories.
- B** Contains the string displayed as a ToolTip for the current tool.
- C** Contains the text displayed in the status bar for the current tool.
- D** Contains the command string assigned to the current tool.
- E** Displays the available tools for the selected category.

Creating a new toolbar

You can create a new toolbar by dragging a tool from the Customize dialog box and dropping it anywhere except on another toolbar. IntelliCAD immediately creates a new toolbar and assigns it a default name. Then you can add tools to the new toolbar. You can also add, delete, or modify tools on any existing toolbar.

When you create a toolbar using tools from the Buttons area of the Customize dialog box, the ToolTip, Help String, and Command fields are filled in automatically with default information. You can edit this information for each tool.

To create a new toolbar

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Toolbars tab.
- 3 In the Categories list, choose a category to display its associated tools.
- 4 Click and drag a tool outside the Customize dialog box and onto an open area of the screen.

- 5 Modify the ToolTip, Help String, and Command fields as needed.
- 6 Click Close.

To add a tool to a toolbar

- 1 Make sure the toolbar you want to modify is visible.
- 2 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 3 Click the Toolbars tab.
- 4 In the Categories list, choose a category to display its associated tools.
- 5 Click and drag a tool onto the toolbar.
- 6 Modify the ToolTip, Help String, and Command fields as needed.
- 7 To add another tool, repeat steps 4 through 6.
- 8 Click Close.

To delete a tool from a toolbar

Make sure the toolbar you want to modify is visible.

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Toolbars tab.
- 3 Drag the tool you want to delete off of the toolbar.
- 4 Click Close.

To add space between tools on a toolbar

Make sure the toolbar you want to modify is visible.

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Toolbars tab.
- 3 On the toolbar, drag the tool away from the tool beside it.
To avoid accidentally deleting a tool, do not drag a tool more than halfway past the edge of the toolbar.
- 4 Click Close.


Naming toolbars

When you create a toolbar, the program assigns it an arbitrary name, such as ToolBar1, ToolBar2, and so on. The toolbar name is displayed on the title bar when the toolbar is floating. You can rename a toolbar at any time.

In the Select Toolbars dialog box, you can rename toolbars, turn the display of toolbars on and off, choose to display large or small tools, choose to display toolbar tools in color or black and white, and control the display of ToolTips.

To rename a toolbar

- 1 Do one of the following:
 - Choose View > Toolbars.
 - Type *tbconfig* and then press Enter.
- 2 From the Toolbars list, choose the toolbar that you want to rename.
- 3 In the Toolbar Name field, replace the current name with the new toolbar name.
- 4 Click OK.



- | | |
|--|--|
| <p>A Select to display a toolbar.</p> <p>B Choose the toolbar that you want to rename.</p> <p>C Type a new name.</p> <p>D Select to display large tools; clear to display small tools.</p> | <p>E Select to display color tools; clear to display black and white tools.</p> <p>F Select to display ToolTips; clear to not display ToolTips.</p> <p>G Click to customize the toolbars.</p> |
|--|--|

Creating flyouts

A flyout displays a set of additional tools under a single toolbar tool. IntelliCAD uses flyouts to organize related tools and to conserve space on toolbars. A flyout is indicated by a small triangle in the lower right corner of a tool. When you click a flyout tool, the other tools on the flyout extend from the original tool so you can select one of them. The flyout tool you select then becomes the default tool on the toolbar. You can add your own flyouts to toolbars.

To add a flyout to a toolbar

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Toolbars tab.
- 3 Select the Insert As Flyout check box.
- 4 In the Categories list, choose a toolbar name to display its associated tools in the Buttons area.
- 5 From the Buttons area, click and drag a tool onto a toolbar outside the Customize dialog box.
- 6 Modify the ToolTip, Help String, and Command fields as needed.
- 7 To add another flyout tool, repeat steps 4 through 6.
- 8 Click Close.

Setting the experience levels for tools

You can set the experience levels for toolbar tools you create, and you can change the experience levels for existing tools.

To set the experience levels for a tool

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Toolbars tab.
- 3 Go outside the Customize dialog box to a toolbar, and click a tool to select it.
- 4 Go back to the Customize dialog box, and click Options.
- 5 Under User Level, select the experience levels you want for that tool.
- 6 Click OK.
- 7 Click Close.

NOTE *Select all the experience levels above the lowest level you want to use. Tools appear in toolbars only at the experience levels you specify. If you select Intermediate without also selecting Advanced, the tool will appear only when you set the experience level to Intermediate.*

Creating custom toolbar tools

IntelliCAD provides tools for most of the available IntelliCAD commands. These tools appear on the Toolbars tab of the Customize dialog box. You can also create your own custom tools and incorporate them into your custom toolbars. To add a custom tool to a toolbar, you must first add one of the program's standard tools and then replace it on the toolbar with your custom tool.

You create custom tools as bitmap (*.bmp) files using any paint or illustration program capable of saving to a bitmap. Because you can configure toolbars to display either large or small tools and to display tools either in color or monochrome, create four different versions of each custom tool. Create custom tools using the following dimensions:


- Small tools: 16 x 15 pixels.
- Large tools: 24 x 22 pixels.

NOTE *If you attempt to use bitmaps that do not match these dimensions, the program will stretch or shrink (rather than crop) the bitmaps to fit the specified size. The resulting tools may not appear as originally intended.*

To add a custom tool to a toolbar

Make sure the toolbar you want to modify is visible.

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Toolbars tab.
- 3 Go outside the Customize dialog box to a toolbar, and click a tool in the toolbar to select it.
- 4 Go back to the Customize dialog box, and click Options.
- 5 In the Toolbar Customization Options dialog box, under Button Bitmaps, click the browse tool (indicated by an ellipsis) adjacent to the Small, Color Button list to display the Select Bitmap dialog box.
- 6 Select the bitmap you want to use for the small color tool.
- 7 Click Open.
- 8 Repeat steps 5 through 7 for the Large Color Button, Small Black and White Button, and Large Black and White Button versions of your custom tool.
- 9 When you have finished, click OK.
- 10 Click Close.



The Toolbar Customization Options dialog box.

Importing toolbars

Toolbars are saved as integral parts of IntelliCAD. In IntelliCAD, you can load toolbars created as part of AutoCAD (*.mnu, *.mns) menus. Importing an AutoCAD menu file from the Toolbars tab of the Customize dialog box loads only the toolbar section of the menu file.

To import a menu file

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Toolbars tab.
- 3 Click Import.
- 4 Select the menu you want to load.
- 5 Click Open.
- 6 Click Close.

NOTE Importing an AutoCAD menu file from the Toolbars tab of the Customize dialog box replaces any custom toolbars you may have defined. Importing the menu file in this way, however, does not affect the current menu.

Creating toolbars that you can share as files

With IntelliCAD, you can manually create toolbars that you can share as files with other IntelliCAD users. You create the toolbar files using any ASCII text editor and the toolbar syntax and definitions shown here:

```

***MENUGROUP=group_name

***TOOLBARS
**toolbar_name
ID_toolbar_name [_Toolbar ("toolbar_name", orient, visible, xval, yval,
rows)]
ID_button_name [_Button ("button_name", id_small, id_large)]command

***HELPSTRINGS
ID_button_name [help_string]

```

Toolbar syntax and explanations

Item	Explanation
<i>group_name</i>	Menu group name.
<i>toolbar_name</i>	Toolbar name.
<i>orient</i>	Orientation. Select Floating, Top, Bottom, Left, and Right (not case sensitive).
<i>visible</i>	Visibility. Select Show or Hide (not case sensitive).
<i>xval</i>	x coordinate, designated in pixels from left edge of screen. Suggested value: 200.
<i>yval</i>	y coordinate, designated in pixels from top edge of screen. Suggested value: 200.
<i>rows</i>	Number of rows
<i>button_name</i>	Tool name. Appears as a ToolTip when user places cursor over button.
<i>id_small</i>	Name of small (16 x 15 pixels) icon bitmap (BMP) file. This file must be located in the IntelliCAD 6.1 folder.
<i>id_large</i>	Name of large (24 x 22 pixels) icon bitmap (BMP) file. This file must be located in the IntelliCAD 6.1 folder.
<i>command</i>	Command string (Example: ^C^C_LINE).
<i>help_string</i>	Help string. Appears in the status bar when cursor passes over the button.

To create a toolbar that you can share

- 1 Open any ASCII text editor.
- 2 Type the following characters exactly as shown here:

```

***MENUGROUP=example

***TOOLBARS
**NewDraw
ID_NewDraw [_Toolbar("NewDraw ", _Bottom, _Show, 200, 200, 1)]
ID_Line_0 [_Button("Line", Iline.bmp, IL_line.bmp)]^C^C_line
ID_Hatch [_Button("Hatch", Ihatch.bmp, IL_hatch.bmp)]^C^C_hatch
ID_Dtext [_Button("Dtext", Idtext.bmp, IL_dtext.bmp)]^C^C_dtext
ID__0 [_Button("Circle Rad", Icirad.bmp, IL_cirad.bmp)]^C^Ccircle;
ID_Erase [_Button("Erase", Ierase.bmp, IL_erase.bmp)]^C^Cerase;

***HELPSTRINGS
ID_Line_0 [Creates straight line segments]
ID_Hatch [Fills an enclosed area with a nonassociative hatch pattern]
ID_Dtext [Displays text on screen as it is entered]
ID__0 [Allows user to draw a circle with a radius value]
ID_Erase [Removes objects from a drawing]

```

- 3 Save the file to the IntelliCAD folder with a *.mnu extension.

To copy an existing toolbar

Make sure the toolbar you want to copy is visible.

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and press Enter.
- 2 Click the Toolbars tab.
- 3 Go outside the Customize dialog box and select a tool on the existing toolbar that you want to copy.
- 4 Copy the information from the ToolTip, Help String, and Command boxes and paste it into the corresponding lines in the text file.
- 5 Save the file to the IntelliCAD folder with a *.mnu extension.

To open the toolbar file on another computer

- 1 Copy the toolbar (MNU) file and all related custom bitmap (*.bmp) files to the IntelliCAD folder on the other computer.
- 2 Open IntelliCAD.
- 3 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and press Enter.
- 4 Click the Toolbars tab.
- 5 Click Import.
- 6 Select the new toolbar file.
- 7 Select the Append To Current Menu check box, and then click Open.
If you don't select this box, the custom shortcut menu deletes all current menus.
- 8 Click Close.

To restore the toolbar defaults


- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and press Enter.
- 2 Click Reset.

Customizing the keyboard

IntelliCAD provides keyboard shortcuts so you can access frequently used commands. You can customize these shortcuts and add new shortcuts using the Customize dialog box.

To customize the keyboard

- Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- Click the Keyboard tab.
- To define a new shortcut key, enter the shortcut in the Press New Shortcut Key box.
- To define a new command string, enter the command string in the Command box.
- To import an existing keyboard shortcut file, click Import.
- To save a keyboard shortcut to a file, click Export.
- To add a command selected in the Available Commands pane to the shortcuts, click Add Command.
- To insert a new keyboard shortcut, click New.



A Shows shortcuts already defined.

B Displays the shortcut key combination when adding a new shortcut.

C Contains the command string assigned to the shortcut.

Creating a keyboard shortcut

You can assign macros to special keys and certain combinations of keys to create a keyboard shortcut. A macro consists of one or more commands that are displayed on the status bar as follows:

- A single command, such as QSAVE.
- A command with options, such as ARC;\A;\.
- More than one command, such as ^C^C^CZOOM;E;QSAVE;QPRINT.

Keyboard shortcuts are more powerful than aliases. An alias lets you abbreviate a single command name; a keyboard shortcut contains one or more macros. To activate a macro, you press the shortcut key; you do not need to press Enter as you do with an alias. A shortcut consists of the following keys:

- The function and the cursor control keys, as well as alphanumeric keys pressed in combination with the Ctrl, Alt, and Shift keys. The Shift key must be used in conjunction with the Ctrl, Alt, and/or function keys.
- Alphanumeric keys are those labeled A through Z and 1 through 0.
- The cursor keys are the up, down, left, and right arrows and the Page Up, Page Down, Home, End, Insert, and Delete keys.
- The function keys are those labeled F1 through F12.

To create a keyboard shortcut

1 Do one of the following:

- Choose Tools > Customize.
- Type *customize* and then press Enter.

2 Click the Keyboard tab.

3 Click New.

4 In the Press New Shortcut Key field, press Alt+A.

The program adds Alt+A to its list of Defined Keys.

5 In the Available Commands list, select Arc Center-Start-Angle.

6 Click Add Command.

The program adds the command to the Command field and enters the complete syntax for you:

```
^C^C^C_CARC;C;\A;
```

7 To save your changes and close the dialog box, click Close.

8 To activate the Arc command with the center, start, and angle options, press Alt+A.

To redefine an existing keyboard shortcut

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Keyboard tab.
- 3 In the Defined Keys list, select the shortcut you want to change.
- 4 In the Command field, change the command string assigned to the keyboard shortcut by doing one of the following:
 - Use the text cursor to delete the current command string, choose a new command in the Available Commands list, and then click Add Command.
 - Edit the command string in the Command field.
- 5 Click Close.

To delete an existing keyboard shortcut

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Keyboard tab.
- 3 In the Defined Keys list, select the shortcut you want to delete.
- 4 Click Delete.
- 5 Click Close.

Saving keyboard shortcut files

IntelliCAD automatically saves any changes you make to the current keyboard shortcuts. You can also create and save your own keyboard shortcut files. The program saves keyboard shortcut files with the *.ick file extension.

To save the current keyboard shortcuts to a file

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Keyboard tab.
- 3 Click Export.
- 4 Specify the directory and file name you want to use to save the keyboard shortcut file.
- 5 Click Save.
- 6 Click Close.

Loading keyboard shortcut files

You can replace the current keyboard shortcut file with other custom keyboard shortcut files.

To load a keyboard shortcut file

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Keyboard tab.
- 3 Click Import.
- 4 Select the file to load.
- 5 Click Open.
- 6 Click Close.

Creating aliases


IntelliCAD provides aliases for many commands. You can use aliases to issue frequently used commands by entering one or two letters rather than the entire command name.

The program also uses aliases to maintain command-name compatibility with AutoCAD. You can use the same aliases and keyboard shortcuts used by AutoCAD. In addition, IntelliCAD has enhanced several AutoCAD commands. For example, IntelliCAD added two useful options to the *rectangle* command: you can draw a rectangle as a square, and you can rotate a rectangle at an angle.

You can customize aliases, and you can add new aliases. You customize aliases using the Customize dialog box.

To display the Customize dialog box

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Aliases tab.



A Shows aliases already defined.

B Contains the current alias.

C Displays the command assigned to the current alias.

Creating, redefining, and deleting aliases

To create a new command alias, you first define the alias and then assign it one of the available IntelliCAD commands.

To create a new alias

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Aliases tab.
- 3 Click New.
- 4 In the Alias field, type the new alias.
- 5 In the Available Commands list, select the command you want to assign to the alias.
- 6 Click Assign.
- 7 Click Close.

To redefine an existing alias

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Aliases tab.
- 3 In the Aliases list, select the alias you want to change.
- 4 In the Available Commands list, select the command you want to assign to the alias.
- 5 Click Assign.
- 6 Click Close.

To delete an existing alias

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Aliases tab.
- 3 In the Aliases list, select the alias you want to delete.
- 4 Click Delete.
- 5 Click Close.

Saving alias files

IntelliCAD automatically saves any changes you make to the current aliases. You can also create and save your own alias files. The program saves alias files with the *.ica file extension. You can also save alias files for use with AutoCAD by saving the files with the *.pgp file extension.

To save the current aliases to a file

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Aliases tab.
- 3 Click Export.
- 4 From the Save As Type list, choose either *.ica or *.pgp.
- 5 Specify the directory and file name you want to use to save the alias file.
- 6 Click Save.
- 7 Click Close.

Loading alias files

You can replace the current alias file with other custom alias files. The program loads both AutoCAD (*.pgp) and IntelliCAD (*.ica) alias files.

To load an alias file

- 1 Do one of the following:
 - Choose Tools > Customize.
 - Type *customize* and then press Enter.
- 2 Click the Aliases tab.
- 3 Click Import.
- 4 From the Files Of Type list, choose either *.ica or *.pgp.
- 5 Select the alias file to load.
- 6 Click Open.
- 7 Click Close.

Customizing entities

IntelliCAD provides ways to customize entities beyond common formats, dimensions, and layers. Further customization includes using custom audio notes and using custom shape files.

Working with audio notes

In IntelliCAD you can record and attach audio notes, which are sound clips attached to entities and available for playback at any time. For example, audio notes in a factory floor plan can describe maintenance activities for specific areas of the factory and employees can play the audio notes to hear instructions.

When you include audio notes in your drawing, they are saved in the drawing file — not in a separate audio file. Note that this can increase the file size of your drawing. Audio notes created from an existing *.wav file are also saved in the drawing file and the separate *.wav file remains unchanged.


NOTE *You can play audio notes in IntelliCAD only.*

Attaching audio notes

Audio notes can be created from existing *.wav files. You can also record an audio note using any microphone that works with your computer. Many computers have a built-in microphone. If you do not have a microphone and you record an audio note, the audio note will contain no sound.


An audio note icon displays on entities that have attached audio notes. The icon is for display only and cannot be selected.

To record and attach an audio note to entities

- 1 Do one of the following:
 - Choose Tools > Audio Note.
 - On the Tools toolbar, click the Audio Note tool ().
 - Type *audionote* and then press Enter.
- 2 Select the desired entities, and then press Enter.
- 3 Choose Record.
- 4 Click Record to begin the audio note, and then speak into the microphone.
- 5 Click Stop to end the audio note.
- 6 To test the audio note, click Test, and then use Pause and Stop in the Test Audio Note area.
- 7 If necessary, you can record the audio note again. This overwrites the previous audio note for the entities you selected in Step 2.
- 8 Click Attach.

TIP *To modify an audio note after you attach it to an entity, select the entity and re-record the audio note using the previous steps.*


To attach an audio note to entities using a .wav file

- 1 Do one of the following:
 - Choose Tools > Audio Note.
 - On the Tools toolbar, click the Audio Note tool ().
 - Type *audionote* and then press Enter.
- 2 Select the desired entities, and then press Enter.
- 3 Choose Attach.
- 4 Select the desired *.wav file, and then click Open.

Selecting audio notes


Audio notes themselves cannot be selected. Instead, you select the entity that corresponds to the desired audio note.

An audio note icon displays on entities that have attached audio notes. The icon is for display only and cannot be selected.



An audio note icon displays on an entity, signifying that an audio note is attached to the entity.


To select audio notes

- 1 Do one of the following:
 - Choose Tools > Audio Note.
 - On the Tools toolbar, click the Audio Note tool ().
 - Type *audionote* and then press Enter.
- 2 Select the entity that is attached to the desired audio note, and then press Enter. You cannot select the audio note icon that displays on the entity.
- 3 Choose an option to continue working with audio notes.

TIP You can change the appearance of audio note icons using the *AUDIOICON*, *AUDIOICONCOLOR*, and *AUDIOICONSCALE* system variables.

Playing audio notes

To play audio notes


- 1 Do one of the following:
 - Choose Tools > Audio Note.
 - On the Tools toolbar, click the Audio Note tool ().
 - Type *audionote* and then press Enter.
- 2 Select the entity that has the audio note you want to play, and then press Enter.
- 3 Choose Playback.
- 4 In the Playback dialog box, do the following:
 - Click Play to begin playback.
 - To pause the audio note temporarily, click Pause and then click Resume to continue.
 - Click Stop to end playback.
- 5 Click OK.

Deleting audio notes

You can remove audio notes from selected entities. In some cases, you may want to remove extra audio notes to reduce the drawing file size.

NOTE *When you remove an audio note from an entity, the audio note is removed permanently and cannot be recovered. However, if the audio note was created using an existing *.wav file, that *.wav file is not removed.*

To delete audio notes

- 1 Do one of the following:
 - Choose Tools > Audio Note.
 - On the Tools toolbar, click the Audio Note tool ().
 - Type *audionote* and then press Enter.
- 2 Select entities that have the audio notes you want to delete, and then press Enter.
- 3 Choose Delete.

Using shape files

Shapes are entities that you define for use as drawing symbols and text fonts. You can specify the scale and rotation to use for each shape as you add it.

To use shape files, you first load the compiled shape file that defines the shape. Then you use insert shapes from the file into your drawing.

To load a shape file

- 1 Type *load* and then press Enter.
- 2 In the Load Shape File dialog box, select a shape file.
- 3 Click OK to close the Load Shape File dialog box.

To use a shape file

- 1 Type *shape* and then press Enter.
- 2 Type a shape name and press Enter.
- 3 Specify an insertion point.
- 4 Specify a height.
- 5 Specify a rotation angle.

Creating and replaying scripts

IntelliCAD can record anything you type on the keyboard and any points you select in a drawing. You can save all of these actions to a script file (with the *.scr extension) and then repeat them by replaying the script. You can use scripts for successively repeating commands, showing snapshots in a slide show, or batch printing. You can also load and run script files created for use with AutoCAD.

IntelliCAD supports most AutoCAD customization files, including menus, script files, and LISP routines. IntelliCAD uses compatible linetypes, hatch patterns, units translation, and command aliases, but you can also substitute your own files for these. This feature allows you to continue to work with your favorite customized drafting environment.

A script is a form of text file. A script file contains one line of text or other data for each action. For example, when you type a command and press Enter, it is recorded on a line in the script file. When you select a point in a drawing, the coordinate of that point is recorded on a line in the script file. You can also create script files outside IntelliCAD using a text editor (such as Microsoft® Notepad or Microsoft® WordPad) or a word-processing program (such as Microsoft® Word) that saves the file in ASCII format. The file type and extension must be .scr.


Script files can contain comments. Any line that begins with a semicolon is considered a comment. The program ignores these lines when replaying the script. The Undo feature reverses the last command performed by the script.

IntelliCAD improves on scripts, AutoLISP, and ADS by providing additional functions. For scripts, IntelliCAD includes a Script Recorder that records both command line entries and screen picks you make with your mouse.

After you activate the Script Recorder, every keyboard entry you make and any points you select in a drawing are recorded until you stop the Script Recorder. You can play back your script at any time.

CAUTION *The Script Recorder does not record your use of toolbars, menus, or dialog boxes. Using these elements while recording a script causes unpredictable results.*


To record a script

- 1 Do one of the following:
 - Choose Tools > Record Script.
 - On the Tools toolbar, click the Record Script tool ().
 - Type *rescript* and then press Enter.
- 2 Specify the name of the script file you want to create.
- 3 Click Save.
- 4 Type commands on the keyboard.


The Script Recorder records all keyboard entries and all points you select in the drawing, saving everything to the script file.

To stop recording

Do one of the following:


- Choose Tools > Stop Recording.
- On the Tools toolbar, click the Stop Recording tool ().
- Type *stopscript* and then press Enter.

To replay a script

- 1 Do one of the following:
 - Choose Tools > Run Script.
 - On the Tools toolbar, click the Run Script tool ().
 - Type *script* and then press Enter.
- 2 In the Run Script dialog box, specify the name of the script file you want to run.
- 3 Click Open.

The program immediately runs the script, performing all the actions originally recorded.

To append to a script

- 1 Do one of the following:
 - Choose Tools > Record Script.
 - On the Tools toolbar, click the Record Script tool ().
 - Type *rescript* and then press Enter.
- 2 In the Record Script dialog box, select the Append To Script check box.
- 3 Select the existing script file to append.
- 4 Click Save.
- 5 Click Yes to the prompt asking whether you want to replace the existing script.
- 6 Repeat the procedure to enter additional commands and steps.

TIP *To invoke a script automatically when you load IntelliCAD, in Windows Explorer, double-click a script file.*

Programming IntelliCAD

Another way you can customize IntelliCAD is to add custom programs written in any of several programming languages that run within IntelliCAD, including the following:

- LISP
- Visual Basic for Applications (VBA)
- ADS
- DCL
- DIESEL

In IntelliCAD, you can run many programs originally created for use with AutoCAD. Specifically, you can use programs written entirely in AutoLISP with no modification. In addition, you can run many ADS programs originally written for use with AutoCAD after first recompiling them using the IntelliCAD run-time libraries. Many AutoCAD third-party programs are compatible with IntelliCAD.

NOTE *For information about programming for IntelliCAD, see the online Help for the IntelliCAD Developer's Reference.*


Using LISP routines

IntelliCAD supports the LISP programming language and is compatible with AutoLISP, the implementation of the LISP language in AutoCAD. This means that you can load and run any AutoLISP program written for use with AutoCAD.

To load a LISP routine

Advanced experience level

- 1 Do one of the following:
 - Choose Tools > Load LISP or SDS Application.
 - Type *appload* and then press Enter.
 - Drag and drop the LISP file into IntelliCAD.
- 2 In the Load Application Files dialog box, click Add File.
- 3 Select the LISP file that you want to load, and then click Open.
- 4 Click OK.



- A** Lists the names of LISP and SDS files already loaded.
- B** Click to add a LISP or SDS file name to the list.
- C** Click to remove the highlighted file name from the list.
- D** Click to load the highlighted file.
- E** Click to unload the highlighted file.
- F** Select to save the current list to the icadload.dfs file when you click Load, Unload, or OK.

TIP You can also load a LISP routine by typing (load “d:/path/routine.lsp”) in the command bar (you must include the parentheses and the quotation marks), where d:/path is the drive and path where the LISP routine is located on your computer, and routine.lsp is the LISP routine file name.

To run a LISP routine

Advanced experience level

- 1 Do one of the following:
 - Choose Tools > Load LISP or SDS Application.
 - Type *appload* and then press Enter.
- 2 In the Load Application Files dialog box, choose the routine you want to run (make sure that it is the only one selected), and then click Load.

Some LISP routines are created in such a way that you can run them by simply typing the name of the routine, or by typing a keyword, directly in the command bar. If nothing happens when you attempt to run the LISP routine from within the Load Application Files dialog box, turn on the display of the command bar or Prompt History window by choosing View > Command Bar or View > Prompt History Window, and look for an entry that is similar to the following:

```
Loading D:\path\routine.lsp
C:KEYWORD
```

where *D:\path\routine.lsp* is the complete drive, path, and file name of the LISP routine. You may need to scroll back several lines in the command bar or Prompt History window to find the lines indicating where the LISP routine was loaded. You can run the LISP routine by typing the name of the routine or keyword appearing after the C drive designation.

For example, if you loaded a LISP routine named *drawbox.lsp* and see the designation *C:DRAWBOX* in the command bar or Prompt History window, you can run the LISP routine by typing *drawbox* in the command bar.

Using ADS applications

To write AutoCAD applications in C or C++, Autodesk® uses the ADS (AutoCAD Development System). This is an API (applications programming interface) that provides a library to access AutoCAD-specific functions and drawing data.

The equivalent in IntelliCAD is called SDS™, the Solutions Development System™. SDS is a C/C++ language interface compatible with the ADS interface in AutoCAD. Like scripts and AutoLISP, you can run your existing ADS applications in IntelliCAD. Simply recompile the source code using the SDS libraries provided on the IntelliCAD CD-ROM, or, if you use an AutoCAD program written by a third-party vendor, contact that vendor for the IntelliCAD version.

IntelliCAD provides the *Sds.H* file, which redefines ADS function names to their SDS equivalents. SDS supports the AutoCAD dialog control language (DCL), which is used by ADS to define the look of a dialog box. You can use all DCL files unmodified within SDS.

Understanding ADS compatibility

The primary difference between ADS and SDS is that all SDS functions have an `sds_` prefix, and ADS functions have a variety of prefixes, such as `ads_`, `acad_`, and `acr_x_`. The exception is dialog-related SDS functions, which have a `dlg_` prefix. IntelliCAD accepts either prefix. Other differences include the additional SDS functions listed in the following table.

SDS functions with no ADS equivalent

SDS function name	Description
<code>sds_grclear</code>	Clears all graphics from the drawing window; similar to the LISP (<code>grclear</code>) function.
<code>sds_name_clear</code>	Clears the entity name or selection set.
<code>sds_name_equal</code>	Verifies whether two entity names or selection sets are equal.
<code>sds_name_nil</code>	Verifies whether the entity name or selection set has been cleared.
<code>sds_name_set</code>	Copies one entity name or selection set to another drawing.
<code>sds_pmtssget</code>	Similar to the <code>ads_ssget</code> function, but allows you to display a prompt appropriate for the specific command, rather than the generic "Select object" prompt.
<code>sds_point_set</code>	Copies a point from one variable to another.
<code>sds_progresspercent</code>	Displays the percentage done in a progress bar.
<code>sds_progressstart</code>	Starts the progress bar.
<code>sds_progressstop</code>	Ends the progress bar.
<code>sds_readaliasfile</code>	Loads the PGP file into IntelliCAD.
<code>sds_sendmessage</code>	Sends a message to the IntelliCAD command line.
<code>sds_swapscreen</code>	Flips the off-screen device context to the display.

Some ADS functions are not supported in SDS, including: `ads_arxload`, `ads_arxloaded`, `ads_arxunload`, `ads_ssetx`, `ads_ssGetKeywordCallbackPtr`, `ads_ssGetOtherCallbackPtr`, `adsw_acadMainWnd`, and `adsw_acadDocWnd`.

For more information

- Read the online documentation for SDS functions.
- See the `\IntelliCAD\Api\Sds` folder, which contains the SDS include, header, and library files.
- See the `\IntelliCAD\Api\Dcl` folder, which contains the core DCL files.

Using DCL with IntelliCAD

IntelliCAD completely supports the AutoCAD DCL (dialog control language). DCL is used by AutoLISP functions to define the look of dialog boxes. You can use all DCL files unmodified within IntelliCAD.

Using VBA

IntelliCAD can be customized using Visual Basic for Applications (VBA) through an integrated interface, available from the IntelliCAD menu. IntelliCAD features a broad range of objects, giving you the power to write your own custom applications that can run within IntelliCAD.

To run a VBA macro

Advanced experience level

- 1 Do one of the following:
 - Choose Tools > Visual Basic > Macros.
 - Type *vbarun* and then press Enter.
- 2 In the Run IntelliCAD VBA Macro dialog box, enter the name of an existing VBA macro, and then click Run.

You can also create, delete, and edit VBA macros from this dialog box.

To edit a VBA macro

Advanced experience level

- 1 Do one of the following:
 - Choose Tools > Visual Basic > Visual Basic Editor.
 - Type *vba* and then press Enter.
- 2 Use the Visual Basic Editor to write or debug VBA macros.

For more information

- Read the online documentation for VBA, available both from the VBA Editor Help and from the IntelliCAD Help.
- Many publications are available that explain how to program in Visual Basic and how to use VBA.

Using DIESEL with IntelliCAD

IntelliCAD supports AutoCAD DIESEL (Direct Interactively Evaluated String Expression Language). DIESEL is a separate interpretive programming language that allows you to customize the following:

- Status bar
- Menus
- LISP functions

For more information

- Read the online documentation for DIESEL, available from the IntelliCAD Help.
- Several publications and tutorials are available online that explain how to use DIESEL.

Using a digitizer tablet

IntelliCAD supports tablets compatible with the TabletWorks driver and has its own tablet overlay. For instructions on installing the tablet driver and using the buttons on your pointing device, refer to your hardware documentation.

Three options are available with the Tablet command:

- **Configure** Maps the tablet overlay to the tablet itself. Configure the tablet if you plan to select IntelliCAD tools from the tablet overlay.
- **Calibrate** Maps points on the tablet, in absolute coordinates, to points on a drawing. Calibrate the tablet if you intend to digitize points. This process is convenient for tracing paper drawings.
- **Tablet ON/OFF** Turns tablet calibration (digitizer mode) on and off. Use this to switch between tool selection and digitizer input. To use the tablet for tool selection, tablet mode must be turned off.


Configuring the tablet

Before you begin to configure the tablet, slip the tablet overlay underneath the tablet's plastic cover, and align it in accordance with the directions for your tablet. If your tablet does not have a plastic cover, align the overlay holes with the pegs on your tablet.

IntelliCAD provides a default configuration for tablets measuring 12" by 12". If you choose to accept the default, be sure to verify that the commands in the grid are activated correctly. If the default alignment does not work for your tablet, you'll need to begin the configuration process again and align the tablet yourself.

To configure the tablet for menu input

- 1 Do one of the following:
 - Choose Settings > Tablet > Configure.
 - Type *tablet*, choose Configure, and then press Enter.
- 2 In response to the prompt to align the tablet, do one of the following:
 - If your tablet is 12" by 12", choose No to accept the default alignment and conclude the configuration process.
 - To align the tablet yourself, choose Yes, and then continue with step 3.
- 3 Click the tablet pointer on the upper left alignment point of the overlay (⊕).
- 4 Click the tablet pointer on the lower left alignment point of the overlay (⊕).
- 5 Click the tablet pointer on the lower right alignment point of the overlay (⊕).
- 6 Click the tablet pointer on the lower left alignment point of the Workspace area of the overlay (⊕).
- 7 Click the tablet pointer on the upper right alignment of the Workspace area of the overlay (⊕).



Click points in the order shown to configure your tablet for menu input.

To turn tablet mode on or off

- 1 Do one of the following:
 - Choose Settings > Tablet > Tablet On (or Tablet Off).
 - Type *tablet*, choose On or Off, and then press Enter.
 - Press the F4 key to toggle tablet mode on or off.
 - On the status bar, double-click TABLET to turn tablet mode on or off.

Calibrating the tablet

You must specify at least two points for tablet calibration. However, the more points you specify, the more accurate the transformation between the tablet and the screen points. Specifying additional points is particularly useful if you plan to trace a paper drawing that is not orthogonal, such as an aerial photograph.

Understanding transformation types

Depending on the number of points specified, you have a choice of transformation types to use, along with the type recommended for IntelliCAD.


Transformation refers to the calculation of the points on the screen that correspond to points you digitize on the tablet.

- **Orthogonal** Preserves all angles between lines, preserves all relative distances, and, in general, preserves shapes. If you specify only two points, an orthogonal transformation is automatically generated. The orthogonal transformation type yields the most precise mapping between the digitized points on the tablet and the corresponding points on the screen.
- **Affine** Preserves parallel lines, but not necessarily the angles between intersecting lines. If you specified three points, IntelliCAD can no longer represent this mapping as an exact orthogonal transformation. Therefore, you have a choice of an exact affine transformation or a “best fit” orthogonal transformation.
- **Projective** Does not preserve parallel lines or angles. If you specify exactly four points, you have a choice of an exact projective transformation or a “best fit” orthogonal or affine transformation.


Recommended and “best fit” transformation types

Number of points specified	Transformation type recommended	“Best fit” (approximate)
2	Orthogonal	None
3	Affine	Orthogonal
4	Projective	Orthogonal, Affine
5-10	None	Orthogonal, Affine

Choose the recommended type unless you know it will not be appropriate for what you are digitizing. The most appropriate type is not always the one with the least error; for example, you might digitize three points and select the orthogonal transformation, even though the affine transformation would yield a closer representation of your calibration entries.




Digitizing by selecting points (1, 2, 3, and 4) on the tablet.




Corresponding screen coordinates:


- 1 Coordinate specification X0, Y0, Z0
- 2 Coordinate specification X0, Y5, Z0
- 3 Coordinate specification X5, Y5, Z0
- 4 Coordinate specification X5, Y0, Z0



Screen result of orthogonal transformation after tracing polyline on tablet.



Screen result of affine transformation after tracing polyline on tablet.



Screen result of projective transformation after tracing polyline on tablet.

To calibrate your tablet for digitizing points

- 1 Do one of the following:
 - Choose Settings > Tablet > Calibrate.
 - Type *tablet*, choose Calibrate, and then press Enter.
- 2 Click a point on the tablet to define as the first calibration point.
- 3 Specify a point within the IntelliCAD drawing window to correspond to the point you digitized on the tablet, or enter coordinate values in the command bar.
- 4 Click a point on the tablet to define as the second calibration point.

Specify a point within the IntelliCAD drawing window to correspond to the point you digitized on the tablet, or enter coordinate values in the command bar. To specify more than the two points required, click a point on the tablet to define as the third calibration point. You can enter up to 10 points.
- 5 Choose the transformation type, and then press Enter.

Customizing the tablet interface

You can customize the digitizer tablet interface by using the LISP commands integrated with IntelliCAD, even if you are not familiar with LISP. For instructions, see “Customizing the Tablet Interface” in the IntelliCAD online Help.

Understanding AutoCAD compatibility

IntelliCAD was designed to interface with AutoCAD as seamlessly as possible. There are, however, some differences for which those accustomed to working in AutoCAD may need to adjust. This appendix provides information specifically for that audience.

Topics in this chapter

<i>Using enhanced AutoCAD commands in IntelliCAD</i>	<i>532</i>
<i>Using additional selection sets</i>	<i>533</i>
<i>Using additional IntelliCAD commands.....</i>	<i>534</i>
<i>Recognizing subtle command differences</i>	<i>537</i>
<i>Identifying unsupported commands and features.....</i>	<i>538</i>
<i>Identifying what does not display.....</i>	<i>539</i>
<i>Supporting AutoCAD customization</i>	<i>540</i>
<i>Understanding menu compatibility.....</i>	<i>540</i>
<i>Importing and exporting customization files</i>	<i>541</i>
<i>Programming IntelliCAD</i>	<i>542</i>
<i>IntelliCAD and AutoCAD list of terms</i>	<i>544</i>

Using enhanced AutoCAD commands in IntelliCAD

IntelliCAD enhances several AutoCAD commands by providing more options. For example, if you hold down the Shift key, IntelliCAD is placed temporarily in orthogonal mode, which you will find to be a useful feature for drawing at right angles. The following table lists examples of other commands with enhanced options.

Enhanced IntelliCAD commands

Command	Enhanced option name	Explanation
circle	Arc	Converts an arc to a circle.
donut	2point	Determines the outside diameter of a donut by two pick points.
donut	3point	Determines the outside diameter of a donut by three pick points.
donut	RadTanTan	Determines the outside diameter of a donut by tangent points.
line	Angle	Draws a line by angle, followed by a length.
line	Length	Draws a line by a length, followed by an angle.
msnapshot (mslide) and vsnapshot (vslide)	EMF	Saves and views screen images in enhanced metafile format.
msnapshot (mslide) and vsnapshot (vslide)	WMF	Saves and views screen images in Windows metafile format.
parallel (offset)	Both sides	Copies an entity parallel on both sides.
plane (solid)	Rectangle	Draws a rectangular solid at any angle.
plane (solid)	Square	Draws a square solid at any angle.
plane (solid)	Triangle	Draws an equilateral solid at any angle.
rectangle	Square	Draws a square rectangle.
rectangle	Rotated	Draws a rotated rectangle.

Using additional selection sets

IntelliCAD has additional selection-set options not found in AutoCAD. In particular, in the circle selection set, the Crossing Circle (CC), Outside Circle (OC), and Window Circle (WC) options select all entities relative to the same distance (radius) of a central pick point.

The following table lists and describes the additional selection sets in IntelliCAD.

Additional selection set options

Selection mode	Description
CC	Crossing Circle: Selects all entities within and crossing a circular area.
D	Selection method: Displays the Drawing Settings dialog box.
O	Outside Window: Selects all entities outside a rectangular area; this is the inverse of the Crossing Circle option.
OC	Outside Circle: Selects all entities outside a circular area.
OP	Outside Polygon: Selects all entities outside a polygonal area; this is the inverse of the CP (Crossing Polygon) and WP (Window Polygon) options.
PRO	Properties: Selects all entities with specific properties, such as area, color, and layer.
WC	Window Circle: Selects all entities within a circular area.

Using additional IntelliCAD commands

Although you can use the AutoCAD command structure with IntelliCAD, the program has its own set of commands. IntelliCAD has numerous command names not found in AutoCAD, although many of these commands have an equivalent function in AutoCAD. When you type the AutoCAD equivalent, the IntelliCAD alias system activates the correct command.

For example, the AutoCAD *offset* command is mapped to the IntelliCAD *parallel* command. You can type either *offset* or *parallel* in the command bar, or you can choose Modify > Parallel.

The following table lists optional IntelliCAD command names that you can use in place of AutoCAD command names to perform the equivalent AutoCAD function.

Command differences in IntelliCAD

IntelliCAD 6 command	AutoCAD 2007 command	AutoCAD 2000/R14 command	Action in IntelliCAD
audionote	No equivalent	No equivalent	Creates and plays audio notes attached to entities.
cmdbar	No equivalent	No equivalent	Positions the command window.
coordinate	Ctrl+D or F6	Ctrl+D or F6	Changes the display of coordinates on the status line.
copyedata	No equivalent	No equivalent	Copies extended entity data from one entity to another.
customize	toolbar	toolbar	Displays the Customize dialog box.
deledata	No equivalent	No equivalent	Deletes extended entity data from an entity.
delete	erase	erase	Removes entities from the drawing.
dimension	dim	dim	Switches to dimension mode.
editedata	No equivalent	No equivalent	Edits extended entity data found in an entity.
editlen	lengthen	lengthen	Changes the length of open entities.
editpline	pedit	pedit	Edits polylines and polymeshes.
entprop	ddmodify and ddchprop	ddmodify and ddchprop	Displays the Entity Properties dialog box.
esnap	-osnap	-osnap	Sets entity snaps from the command line.
expblocks	ddinsert	ddinsert	Displays the IntelliCAD Explorer - Blocks.

Command differences in IntelliCAD (continued)

IntelliCAD 6 command	AutoCAD 2007 command	AutoCAD 2000/R14 command	Action in IntelliCAD
expdimstyles	ddim	ddim	Displays the IntelliCAD Explorer - Dimension Styles.
expfonts	style	style	Displays the IntelliCAD Explorer - Styles.
explayers	layer	layer	Displays the IntelliCAD Explorer - Layers.
explorer	ddrename	ddrename	Displays the IntelliCAD Explorer.
expltypes	linetype	linetype	Displays the IntelliCAD Explorer - Linetypes.
expucs	dducs	dducs	Displays the IntelliCAD Explorer - UCS.
expviews	ddview	ddview	Displays the IntelliCAD Explorer - Views.
face	3dface	3dface	Draws three-dimensional faces with three or four vertices.
flatten	No equivalent	No equivalent	Sets thickness to zero at user-specified elevation.
font	-style	-style	Displays the Text Style dialog box.
freehand	sketch	sketch	Allows freehand sketching.
idpoint	id	id	Returns the x-, y-, and z-coordinates of a picked point.
infiline	xline	xline	Draws a line of infinite length.
join	pedit join	pedit join	Joins lines and arcs.
mesh	3dmesh	3dmesh	Draws a surface mesh.
moveedata	No equivalent	No equivalent	Moves extended entity data from one entity to another.
msnapshot	mslide	mslide	Makes an SLD, EMF, or WMF file of the current view.
orthogonal	ortho	ortho	Toggles orthogonal mode.
parallel	offset	offset	Copies an entity by a parallel offset distance.
plane	solid	solid	Draws a two-dimensional solid plane.
pmthist	F2	F2	Switches between the Prompt History window and the graphics screen.
polyline	pline	pline	Draws a polyline.
ppreview	preview	preview	Previews the print.

Command differences in IntelliCAD (continued)

IntelliCAD 6 command	AutoCAD 2007 command	AutoCAD 2000/R14 command	Action in IntelliCAD
print	plot	plot	Prints the drawing.
printstyle	plotstyle	printstyle (not applicable before AutoCAD 2000)	Assigns a print style.
psetup	No equivalent	No equivalent	Displays the Print Setup dialog box.
qprint	No equivalent	No equivalent	Quickly prints the current viewport (window) with no options.
reassocapp	No equivalent	No equivalent	Reassociates extended entity data with an application.
recscript	No equivalent	No equivalent	Starts the Script Recorder.
rtrot	3dorbit	No equivalent	Rotates the view of entities.
rtrotx	No equivalent	No equivalent	Rotates the view of entities while maintaining the x-axis.
rtroty	No equivalent	No equivalent	Rotates the view of entities while maintaining the y-axis.
rtrotz	3dorbit	No equivalent	Rotates the view of entities while maintaining the z-axis.
saveall	No equivalent	No equivalent	Saves all currently open drawings.
setcolor	ddcolor	ddcolor	Displays the Color dialog box.
setdim	ddim	ddim	Displays the Dimension Settings dialog box.
setesnap	osnap	osnap	Displays the Drawing Settings dialog box with the Coordinate Input tab displayed.
setlayer	ai_molc	ai_molc	Sets the current layer based on the selected entity's layer.
settings	No equivalent	No equivalent	Displays the Drawing Settings dialog box.
setucs	dducs	dducs	Displays the User Coordinate Systems dialog box.
setviewport	No equivalent	No equivalent	Displays the Preset Viewpoints dialog box.
stopscript	No equivalent	No equivalent	Stops running the script.
tipofday	No equivalent	No equivalent	Displays the Tip of the Day.
undelete	oops	oops	Restores the last deleted entity.
vba	vbaide	vbaide	Opens the Visual Basic Applications editor.
vbaload	vbaload	vbaload	Displays the VBA Add-In Manager dialog box.

Command differences in IntelliCAD (continued)

IntelliCAD 6 command	AutoCAD 2007 command	AutoCAD 2000/R14 command	Action in IntelliCAD
vbarun	vbarun	vbarun	Runs a VBA application.
vbaunload	vbaunload	vbaunload	Unloads one or more VBA applications.
viewctl	ddvpoint	ddvpoint	Sets the three-dimensional viewing direction via an interactive dialog box.
viewpoint	vpoint	vpoint	Sets the three-dimensional viewing direction via the command line.
vsnapshot	vslide	vslide	Displays an SLD, EMF, or WMF file in the current viewport.

Recognizing subtle command differences

The commands listed below function slightly differently in IntelliCAD than in AutoCAD.

Command function differences

IntelliCAD command	AutoCAD command	Function in IntelliCAD
cal	cal	Displays the Windows calculator.
pan	-pan	Performs a vector pan instead of a real-time pan.
zoom	-zoom	Performs a stepped zoom instead of a real-time zoom.

Identifying unsupported commands and features

A few AutoCAD commands and features are not supported in this release of IntelliCAD, as shown in the following table.

AutoCAD commands not supported by IntelliCAD

2008	<p>Features: Annotation property, Multi-line Attributes, DGN Support, Ribbon, Info Center.</p> <p>Commands: <i>annoupdate, annoreset, attipedit, autopublish, dataextraction, datalink, datalinkupdate, dimbreak, diminspect, dimjogline, dimspace, dwflayers, freeweb, freespot, +layer, layerstate, mleader</i> and <i>mleader</i>-related commands, <i>objectscale, quickcui, recoverall, renderexposure, setbylayer, targetpoint, tnavigate, and weblight</i>.</p>
2007	<p>Features: Materials property, Shadow property</p> <p>Commands: <i>camera, helix, light, loft, planar, and sweep</i></p>
2005	<p>Features: Zoom to Selection, Layer States, Tables, Fields, Trimming Hatches, and Sheet Set Manager</p> <p>Commands: <i>archive, assistclose, field, markup, netload, newsheetset, opendwfmarkup, sheetset, table</i> and <i>-table, tableedit, tableexport, tablestyle, taskbar, texttofront, tinsert, updatefield, viewplotdetails, vpmx, and vpmn</i></p>
2004	<p>Features: Gradient Fills, Ctrl + O Clean Screen, Error Reporting, Reference Manager, External Reference Notification, Background Printing, and Miscellaneous Print Style Features (Dithering, Grayscale, Screening, Adaptive, Line End Styles, Line Join Styles, Fill Styles)</p> <p>Commands: <i>3dorbitctl, jpgout, layout, pngout, publish, qnew, revcloud, tifout, toolpalettes, and xopen</i></p>
2002	<p>Features: Today window</p> <p>Commands: <i>attext, and eattext</i></p>
2000	<p>Features: Parallel Entity Snap, Viewports with UCS and Elevation Settings, AutoTrack, True Color Raster Output</p> <p>Commands: <i>3dclip, 3dcorbit, 3ddistance, 3dorbit, 3dswivel, 3dzoom, blockicon, camera, copybase, dbclose, dbconnect, dwgprops, adcclose, adcenter, adcnavigate, find, layoutwizard, model, olescale, pagesetup, partialload, partialopen, pasteblock, pasteorig, pcinwizard, plottermanager, properties, propertiesclose, psetupin, qleader, qselect, vports, refclose, refedit, refset, shademode, ucsman, vbaman, vlist, vpcip, and whohas</i></p>
R14	<p>Features: Tracking Points and Command Bar File Open</p> <p>Commands: <i>xbind, rectang, and qdim</i></p>
R13	<p>Commands: <i>arx, copylink, dsviewer, dxbin, edge, mline, mledit, treestat, and wmfopts</i></p>

AutoCAD commands not supported by IntelliCAD

Advanced
AutoCAD
modules

ACIS commands (solids modeling): *ameconvert, soldraw, solprof, solview, and stlout*

ASE commands (AutoCAD SQL extension): *aseadmin, aseexport, aselinks, aserows, aseselect, and asesqled*

Internet commands: *listurl, openurl, saveurl, and selecturl*

Landscape commands: *lsedit, lslib, and lsnew*

PostScript commands: *psdrag, psfill, psin, and psout*

Render commands: *fog, matlib, replay, saveimg, scene, setuv, showmat, stats, transparency, 3dsin, and 3dsout*

Identifying what does not display

When a drawing containing AutoCAD proxy entities is loaded into IntelliCAD, the program displays the following message: “This drawing contains one or more entities that will not display. These entities WILL be stored and saved back into the drawing.”

The following table identifies which AutoCAD objects are not displayed in IntelliCAD.

AutoCAD objects not displayed in IntelliCAD

AutoCAD object	Description
Arc aligned text	Text that is aligned along the curve of an arc.
Camera	Point at which a camera is inserted into a drawing.
Light	Point at which a light is inserted into a drawing.
Read text	Dynamically linked text that displays in a drawing but resides in an external file.
Tables	Tables display as anonymous blocks but cannot be edited.

Supporting AutoCAD customization

The following table lists and describes the ways IntelliCAD supports the AutoCAD customization files.

IntelliCAD support of AutoCAD customization files

File extension	Description
LIN	Supported: Linetypes and complex linetypes with text and shapes.
MNU and MNS	Supported: Toolbar and menu macros. Supported: ***POPO, ***POPn, and ***TOOLBAR sections. Not supported: ***TABLET, ***BUTTONS, ***SCREEN, ***AUX, and ***ICON sections.
MIN	Not supported: The multiline definition file is used by the AutoCAD <i>mline</i> command.
PAT	Supported: Hatch patterns.
PGP	Supported: Command aliases. Not supported: External commands.
PSF	Not supported: PostScript fill pattern file is used by the AutoCAD <i>psfill</i> command.
SHP and SHX	Supported: Text fonts and shapes.
SLD	Supported: Slide files.
UNT	Supported: Unit translation file used by the LISP (cvunit) and SDS sds_cvunit functions to translate values from one unit of measurement to another.

Understanding menu compatibility

MNU files are menu files created by all AutoCAD releases, and MNS files are included in AutoCAD Releases 13, 14, and 2000. IntelliCAD reads both file formats, even when menu macros include AutoLISP code. This feature allows you to continue using your existing AutoCAD menus

IntelliCAD support of specific sections in AutoCAD MNU and MNS files

Menu section	Definition	IntelliCAD support
***POPO	Cursor menu	Supported
***POPn	Pull-down menus	Supported
***AUXn	Auxiliary menus	Not supported
***BUTTONn	Button menus	Not supported
***ICON	Icon menus	Not supported
***SCREEN	Screen menus	Not supported
***TABLETn	Tablet menus	Not supported

Importing and exporting customization files

You can continue using aliases and menu files from AutoCAD by importing the appropriate file. You can import AutoCAD customization files and export IntelliCAD formats using the Customize dialog box. All of the files listed in the following table are in ASCII format, which means you can view and edit them with a text editor, such as Notepad.

Customizing files

Customization	Import file formats	Export file formats
Aliases	PGP: AutoCAD aliases ICA: IntelliCAD aliases ICA: IntelliCAD aliases	PGP: AutoCAD aliases
Keyboard	ICK: IntelliCAD keyboard	ICK: IntelliCAD keyboard
Menus	MNU: All AutoCAD menus MNS: AutoCAD R13, R14 and 2000 menus ICM: IntelliCAD menu	ICM: IntelliCAD menu
Toolbars	MNU: All AutoCAD menus	None

TIP You can manually add toolbar customizations to a MNU file. For more information, see “Customizing toolbars” on page 498.

Programming IntelliCAD

IntelliCAD supports more AutoCAD application programming interfaces (APIs) than any other software, but not all of the AutoCAD APIs are available in IntelliCAD. The following table summarizes the AutoCAD APIs IntelliCAD supports.

IntelliCAD support of the AutoCAD programming interface

AutoCAD programming interface	IntelliCAD support
Scripts (SCR files)	Supported
AutoLISP (LSP files)	Supported
Dialog Control Language (DCL files)	Supported
AutoCAD Development System (ADS)	Supported; source code must be recompiled
Visual Basic Applications (VBA)	Supported, depending on your version of IntelliCAD
Direct Interactively Evaluated String Expression Language (Diesel)	Supported
AutoCAD SQL Interface (ASI)	Not supported
Autodesk® Threaded Language Application System Toolkit (Atlast)	Not needed
AutoCAD Runtime Extension (ARx)	Not supported

Understanding AutoLISP compatibility

IntelliCAD adds LISP functionality that you will find useful. The following table lists functions that are unique to IntelliCAD LISP.

Additional IntelliCAD LISP functions

Unique LISP function	Definition
(log10)	Returns log base 10.
(lpad)	Pads a text string with spaces to the left.
(rpad)	Pads a text string with spaces to the right.
(tan)	Returns the tangent.
(trim)	Trims spaces from a string.

Not all IntelliCAD LISP functions are completely compatible with AutoLISP functions. The following table identifies IntelliCAD LISP functions that are partially compatible with AutoLISP functions.

Partially compatible LISP functions

LISP function	Description
(menucmd)	Supports <i>P0</i> (cursor menu), <i>P1</i> through <i>P16</i> (the pull-down menus), and <i>M</i> (diesel expressions), but does not support <i>A</i> (aux menus), <i>B</i> (button menus), <i>I</i> (icon menus), <i>S</i> (screen menu), or <i>T</i> (tablet menus).
(print1)	Does not support Unicode characters, such as \U+00B0 (the degree symbol) and M+Nxxxx (multi-byte Unicode sequences).
(ssget) and (ssadd)	Supports additional selection modes: CC = Crossing Circle O = Outside OC = Outside Circle OP = Outside Polygon PO = POint PRO = Properties

In addition, IntelliCAD LISP does not support all AutoLISP functions. The following areas are not supported by IntelliCAD LISP:

- (acditableupdate), (acet-attsync), (acet-layerpmode), (acet-layerp-mark), (acet-laytrans), (acet-ms-to-ps), (acet-ps-to-ms), (defun-q), (defun-q-list-ref), (defun-q-list-set), (entmakex), (initdia), (namedobjdict), (ssnamex), and (tablet)
- ARX-related functions that run ARX applications
- (dict)-related functions
- (vl)-related functions for Visual LISP
- SQL-related functions that link AutoCAD entities with external database records. These functions start with ase_, for example, (ase_lsunite) and (ase_docmp)

IntelliCAD and AutoCAD list of terms

List of terms

IntelliCAD term	Meaning for AutoCAD users
command bar	command prompt area
edit length	lengthen
entity	object
entity snap	object snap
entity snap precision	aperture
fixed attribute	constant attribute
follow	continue
freehand	sketch
hidden attribute	invisible attribute
infinite line	XLine
insert	draw
orthogonal	ortho
parallel	offset
plane	solid (2D)
predefined attribute	preset attribute
print	plot
print style	plot style
prompt box	context menu
Prompt History window	text screen
reference grid	grid
point snap	node snap
snapshot	slide (SLD)
validate attribute	verify attribute



Glossary

2D Two-dimensional locations defined by x- and y-coordinates.

3D Three-dimensional locations defined by x-, y-, and z-coordinates.

3D DWF Acronym for Three-Dimensional Design Web Format, which is a type of file that can be viewed in three dimensions using a Web browser, if Autodesk® DWF Viewer is also installed on the computer.

3D solids Three-dimensional ACIS entity.

absolute coordinates Coordinates defined in relation to the origin point of the current user coordinate system. *See also* **coordinate system**, **coordinates**, **origin**, **relative coordinates**, **user coordinate system**, and **World Coordinate System**.

ActiveX A mechanism for exchanging information between different programs whereby a copy of a source document is embedded or a pointer to a source document is linked to a target document. *See also* **embed** and **link**.

acute angles Angles of fewer than 90 degrees.

alias An abbreviation or alternative word for an IntelliCAD command.

aligned dimension A dimension aligned parallel to an entity or measuring the distance between two points at any angle.

angle The difference in direction between two nonparallel linear entities, measured in degrees or radians.

angular dimension A dimension measuring the angle between two lines or subtended by an arc.

angular unit The unit of measurement for angles. Angular units can be measured in decimal degrees, degrees/minutes/seconds, grads, and radians.

annotation Any text, dimensions, tolerances, or notes added to a drawing.

ANSI Acronym for American National Standards Institute. In the context of text, a standard character set defined by ANSI used in computer-aided drafting.

arc A segment of a circle or ellipse.

area Measurement of a planar region or the calculated space within an entity.

array Multiple copies of selected entities in a circular or rectangular pattern.

ASCII Acronym for American Standard Code for Information Interchange, a commonly used system for assigning numbers to printable alphanumeric characters, punctuation, and symbols.

attribute A component of a block containing specific text or numeric information. You can copy the information contained in an attribute from the drawing to an external database.

attribute definition An entity composed of a name, prompt for information, display characteristics, and default text that, when incorporated into a block, creates an attribute when the block is inserted into a drawing.

attribute name Text that identifies an attribute within a block.

attribute text The text containing an attribute's information within a block.

B-spline curve *See spline.*

base point A point on an entity that serves as its reference or insertion point. A point of reference when specifying relative distances.

baseline The line on which text characters appear to sit. The descenders of individual characters drop below the baseline.

baseline dimension Multiple parallel dimensions measured from the same baseline origin.

bind To convert an externally referenced drawing into a standard block definition.

blips Temporary screen markers displayed in a drawing when you select a point. Also called *marker blips*.

block One or more entities grouped together to create a single entity. *See also nested block.*

block definition The name, base point, and entities grouped together when creating a block.

boundary polyline A selected area bounded by a single closed entity or by multiple entities that intersect.

BYBLOCK A property whereby an entity inherits the color, linetype, lineweight, or print style of any block that contains it.

BYLAYER A property whereby an entity inherits the color, linetype, lineweight, or print style of its associated layer.

CAD Acronym for computer-aided design.

Cartesian coordinates Coordinates defined using three perpendicular axes (x, y, and z) to define locations in three-dimensional space. *See also cylindrical coordinates, polar coordinates, and spherical coordinates.*

center line A line used to indicate the center of a circle or an arc, usually consisting of a center mark and lines extending slightly beyond the diameter of the circle or the arc.

center mark A cross marking the center of a circle or an arc.

chamfer A beveled edge between two lines.

chord A line connecting two points on a circle or an arc.

circumference The measurement of the distance around a circle.

closed A condition whereby the start point and endpoint of an entity are the same.

color-dependent print style table A collection of print styles that determine how entities print according to their assigned color. *See* **print style table**.

comma-delimited Data that is separated by a comma to represent the end of a field.

command bar A dockable window in which you type IntelliCAD commands and view prompts and other program messages.

cone A three-dimensional entity where a vertex exists above or below the circular shape and where a surface has been applied between the vertex and the circular shape.

contiguous Connected, unbroken, or uninterrupted. Entities that share the same endpoint.

continued dimension A dimension measured from the previous extension line of an existing dimension, resulting in two or more dimensions positioned end to end.

control point A point used to define a spline.

Coons patch A surface interpolated among three or four boundary curves.

coordinate filter A function that extracts individual x-, y-, and z-coordinate values from different points to create a new composite point.

coordinate system A system of points that represents the drawing space in relation to an origin (0,0,0) and a set of axes that intersect at the origin. In two dimensions, the x- and y-axes represent horizontal and vertical directions, respectively. In three dimensions, the z-axis represents locations above and below the two-dimensional xy plane. Locations in the drawing can be represented using two-dimensional and three-dimensional rectangular (Cartesian) coordinates, two-dimensional polar coordinates, three-dimensional polar (cylindrical) coordinates, and three-dimensional spherical coordinates. *See also* **polar coordinates**, **relative coordinates**, **spherical coordinates**, **user coordinate system**, and **World Coordinate System**.

coordinates A set of values that determines a location in two-dimensional or three-dimensional space. *See also* **absolute coordinates**, **Cartesian coordinates**, **polar coordinates**, **relative coordinates**, and **spherical coordinates**.

coplanar Lying within the same plane.

- crosshairs** A cursor that consists of two or three lines that intersect at the cursor location.
- crosshatch** To fill an area with a pattern of evenly spaced perpendicular lines. *See also hatch.*
- crossing circle** An entity-selection method that selects entities contained within or crossing the boundary of a circular selection window.
- crossing polygon** An entity-selection method that selects entities contained within or crossing the boundary of a polygon selection window.
- crossing window** An entity-selection method that selects entities contained within or crossing the boundary of a rectangular selection window.
- cube** A boxed, three-dimensional, geometric shape where length, width, and height are equal.
- cursor** The insertion-point symbol on the screen. The appearance of the cursor changes based on the current task.
- curve** A smooth, continuous path made up of linear and arc segments. Curve types include arcs, splines, circles, and ellipses.
- cylindrical coordinates** Coordinates describing a point in three-dimensional space based on its distance from the origin, its angle in the xy plane, and its z-coordinate value. *See also polar coordinates and spherical coordinates.*
- datum-line dimensioning** *See ordinate dimension.*
- default** An initial or predefined setting.
- detach** To remove an external reference from a drawing. *See also external reference.*
- diameter** The distance across a circle or sphere.
- digitizer tablet** A hardware input device that incorporates an electronic pad and a hand-held pointer similar to a mouse. A digitizer tablet serves two purposes: (1) You can select tools from paper representations attached to the pad (called an overlay), providing access to all tools at once while freeing your screen space; and (2) you can input digital points into the computer that correspond to points on a paper drawing, photograph, or blueprint attached to the pad.
- dimension** A measurement, as in height or width. In the context of drafting, a set of lines, arrowheads, and text used to indicate a measurement.
- dimension style** A named group of dimension variable settings that determines the appearance of the dimension. You can save multiple dimension styles for reuse.
- dimension text** The measurement value. Dimension text can include prefixes, suffixes, tolerances, and other annotations.

dimension text rotation The angle in degrees between the x-axis and the dimension text baseline.

dimension tolerance A value specifying the allowed variation of a dimension (+ or $-n$).

dish The lower half of a sphere. *See also* **dome**.

displacement point The point to which a base, or reference, point will be relocated when moving or copying entities.

distance The measure of space between two points.

dock To position a toolbar or the command bar at the edge of the drawing window, where it locks into place. *See also* **float**.

dome The upper half of a sphere. *See also* **dish**.

donut A filled circle or flat ring created as a polyline.

drawing extents *See* **extents**.

drawing limits *See* **limits**.

drawing unit The linear measurement system used in a drawing. The user determines what a drawing unit represents, such as one inch, one centimeter, one foot, or one meter.

DWF Acronym for Design Web Format, a file format for viewing drawings in a Web browser and distributing for review using free Autodesk® software and tools.

.dwg A standard format used by CAD programs to store drawing files.

.dwt A standard format used by CAD programs to store drawing templates, which are drawings that contain predefined settings that you can use when creating a new drawing. *See also* **template**.

DXF Acronym for Drawing Exchange Format, a standard ASCII or binary file format for importing and exporting files between most CAD programs.

elevation The z value measured from the xy plane. Positive values are above the xy plane; negative values are below the xy plane.

embed A technique for exchanging information between different programs whereby a copy of the source document is stored in the target document. *See also* **ActiveX** and **link**.

EMF Acronym for Enhanced Metafile, a file format with the type and extension of .emf. It is a native internal file format of Windows 98. EMF supports both raster and vector information and 24-bit RGB color. Most Windows-based programs support this format.

endpoint The point at which a line or curve ends.

entity Any single basic item in a drawing. Entities include arcs, attributes, blocks, circles, dimensions, ellipses, elliptical arcs, infinite lines, lines, polylines, rays, and text.

entity data Any of a variety of additional information, such as text, numbers, and distances, that can be attached to drawing entities.

entity snap A technique for accurately locating and specifying key geometric points on entities, such as endpoints and midpoints of lines, and center points and tangents of arcs and circles.

entity snap override To disable or change an entity snap mode for a single input. *See also* **entity snap** and **running entity snap**.

Esnap *See* **entity snap**.

explode The conversion of a complex entity into its basic entities.

extension lines Lines extending away from an entity being dimensioned so that you can place the dimension line away from the entity. Also called *projection lines*.

extents The smallest rectangle that can contain all the entities in a drawing. Infinite lines and rays do not affect a drawing's extents. *See also* **limits**.

external reference A drawing that is linked to another drawing.

extrude The process of converting a two-dimensional entity into a three-dimensional entity by stretching (extruding) the two-dimensional entity along a straight path. Changing the thickness of a two-dimensional entity effectively extrudes it along its z-axis. *See also* **tabulated surface**.

face A planar surface defined by three or four points.

fence An entity-selection method that selects entities crossing a multisegmented line.

fillet An arc that smoothly connects the end of one line to another.

float To position a toolbar or the command bar away from the edges of the drawing window where it can be moved independently. *See also* **dock**.

freeze To suppress the display of, and ignore the entities on, a specified layer when regenerating a drawing, thus accelerating the display of the drawing. *See also* **thaw**.

grid An adjustable, regularly spaced pattern of dots on the screen, used as an aid in drawing and aligning entities. The grid is not printed.

grip A small square displayed at key positions on an entity when the entity is selected that can be used to modify the entity by clicking and dragging.

halfwidth The distance from the center of a wide polyline to its edge.

hatch To fill a selected area either with lines, crosshatching, or a hatch pattern. *See also crosshatch.*

hatch pattern A pattern, often representing a material such as steel, wood, or sand, for filling selected areas.

hidden-line removal A visualization technique in which all lines that are hidden behind other entities or surfaces from your viewpoint are clipped or removed, giving the image the appearance of a solid entity.

horizontal dimension A linear dimension measuring a horizontal distance.

infinite line A line extending infinitely in both directions.

insertion point The point where you place an entity into a particular space. A reference point by which an entity is inserted in a drawing.

intersection The point where two entities meet or cross.

isometric drawing A drawing aligned with an isometric plane.

isometric plane One of three planes representing the left, right, or top sides of an implied three-dimensional, orthogonal entity. Snap and grid points are aligned with the plane to constrain drawings.

layer The computer equivalent of overlays used in manual drafting. A tool by which drawing components can be organized into related sets, such as plumbing, framing, and electrical systems of a house, each being drawn on its own layer.

layout Similar to a sheet of paper, a representation of how a drawing will look when printed.

layout viewport A window in a Layout tab (paper space) that displays all or a portion of a drawing's model space entities. *See also paper space* and **model space**.

leader A line leading from a feature of a drawing to an annotation.

limits The user-defined boundary of a drawing, defined by its lower left and upper right corner coordinates. *See also extents.*

limits tolerance Dimension text in which the measured dimension is replaced by the largest and smallest dimensions allowed, with the upper limit displayed above the lower limit. *See also tolerance* and **variance tolerance**.

linetype The appearance of a line, defined as a solid (continuous) line or as a pattern of dashes, dots, and blank spaces.

lineweight The width of a line, defined in millimeters or inches.

link A technique for exchanging information between different programs whereby the target document maintains a pointer to the original source document. Any changes to the source document are reflected in all target documents containing links to the source. *See also ActiveX* and **embed**.

LISP Acronym for List Processing Language, a computer language invented in the late 1950s by John McCarthy for use in artificial intelligence. Because it is interpreted rather than compiled, and is relatively straightforward, it is a convenient language for users to write routines to extend the set of commands and functionality of IntelliCAD.

lock Prevents unauthorized access to drawing layers.

M direction In a polygon mesh, the direction from the first to the second row. *See also N direction.*

macro In menus and toolbars, several commands grouped together as one. Also Visual Basic for Applications code.

major axis The longest distance across an ellipse, from one end to the other. *See also minor axis.*

marker blips Temporary screen markers displayed in a drawing when you select a point. Also called *blips*.

MDI Acronym for multiple-document interface. *See multiple-document interface.*

mesh A set of connected polygon faces approximating a curved surface.

minor axis The shortest distance across an ellipse, from one side to the other. *See also major axis.*

mirror To create a reverse-image copy of selected entities by reflecting the entities symmetrically about a line or plane.

model space The primary drawing area in which you create entities. *See also paper space.*

multiple-document interface The ability to view and work with different drawings simultaneously.

N direction In a polygon mesh, the direction from the first to the second column. *See also M direction.*

named print style table A collection of print styles that determine how entities print according to the print styles you create and assign to entities and layers. *See print style table.*

named view A saved view that can be recalled at a later time by specifying its name.

nested block A block contained as part of the definition of another block. *See also block.*

nonassociative hatch A hatch that is not associated with or linked to an entity.

oblique Geometric lines or planes that are not parallel or perpendicular.

offset *See parallel.*

OLE Acronym for Object Linking and Embedding. *See* **ActiveX**.

ordinate dimension A measurement of the horizontal (x-ordinate) or vertical (y-ordinate) distance from an established reference base point or datum.

origin The intersection point of the coordinate system axes. In a Cartesian coordinate system, the origin is the point at which the x-, y-, and z-axes intersect (the 0,0,0 coordinate).

orthogonal Having perpendicular slopes or tangents at the point of intersection.

orthogonal mode (ortho) A drawing mode in which the entity creation is constrained to parallel the horizontal and vertical axes relative to the current snap angle.

orthographic projection A drafting technique by which a three-dimensional item is described in two dimensions by showing it from various directions, most commonly front, top, and side views.

outside circle An entity-selection method that selects entities falling completely outside a circular selection window.

outside polygon An entity-selection method that selects entities falling completely outside a polygon selection window.

outside window An entity-selection method that selects entities falling completely outside a rectangular selection window.

pan To shift the displayed view of a drawing without changing the magnification. *See also* **zoom**.

paper space A two-dimensional work area similar to a sheet of paper, in which you can arrange different views of your model as layout viewports. *See also* **model space**.

parallel Two or more coplanar lines that never intersect one another.

parallel dimension *See* **baseline dimension**.

PDF Acronym for Portable Document Format. PDF files can be viewed using Adobe® Acrobat Reader, which is free software that users can download; they can also be viewed, reviewed, and edited using Adobe® Acrobat.

perimeter The distance around the boundary of an entity.

perpendicular Entities at right angles to one another.

planar Entities whose extents are situated entirely within a plane.

plane Two-dimensional surface.

plan view A view of the drawing from above, looking down the z-axis perpendicular to the xy plane of the current UCS.

point A location in space specified by its x-, y-, and z-coordinates. A drawing entity consisting of a single x,y,z-coordinate location and represented by one of several symbols.

point filter *See* **coordinate filter**.

polar array Multiple copies of selected entities in a circular pattern.

polar coordinates Coordinates describing a two-dimensional point on a two-dimensional plane based on the point's distance from the origin and its angle in the plane. *See also* **Cartesian coordinates**, **coordinates**, **cylindrical coordinates**, **relative coordinates**, and **spherical coordinates**.

polygon A closed single entity with three or more sides.

polyline A drawing entity composed of one or more connected line or arc segments treated as a single entity.

print style A collection of settings, including color, pen width, linetype, and line-weight, that determine how a drawing looks when it is printed. *See* **print style table**.

print style table A collection of print styles that you can assign to the Model tab or to a Layout tab. Print style tables change how a drawing looks when you print it without modifying the actual entities. *See* **print style**.

profile File that contains your preferred drawing environment settings.

projection lines *See* **extension lines**.

prompt box A list of options displayed when a command or tool provides several choices.

Prompt History window A window containing a history of the most recent commands and prompts issued since you started the current session of IntelliCAD.

quadrant One-fourth of a circle, arc, or ellipse entity. In the context of entity snaps, the option that snaps to points on a circle, arc, or ellipse at each quadrant.

radial dimension A dimension that measures the radius of a circle or arc.

radian A unit of angular measurement; 360 degrees equals 6.283185 or 2π radians.

radius The distance from the center of a circle or sphere to its periphery.

ray A line that starts at a designated point and runs infinitely.

ray tracing A visualization technique in which rays from imaginary light sources are traced as they refract off the surfaces of a model, determining where shadows fall and how reflections on shiny materials such as metal and glass appear.

rectangle A four-sided, closed entity whereby opposite sides are equal in length.

rectangular array Multiple copies of selected entities in a rectangular pattern consisting of a specified number of columns and rows.

redo To reverse the effect of previous undo commands. *See also* **undo**.

redraw To quickly update or refresh the drawing screen display. *See also* **regenerate**.

regenerate To update or refresh the drawing screen display by recalculating the drawing from its database. *See also* **redraw**.

region A two-dimensional closed, surfaced, planar boundary.

relative coordinates Coordinates expressed in relation to a previous coordinate. *See also* **absolute coordinates**.

render A visualization technique in which all surfaces of a model are shaded as though they were illuminated from an imaginary light source located behind you as you face the screen. Rendered images are photo-realistic, having depth, shadow, reflection, and texture.

revolve Creating a three-dimensional surface entity by rotating a two-dimensional profile around an axis.

right-hand rule A visual aid for remembering the relative directions of the positive x-, y-, and z-axes of a Cartesian coordinate system and the positive rotation direction about an axis.

rotate To change the orientation of an entity, without modifying it, by repositioning it equidistant from, but at a new angle with respect to, a point or axis.

rotation angle The angle by which an entity is displaced from its original location when rotating it about a point or axis.

rubber-band line A ghosted image line that stretches dynamically on the screen with the movement of the cursor. The line extends between a fixed point and the cursor position to provide dynamic feedback.

ruled surface A three-dimensional polygon mesh that approximates a smooth surface between two entities.

running entity snap Setting an entity snap so that it continues for subsequent selections. *See also* **entity snap** and **entity snap override**.

scale To resize an entity. To draw according to the proportions of an entity.

script A set of commands stored in an ASCII script file and replayed in sequence by running the script.

SDS Acronym for Solutions Development System, a C programming interface for developing specialized programs to run inside IntelliCAD.

segment Any part of an entity bounded by two points.

selection set One or more drawing entities selected on which one can operate as a single unit.

shade To fill planar entities with solid colors for easier visualization.

snap angle The angle around which the snap grid is rotated.

snap grid An invisible grid that locks entity creation to a specified alignment and snap increment when Snap is enabled.

snap resolution The spacing between points on the snap grid.

snapshot A raster representation of the current view of one's drawing.

spherical coordinates Coordinates describing a point in three-dimensional space based on its distance from the origin, its angle in the *xy* plane, and its angle up from the *xy* plane. *See also* **Cartesian coordinates**, **coordinates**, **cylindrical coordinates**, and **polar coordinates**.

spline A curve generated along the path of three or more control points. The curve passes through the start point and endpoint, but does not necessarily pass through the intermediate control points.

status bar The bar at the bottom of the IntelliCAD window that displays information about the selected command or tool as well as the cursor coordinates, the name of the current layer, mode settings, and other information about drawing settings.

surface model A three-dimensional model consisting of both edges and the surfaces between those edges. *See also* **wire-frame model**.

surface of revolution A three-dimensional polygon mesh that approximates the surface generated by rotating a two-dimensional profile around an axis.

SVG An acronym for Scalable Vector Graphic, which is a file format for working with interactive graphics, including a Web development language.

system variable A setting or value that stores operating environment and command information (such as the drawing limits or global linetype scale factor).

tabulated surface A three-dimensional polygon mesh that approximates the surface generated by extruding a curve along a vector. *See also* **extrude**.

tangent A line that passes through a single point on a curve.

template A drawing with preset layers, linetypes, and other settings (and entities) that can be used as the basis for creating a new drawing. Templates are saved with a .dwt file extension.

text style A named, saved collection of format settings that determines the appearance of text.

thaw To redisplay a layer that was frozen. *See also* **freeze**.

thickness An entity's depth, as measured along its *z*-axis. The distance an entity is extruded above or below its elevation. *See also* **elevation** and **extrude**.

through point In creating a parallel entity, a point through which the new entity passes.

tolerance Dimension text indicating how much the actual dimension of a manufactured component can vary from the specified dimension. *See also* **limits tolerance** and **variance tolerance**.

tolerance command A command that creates a feature-control frame used in mechanical geometric dimensioning and tolerancing.

toolbar A collection of tools arranged on a palette that can be moved and resized anywhere on the screen.

torus A donut-shaped, three-dimensional entity.

transparent command A command started while another command is already active. You can use a command transparently by preceding it with an apostrophe.

true color Colors defined using 24-bit color. There are more than 16 million true colors from which you can choose.

UCS Acronym for user coordinate system. *See* **user coordinate system**.

UCS icon A user coordinate system icon that shows the orientation of the coordinate axes, the location of the coordinate system origin, and the viewing direction relative to the xy plane.

undo To reverse the effect of previous commands. *See also* **redo**.

unit *See* **drawing unit**.

unlock Free access to layers in a drawing that would be otherwise locked, thus prohibiting them from being viewed or edited by another user.

user coordinate system A Cartesian coordinate system with origins and orientation defined by the user. *See also* **World Coordinate System**.

variance tolerance Dimension text in which a plus/minus value is appended to the specified dimension to indicate how much the actual dimension of a manufactured component can vary from the specified dimension. *See also* **limits tolerance** and **tolerance**.

VBA Acronym for Visual Basic for Applications, a macro programming language embedded in programs that allows the user to customize the program.

vector A means of describing a displacement using magnitude and orientation. For example, you can create a line entity, or move an entity, by specifying an initial point, a direction, and a distance.

vertex The point of intersection of the sides of an angle. The start points or end-points of a line or arc segment in a polyline.

vertical dimension A linear dimension measuring a vertical distance.

view A representation of a drawing or portion of a drawing from a specific viewpoint in three-dimensional space.

viewpoint A location in three-dimensional space for viewing one's drafting.

viewport A window that displays all or a portion of a drawing's model space entities while in model space on the Model tab. *See also* **model space** and **paper space**.

viewport configuration A named arrangement of windows that can be saved and restored.

WCS Acronym for World Coordinate System. *See* **World Coordinate System**.

wedge A three-dimensional entity that resembles a box divided along one side from one corner to the opposite corner; for example, a doorstop or a ramp.

window circle An entity-selection method that selects entities contained entirely within a circular selection window.

window inside An entity-selection method that selects entities contained entirely within a rectangular selection window.

window polygon An entity-selection method that selects entities contained entirely within a polygon selection window.

wipeout An entity that displays with the current background color, so the details behind it do not display or print.

wire-frame model A three-dimensional model consisting of lines and curves that define the edges of a three-dimensional entity. *See also* **surface model**.

WMF Acronym for Windows metafile, a format containing vector and color information to render entities.

World Coordinate System The fixed Cartesian coordinate system used as the basis for defining other coordinate systems. *See also* **user coordinate system**.

xref *See* **external reference**.

zoom To increase or decrease the magnification of the display of a drawing. *See also* **pan**.

Symbols

- (hyphen characters) 149, 366, 367
- \$ (dollar signs) 149, 366, 367
- % (percent signs) 285
- & (ampersand character) 494
- , (commas) 165
- . (period characters) 166
- < (angle brackets) 162, 164, 165
- @ (at symbols) 260
- _ (underscore characters) 149, 366, 367
- ± (plus or minus signs) 285
- ° (degree symbols) 285

Numerics

- 0 layer 181
- 24-bit color 59
- 2D DWF files 470
- 2-dimensional drawings
 - 2-dimensional coordinate systems 159
 - coordinate systems 156
 - defined 545
 - isometric drawings 71
 - point filters 166
 - polar coordinates 162
- 2-dimensional entities
 - See also* 2-dimensional entity types; entities
 - arraying in columns or rows 248
 - extruding to create 3-dimensional entities 399–402
- 2-dimensional entity types
 - arcs 93
 - circles 91
 - donuts 107
 - ellipses 96
 - elliptical arcs 97
 - freehand sketches 103
 - infinite lines 101
 - lines 90
 - planes 119
 - point entities 98
 - polygons 110
 - polylines 104
 - rays 100
 - rectangles and squares 108
 - splines 114

- 3D Array command or tool (*3darray*) 426, 427
- 3D DWF files 470
- 3D Mirror command or tool (*mirror3d*) 428
- 3D Rotate command or tool 425
- 3D solids 399
- 3-dimensional coordinate systems 164
 - defined 545
 - specifying locations with 163
- 3-dimensional drawings
 - compared to isometric 2-dimensional drawings 71
 - coordinate system icons 157
 - coordinate systems 156, 163
 - defined 545
 - point filters 167
 - setting viewpoints 396–399
 - snapping to entity intersections 80–81, 81–82
 - user coordinate systems 168
 - wire-frame and surface models 399
- 3-dimensional entities
 - 3D solids 399
 - See also* 3-dimensional entity types; entities
 - aligning 429
 - arraying copies of entities 426–427
 - creating regions 420
 - editing 425–429, 430–441
 - hiding lines in drawings 441
 - mirroring 428
 - rotating entities 425
 - shading surfaces 442
 - thickness and elevation 399–403
- 3-dimensional entity types
 - boxes 410
 - cones 412
 - cylinders 415
 - dishes 417
 - domes 418
 - edge-defined Coons surface patch meshes 409
 - extruded surface meshes 406
 - faces 403
 - polyface meshes 405
 - pyramids 413
 - rectangular meshes 404
 - regions 420
 - revolved surface meshes 407–409

- ruled surface meshes 405
- spheres 416
- tori 419, 421
- wedges 411
- wire-frame 441
- 3-Point Arc tool 93

A

- absolute coordinates

- See also* coordinate systems; user coordinate systems (UCS); World Coordinate System (WCS)
 - defined 545
 - specifying locations with 159, 163

- absolute size of point entities 98

- access keys for commands 494

- accuracy

- drawing unit display 51
 - IntelliCAD compared to manual drafting 7–8
 - precise point locations with entity snaps 227

- ACIS solids

- boxes 410
 - combining 423
 - cones 412
 - cylinders 415
 - defined 545
 - dishes 417
 - domes 418
 - extruding 421
 - intersecting 424
 - pyramids 413
 - regions 420
 - revolving 422
 - spheres 416
 - subtracting 423
 - tetrahedrons 413
 - tori 419
 - wedges 411

- acisin* command 463

- acisout* command 471

- ActiveX

- defined 545
 - dragging drawings into other applications 466–467
 - editing linked or embedded objects 461, 465
 - linking drawings to other applications 465
 - linking objects to drawings 460–461
 - sharing drawing information and data 12

- acute angles 545

- Add To Set selection method 234

- adding

- aliases for commands 512
 - areas of entities 224
 - commands to menus 491, 493, 518
 - entities to selection sets 237
 - hyperlinks 472
 - keyboard shortcuts for commands 508
 - layouts for printing 361
 - space between tools 500
 - tools to toolbars 500

- ADS programs 3, 4, 521

- ADT files 43

- advanced experience level

- changing level 3, 32, 476
 - defines menus 32

- aliases for commands

- creating 512
 - defined 545
 - deleting 513
 - importing or exporting 513
 - redefining 513

- align* command 429

- Align command or tool (*align*) 429

- Aligned command or tool (*dimaligned*) 304

- aligned dimensions

- creating 304
 - defined 545
 - illustrated 300

- aligning coordinate systems

- with current view 170
 - with entities 168

- aligning entities 429

- aligning marker blocks on entities 221, 222

- aligning text

- on dimension lines 323
 - options 319

- alternate dimension units, controlling 332

- alternate font

- setting the default file 479

- alternate text editor 293

- ambient light 443

- American National Standards Institute (ANSI) defined 545

- American Standard Code for Information Interchange (ASCII) defined 546

- ampersand characters 494

- angle brackets 162, 164, 165
- angle drawing method
 - infinite lines 101
 - rays 100
- angles
 - angle direction and base settings 52
 - calculating angle between points 227–228
 - defined 545
 - displaying instead of coordinates 158
 - drawing unit settings 51, 549
 - specifying for arcs 93, 94, 113
 - specifying for chamfering 272
 - specifying for dimension lines 307
 - specifying for grid 69
 - specifying for lines 90
 - specifying for rotated entities 249–251
 - specifying for text styles 198
 - specifying locations by 162
 - specifying text angle in text styles 201
 - spherical and cylindrical coordinates 164
 - zero angle settings 52
- Angular command or tool (*dimangular*) 307
- angular dimensions 307, 308
 - creating 307
 - defined 545
 - formatting dimension unit display 325
- angular drawing units 545
- angularity tolerance symbol 327
- annotations
 - adding in paper space 362
 - creating as dimension text 311
 - defined 545
- ANSI character sets 295
- aperture for entity snaps 74
- apostrophes 33
- app* command modifier 34, 82
- Apparent Intersection Snap command (*apparent*) 81
- appending scripts 520
- appload* command 521, 523
- Arc command (*arc*) 93
- Arc Start-Center-Angle tool 93
- Arc Start-Center-End tool 94
- architectural
 - drawing scale ratios 53
 - drawing units 50
- arcs
 - adding lines to 90
 - angle dimensions for 307
 - center marks 301
 - converting donuts into arc entities 118
 - converting polyline segments to arcs 113
 - converting to circles 92
 - defined 545
 - diameter dimensions for 308
 - direction of 97
 - drawing methods 93
 - elliptical arcs 97
 - extending to boundaries 253
 - joining 260, 266–267
 - measuring and marking off intervals 220–223
 - moving with grips 249
 - polyline drawing methods 113
 - radius dimensions for 308
- Area command or tool (*area*) 223, 545
 - calculating areas 223
- ARG files (profiles) 488
- arranging windows 146
 - See also* views and viewports
- Array command or tool (*array*) 248
- arraying entities 246, 426, 545
- arrows and arrowheads 301, 317–319
- ASCII
 - AutoCAD files. *See* DXF files
 - defined 546
 - text files 346
- assembling master drawings 348
- assigning aliases to commands 512
- at symbol 260
- Attach Drawing tool (Blocks toolbar) 210, 214
- attaching
 - attributes to blocks 345
 - external references 349
 - raster images 449
- attachment points 279
 - See also* insertion points
- attributes
 - after exploding blocks 270
 - attaching to blocks 345
 - data in 336
 - defined 209, 546
 - definitions 342–344
 - editing definitions 344
 - extracting values 346–347
 - fixed or variable values 342

- flags 342
- invisible data 342
- names 546
- overview 342–343
- snapping to insertion points 79
- text 546
- updating values for 345
- visible or hidden 342
- Audio Note command or tool (*audionote*) 515, 516, 517
- audio note icon 516
- audio notes
 - attaching 515
 - deleting 517
 - overview 514
 - playing 517
 - selecting 516
- Audit command (*audit*) 43
- AutoCAD
 - alias files 513
 - command name compatibility 511
 - exporting IntelliCAD files as AutoCAD files 467–471
 - font compatibility 199
 - importing toolbars from menu files 504
 - IntelliCAD compatibility 3, 531
 - loading menu files 491, 496
 - script files 518
- AutoCAD Development System programs (ADS) 3, 4, 521
- AutoLISP programs 3, 4, 521–523
- automatically
 - changing code pages 296
 - loading menus 481
 - loading profiles 486
 - reloading external references 353
 - running scripts 520
 - saving drawings 476
- automating IntelliCAD functions 476
- AutoSave 476
- axes
 - changing display color 483
 - in coordinate systems 156, 159
 - in ellipse drawing methods 96
 - in elliptical arc drawing methods 97
 - rotating entities around 425

B

- background 443, 445
- background screen color 481
- Backgrounds command or tool (*backgrounds*) 445
- backward text 201, 281, 286
- base 443
- base points
 - See also* origin points
 - defined 546
 - for copying entities 242
 - for entities to be moved 248
 - for scaling entities 252
 - for stretching entities 251
- baseline
 - of text 546
 - offset in dimensions 321
 - text alignment 283
- Baseline command or tool (*dimbaseline*) 305
- baseline dimensions
 - adding to linear dimensions 302
 - angular baseline dimensions 307
 - creating 305
 - defined 546
 - illustrated 300
- basing drawings on templates 40–41
- basing layouts on templates 366
- beginner experience level
 - changing level 3, 32, 476
 - defines menus 32
 - explained 3
- best fit for dimension text and arrows 319–321
- beveled edges on entities 271–274
- binding external references 355, 546
- bisect drawing method (infinite lines or rays) 100
- BL notation in extracted attribute file fields 346
- black-and-white
 - printing 384
 - tool icons 501, 503
- blipmode* command 153
- blips
 - defined 546
 - displaying current settings 229
 - marker blips 153, 552
 - turning on or off 153
- block* command 337, 341
- Block command (IntelliCAD Explorer) 212

- Block command or tool (*ddinsert*) 338
 - Block toolbar 210
 - blocks
 - See also* Xref Manager command or tool (*xrm*)
 - as interval markers 220
 - attributes 336–342
 - Blocks list in IntelliCAD Explorer 209
 - BYBLOCK property 45–47
 - clipping 356
 - copying to other drawings 174
 - creating 212, 336–338
 - definitions 342–344
 - deleting in IntelliCAD Explorer 175
 - editing definitions 344, 345
 - entity storage in files 348
 - exploding 270, 339, 341
 - external references 348–358
 - inserting 213, 338–340
 - inserting drawings as 213
 - insertion points 79, 211–213, 338–340
 - instances of 338, 340
 - listing 209
 - multiple instances of 336, 337
 - names in extracted attribute file fields 346
 - nesting 336
 - number of occurrences 211
 - overview 209, 336
 - redefining and updating 336, 340
 - reusing blocks and drawings 10
 - rotation angle and scale 339, 340
 - saving 336–338
 - saving as drawing files 215, 337
 - search path for files 478
 - snapping to insertion points 79
 - BMP files 503
 - bodies
 - slicing and sectioning 431
 - borders on drawings 362
 - borders on images 454
 - borders on viewports
 - as available in each view 8
 - setting as invisible 369
 - bottom-aligned text 283
 - boundaries
 - extending entities to 253–256
 - setting for paragraph text 279
 - trimming or clipping entities to 256–257
 - xref clipping 356
 - Box command or tool (*box*) 410
 - Break command or tool (*break*) 259
 - breaking entities into pieces
 - exploding blocks 341
 - exploding into components 270
 - splitting into two parts 259
 - brightness of images 452
 - B-Spline curves. *See* splines
 - buttons. *See* toolbars and tools
 - BYBLOCK property
 - after exploding 270
 - colors 45–46
 - creating blocks from entities on different layers 336
 - defined 546
 - linetypes 46–47, 190–192
 - lineweights 48
 - print styles 49
 - BYLAYER property
 - colors 185
 - creating blocks from entities on different layers 336
 - defined 546
 - linetypes 46, 187–198
 - lineweights 48
- ## C
- C character
 - closing entities 161
 - in extracted attribute file fields 346
 - CAD defined 546
 - calculating areas 223
 - calculations
 - area and perimeter 223
 - distances and angles 227–228
 - in IntelliCAD and manual drafting 11–12
 - scale factors and printed size 53–54
 - callout lines. *See* leaders in dimensions
 - Cartesian coordinates
 - See also* cylindrical coordinates; polar coordinates; spherical coordinates
 - 2-dimensional coordinate systems 159
 - 3-dimensional coordinate systems 163
 - absolute and relative coordinates 160
 - defined 546
 - overview 7
 - understanding coordinate systems 156, 158
 - Cascade* command 146, 177

- CDF files 346
- center* command 77
- center lines
 - defined 547
 - for circles and arcs 301
- center marks
 - defined 547
 - for circles and arcs 301
 - formatting 321–323
- center points of entities
 - arcs 113
 - circles 91
 - dishes 417
 - domes 418
 - ellipses 96
 - elliptical arcs 97
 - polygons 110
 - snapping to 74, 76, 77
 - spheres 415
- center points of views 144
- Center Snap command (*center*) 77
- center-aligned text 283
- Center-Diameter circle method 91
- Center-Radius circle method 91
- chain dimensions. *See* continued dimensions
- Chamfer command or tool (*chamfer*) 274
- character sets for text display 295
- character string fields in extracted attribute file fields 346
- check spelling 289
- checking
 - damaged files 43
 - damaged files when opening 476
 - solids 441
- chords in arcs 93, 113, 547
- Circle Center-Radius tool 91
- Circle command (*circle*) 91
- circle diameter symbol 285
- Circle Radius-Tangent tool 92
- circles
 - See also* donuts 549
 - center marks 301
 - creating from arcs 92
 - diameter dimensions 308
 - drawing 116
 - measuring and marking off intervals 220
 - moving with grips 249
 - radius dimensions 309
- circular
 - arrays of entities. *See* polar arrays of entities
 - runout tolerance symbol 327
- circularity tolerance symbol 327
- circumferences, defined 547
- cleaning solids 440
- Clear Entity Snaps command or tool (*none*) 75, 82
- Clipboard
 - copying entities into other drawings 244
 - embedding objects into drawings 459
 - embedding objects into other applications 466
 - linking drawings into other applications 465
- clipping
 - entities 256
 - external references 356
 - raster images 455
- closed (entities), defined 547
- closing
 - polylines 112, 264
 - prompt boxes 30
 - splines 116
- coaxiality tolerance symbol 327
- codepage* command 296
- color books
 - creating 62, 65
 - current entity color 45
 - loading 66
 - selecting a color 61
 - selecting for layers 186
- Color dialog box 58, 60, 61, 180
- color-dependent print style tables
 - changing a drawing's table type 387
 - comparing with named tables 380
 - converting to named 388
 - copying, renaming, deleting 387
 - creating 384
 - default settings 488
 - defined 379
 - modifying 385
- colors
 - applying shading 442–446
 - changing in entity properties 240
 - color books 61
 - creating blocks from entities on different layers 336
 - current settings 229
 - default layer color 180
 - dimension lines 321

- dimension text 324
- displaying information about entities 228
- grip color 239
- index colors 58
- layer settings 177, 185–187
- mapping during printing 379
- multiline text 279
- overriding layer color 186
- print styles 385
- selecting entities by color 235
- solid faces 437
- status bar information 29
- text entity color 286
- true colors 59
- working with 58
- columns of entities. *See* arraying entities; rectangular arrays of entities
- combining entities
 - chamfering and filleting 271
 - finding area of combined entities 224–227
 - joining 260, 266
 - lines and arcs in polylines 112
 - solids 423
- combining zooming and panning actions 144
- Comma Delimited Format files 346, 547
- command bar
 - Command Bar command 28
 - defined 547
 - displaying or hiding 28
 - illustrated 26
 - moving 25, 28
 - navigating with arrow keys 480
 - starting commands with 33
- command strings for keyboard shortcuts 509–510
- commands
 - active commands 32
 - adding to menus 493
 - aliases 511–518
 - AutoCAD command name compatibility 511
 - deleting from menus 494
 - displaying shortcut menus 27
 - ending 32
 - experience levels 476, 495
 - information in status bar 29
 - keyboard shortcuts for 509–511
 - loading custom programs 523
 - modifying commands 34
 - mouse shortcuts for 35
 - nesting several commands 33
 - prompt boxes 30
 - renaming 494
 - repeating 33
 - Script Recorder 35
 - starting 33
 - tracking history 34, 480
- commenting
 - scripts 518
- company names on printouts 488
- complex entities
 - See also* types of entities (polylines; rectangles; donuts; and so on)
 - defined 107
 - exploding into components 270
- complex hatch patterns 127
- complex linetypes (IntelliCAD Explorer) 194
- composite solids 423
- composite tolerances 328–333
- compressing or expanding text 281, 284
- concentric entities. *See* donuts; tori
- concentricity tolerance symbol 327
- Cone command or tool (*cone*) 412
- cones 412, 547
- config* command 477
- configuring
 - code pages 296
 - IntelliCAD 475
 - layouts 361
 - print settings 373
 - printer configuration files 389
- connecting entities
 - chamfering and filleting 271
 - joining 260, 266
- constraining drawing
 - to drawing limits 56
 - to right angles 72, 73
- construction lines. *See* infinite lines
- construction planes. *See* user coordinate systems (UCS)
- contiguous (entities), defined 547
- Continue command or tool (*dimcontinue*) 306
- continued dimensions
 - adding to linear dimensions 302
 - angular continued dimensions 307
 - creating 307
 - defined 547

- illustrated 300
- continuous inertial motion 481
- CONTINUOUS linetype 46, 48, 190
- contrast of images 452
- control codes for text 285
- control points 115, 547
- convertctb* command 388
- converting
 - 2-dimensional entities to three dimensions 399
 - code pages 296
 - color-dependent print style tables 388
 - donut sides to arc entities 118
 - drawing's print style table type 387
 - entities into components 270
 - entities to other linetypes before deleting 175
 - entities to other text styles before deleting 175
 - entities to polylines 264
 - plane sides to line entities 120
 - polygon sides to line entities 111
 - polyline segments to curves 265–266
 - polyline segments to entities 113
 - rectangle sides to line entities 108
- converting arcs to circles 92
- convertptstyles* command 387, 388
- Coons Surface command or tool (*edgesurf*) 409
- Coons surface patch meshes 409, 547
- coordinate filters (point filters) 166, 547
- coordinate systems
 - 2-dimensional coordinate systems 159
 - 3-dimensional coordinate systems 163
 - absolute and relative coordinates 160
 - Cartesian coordinates 7, 156, 159, 546
 - copying to use in other drawings 174
 - cylindrical coordinates 165, 548
 - defined 547
 - deleting in IntelliCAD Explorer 175
 - icons for 157
 - listing 202–204
 - point filters 166, 168
 - polar coordinates 158, 162, 554
 - preset user coordinate systems 169
 - right-hand rule 163
 - spherical coordinates 164, 556
 - user coordinate systems 157, 168, 170, 371
 - World Coordinate System 157, 170, 202, 398, 558
- Coordinate Systems list in IntelliCAD Explorer 169, 202
- coordinates
 - See also* coordinate systems
 - defined 547
 - displaying for entities 228
 - finding point coordinates 159
 - in ordinate dimensions 309
 - of drawing limits 56
 - viewpoints in three-dimensional drawings 396
- coplanar (entities), defined 547
- Copy command or tool (*copy* or *copyclip*) 243–244
- Copy command or tool (IntelliCAD Explorer) 174–175
- copyclip* command 244
- copying
 - layers to other drawings 175
 - layouts 366
 - print style tables 387
 - profiles 487
 - settings to other drawings 174
 - solid faces 437
 - text in Prompt History window 34
- copying drawings
 - dragging into other applications 466–467
 - with external references for distribution 355
- copying entities 242–248
 - arrays of entities 246, 426–427
 - mirroring entities 246, 428
 - parallel copies 244–246
 - to other drawings 149, 244
- copying objects
 - embedding IntelliCAD data into other applications 464–465
 - embedding objects into drawings 458
 - linking drawings to other applications 465
 - linking objects to drawings 460
- corner points
 - of planes 119
 - of rectangles 108
- correcting mistakes 36
- Create Block command or tool (*block*) 337, 341
- Create Snapshot dialog box 448
- creating
 - audio notes 515
 - blocks 213
 - color books 62, 65
 - files in different formats 467
 - hyperlinks 472
 - layout viewports 368
 - print style tables 384

- printed drawings 359
 - printer configuration files 389
 - profiles 484
 - cropping
 - entities (trimming) 256, 272–274
 - external references 356
 - raster images 455
 - crosshairs
 - defined 548
 - entity snap target box 74
 - crosshatching 127, 548
 - See also* hatch patterns and hatching
 - Crossing Circle selection method 235, 548
 - Crossing Polygon selection method 235, 251, 548
 - Crossing Window selection method 234, 236, 251, 548
 - CTB files
 - assigning 383
 - changing a drawing's table type 387
 - compared with STB files 380
 - converting to STB files 388
 - creating 384
 - default settings 488
 - defined 379
 - modifying 385
 - cubes 410, 548
 - current editing session timer 230
 - current settings
 - layers 182
 - linetypes 191
 - lineweights 48
 - loading profiles 486
 - print styles 49
 - text styles 202
 - three-dimensional elevation and thickness 401
 - tools 174
 - user coordinate systems 205
 - Current tool (IntelliCAD Explorer) 202, 205
 - cursors
 - coordinate information in status bar 29
 - current position in coordinate systems 158
 - defined 548
 - entity snap cursor decoration 490
 - fly-over snap cursors 83, 490
 - magnifying glass cursor 142
 - curves. *See also* arcs; circles; ellipses; splines
 - curving polyline segments 265
 - Customize command (*customize*)
 - customizing aliases 511–518
 - customizing keyboard shortcuts 508–511
 - customizing menus 491–498
 - customizing toolbars and tools 499, 508
 - Customize dialog box
 - Aliases tab 511
 - Keyboard tab 508–511
 - Menus tab 491–498
 - Toolbars tab 498–508
 - customizing
 - IntelliCAD 36
 - text editor 293
 - customizing IntelliCAD options
 - aliases 511–518
 - coordinate systems 168
 - hatch patterns 127
 - keyboard shortcuts 508–511
 - menus 491–498
 - print settings 373
 - program settings 476–491
 - running custom programs 521–523
 - scripts for 518, 521
 - templates 40
 - toolbars and tools 25, 499
 - Cut command or tool (*cutclip*) 244
 - cutting entities
 - moving to other drawings 149
 - pasting in other drawings 244
 - Cylinder command or tool (*cylinder*) 415
 - cylinders 264, 415
 - cylindrical coordinates 165, 548
 - See also* polar coordinates; spherical coordinates
 - 159
- ## D
- data
 - attaching to blocks. *See* attributes
 - attaching to drawings 11–12
 - data fields for extracted attribute files 346–347
 - databases
 - for drawing data 138
 - using information in drawings 11
 - dates
 - date stamps on printouts 488
 - tracking time spent on drawings 230
 - ddattdef* command 342
 - ddatte* command 345

- ddattext* command 347
- ddedit* command 285, 289, 344
- ddgrips* command 239
- ddinsert* command 338
- decimal
 - degrees in angular units 51
 - drawing units 51
- decurving polyline segments 265
- default profile 486
- defaults
 - arc direction 97
 - code pages 295
 - colors 180
 - defined 548
 - drawing environment (profiles) 486
 - elevation 399
 - entity colors 45
 - icad.dwt* template 25
 - layers 175
 - linetypes 46, 180, 187
 - lineweights 48, 154, 188
 - print style table settings 488
 - print styles 49, 189
 - text styles 281
 - thickness 399
 - values for attributes 342
- Define Attributes
 - command or tool (*ddattdef*) 342
 - dialog box 342
- defining
 - complex linetypes 194–197
 - dimension styles 316
 - keyboard shortcuts 509
 - linetypes 193–198
 - lineweights 48, 154
 - print settings 373
 - text styles 199
 - user coordinate systems 168, 204
- definition points 302
- degree symbols 285
- Delete command or tool (*delete*) 242
- Delete command or tool (IntelliCAD Explorer) 176
- deleting
 - aliases 513
 - audio notes 517
 - clipping boundary 357, 455
 - commands from menus 494
 - custom programs 522
 - dimension styles 317
 - elements in IntelliCAD Explorer 175–177
 - entities 242
 - external references 352
 - freehand sketches 104
 - hyperlinks 473
 - images 458
 - keyboard shortcuts 510
 - layouts 367
 - lines in 3-dimensional entities 441–443
 - print style tables 387
 - profiles 487
 - segments of polylines 112
 - solid faces 436
 - xref clipping 358
- delta distances, calculating 227
- density of mesh surfaces 406, 407, 408, 409
- descenders on text characters 283
- deselecting entities 238
- Design Web Format
 - exporting 462, 470
 - importing 462
 - opening files 41
- detaching external references 548
 - See also* Xref Manager command or tool (*xrm*)
- Details tool (Block toolbar) 210
- Diameter command or tool (*dimdiameter*) 308
- diameter dimensions
 - creating 308
 - defined 548
 - illustrated 300
- diameters
 - circles 308
 - donuts 117
- DIESEL programs 525
- dimaligned* command 304
- dimangular* command 307
- dimbaseline* command 305
- dimcontinue* command 306
- dimdiameter* command 308
- dimedit* command
 - obliquing dimensions 313
 - replacing dimension text with new text 315
 - restoring dimension text to home position 315
 - rotating dimension text 314
- dimension lines 323

- See also* dimension text; dimensions and dimension styles; extension line
 - aligning text on 323
 - defined 300, 548
- Dimension Settings command or tool (*setdim*)
 - arrows and arrowheads 318, 320
 - baseline dimension offset 305
 - creating, renaming, or deleting dimension styles 316
 - dimension line colors 321
 - formatting and positioning dimension text 319, 323
 - rounding off numbers 325
- Dimension Settings dialog box
 - Arrows tab 318–319
 - Format tab 319
 - Lines tab 321
 - Text tab 323
 - Units tab 325–327
- Dimension Style command 316
- Dimension Styles (IntelliCAD Explorer) 216
- dimension text
 - aligning on lines 323
 - defined 313, 548, 549
 - formatting and positioning text 313–315, 319–321, 323–325
 - overview 301
 - replacing dimension text with new text 315
 - restoring dimension text to home position 315
 - rotating dimension text 313
- dimension tolerance
 - controlling 330
- dimension units, alternate 332
- dimensions and dimension styles
 - See also* dimension text
 - aligned dimensions 304
 - angular dimensions 307–308
 - arrows and arrowheads 317
 - baseline dimensions 305
 - creating dimensions 302–313
 - creating or deleting styles 316
 - diameter dimensions 308
 - dimension styles defined 300, 316–327
 - dimension variables 316, 549
 - dimensions defined 548
 - extension lines 301
 - in paper space 312
 - leaders and annotations 301, 311
 - line colors 321
 - line formats 321
 - linear dimensions 302–307
 - obliquing 313
 - ordinate dimensions 309
 - overview 300–302
 - radius dimensions 309
 - renaming styles 317
 - types of dimensions 300
 - units and rounding 325–327
- dimleader* command 311
- dimlinear* command 303
- dimordinate* command 310
- dimradius* command 309
- dimtedit* command 314
- directory paths for files 478
- disabling. *See* turning features on or off
- Dish command or tool (*dish*) 417, 549
- disk space requirements for IntelliCAD 24
- displacement points
 - defined 549
 - for copying entities 242
 - for moving entities 248
 - for stretching entities 251
- displaying
 - audio note icons 516
 - command bar 28
 - drawing information 228
 - embedded files as icons 459
 - entire drawings 145
 - layers 182–184
 - lineweights 154
 - lists of text styles 282
 - memory-intensive display elements 151
 - Model and Layout tabs 365, 480
 - multiple views of drawings. *See also* views and viewports 146
 - online Help 37
 - plan view of user coordinate systems 170
 - point entities 98
 - Prompt History window 34
 - reference grid 66
 - rotated views 141
 - scroll bars 481
 - shortcut menus 27
 - snapshots 449
 - text 295
 - text as boxes 151

- toolbars 27
 - ToolTips 27
 - warning messages 476
 - xref clipping boundaries 358
- Distance command or tool (*distance*) 227
- Distance-Angle chamfer method 272–273
- Distance-Distance chamfer method 272
- distances
 - calculating between points 227
 - defined 549
 - displaying instead of coordinates 158
 - specifying in chamfering 272
 - specifying locations by 162
 - spherical and cylindrical coordinates 163, 165
- distant lighting 443
- Divide command (*divide*) 220, 222
- dividing display into multiple views. *See* views and viewports
- dividing entities into equal segments 220
- docking
 - defined 549
 - toolbars and command bar 25–29
- dollar signs 149, 366, 367
- Dome command or tool (*dome*) 418, 549
- Donut command or tool (*donut*) 117
- donuts
 - 3-dimensional donuts (tori) 419, 421
 - converting sides to arc entities 118
 - defined 549
 - drawing 117
 - editing 264
 - filled or outlined 118
- dots
 - in linetypes 193
 - point entities 98
- doughnuts. *See* donuts 549
- draft quality images 454
- drafting manually compared to IntelliCAD 5–13
- dragging
 - drawings from the Internet 474
 - drawings into other applications 466–467
 - moving entities with grips 249
 - new tools to toolbars 500
- Draw 2D toolbar 27
- Draw Freehand tool 103
- Draw Order command or tool (*draworder*) 250
- Draw Orthogonal tool 72, 73
- Draw Point command (*point*) 98
- drawing code page 295
- drawing entities
 - 3-dimensional faces 403
 - arcs 93
 - boxes 410
 - circles 116
 - cylinders 415
 - dishes 417
 - domes 418
 - donuts 117
 - edge-defined Coons surface patch meshes 409
 - ellipses 96
 - elliptical arcs 97
 - extruded surface meshes 407
 - freehand sketching 103
 - hatching entities 127
 - lines 90
 - planes 119
 - point entities 98
 - polyface meshes 405
 - polygons 110
 - polylines 111
 - pyramids 413
 - rays 100
 - rectangles 108
 - rectangular meshes 404
 - rendering 443
 - revolved surface meshes 407
 - ruled surface meshes 406
 - shading 442, 555
 - spheres 416
 - splines 114
 - squares 108
 - tori 419
 - wedges 411
 - wipeouts 121
- drawing environment settings 484–488
- Drawing Exchange Format files 346, 467–471, 549
- Drawing Settings command or tool (*settings*)
 - Blips display 153
 - coordinate display in status bar 158
 - drawing limits 56–66
 - drawing units 50–53
 - elevation and thickness settings 401
 - entity snap target box 74
 - freehand sketch settings 103

- grid rotation 69
- grid settings 66–71
- grip display options 239
- highlighting entities 234
- highlighting settings 153
- isometric snap and grid 71
- linetype scale settings 47–50
- linetype settings 46
- lineweight settings 48
- mesh surface settings 405, 407
- orthogonal setting 72
- point entity display 98
- polar tracking setting 73
- Quick Text feature 152
- shaded surface settings 442
- snap angle settings 70
- snap spacing settings 69
- text height settings 54
- Drawing Settings dialog box - 3D Settings tab
 - elevation and thickness settings 401
 - mesh surface settings 407
 - shaded surface settings 442
- Drawing Settings dialog box - Coordinate Input tab
 - drawing limits 56
 - entity snap settings 75
 - entity snap target box 75
 - grid rotation 69
 - grid settings 66
 - isometric snap and grid 71
 - mesh surface settings 406
 - orthogonal setting 72, 73
 - snap angle settings 70
 - snap spacing settings 69
- Drawing Settings dialog box - Display tab
 - coordinate display in status bar 158
 - grip display options 239
 - highlighting entities 234
 - highlighting settings 153
 - Marker Blips display 153
 - Quick Text feature 153
- Drawing Settings dialog box - Drawing Units tab 50
- Drawing Settings dialog box - Entity Creation tab
 - entity color settings 45
 - freehand sketch settings 104
 - linetype scale settings 47
 - linetype settings 46
 - lineweight settings 48
 - point entity display 98
 - print style settings 49
 - text height settings 54–56
- Drawing Settings dialog box - Entity Modification tab 271–273
- Drawing Status command (*status*) 229
- drawing units
 - angular units 51–53
 - linear units 50
 - real-world units and 50
 - relationship to printed units 374
 - rounding in dimension display 325
 - scale factors and 53
 - text height and 54
- drawings
 - See also* 2-dimensional drawings; 3-dimensional drawings
 - 3-dimensional and isometric drawings compared 71
 - adding audio notes 514
 - annotations, borders, and title blocks 362
 - blocks 213, 215, 338–342
 - code pages 295
 - copying entities to other drawings 149, 244
 - copying settings to other drawings 174
 - creating new drawings 25, 40
 - damaged files 42
 - default template 479
 - displaying entire drawings 145
 - displaying information about 228–231
 - drawing limits 54, 56, 145, 229, 549
 - drawing units 50
 - embedding or linking into other applications 464–467
 - exporting 467
 - extents 100, 138, 145, 550
 - external references 10, 209, 214, 348
 - grid settings 66–69
 - isometric snap and grid 71
 - layer settings 44
 - layout viewports 368
 - linetype settings 46, 48
 - master and component drawings 348
 - moving around in 138
 - multiple drawings 3, 149
 - opening 41
 - orientation 373
 - orthogonal setting 72, 73

- paper size 373
- passwords 86
- printing 393
- redrawing and regenerating 138
- reusability 5, 8, 10, 174
- saving 37
- scale factors 53–54
- search path for files 478
- sending through e-mail 471
- snap settings 74
- tracking time spent on drawings 230
- views 142
- writing sketches into drawings 103
- drivers for printers 374
- dtext* command
 - adding text to drawings 278
 - setting text style 282
 - specifying alignment 284
- duplicating entities 242
- DWF files
 - defined 549
 - exporting 470
 - importing 462
 - opening 41
- DWG files
 - creating 40
 - defined 549
 - exporting IntelliCAD files as 467–471
 - IntelliCAD compatibility with 3
 - opening 41
 - saving 85
- DWGCODEPAGE 295
- DWT files
 - defined 549
 - importing 462
 - opening 41
 - saving 86
- DXF files 346, 462, 467, 549
 - defined 549
- DXX files 346
- dynamic
 - panning 140
 - zooming 143
- Dynamic View Control
 - command or tool (*viewctl*) 397
 - dialog box 397
- dynamically rotating viewpoints in 3-dimensional draw-
 - ings 397
- E**
 - edgesurf* command 409
 - Edit Block Attributes
 - command or tool (*ddate*) 345
 - dialog box 345
 - Edit Dimension Text command or tool (*dmedit*) 315
 - Edit Length command or tool (*editlen*) 258
 - Edit Polyline command or tool (*editpline*)
 - curving and decurving 266
 - joining 267
 - moving polyline vertices 268
 - opening and closing 264
 - tapering polyline segments 269
 - width and tapering 267
 - Edit Text command or tool (*ddedit*)
 - changing text properties 286
 - editing attribute definitions 344
 - editing text 285
 - editing
 - color book files 62, 65
 - layout viewports 371
 - linked or embedded objects 461
 - polylines 264–270
 - print style tables 385
 - settings, single-click (IntelliCAD Explorer) 198
 - VBA programs 525
 - editing drawings
 - blocks 212
 - embedded IntelliCAD objects in other applications
 - 465
 - in model space 368
 - IntelliCAD compared to manual drafting 11
 - keyboard shortcuts 509
 - layers 175, 176, 180, 182, 185
 - linetypes 187, 191, 193
 - lineweights 188
 - linking objects to drawings 460
 - print styles 189
 - text styles 199–202, 281
 - user coordinate systems 204–206
 - views 207
 - editing entities
 - 3-dimensional entities 425–429, 430–441
 - aligning 429
 - arraying 246, 426, 427

- attribute definitions 344
- breaking and joining 259–260, 266
- chamfering and filleting 271
- changing properties 240
- copying and pasting to other drawings 242
- curving and decurving 265
- cutting to Clipboard 244
- deleting 242
- dividing 222
- editing length 257
- elevation and thickness settings 402
- exploding into components 270, 341
- extending to boundaries 253
- grouping 261–263
- in model space 368
- measuring 221
- mirroring 246, 428
- moving 248
- moving polyline vertices 268
- parallel entities 245
- polylines 264
- rotating 249, 425
- scaling 252
- selecting before editing 234–237
- stretching 251
- tapering polyline segments 267, 269
- trimming 256
- vertices 268–270
- width of polylines 267
- with grips 239
- editing text
 - alignment settings 283
 - alternate text editor 293
 - changing character sets 295
 - changing text properties 286
 - editing attribute definitions 344
 - formatting 285
 - moving dimension text 314
 - replacing dimension text with new text 315
 - restoring dimension text to home position 315
 - rotating dimension text 314
 - spelling 289
 - text style settings 281
 - unicode characters 295
- editlen* command 258
- editpline* command
 - curving and decurving 266
 - joining 267
 - moving polyline vertices 268
 - opening and closing 264
 - tapering polyline segments 267, 269
 - width 267
- elapsed-time timer 230
- electronically mailing files 471
- elements pane in IntelliCAD Explorer 173
- Elevation command or tool (*elev*) 400
- elevation in 3-dimensional entities 399
 - defined 549
 - entering coordinates 167
 - setting default elevation 400, 401
- Ellipse Axis-Axis tool 96
- Ellipse command (*ellipse*) 96
- ellipses
 - drawing methods 96
 - moving with grips 249
- Elliptical Arc Axis-Axis tool 97
- Elliptical Arc command (*ellipse*) 97
- e-mailing files 471
- embedding
 - See also* ActiveX; linking
 - defined 549
 - editing embedded objects 462, 465
 - IntelliCAD objects into other applications 464
 - objects into IntelliCAD drawings 458–461
- EMF files
 - defined 549
 - exporting IntelliCAD files as 467
 - snapshot files 448
- enabling features. *See* turning features on or off
- end arrows 317
- ending
 - commands 32
 - points for moving entities. *See* displacement points
 - script recording 519
- Endpoint Snap command (*endpoint*) 76
- endpoints of entities
 - defined 549
 - line entities 90
 - methods of drawing arcs 93, 112
 - snapping to 74, 76
- engineering drawing
 - scale ratios 53
 - units 51
- Enhanced Metafiles. *See* EMF files

enlarging or reducing view of drawings 142

entities

See also types of entities (lines; rays; arcs; and so on)
550

3-dimensional entities 399–409

area and perimeter 223

arraying copies of entities 246, 426

attaching audio notes 515

attributes 342–347

blocks 209, 212, 336–342

breaking and joining 259, 266

chamfering and filleting 271

color settings 185

complex entities 107

copying or duplicating 242

defined 550

deleting 242

displaying information about 228

editing in viewports 368

elevation and thickness 399

embedding into other applications 464

grips 238–240

linetypes 187

lineweights 188

measuring and marking off intervals 220

moving and rotating 248–251, 425

on deleted layers 175

polylines 264

print styles 189

printing 359

properties 240

resizing 251–258

selecting 182, 234, 302, 303

simple entities 113

text as 279

viewing in 3D drawings 396–399

Entity Data defined 550

Entity Properties dialog box

changing entity properties 240

editing attribute definitions 344

elevation and thickness settings 401

overriding layer color 186

overriding layer linetype 187

overriding layer lineweight 188

overriding layer print style 189

entity selection methods 234–237

entity snap

See also entity snap tools

angle and base point 69

aperture 74

command modifiers 34

controlling separately in multiple views 146

current settings 75, 229

defined 550

definition point locations 302

finding point coordinates with 159, 227

fly-over snapping 83, 490

isometric snap and grid 71

model space from paper space 364

one-time entity snaps 34, 74

origin 69

override 550

overview 7

positioning ordinate points 309

running entity snaps 74

snap resolution defined 556

spacing 69

status bar information 29, 75

target box 74–75

turning off settings 82

entity snap tools

Apparent Intersection Snap 81

Center Snap 75, 77

Clear Entity Snaps 75, 82

Endpoint Snap 75, 76

illustrated 75

Insertion Point Snap 75, 79

Intersection Snap 75, 80

Midpoint Snap 75, 76

Nearest Snap 75

overview 74

Perpendicular Snap 75, 77

Point Snap 75, 80

Quadrant Snap 75, 79

Quick Snap 82

Tangent Snap 75, 78

entprop command

changing entity properties 240

layout viewports 371

setting elevation and thickness 401

erase command. *See* Delete command or tool (*delete*)

erasing

eraser tool 104

freehand sketches 104

- segments of polylines 112
- ESNAP setting in status bar 75
- Esnap. *See* entity snap
- exiting IntelliCAD 37
- expanding or compressing text 281
- expblocks* command
 - creating and saving blocks 212
 - inserting blocks 213
 - inserting drawings as blocks 213
 - inserting external references 214
 - listing blocks 210
 - saving blocks as separate drawings 215
- experience levels
 - changing level 3, 32, 476
 - explained 3
 - setting for menus or commands 476, 495
 - setting for toolbars 502
- expfonts* command
 - See also* Explore Text Styles command or tool 556
 - creating new text styles 199, 281
 - current text style 202
 - editing text styles 201
- explayers* command
 - copying and pasting layers to other drawings 175
 - creating and naming layers 180
 - current layer settings 44, 182
 - deleting layers 176
 - displaying list of layers 177
 - hiding or freezing layers 183
 - layer color settings 186
 - layer linetype settings 187
 - layer lineweight settings 188
 - layer print settings 185
 - layer print style settings 189
 - locking and unlocking layers 184
- Explode command or tool (*explode*)
 - converting donut sides to arc entities 118
 - converting plane sides to line entities 120
 - converting polygon sides to line entities 111
 - converting polyline segments to entities 113
 - converting rectangle sides to line entities 108
 - exploding blocks 341
 - exploding entities into components 270
- exploded hatching 131
- Explore Blocks command or tool (*expblocks*)
 - creating and saving blocks 212
 - inserting blocks 213
 - inserting drawings as blocks 214
 - inserting external references 214
 - listing blocks 211
 - saving blocks as separate drawings 215
- Explore Coordinate Systems command or tool (*expucs*) 203
- Explore Layers command or tool (*explayers*) 172
 - copying layers to other drawings 175
 - creating and naming layers 181
 - current layer settings 44, 182
 - deleting layers 176
 - displaying list of layers 178
 - hiding or freezing layers 183
 - layer color settings 186
 - layer linetype settings 187
 - layer lineweight settings 188
 - layer print settings 185
 - layer print style settings 189
 - locking and unlocking layers 184
 - opening IntelliCAD Explorer 172
- Explore Linetypes command or tool (*expltypes*)
 - creating new linetypes 193, 194
 - current linetype 191
 - listing linetypes 190
 - renaming linetypes 197
- Explore Text Styles command or tool (*expstyles*)
 - creating new styles 281
 - creating new text styles 200
 - current text style 202
 - editing text styles 201
 - listing text styles 199
- Explore Views command or tool (*expviews*)
 - listing views 206
 - saving and naming views 207
- expltypes* command
 - creating new complex linetypes 194
 - creating new linetypes 193
 - current linetype 191
 - listing linetypes 190
 - loading additional linetypes 192
 - renaming linetypes 197
- Export To File command or tool (*export*) 468, 470
- exporting
 - drawings 467
 - profiles 488
- expstyles* command 198
 - See also* Explore Text Styles command or tool

- expucs* command 203
 - See also Explore Coordinate Systems command or tool
 - expviews* command 206, 207
 - See also Explore Views command or tool
 - Extend command or tool (*extend*)
 - extending to boundaries 253, 285
 - extending to implied boundaries 254, 286
 - extending
 - Apparent Intersection Snap 81
 - dimensions 321
 - entities to meet boundaries 253
 - Intersection Snap 80
 - extension lines
 - adding dimensions by selecting origins 302, 303
 - adding dimensions by specifying lines 302
 - arrows and arrowheads 317
 - defined 301, 550
 - formatting 321
 - obliquing 313
 - extension snaps 34, 80, 81
 - extents
 - See also limits
 - defined 550
 - displaying entire drawings 145
 - rays and 100
 - scroll bar indicators 138
 - Extract Attributes command or tool (*ddattext*) 347
 - extracting attribute data 342, 346–347
 - Extruded Surface command or tool (*tabsurf*) 407
 - extruding
 - 3-dimensional entities 402, 550
 - solid faces 432
 - surface meshes 406
- F**
- Face command or tool (*face*) 403
 - faces 403, 442, 550
 - fade of images 452
 - feature control frames 327
 - fence
 - defined 550
 - extending entities with 255
 - illustrated 237
 - trimming or clipping entities with 257
 - Fence selection method 235
 - fields in extracted attribute files 346
 - file formats
 - default Save As format 476
 - exporting 467
 - importing 462
 - IntelliCAD and AutoCAD files 3
 - file paths
 - for external references 354
 - for raster images 457
 - file size
 - blocks and 336
 - external references and 348
 - linked and embedded objects and 460, 466
 - files
 - aliases 511, 513
 - audio 515
 - basing on templates 40
 - creating 40
 - damaged 42, 476
 - default Save As format 476
 - embedding into drawings 459
 - embedding into other applications 464, 465
 - exiting 37
 - exporting 467
 - external references 214, 348
 - extracted attribute data 342, 346
 - fonts 199
 - importing 462
 - inserting as blocks 338
 - keyboard shortcuts 510
 - linking drawings into other applications 465
 - menus 495
 - opening 41
 - passwords 86
 - previewing before printing 391
 - print style tables 379
 - printing drawings 393
 - profiles 484
 - raster images 449
 - saving 37
 - saving blocks as drawings 337
 - scripts 518
 - search paths 478
 - sending through e-mail 471
 - shapes 517
 - Fill command or tool (*fill*)
 - filled or outlined lines on entities 108, 111, 113, 118
 - turning fill display on or off 151

Fillet command or tool (*fillet*) 274

filleting
 defined 271, 550
 methods 274

filling entities
 displaying current settings 229
 donut lines 118
 hatching 127
 planes 119
 polygon lines 111
 polyline lines 113
 rectangle lines 108
 turning off display to improve performance 151

finding point coordinates 159

Fit Tolerance values for splines 115

fitting
 text and arrowheads on dimensions 319
 viewports to screen 368

fixed
 attribute values 342
 coordinate systems 157

flatness tolerance symbols 327

flipping entities (creating mirror images) 246, 428

flipping printed page 373

floating toolbars and command bar 25, 31, 32, 550

floating viewports
 scale factor 370

flyouts on tools 32, 501–502

font map
 setting the default file 479

fonts 198
 AutoCAD fonts 199
 character sets 295
 defined 199
 font files 281
 in paragraphs 279
 in text styles 281
 search path for files 478

footers and headers on printouts 488

forcing text to fit 283, 319

form tolerance symbols 327–328

formatting lines in dimensions 321

formatting text
 dimension text 323–325
 text styles 281, 282

fractional drawing units 50

frames of images 454

frames of wipeouts 122

Freehand command (*freehand*) 103

freehand sketches
 drawing and inserting 103
 erasing 104
 setting as polylines or lines 104

Freeze/Thaw tool (IntelliCAD Explorer) 180, 183, 184

freezing layers 177, 180, 183, 184, 550

Full Render command or tool (*fullrender*) 443

full-size drawings 53

G

gaps in linetypes 193

Geometric Tolerance dialog box 329

geometric tolerances 327

geometry, overlaying reference geometry 350

global linetype scale 47

greeking text (Quick Text feature) 152

grid settings
 changing settings 66
 controlling separately in multiple views 146
 displaying current settings 229
 grid defined 550
 GRID setting in status bar 67
 isometric snap and grid 68, 71
 rotating grid 68, 69

grips
 color and size 239
 editing entities with 239
 moving entities with 249
 resizing dimensions with 314
 resizing entities with 251
 scaling entities with 252–253
 selecting entities with 238
 stretching entities with 251
 turning on or off 239

grouped entities. *See* blocks

grouping entities 261–263

H

hand cursor (Pan tool) 139

hand method to determine coordinates 163

handles (entity grips). *See* grips

hardware requirements for IntelliCAD 24

hatch boundaries 127

Hatch command or tool (*hatch*) 127

hatch patterns and hatching

- adding to entities 127
 - IntelliCAD compatibility with AutoCAD files 3
 - search path for files 478
 - headers and footers on printouts 488
 - height of named views 206
 - height of text. *See* text height
 - Help
 - assistance for IntelliCAD 14
 - displaying online Help 37
 - search path for files 478
 - hidden
 - attributes 342
 - edges on 3-dimensional polyface meshes 405
 - lines 442
 - hidden-line removal, defined 551
 - Hide command or tool (*hide*) 442
 - hiding
 - command bar 28
 - entities using wipeouts 121
 - image frames 454
 - layers 182, 185
 - lines in 3-dimensional entities 442
 - Model and Layout tabs 365, 480
 - Prompt History window 34
 - reference grid 67
 - scroll bars 481
 - toolbars 27
 - ToolTips 27
 - warning messages 476
 - wipeout frames 122
 - xref clipping boundaries 358
 - hierarchical viewing, external references 351
 - high quality images 454
 - highlight* command 153
 - highlighting entities
 - edges of shaded entities 442
 - turning highlighting on or off 234
 - when selected 153
 - horizontal
 - grid spacing 66–69
 - text orientation 281
 - horizontal dimensions
 - creating 302
 - defined 551
 - illustrated 300
 - horizontal drawing method
 - infinite lines 101
 - rays 100
 - HSL values 59
 - hue 59
 - hyperlink* command 472
 - hyphens 149, 366, 367
- I**
- ICA files (IntelliCAD aliases) 513
 - icad print style tables 384
 - icad.dwt* template 25, 40
 - icad.fnt* font 281
 - icad.lin* file 192
 - icad.pat* library file 127
 - icadload.dfs* files 522
 - ICM files (IntelliCAD menu files) 491, 495, 496
 - icons
 - audio notes 516
 - coordinate system 157
 - display options for tool icons 501
 - displaying embedded files as 459
 - large tools 501, 503
 - ID Coordinates command or tool (*idpoint*) 159
 - idpoint* command 159
 - i-drop feature 474
 - image* command 452, 456, 457
 - imageattach* command 449
 - imageclip* command 455
 - imageframe* command 454
 - imagequality* command 454
 - images
 - attaching 449
 - changing paths 457
 - clipping 455
 - deleting 458
 - modifying 452
 - unloading and loading 456
 - Images tool (Block toolbar) 210
 - implied boundaries
 - extending entities to 254
 - trimming or clipping entities with 256
 - importing
 - files 462
 - profiles 488
 - imprinting solids 439
 - improving performance
 - hatch pattern memory requirements 131
 - memory-intensive display elements 151

- included angles in arcs 93, 94, 113
- indents in paragraphs 279
- index colors
 - current entity color 45
 - selecting 58
 - selecting for layers 186
- Infinite Line command or tool (*inline*) 101
- infinite lines
 - defined 551
 - drawing 101
 - filleting entities 276
- inline* command 101
- Inquiry toolbar tools
 - coordinates 159
 - distances 227
 - drawing status 229
 - listing entity info 228
 - time variables 231
- Insert Block dialog box 214, 339–340
- Insert External file Blocks tool (Block toolbar) 210, 214
- Insert Object dialog box 459, 461
- Insert tool (Block toolbar) 210, 214
- inserting
 - blocks 338
 - drawings from a Web site 474
 - hatch patterns 127
 - hyperlinks 472
 - menu items 492
 - menu sub-items 493
 - objects 459, 461
 - raster images 449
 - text 278
 - tolerances 329
- inserting dimensions
 - aligned 304
 - angular 307
 - baseline 305
 - continued 306
 - diameter 308
 - horizontal or vertical 303
 - in paper space 312
 - leaders on 311
 - obliqued 313
 - ordinate 309
 - radius 309
- inserting drawings into other drawings. *See* Xref Manager command or tool (*xrm*)
- insertion* command 79
- Insertion Point Snap command (*insertion*) 79
- insertion points
 - attachment points 279, 285
 - base points for drawings 229
 - for blocks 212, 213, 336, 339–340
 - for external references 214, 350
 - for text 278, 279, 282, 285
 - in attribute definitions 342, 343, 344
 - in extracted attribute file fields 346
 - snapping to 79
- insertobj* command 459, 461
- installing IntelliCAD 24
- int* command modifier 34, 81
- IntelliCAD Explorer
 - Blocks list 209–216
 - Coordinate Systems element 169, 202–206
 - copying elements to other drawings 174
 - deleting elements 175
 - Dimension Styles 216–218
 - Layers element 177
 - overview 172–174
 - purge tool 177
 - single-click editing 198
 - Text Styles element (text styles) 198–202
 - tools 83, 174
 - Views element 206–209
- IntelliCAD Explorer command or tool (*explayers*) 172
- intermediate experience level
 - changing 3, 32, 495
 - defines menus 32
 - explained 3
- Internet
 - e-mailing drawings 471
 - hyperlinks for 472
 - opening drawings from 474
 - publishing drawings to 474
- intersection* command 80
- intersection of 3-dimensional entities
 - defined 551
 - intersecting solids 424
 - snapping to 80, 81
- Intersection Snap command (*intersection*) 80, 81
- intervals on entities, marking off 220
- invisible data. *See* attributes
- invisible edges
 - of raster images 454

- on 3-dimensional faces 402, 403
- on 3-dimensional polyface meshes 405

- invisible layers 177, 179, 182

- isometric drawings

- defined 551

- enabling snap and grid settings 68

- isometric planes

- defined 551

- illustrated 71

- setting current plane 68

J

- Join command or tool (*join*) 260

- joining

- combining solids 423

- entities 260, 266, 271

- two views 148

- justification

- attribute text 343

- dimension line text 324

- text settings 286

K

- keyboard shortcuts

- adding or deleting 509

- customizing 508

L

- Last Entity In Drawing selection method 234

- latitude lines

- dishes 417

- domes 418

- spheres 416

- Layer On/Off tool (IntelliCAD Explorer) 180

- layers

- blocks with entities from different layers 336

- BYLAYER property 45–49

- changing for text entities 285

- colors and linetypes 45–47, 185–190

- colors, linetypes, lineweights, and print styles 178

- copying to other drawings 174–175

- creating and naming 180, 182

- current layer settings 44, 182, 229

- defined 551

- deleting in IntelliCAD Explorer 175

- displaying layer information 228

- freezing and thawing 179, 183, 184

- hidden and visible 177, 178, 182, 185

- in entity properties 240

- Layer toolbar in IntelliCAD Explorer 179

- Layers dialog box 186, 187, 188

- Layers element in IntelliCAD Explorer 175, 177

- locking and unlocking 178, 179, 184

- overview 6–7, 177–217

- print settings 185

- printing and nonprinting 177, 182, 185

- renaming 181

- selecting entities by layer 235

- status bar information 29

- transparent overlays 6

- layout* command 366

- Layout tabs

- displaying 365, 480

- print options 373

- reordering 367

- layout viewports

- changing size 371

- creating 368

- creating dimensions in 312

- defined 551

- invisible borders on 369

- locking 371

- modifying 371

- scale factor 370

- selecting 371

- turning on and off 370

- UCS per viewport 371

- layouts

- command or tool (*layout*) 364

- copying 366

- creating from templates 366

- defined 551

- deleting 367

- displaying information for entities 228

- lineweights 377

- maximum number 365

- model space and paper space defined 363

- print area and origin 374

- print options 373

- printing 393

- renaming 367

- reordering 367

- saving as templates 366

- scale factor 374

- viewing list of 367
- Leader command or tool (*dimleader*) 311
- leaders in dimensions
 - allowing text without leader 320
 - creating 311
 - defined 301, 551
- leading zeros in dimensions 326
- least material condition (LMC) 328
- left-aligned text 283
- length of lines
 - in freehand sketches 103
 - specifying before drawing 90
- lengthening or shortening entities. *See* resizing entities
- levels of entities in arrays 426
- levels of precision. *See* accuracy
- libraries
 - of hatch patterns 127
 - of linetype 190, 192
- light sources 441, 442, 445
- Lighting command or tool (*lighting*) 445
- limits
 - See also* extents
 - defined 551
 - displaying entire drawings 145
 - displaying limits for drawings 229
 - drawing limits for printing 375
 - setting 54, 56
- limits tolerance. *See* tolerances
- lin files (linetype libraries) 192
- Line command or tool (*line*) 90
- Linear command or tool (*dimlinear*) 303
- linear dimensions
 - aligned 304
 - baseline 305
 - continued 306
 - creating 302
 - formatting dimension unit display 326
 - illustrated 300
 - rounding in 325
- linear drawing units 50–51
- lines
 - adding to arcs 90
 - colors in dimensions 321
 - converting complex entity sides to 108, 111, 113, 120
 - dimensioning angles between lines 308
 - drawing lines 90
 - extending to boundaries 253
 - filled or outlined on complex entities 108, 111, 113
 - formats in dimensions 321
 - freehand sketches as 104
 - hiding in 3D entities 442–443
 - in hatching 127, 162
 - in polylines 111
 - infinite lines 101
 - joining 260, 266
 - measuring and marking off intervals 220
 - moving with grips 249
 - of text *See* text entities
 - profile tolerance symbols 327
 - width 109
- linetype scale
 - changing global 47
 - setting current 46
- linetypes
 - changing in entity properties 240
 - compatibility with AutoCAD files 3
 - copying to other drawings 174
 - creating new linetypes 193
 - current settings 46, 229
 - default linetypes 180
 - defined 551
 - deleting in IntelliCAD Explorer 175
 - displaying information about entities 228
 - drawing scale factor and 53
 - global scale settings 47
 - layer settings 177, 187
 - library files 192
 - linetype scale settings 47
 - loading additional linetypes 192
 - overriding for entities 187, 191
 - overview 190–191
 - print styles 385
 - status bar information 29
- Linetypes element (IntelliCAD Explorer) 192, 193
- lineweights
 - current settings 48
 - defined 551
 - displaying 154
 - layer settings 188
 - overriding for entities 188
 - print settings 377
 - print styles 385
 - scale factor 154

- set default 154
 - linking
 - See also* ActiveX; embedding
 - defined 551
 - drawings into other applications 465
 - editing linked objects 461
 - external reference files 348–358
 - objects into drawings 460–461
 - raster images 449
 - LISP programs
 - calculating coordinates in rectangular meshes 404
 - defined 552
 - IntelliCAD compatibility 4
 - running programs 521–523
 - List Entity Info command or tool (*list*) 228
 - List Processing Language. *See* LISP Programs
 - listening to audio notes 517
 - listing
 - blocks and external references 210
 - external references 351
 - fonts and text styles 198, 216, 282
 - hatch patterns 128, 129
 - layers 178
 - linetypes 190
 - named views 206
 - print style tables 387
 - user coordinate systems 203
 - LMC (least material condition) 328
 - Load Application Files dialog box 521
 - load* command 518, 522
 - Load LISP or SDS Application command (*appload*) 521, 523
 - loading
 - additional linetypes 192
 - alias files 514
 - code pages 296
 - color books 66
 - default drawing environment settings 486
 - keyboard shortcut files 511
 - LISP programs 521
 - menu files 481, 496
 - profiles 486
 - raster images 456
 - location tolerance symbols 327
 - locations in drawings
 - absolute and relative coordinates 160, 164
 - coordinate systems 156
 - display order 250
 - displaying entity coordinates 228
 - finding point coordinates 159
 - moving and rotating entities 249–251
 - obtaining precise point locations 227
 - Lock/Unlock command tool (IntelliCAD Explorer) 184
 - locking layers 178, 179, 184, 552
 - locking layout viewports 371
 - log file
 - setting the default file 479
 - luminance 59
- ## M
- M or N direction
 - defined 552
 - in rectangular meshes 404
 - in surface meshes 406, 407, 409
 - macros 525, 552
 - See also* scripts
 - magnification of drawings
 - See also* scale factors
 - magnifying views 5
 - methods 142
 - zooming and panning in 3-dimensional drawings 398
 - magnifying glass cursor 142
 - major axes 552
 - Make Oblique command or tool (*dimedit*) 313
 - Make Snapshot command or tool (*msnapshot*) 448
 - manual drafting compared to IntelliCAD 5
 - MAPI protocol 471
 - margins on drawings. *See* extents; limits
 - marker blips. *See* blips
 - marker blocks 220
 - marking off interval on entities 220
 - master drawings from component drawings 348
 - material condition symbols 328
 - materials 445
 - Materials command or tool (*materials*) 445
 - maximum material condition (MMC) 328
 - MDI (multiple-document interface) 3, 149, 552
 - Measure command or tool (*measure*) 220, 221
 - measurement lines. *See* dimensions and dimension styles
 - measuring and marking entities 220
 - memory requirements
 - for IntelliCAD 24
 - hatch pattern requirements 131

- memory-intensive display elements 151
- menu files
 - customizing menus 491–498
 - IntelliCAD compatibility with AutoCAD files 3
 - loading 496
 - saving 495
- Menu Item command 493
- Menu Sub-Item command 493
- menus
 - adding commands 493
 - automatically loading 481
 - changing experience levels 3, 32, 476, 495
 - creating new menus 493
 - customizing 491
 - deleting commands from 494
 - menu bar illustrated 27
 - renaming commands 494
 - search path for files 478
 - starting commands with 32
- Mesh command or tool (*mesh*) 404
- mesh surfaces. *See* surface meshes
- Messaging Application Program Interface (MAPI) 471
- middle-aligned text 283
- midpoint of two points 34
- Midpoint Snap command (*midpoint*) 76
- midpoints of entities 74, 76
- minor axes 552
- Mirror command or tool (*mirror*) 246
- mirror3D* command 428
- mirroring entities 246, 552
- mistakes, correcting 36
- MMC (maximum material condition) 328
- MNS files (AutoCAD menu files) 491, 496, 504
- MNU files (AutoCAD menu files) 491, 496, 504
- model space
 - See also* paper space
 - defined 552
 - displaying information for entities 228
 - overview 8, 362
 - print options 373
 - snap from paper space 364
 - status bar information 29
 - switching to 364, 365
 - switching to paper space 364
 - viewport scale factor 370
- Model tab
 - cannot delete 367
 - displaying 365, 480
 - displaying information for entities 228
 - model space and paper space defined 362
 - print options 373
 - printing from 360, 393
 - viewports illustrated 362
- Modify toolbar 27
- modifying. *See* editing
- monochrome print style tables 384
- mouse shortcuts 35
- mouse wheel direction 481
- Move command or tool (*move*) 248
- moving
 - around in drawings 138
 - external reference files 354
 - profiles 488
 - prompt boxes 30
 - raster image files 456
 - toolbars and command bar 25
- moving entities
 - dimension text 314
 - move* command 248–249
 - solid faces 433
 - to other drawings 149
 - to other layers before layer deletion 176
 - vertices in polylines 268
 - with grips 239
- msnapshot* command 448
- mtext* command 279, 294
- MText dialog box 279
- mtexted* command 293
- mtp* command modifier 34
- multiple commands
 - modifying commands 34
 - nesting several commands 33
 - repeating commands 33
 - using while commands are active 32
- multiple copies
 - of entities 243
 - of external references 350
 - of layouts 366
- multiple drawings 3, 149
- multiple views
 - See* views and viewports
- multiple-document interface (MDI) 3, 149, 552
- mview* command 370

- N**
- N direction. *See* M or N direction
- N symbol in extracted attribute file fields 346
- named print style tables
- changing a drawing's table type 387
 - comparing with color-dependent tables 380
 - converting to 388
 - copying, renaming, deleting 387
 - creating 384
 - default settings 488
 - defined 379
 - modifying 385
 - setting current print style 49
- named text styles 281
- See also* text styles
- named views 206, 552
- See also* views and viewpoints
- Nearest Snap command (*nearest*) 76
- negative coordinate locations 156
- nested
- blocks 336, 552
 - commands 33
 - external reference files 350
- nested blocks
- See also* blocks
- New command (*newwiz*) 40
- new drawings 40
- new features 14
- New Item tool 83, 169, 174
- newwiz* command 40
- node* command 80
- nonassociative hatches 552
- none* command 82
- See also* Clear Entity Snaps command or tool
- non-ISO linetypes 385
- numbers, rounding 325–327
- numeric fields in extracted attribute file fields 346
- O**
- Object command (*insertobj*) 459, 461
- object linking and embedding. *See* Active X
- oblique angle
- in dimension lines 313
 - in text styles 199, 201, 281, 285
- offset copies of entities. *See* parallel entities
- offsetting
- baseline dimensions 305
 - solid faces 435
 - text on dimension lines 324
- OLE. *See* Active X
- On/Off tool (IntelliCAD Explorer) 180, 183
- online Help 14, 37
- onweb* command 474
- oops* command 337
- Open command or tool (*open*) 41
- Open Drawing dialog box 42
- opening
- color books 62, 65
 - damaged files 42
 - drawings from a Web site 474
 - drawings using Recover 476
 - drawings with prompt for code page 296
 - existing drawings 41
 - external references 352
 - files in other formats 462
 - files sent through e-mail 471
 - IntelliCAD 25
 - polylines 264
 - profile files 488
 - templates for printed layouts 366
- operating system code page 295
- Options command (*config*) 477, 479, 481, 483, 489, 490
- Options dialog box 478
- options, setting or changing 476
- Ordinate command or tool (*dimordinate*) 310
- ordinate dimensions
- creating 310
 - defined 553
 - illustrated 300
- organizing information
- color books 62, 65
 - for printing 359
 - on layers 6, 177
 - with blocks 336
- orientation
- of page 373
 - of text 198
 - of view 146, 147
 - printing upside down 373
 - tolerance symbols 327–333
- origin points
- adding dimensions by selecting origins 302, 303
 - compared to viewpoints in 3-dimensional drawings 396–399

- defined 553
- displaying distances in ordinate dimensions 310
- of coordinate systems 168, 203
- of extension lines 302
- of print areas 377
- of snap and grid 69
- specifying locations by 161
- ORTHO setting in status bar 72
- orthogonal mode
 - defined 553
 - displaying current settings 229
 - overview 7
 - status bar information 29
 - turning on 68, 72
- orthogonal projection 553
- osnap* command. *See* entity snap
- outlined elements in IntelliCAD Explorer 173
- outlining
 - donut lines 118
 - image frames 454
 - planes 120
 - polygon lines 111
 - polyline lines 113
 - rectangle lines 108
 - turning off fill display to improve performance 152
 - wire-frame models 399
- output files of extracted attribute data 347
- Outside Circle selection method 235, 553
- Outside Polygon selection method 235, 553
- Outside Window selection method 234, 553
- overlying external references 350
- overlays. *See* layers
- overscoring text 285

P

- Pan command or tool (*pan*) 139
- panning
 - See also* zooming in or out
 - defined 553
 - in 3-dimensional drawings 398
 - in viewports 364
 - methods 139
 - viewing drawings by 5
- paper size 373
- paper space
 - See also* model space
 - copying or resizing viewports. *See* model space

- defined 553
- dimensions 312
- displaying information for entities 228
- editing method 368
- layout viewports 368
- overview 8, 362
- print options 373
- printing from 361
- scale factor 370
- snap from 364
- status bar information 29
- switching to 364
- paragraph text
 - aligning 284
 - creating 279
- parallel
 - dimensions. *See* baseline dimensions
 - drawing method, infinite lines and rays 100
- Parallel command or tool (*parallel*) 245
- parallel entities
 - defined 553
 - filleting parallel lines 276
 - parallel copies of entities 244
- parallelism tolerance symbols 327
- partial coordinates 166
- passwords for drawings 87
- Paste command or tool
 - IntelliCAD Explorer 174
 - pasteclip* command 244
- Paste command or tool (IntelliCAD Explorer) 83, 174
- Paste Special command and dialog box 461
- pasting
 - embedded objects into drawings 459
 - entities into other drawings 149, 244
 - layers into other drawings 175
 - linked objects into drawings 461
 - settings into other drawings 174
 - text 280
 - text in Prompt History window 34
- patch meshes 409
- paths for files
 - color books 66
 - external references 354
 - raster images 457
 - search paths 478
- patterned
 - lines. *See* linetypes

- PCP files 390
- PDF files 468
- pen assignments 379–389
- pen numbers 385
- pencil tool 103
- percent signs 285
- performance issues. *See* improving performance
- perimeters 553
 - calculating areas 223
- perpendicular distances from origin points 309
- perpendicular entities
 - defined 553
 - infinite lines 101
 - rays 100
 - snapping to 74, 77
- Perpendicular Snap command (*perpendicular*) 77
- perpendicularity tolerance symbols 327
- pface* command 405
- PGP files (AutoCAD aliases) 513
- photo-realistic 441, 443
- plan view
 - coordinate system icons 157
 - defined 553
 - displaying 3-dimensional drawings 398
- Plan View command or tool (*plan*) 398
- planar entities
 - converting to 3D 400
 - defined 553
- planar tops for pyramids 414
- Plane command or tool (*plane*) 119
- planes
 - 3-dimensional faces 403
 - converting sides to lines 120
 - defined 553
 - drawing 119
 - isometric planes 71
- playing
 - audio notes 517
 - scripts 518–521
- pline* command. *See* Polyline command or tool (*polyline*) 554
- plotters
 - printer configuration files 390
 - printing drawings 393
 - selecting 374
- plotting. *See* printing drawings
- plus or minus signs 285
- pmspace* command 364
- point* command 98
- point filters (coordinate filters) 166, 547
- Point Selection method 235
- Point Snap command (*node*) 80
- Point tool 98
- points
 - See also* base points; displacement points; endpoints of entities; insertion points; midpoints of entities; origin points; start points of entities
 - changing point entity appearance 98
 - defined 553, 554
 - drawing point entities 98
 - finding point coordinates 159
 - interval marker point entities 220
 - parallel copies passing through points 245
 - point locations in coordinate systems 156
 - snapping to point entities 80
- polar
 - arrays of entities 247, 426–427, 554
 - coordinates 159, 162
 - See also* coordinate systems
- POLAR setting in status bar 73
- polar tracking, turning on 73
- Polyface Mesh command or tool (*pface*) 405
- polyface meshes 405
- Polygon command (*polygon*) 110
- polygon meshes
 - edge-defined Coons surface patch meshes 409
 - extruded surface meshes 406
 - revolved surface meshes 407
 - ruled surface meshes 405
- Polygon, Center-Side tool 111
- Polygon, Center-Vertex tool 110
- polygons
 - See also* polygon meshes 554
 - calculating area and perimeter 223
 - clipped images 455
 - converting sides to lines 111
 - defined 554
 - drawing 110
 - editing 264
 - using as selection windows 236
- Polyline command or tool (*polyline*) 111
- polylines
 - chamfering 273
 - converting entities to polylines 264

- converting segments to entities 113
- curving and decurving 265
- defined 554
- donuts 117
- drawing 111
- editing 264
- editing vertices 268
- extending to boundaries 253
- filleting entities 274
- freehand sketches as 103
- joining 266
- measuring and marking off intervals 220
- opening and closing 112, 264
- polygons 110
- rectangles 108
- tapering 111, 255
- width 111, 267
- position tolerance symbols 327
- positioning
 - text on dimension lines 323
- positioning dimensions
 - aligned dimensions 304
 - angular dimensions 307
 - baseline dimensions 305
 - diameter dimensions 308
 - dimension text 314
 - horizontal or vertical dimensions 303
 - leaders and annotations 311
 - radius dimensions 309
 - text and arrowhead positioning 319
- positioning entities 248
 - See also* insertion points
 - blocks 338
 - moving entities 239
- positive coordinate locations 156
- ppreview* command 391
- precision. *See* accuracy
- preferences command. *See* config command
- prefixes on dimension text 324
- presentations 448
- Preset Viewpoints
 - command or tool (*setvpoint*) 396
 - dialog box 397
- previewing
 - block images 210
 - files before opening 42, 86
 - print jobs 391
 - Previous Selection selection method 234
 - print area 375, 377
 - print* command 393
 - Print command or tool (*print*) 393
 - Print dialog box 376, 378
 - Print Preview command or tool (*ppreview*) 391
 - Print Style Table Editor dialog box 386
 - print style tables
 - assigning 383
 - changing drawing's type 387
 - comparing types 380
 - copying, renaming, deleting 387
 - creating 384
 - default settings 488
 - explained 379
 - getting started with 381
 - modifying 385
 - search paths 478
 - turning off 389
 - print styles
 - changing in entity properties 240
 - default settings 488
 - explained 379
 - layer settings 189
 - modifying 385
 - setting current 49
 - printers
 - printer configuration files 390
 - printing drawings 393
 - selecting 374
 - printing drawings
 - default print style settings 488
 - drawing limits 375
 - getting started 360
 - headers and footers 488
 - layer control 185
 - layout viewports 368
 - lineweights 377
 - paper size and orientation 373
 - paper space 8
 - plotter drivers 374
 - previewing before printing 391
 - print styles 379–389
 - printing and nonprinting layers 177, 182, 185
 - printing drawings 393
 - rendered drawings 446
 - saving settings 390

- scale factors 53, 374
- selecting printer 374
- setting the scale 374
- upside down 373
- profile tolerance symbols 327
- profiles 484–488
 - copying 487
 - creating 484
 - deleting 487
 - explained 484
 - exporting 488
 - importing 488
 - loading 486
 - renaming 487
- profiles for revolved surface meshes 407–409
- programming IntelliCAD 521–525
- projected tolerances 328–333
- projection lines. *See* extension lines
- prompt boxes
 - choosing command options 30
 - defined 554
 - turning off 30, 481
- Prompt History window
 - defined 554
 - displaying drawing information 228
 - navigating with arrow keys 480
 - tracking history 34, 480
- prompts in status bar 342
- Properties command or tool (*entprop*)
 - changing entity properties 240, 370
 - changing viewport properties 371
 - IntelliCAD Explorer 83, 174, 186, 187, 188, 201
 - setting elevation and thickness 402
- properties, selection by 237
- publishing drawings to the Internet 474
- pull-down menus 492
- purge tool 177
- Pyramid command or tool (*pyramid*) 413, 414
- pyramids
 - drawing 413
 - editing 264

Q

- qtext* command 152
- quadrant points of entities 79, 554
- Quadrant Snap command (*quadrant*) 79
- quadrilateral filled planes 119

- quality of images 454
- quick* command 82
- Quick Snap command (*quick*) 82
- Quick Text feature 152
- quitting IntelliCAD 37

R

- radial dimensions 300, 301
- radians 554
- radii of entities
 - arc 93
 - arcs 113
 - circles 91
 - cylinders 415
 - defined 554
 - dishes 417
 - domes 418
 - filleting entities 271, 274
 - spheres 416
 - tori 419, 421
- Radius command or tool (*dimradius*) 309
- radius dimensions 309, 554
- Radius-Tangent-Tangent circle method 91
- RAM requirements. *See* memory requirements
- raster images
 - attaching 449
 - changing paths 457
 - clipping 455
 - deleting 458
 - modifying 452
 - unloading and loading 456
- Ray command or tool (*ray*) 100
- ray tracing 443
 - defined 554
- rays
 - defined 554
 - drawing 100
 - extending to boundaries 253
 - filleting 276
- read-only files 42
- Real-Time Pan command (*rtpan*) 140
- Real-Time Sphere command (*rtrot*) 141
- Real-Time Zoom command (*rtzoom*) 143
- Record Script command or tool (*recscript*) 519, 520
- recording audio notes 515
- recording scripts 35, 518
- Recover command (*recover*) 43

- Rectangle command or tool (*rectangle*) 108
- rectangles
 - converting sides to lines 108
 - defined 554
 - drawing 108
 - editing 264
 - squares 108
- rectangular
 - arrays of entities 247, 426, 554
 - boxes 410
 - clipped images 455
 - filled planes 119
- Redo tool 36
- redoing actions 36, 554
 - See also* undoing actions
- redrawing screen 138, 554
 - See also* regenerating drawings 138
- reducing or enlarging view of drawings 142
- reference
 - geometry 350
 - grid. *See* grid settings
- Reference Grid tool 67
- reflections 443
- refreshing screen 138
- regardless of feature size (RFS) condition 328
- Regen command or tool (*regen*) 138, 152
- regenall* command 138
- regenerating drawings
 - See also* redrawing screen 555
 - after editing text styles 200
 - after enabling Quick Text 152
 - compared to redrawing 138
 - defined 555
- Region command or tool (*region*) 420
- regions 420
 - slicing and sectioning 431
- relative coordinates
 - See also* absolute coordinates; user coordinate systems (UCS); World Coordinate System (WCS) 555
 - 3-dimensional coordinate systems 163
 - defined 555
 - point filters 166
 - polar coordinates 162
 - spherical and cylindrical coordinates 164
- relinking external reference files 354
- reloading
 - external reference drawings 214, 349, 353
 - raster images 456
- removing. *See* deleting
- Rename Command (IntelliCAD Explorer) 181
- renaming
 - attribute definitions 344
 - blocks 212
 - commands in menus 491, 494
 - dimension styles 317
 - layers 181
 - layouts 367
 - linetypes 197
 - print style tables 387
 - profiles 487
 - toolbars 501
- Render command or tool (*render*) 443
- rendering 3-dimensional entities 441
- reordering
 - entities 250
 - Layout tabs 367
- repeating commands 33
- replacing dimension text with new text 315
- Reposition Dimension Text command or tool (*dimedit*) 314
- resetting timer 230
- resizing
 - layout viewports 371
 - lineweights during printing 377
 - toolbars 27
 - viewports 371
- resizing entities
 - arrowheads 318
 - changing length 257
 - extending to boundaries 253
 - scaling 252
 - stretching 251–252
 - trimming or clipping 256
- Restore Text Position command or tool (*dimedit*) 315
- restoring
 - aliases to unchanged condition 512
 - changed blocks to originals 341
 - default drawing environment settings 486
 - deleted entities 242
 - dimension text to home position 315
 - menus to unchanged condition 491
 - named views 208–209
 - previous print settings 378

- previous user coordinate system 170
 - previous view of drawing 144, 149
 - restricting. *See* constraining drawing
 - reusing information 5
 - copying settings into other drawings 174
 - drawing environment settings 484
 - IntelliCAD compared to manual drafting 8
 - layouts 366
 - previous print settings 378
 - printer configuration files 389
 - reusing entire blocks and drawings 10
 - reversing
 - mouse wheel direction 481
 - text 201
 - Revolved Surface command or tool (*revsurf*) 408
 - revolved surface meshes 407, 555
 - revolving solids 422
 - RFS (regardless of feature size condition) 328
 - RGB values 59
 - right-aligned text 284
 - right-click menus 27
 - right-click shortcuts 35
 - right-hand rule to determine coordinates 163, 555
 - Rotate command or tool (*rotate*) 249
 - Rotate Dimension Text command or tool (*dimedit*) 314
 - rotating
 - 3-dimensional entities 425
 - angles in attribute text 343
 - angles in elliptical arc drawing methods 97
 - blocks 212, 213, 338–340
 - coordinate systems 168
 - creating 3D arrays 427
 - dimension text 313–314
 - dimensions. *See* aligned dimensions
 - entities 249, 425, 555
 - external references 214
 - grid 69
 - images 452
 - paragraph text 279
 - printed page 373
 - solid faces 434
 - text 278, 282, 285
 - viewpoints in 3-dimensional drawings 397
 - views 141
 - visualizing rotation direction 163
 - rotation points
 - defined 555
 - specifying 249
 - rounding corners on entities. *See* filleting
 - rounding numbers in dimension display 325
 - roundness tolerance symbols 327
 - rows and columns of entities. *See* rectangular arrays of entities
 - rtrot* command 141
 - rubber-band lines 555
 - Ruled Surface command or tool (*rulesurf*) 406
 - ruled surface meshes 406, 555
 - running
 - entity snaps 74, 555
 - IntelliCAD 25
 - VBA programs 525
 - runout tolerance symbols 327
- ## S
- SAT files
 - importing 462
 - saturation 59
 - Save As command or tool (*saveas*) 86
 - Save Block dialog box 215
 - Save Block to Disk
 - command or tool (*wblock*) 337
 - tool (Block toolbar) 210
 - Save command or tool (*save*) 37, 85
 - Save/Restore View command or tool (*view*) 207
 - saving
 - attributes 342
 - blocks 212
 - blocks as drawing files 337
 - blocks as separate drawing files 215
 - color books 62, 65
 - default Save As format 476
 - drawings 37
 - in other formats 467
 - layouts as templates 366
 - named views 207–208
 - new complex linetypes 194–197
 - new linetypes 193–197
 - passwords with drawings 87
 - print settings 390
 - profile settings 484
 - sketches as part of drawings 103
 - snapshots 448
 - tracking last save time 230
 - user coordinate system 157, 168, 169

- viewport configuration 149
- Scale command or tool (*scale*) 252
- scale factor
 - lineweights 154
- scale factors
 - blocks 212, 213, 338
 - drawing to scale 5–6
 - drawing units 50
 - external references 214
 - floating viewports 370
 - hatching 127
 - in dimensions 326
 - linetype scale 47
 - magnifying view by precise scale factor 144
 - printing lineweights 377
 - printing to scale 374
 - scaling entities 252
 - understanding drawing scale factors 53
 - viewports 370
- scaling. *See* resizing entities; scale factors
- scientific drawing units 51
- screen display
 - customizing 480
 - magnifying 5
 - redrawing and regenerating 138
 - turning off memory-intensive display elements 151
- screenshots (snapshots) 448
- Script Recorder 35
- scripts defined 555
- scroll bars 138
 - displaying 481
- SDF files (Space Delineated Format) 346
- SDS programs 4, 36, 555
- search paths for files 354, 478
- sectioning solids 431
- security for drawings 87
- segmented dimension lines. *See* continued dimensions
- segments
 - converting polyline segments into curves 265
 - defined 555
 - editing in polylines 111
 - measuring and marking off intervals on entities 220
- Select All Entities selection method 234
- Select Color command 186
- Select File to Attach dialog box 214
- Select Font dialog box 281
- Select Layer by Entity command or tool (*setlayer*) 182
- Select Toolbars dialog box 27–28
- selecting entities
 - adding or removing entities from sets 238
 - by properties 237
 - highlighting 153, 234
 - matching specific properties 235
 - selection methods 234
 - to copy or duplicate 243
 - to delete 242
 - with audio notes 516
- selection
 - sets 234, 555
 - windows 234
- semicolon 518
- separating solids 439
- setdim* command 216
 - arrows and arrowheads 318, 319, 323
 - baseline dimension offset 305
 - blocks and external references 172
 - creating dimension styles 316
 - deleting dimension styles 317
 - dimension line colors 321
 - formatting dimension text 323
 - renaming dimension styles 317
 - rounding off numbers 325
 - text positioning 320, 323
- settings
 - arrows and arrowheads 318
 - blips display 153
 - blocks and external references 210, 211, 213, 215
 - colors 185
 - coordinate systems 172, 202
 - default drawing environment 486
 - default print style table options 488
 - dimension styles 316
 - distances and angles display 158
 - drawing environment 484
 - elevation and thickness 399–403
 - entity snap 74
 - fills 151
 - grip display options 239
 - highlighting 234
 - layers 44, 174–189
 - linetypes 174
 - lineweights 154, 188
 - mesh surfaces 405
 - Quick Text display 152

- setting layers by selecting entities 182
- shaded surfaces 442
- text styles 172, 198, 281
- user coordinate systems 168
- views 172, 206, 207
- settings* command
 - dimension styles 325
 - drawing limits 56
 - drawing units 51
 - elevation and thickness 400–402
 - entity snap target box 74
 - freehand sketches 104
 - grid settings 67, 69
 - highlighting 234
 - isometric snap and grid 71
 - linetype scale 47
 - linetypes 46
 - lineweights 48
 - orthogonal mode 72, 73
 - point entity display 98
 - print styles 49
 - shaded surfaces 442
 - snap angles 69
 - snap spacing 69
 - text height 54
- Settings pane in IntelliCAD Explorer 172
- setucs* command 169, 170
- setvpoint* command 396
- Shade command or tool (*shade*) 442
- shaded image 442
- shading surfaces of 3-dimensional entities 442, 555
- shadows 443, 445
- shape* command 518
- shelling solids 440
- shortcuts
 - adding access keys to commands 494
 - customizing keyboard shortcuts 508
 - displaying shortcut menus 27
 - entity snaps menu 75
 - using the mouse 35
- shortening or lengthening entities. *See* resizing entities
- SHP files (fonts) 199
- SHX files (fonts) 199
- sides of entities
 - editing polygons 111
 - editing polylines 113
 - editing rectangles 108
 - maximum number for polygons 110
 - specifying to draw polygons 111
- simple entities 89
 - See also types of entities* (lines; rays; arcs; and so on)
- simulating
 - 3-dimensional drawings 71
 - paper output on screen. *See* paper space
- size
 - of files. *See* file size
 - of grips 239
 - of printed drawings 54, 373
 - of text. *See* text height
- size of entities
 - displaying size information 228
 - point entities 98
 - resizing. *See* resizing entities
- sketch* command. *See* freehand command 103
- sketching freehand entities 103
- slanted
 - dimensions. *See* aligned dimensions
 - text. *See* obliquing angle
- SLD files (snapshots) 448
- slicing solids 431
- slide
 - files 448
 - shows 448
- small tool icons 501, 503–504
- snap
 - angle 555
 - grids 555
 - model space from paper space 364
 - resolution 556
 - settings. *See* entity snap
 - tool 69
- SNAP setting in status bar 69
- snapshots
 - defined 556
 - saving 448
- solid
 - boxes 410
 - composites 423
 - cones 412
 - cylinders 415
 - dishes 417
 - domes 418
 - extruding solids 421
 - filled planes 119

- fills 151
- pyramids 413
- regions 420
- revolving solids 422
- spheres 416
- tetrahedrons 413
- tori 419
- wedges 411
- Solutions Development System (SDS) 4, 36, 522, 555
- sound clips 514
- Space Delimited Format files 346
- spacers
 - in menus 491
 - in toolbars 500
- spacing
 - for entity snap 69
 - in reference grid 67
- special characters 285
- speed of processing. *See* improving performance
- Spelling command or tool (*spell*) 289
- spelling of text 289
- Sphere command or tool (*sphere*) 416
- spheres, drawing 416
- spherical coordinates 164, 556
 - See also* coordinates
- Spline command or tool (*spline*) 114
- splines
 - closing entities 116
 - drawing 114
 - fit tolerance 115
- splitting entities 259
- spotlights 443
- squares 109
- stacking entities in arrays 426
- standard
 - text style 198, 281
- Standard toolbar 27
- start arrows 317
- start points of entities
 - line entities 90
 - methods of drawing arcs 93, 112
- starting
 - direction of arcs 93
 - IntelliCAD 25
 - new drawings with templates 25, 40
 - points for moving entities. *See* base points
 - script recording 518
 - starting commands
 - from command bar 33
 - from menus 32
 - from toolbars 32
 - status bar
 - assistance with IntelliCAD functions 13
 - displaying cursor position 158
 - illustrated 27, 29
 - prompts for commands 491
 - viewing model space and paper space 364
 - status* command 229
 - status of drawings, displaying 43, 229
 - STB files
 - assigning 383
 - changing a drawing's table type 387
 - compared with CTB files 380
 - converting to 388
 - creating 384
 - default settings 488
 - defined 379
 - modifying 385
 - Stop Recording command or tool (*stopscript*) 519
 - straightening curves in polylines 265
 - straightness tolerance symbols 327
 - Stretch command or tool (*stretch*) 251
 - stretching
 - entities 239, 251
 - text 284
 - style command (IntelliCAD Explorer) 200
 - styles
 - dimension styles 316
 - print styles 379
 - text styles 281
 - stylesmanager* command
 - copying print style tables 387
 - deleting print style tables 387
 - modifying print style tables 385
 - new print style tables 384
 - renaming print style tables 387
 - Sub-items in menus 491
 - subtended angles 307
 - Subtract From Set selection method 234
 - subtracting areas of combined entities 225–227
 - subtracting solids 423
 - suffixes on dimension text 324
 - surface
 - material properties 443

- of revolution 556
- profile tolerance symbols 327
- shading 442
- surface meshes
 - density 406, 407, 408, 409
 - edge-defined Coons surface patch meshes 409
 - extruded mesh surfaces 406
 - polyface meshes 405
 - rectangular meshes 404
 - revolved surface meshes 407
 - ruled surface meshes 405
- surface models
 - See also* wire-frame models
 - defined 399
 - removing lines and applying shading 442–443
- SVG files
 - defined 556
 - exporting 467
- switching between model space and paper space 364
- symbols
 - datum reference letters 329
 - material condition symbols 328, 329
 - special characters in text 285
 - symmetry tolerance 327
 - tolerance 327, 329
- SYSCODEPAGE 295
- system requirements for IntelliCAD 24
- system variables 556

T

- tables, mapping print settings 379
- tabs in paragraphs 279
- tabsurf* command 407
- tabulated surfaces 556
- Tangent Arc tool 95
- tangent* command 78
- tangent entities 556
 - drawing arcs tangent to an arc or line 95
 - drawing circles tangent to entities 92
 - drawing donuts tangent to entities 118
 - snapping to 74, 78
- tangent points on splines 114
- Tangent Snap command (*tangent*) 78
- tapered polylines 112, 269
 - after joining 266
 - changing width 267
 - results of extending 255

- tapering solid faces 435
- target box for entity snaps 74
- tbconfig* command 501
- templates
 - basing new drawings on 40
 - default icad.dwt template 25
 - defined 556
 - for extracted attribute files 346–347
 - for printed layouts 366
 - importing 462
 - opening new drawings with 25
 - saving from layouts 366
 - setting default template 479
- temporary files search path 478
- terrain models 404
- tetrahedrons 413
- text annotations 311
- Text command or tool (*dtext*)
 - adding text entities 278
 - setting text style 282
 - specifying alignment 283
- text editor 293
- text entities
 - See also* text height; text in attributes; text on dimension lines
 - adding text to drawings 278
 - alignment 283
 - alternate text editor 293
 - attachment points 282, 285
 - backward or upside-down text 281
 - changing properties 286
 - character sets 295
 - code page 295
 - color 285
 - compressing or expanding 284
 - control codes and special characters 285
 - editing text 285
 - fitting between two points 284
 - insertion points 79, 278, 282
 - layer settings 285
 - obliquing 281
 - paragraph text 279
 - Quick Text feature 152
 - rotation angle 278
 - short lines of text 278
 - spelling 289
 - text styles 281

- turning off display to improve performance 153
 - width 281
- text files
 - script files 518
 - templates for extracted attribute files 346
- text height
 - calculating for different scale factors 53
 - changing height 201
 - drawing scale factor and 53
 - in dimension styles 324
 - printed drawings and 53
 - short lines of text 278
 - specifying 54, 282, 285
 - text styles 281
- text in attributes 343, 344
- text on dimension lines
 - colors 324
 - formatting and positioning 319–321, 323
 - illustrated 300
 - moving text 314
 - prefixes or suffixes 324
 - replacing with new text 315
 - restoring to home position 315
 - rotating 314
 - specifying text styles in dimension styles 324
- text size. *See* text height
- text styles
 - applying 282
 - attribute text 343
 - changing styles 285
 - compatibility with AutoCAD files 3
 - copying to other drawings 174
 - creating new styles 199, 281
 - current text style 202
 - deleting in IntelliCAD Explorer 175
 - editing attribute definitions 344
 - editing styles 199
 - listing available styles 282
 - overview 198
 - vertical, upside-down, or backward text 199
- Text Styles dialog box 281
- Text Styles element in IntelliCAD Explorer 198
- text-based data. *See* attributes
- thawing layers 179, 183, 184, 556
- Thickness command or tool (*thickness*) 399
- thickness in 3-dimensional entities 556
 - See also* elevation in 3-dimensional entities
 - changing in entity properties 240
 - default thickness 399
- three-dimensional drawings. *See* 3-dimensional drawings
- three-dimensional entities. *See* 3-dimensional entities
- three-point
 - arc method 93
- through points 245, 556
- thumbnails of blocks 210
- thumbnails of drawings 41
- tick marks on dimension lines 317
- tiers of dimensions. *See* baseline dimensions
- Tile Horizontally command 146
- Tile Vertically command 146
- tiling windows 146
- tilting. *See* obliquing angle
- time stamps on printouts 488
- Time Variables command or tool (*time*) 231
- timers
 - for AutoSave 476
 - tracking drawing sessions 230
- Tip of the Day 25
- title blocks
 - adding in paper space 362
 - as available in each view 8
- toggle features on or off. *See* turning features on or off
- Tolerance command or tool (*tolerance*) 329
- tolerances
 - adding geometric tolerances to drawings 327
 - composite tolerances 328
 - datum reference letters 329–330
 - defined 556
 - in Geometric Tolerances dialog box 329
 - limits tolerance 556
 - material condition symbols 328–333
 - projected tolerances 328
 - symbols, defined 327
 - tolerance commands 556
 - variance tolerance 556
- toolbars and tools
 - compared to manual drafting 6
 - creating new toolbars 499
 - customizing tools and toolbars 25, 499
 - defined 557
 - displaying and hiding toolbars 27
 - docking or floating toolbars 27
 - entity snaps tools 75
 - experience levels for toolbars 476, 502

- flyouts 32, 501
 - illustrated 27
 - IntelliCAD Explorer tools 83, 174
 - large tool icons 501, 503
 - Layer toolbar 179
 - naming new toolbars 501
 - size and color of tools 27
 - spacing in toolbars 500
 - starting commands from 32
 - toolbars command (*tbconfig*) 501
 - Toolbars tab (Custom dialog box) 498
 - triangles on tools 501
 - ToolTips
 - adding to tools 499
 - assistance with IntelliCAD tools 13
 - turning on or off 27, 501
 - top-aligned text 283
 - tori 419, 421, 557
 - total runout tolerance symbols 327
 - tracking
 - command history 34, 480
 - last files used 42
 - number of entities 209
 - trailing zeros in dimensions 326
 - transferring drawings to other people 355
 - transparent
 - commands 557
 - images 452
 - overlays. *See* layers
 - triangles on tools 501
 - triangular filled planes 119
 - Trim command or tool (*trim*) 256
 - trimming
 - external references 356
 - printed drawings 375
 - trimming entities
 - chamfering 272
 - filletting 274
 - troubleshooting
 - drawing disappears from paper space 364
 - lineweight display 154
 - profile settings not saved 485
 - setting layout viewport borders as invisible 369
 - text display 295
 - wipeout display 121
 - true colors
 - current entity color 45
 - selecting 59
 - selecting for layers 186
 - turning features on or off
 - automatically loading menus 481
 - AutoSave 476
 - blips 153
 - continuous inertial motion 481
 - entity snaps 82
 - extension line options 322
 - grips 239
 - highlighting 153, 234
 - image frames 454
 - orthogonal setting 72
 - polar tracking setting 73
 - print style tables 389
 - prompt boxes 30, 481
 - reference grid 67
 - snap settings 69
 - solid fill display 151
 - text display 152
 - Tip of the Day 25
 - ToolTips 501
 - wipeout frames 122
 - xref clipping boundaries 358
 - two-dimensional
 - drawings. *See* 2-dimensional drawings 159
 - entities. *See* 2-dimensional entities 159
 - two-point circle method 91
 - typing commands
 - aliases 511
 - entity snap commands 74
 - in command bar 33
 - to load custom programs 523
- ## U
- UCS. *See* user coordinate systems (UCS) 168
 - undelete command (*undelete*) 242, 337
 - underscore characters 149, 366, 367
 - underscoring text 285
 - undoing actions 36
 - See also* redoing actions
 - Unicode characters 295
 - uniform width for polylines 267
 - units. *See* drawing units
 - unloading
 - custom programs 522
 - external references 352

- print style tables 389
- raster images 456
- unlocking layers 184, 557
- updating
 - all instances of blocks 336, 340
 - attribute values 345
 - block definitions 340
 - drawings inserted as blocks 214
 - external references 215, 348, 353
 - file paths for external references 354
 - file paths for raster images 457
- upside-down printing 373
- upside-down text 201, 281, 286
- user coordinate systems (UCS)
 - See also* coordinates, World Coordinate System (WCS)
 - command (IntelliCAD Explorer) 169, 204
 - command or tool (*setucs*) 168
 - current UCS 205
 - defined 157, 557
 - defining per layout viewport 371
 - defining systems 168, 204
 - dialog box 168
 - icon 26
 - listing 202
 - plan views of drawings 398
 - preset user coordinate systems 169
- user levels. *See* experience levels

V

- validated attribute values 343
- values
 - editing attribute values 345
 - extracting attribute values 346
 - variable attribute values 342
- variables
 - dimension variables 316
 - system variables 556
- variance tolerance
 - See also* tolerances
- variations in geometry. *See* tolerances
- vba* command 525
- VBA macros command (*vbarun*) 525
- VBA programs 4, 557
- vbarun* command 525
- vectors 557
- vertical
 - drawing method (infinite lines) 101
 - drawing method (rays) 100
 - grid spacing 67
 - orientation for text 281
 - text orientation 201
- vertical dimensions
 - creating 303–304
 - defined 557
 - illustrated 300
- vertices
 - chamfering 273
 - defined 557
 - drawing polygons 110
 - editing polyline vertices 268
 - filleting 275–276
- View command (IntelliCAD Explorer) 207
- View Snapshot
 - command or tool (*vsnapshot*) 449
 - dialog box 449
 - snapshots 449
- viewing
 - See also* views and viewports; windows 557
 - 3-dimensional drawings 396
 - command bar 28
 - drawing thumbnails 41
 - dynamic view controls 397
 - external references 351
 - hiding lines in 3-dimensional entities 442
 - layout viewports 370
 - list of layouts 367
 - locked layers 184
 - Model and Layout tabs 480
 - panning drawings 139
 - plan view 398
 - preset viewpoints 396
 - print jobs before printing 391
 - print style tables 385
 - Prompt History window 34
 - redrawing screen 138
 - regenerating drawings 138
 - rotating the view 141
 - scroll bars 481
 - shading on entities 442
 - text 295
 - thawed layers 183, 184
 - ToolTips 27
 - turning layers on 183

- viewpoints in 3-dimensional drawings 396
 - zooming 142
- viewpoints in 3-dimensional drawings 557
- views and viewports
 - See also* model space; paper space 557
 - arranging windows 146
 - changing properties 208, 371
 - copying views to other drawings 83, 174
 - creating layout viewports 368
 - deleting views in IntelliCAD Explorer 175
 - displaying entire drawings 145
 - height and width of views 206
 - invisible borders on layout viewports 369
 - joining two views 148
 - layout viewports overview 368
 - listing named views 206–207
 - moving around in viewports 138
 - multiple views 146
 - orientation of viewports 147
 - restoring named views 208
 - restoring previous view of drawing 144
 - saving view configuration 149, 207
 - scale factor 370
 - switching between model and paper space 364
 - turning on and off 370
 - viewport configuration defined 558
 - viewports defined 362, 557
 - views defined 557
 - zooming and panning 368
- Views list in IntelliCAD Explorer 206
- visibility of layers 177, 179, 182
- visible
 - attributes 342
 - grid. *See* grid settings
- Visual Basic Editor command (*vba*) 525
- Visual Basic for Applications 4
- Visual Basic for Applications (VBA) 4, 525, 557
- visualizing coordinate systems 163

W

- warnings when opening drawings 476
- WAV files 514
- wblock* command 337
- WCS. *See* Word Coordinate System (WCS)
- Web sites
 - accessing IntelliCAD 474
 - hyperlinks for 472

- opening files from 474
 - publishing drawings for 474
- Wedge command or tool (*wedge*) 411
- wedges 411, 558
- what's new 14
- width
 - after creating regions 420
 - after exploding 270
 - after joining 266
 - changing the polyline width 267
 - lineweight settings 48
 - of donuts 117
 - of fields in extracted attribute files 346
 - of lines 109
 - of polylines 111, 269
 - printing lineweights 377
- width of text
 - in text styles 199, 201, 281
 - specifying 285
- Window Circle selection method 235
- Window Polygon selection method 235, 236
- Window-Inside selection method 234, 235
- Windows
 - metafiles. *See* WMF files
- windows
 - See also* views and viewports 557
 - arranging 146
 - cascading 146
 - displaying entire drawings 145
 - joining two views 148
 - listing and saving named views 206
 - main IntelliCAD window 27
 - model space and paper space defined 362
 - moving around in 138
 - multiple views 146
 - opening new windows 146
 - saving arrangements 149
 - selection windows 234
 - tiling 146
 - unique numbers 146
- Windows Clipboard
 - See* Clipboard
 - embedding objects into drawings 458
 - embedding objects into other applications 464, 472
 - linking drawings into other applications 466
- Wipeout command or tool (*wipeout*) 121
- wipeouts 121–122

wire-frame models
See also surface models
 defined 399, 558
 removing lines and applying shading 442

witness lines. *See* extension lines

WMF files
 defined 558
 exporting IntelliCAD files as 467
 snapshots 448

World Coordinate System (WCS)
 defined 558
 overview 157
 plan views of drawings 398
 selecting 170
 working with coordinate systems 202

World tool (IntelliCAD Explorer) 83, 174

Write, Then Resume option (*freehand* command) 103

writing sketches into drawings 103

X

x-axis
 color 483
 in coordinate systems 156

xclip command
 deleting 358
 polyline clipping boundaries 357
 rectangular clipping boundaries 357
 turning xref clipping on and off 358

Xlines 101
See also infinite lines

x-ordinate dimensions 309

Xref Manager command or tool (*xrm*) 348, 349
See also blocks
 attaching files to drawings 214
 attaching or detaching external references 350
 binding external references 355
 changing file paths 354
 clipping 356
 defined 209, 550
 inserting drawings as 214
 nesting 350
 overlaying 350
 overview 348
 reloading or updating 353
 reusing entire blocks and drawings 10

xrm command
See also Xref Manager command or tool (*xrm*)

attaching external references 350
 binding external path names 355
 clipping boundaries 356
 detaching external references 353
 moving or changing the path name 354
 opening external references 352
 reloading or uploading external references 353
 search path for files 478
 searching for external references 354
 unloading external references 352
 viewing external references 351

Y

y-axis
 color 483
 in coordinate systems 156

y-ordinate dimensions 309

Z

z-axis
 in coordinate systems 156

z-coordinates in elevation 399, 402

zero angle settings 52

Zoom All tool 145

Zoom Center tool 144

Zoom command (*zoom*) 142, 370

Zoom Extents tool 145

Zoom In command or tool (*zoom*) 142, 144

Zoom Left tool 144

Zoom Out tool 142

Zoom Previous tool 144

zooming in or out
 changing mouse wheel zoom direction 481
 changing viewport scale factor 370
 defined 558
 in 3-dimensional drawings 398
 in print preview window 392
 in viewports 368
 overview 142
 viewing drawings 5

zooming methods 142

